# **SAFETY DATA SHEET**

B66W1561

# Section 1. Identification

Product name	: PRO INDUSTRIAL™ Multi-Surface Acrylic Eg-Shel Coating Extra White
Product code	: B66W1561
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses of t	he substance or mixture and uses advised against
Paint or paint related material.	
Manufacturer	: THE SHERWIN-WILLIAMS COMPANY 101 W. Prospect Avenue Cleveland, OH 44115
National contact	: Sherwin-Williams Canada Inc. 180 Brunel Road Mississauga, Ontario L4Z 1T5 Canada
Emergency telephone number of the company	: US / Canada: (800) 424-9300 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year
Product Information Telephone Number	: US / Canada: (800) 524-5979 Mexico: Not Available
Transportation Emergency Telephone Number	: US / Canada: (800) 424-9300 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year

## Section 2. Hazards identification

Classification of the substance or mixture	: CARCINOGENICITY - Category 2
GHS label elements	
Hazard pictograms	
Signal word	: Warning
Hazard statements	: Suspected of causing cancer.
Precautionary statements	
Prevention	<ul> <li>Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection.</li> </ul>
Response	: IF exposed or concerned: Get medical advice or attention.
Storage	: Store locked up.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Date of issue/Date	of revision	: 4/19/2024	Date of previous issue	: 2/4/2024	Version	:18.01	1/11
B66W1561	PRO INDUSTRIAL™ N Extra White	/lulti-Surface Ad	crylic Eg-Shel Coating		SHW-85-	NA-GHS-CA	

## Section 2. Hazards identification

Supplemental label elements	WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. FOR INDUSTRIAL USE ONLY.
	This product contains a component that is either subject to a CEPA ministerial condition or an existing/proposed SNAC (Significant New Activity).
	Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
Hazards not otherwise classified	: None known.

## Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of identification	: Not available.

#### **CAS number/other identifiers**

Ingredient name	% by weight	CAS number
Titanium Dioxide	20.82	13463-67-7
Amorphous Silica	2.54	7631-86-9

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

Description of necess	ary first aid measures
Eye contact	<ul> <li>Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.</li> </ul>
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

Potential acute health effect	<u>ts</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.

Date of issue/Date	of revision	: 4/19/2024	Date of previous issue	: 2/4/2024	Version	<mark>:</mark> 18.01	2/11
B66W1561	PRO INDUSTRIAL™ № Extra White	Iulti-Surface Ac	rylic Eg-Shel Coating		SHW-85-	NA-GHS-CA	

## Section 4. First aid measures

Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/s	<u>ymptoms</u>
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.
Indication of immediate	medical attention and special treatment needed, if necessary
Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk

aiders : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

#### See toxicological information (Section 11)

# Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: metal oxide/oxides
Special protective actions for fire-fighters	<ul> <li>Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.</li> </ul>
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

Personal precautions, protect	tiv	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	This product contains a component that is either subject to a CEPA ministerial

Date of issue/Date of revision	: 4/19/2024	Date of previous issue	: 2/4/2024	Version : 18.01	3/11
B66W1561 PRO INDUSTRIAL Extra White	.™ Multi-Surface A	crylic Eg-Shel Coating		SHW-85-NA-GHS-CA	

condition or an existing/proposed SNAC (Significant New Activity).

### Section 6. Accidental release measures

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### Methods and materials for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

#### Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

#### **Control parameters**

**Occupational exposure limits (OSHA United States)** 

Ingredient I	name		CA	AS #	Exposure limi	ts		
Titanium Dioxide		13	13463-67-7		OSHA PEL (United States, 5/2018). TWA: 15 mg/m <sup>3</sup> 8 hours. Form: Total dust ACGIH TLV (United States, 1/2023). TWA: 2.5 mg/m <sup>3</sup> 8 hours. Form: respirable fraction, finescale particles			
Amorphous	Silica		76	31-86-9	NIOSH REL ( [SILICA, AMC TWA: 6 mg/	-	10/2020).	
Date of issue/Da	te of revision	: 4/19/2024	Date of previou	is issue	: 2/4/2024	Version	:18.01	4/11
366W1561	PRO INDUSTRIA Extra White	L™ Multi-Surface Ao	crylic Eg-Shel Coa	ting		SHW-85	-NA-GHS-C/	A

## Section 8. Exposure controls/personal protection

# Occupational exposure limits (Canada) Ingredient name CAS # Exposure limits None. Image: Canada Image: Canada Image: Canada Occupational exposure limits (Mexico) Exposure limits Exposure limits Ingredient name CAS # Exposure limits None. Image: Canada Image: Canada Image: Canada Biological exposure indices (United States) Image: Canada Image: Canada Image: Canada

No exposure indices known.

#### **Biological exposure indices (Canada)**

No exposure indices known.

#### **Biological exposure indices (Mexico)**

No exposure indices known.

Appropriate engineering controls Environmental exposure controls		If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. <b>This product contains a component that is either subject to a CEPA ministerial condition or an existing/proposed SNAC (Significant New Activity).</b> Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measure	es	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Date of issue/Date	of revision	: 4/19/2024	Date of previous issue	: 2/4/2024	Version	:18.01	5/11
B66W1561	PRO INDUSTRIAL™ № Extra White	Iulti-Surface Ac	rylic Eg-Shel Coating		SHW-85-1	NA-GHS-CA	

## Section 8. Exposure controls/personal protection

**Respiratory protection** 

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

<u>Appearance</u>					
Physical state	1	Liqu	id.		
Color	1	Whi	te.		
Odor	:	Not	t available.		
Odor threshold	:	Not	available.		
рН	1	9.3			
Melting point/freezing point	1	Not	available.		
Boiling point, initial boiling point, and boiling range	:	100	°C (212°F)		
Flash point	:	Clos	Closed cup: Not applicable.		
Evaporation rate	:	0.09	0.09 (butyl acetate = 1)		
Flammability	:	Not	available.		
Lower and upper explosion limit/flammability limit	:	Not	available.		
Vapor pressure	:	2.3	kPa (17.5 mm Hg)		
Relative vapor density	:	1 [A	ir = 1]		
Relative density	:	1.24	L Contraction of the second		
Solubility(ies)	:				
Media			Result		
cold water			Partially soluble		
Partition coefficient: n- octanol/water	:	Not	applicable.		
Auto-ignition temperature	1	: Not available.			
Decomposition temperature	1	Not	available.		
Viscosity	1	: Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)			
Molecular weight	:	Not	applicable.		
Heat of combustion	:	0.68	39 kJ/g		
			1 /1 //		

## Section 10. Stability and reactivity

<b>Reactivity</b> : No specific test data related to reactivity available for this product or its ingredient						
Chemical stability : The p			t is stable.			
Possibility of har reactions	azardous	: Under norm	al conditions of storage	and use, hazardous	reactions will not occur.	
Conditions to a	void	: No specific	data.			
Incompatible ma	aterials	: No specific	data.			
Date of issue/Date of	of revision	: 4/19/2024	Date of previous issue	: 2/4/2024	Version : 18.01	6/11
	PRO INDUSTRIA Extra White	L™ Multi-Surface A	crylic Eg-Shel Coating		SHW-85-NA-GHS-CA	

## Section 10. Stability and reactivity

# Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

#### Information on toxicological effects

Acute toxicity

Not available.

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Titanium Dioxide	Skin - Mild irritant	Human	-	72 hours 300	-
Amorphous Silica	Eyes - Mild irritant	Rabbit	-	ug I 24 hours 25 mg	-

#### **Sensitization**

Not available.

#### **Mutagenicity**

Not available.

#### **Carcinogenicity**

Not available.

#### **Classification**

Product/ingredient name	OSHA	IARC	NTP
Titanium Dioxide Amorphous Silica	-	2B 3	-

#### **Reproductive toxicity**

Not available.

#### **Teratogenicity**

Not available.

#### Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure)

Not available.

#### Aspiration hazard

Not available.

# Information on the likely : Not available. routes of exposure

# Potential acute health effects Eve contact No known significant effects or critical bazards

Eye contact	. NO KIOWI SIGNICAN ENECTS OF CHICAI NAZARUS.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.

Date of issue/Date of revision		: 4/19/2024	Date of previous issue	: 2/4/2024	Version : 18.01	7/11
B66W1561 PRO INDUSTRIAL™ Extra White		/lulti-Surface Ac	rylic Eg-Shel Coating		SHW-85-NA-GHS-CA	<b>N</b>

# Section 11. Toxicological information

Symptoms related to the p	physical, chemical and toxicological characteristics
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.
Delayed and immediate ef	fects and also chronic effects from short and long term exposure
Short term exposure	
Potential immediate	: Not available.
effects	
Potential delayed effects	: Not available.
<u>Long term exposure</u>	
Potential immediate	: Not available.
effects	
Potential delayed effects	
Potential chronic health e	ffects
Not available.	
General	: No known significant effects or critical hazards.
Carcinogenicity	: Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
<b>Developmental effects</b>	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.
Numerical measures of to	vicity

#### Numerical measures of toxicity Acute toxicity estimates

Not available.

# Section 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
Titanium Dioxide Amorphous Silica	Acute LC50 >1000000 µg/l Marine water Acute EC50 2.2 g/L Fresh water	Fish - <i>Fundulus heteroclitus</i> Daphnia - <i>Daphnia magna</i> - Neonate	96 hours 48 hours
	Chronic NOEC 12.5 mg/l Fresh water	Daphnia - <i>Daphnia magna</i> - Neonate	21 days

#### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

Not available.

Date of issue/Date of revision		: 4/19/2024	Date of previous issue	: 2/4/2024	Version : 18.01	8/11
B66W1561	PRO INDUSTRIAL™ Extra White	Multi-Surface A	crylic Eg-Shel Coating		SHW-85-NA-GHS-CA	

## Section 12. Ecological information

<u>Mobility in soil</u>			
Soil/water partition			
coefficient (Koc)			

: Not available.

**Other adverse effects** : No known significant effects or critical hazards.

## Section 13. Disposal considerations

Disposal methods : This product contains a component that is either subject to a CEPA ministerial condition or an existing/proposed SNAC (Significant New Activity). The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

Extra White

	DOT Classification	TDG Classification	Mexico Classification	ΙΑΤΑ	IMDG
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.
Additional information	-	-	-	-	-
Special precautions	conside mode o suitably to shipn of the p	odal shipping descriper odal shipping descriper f container sizes. The f transport (sea, air, for that mode of trans for that mode of trans nent, and compliance erson offering the propus goods must be the	e presence of a ship etc.), does not indic nsport. All packaging e with the applicable oduct for transport.	pping description for ate that the product must be reviewed regulations is the se People loading and	a particular is packaged for suitability prior ole responsibility unloading
hate of issue/Date of rev 66W1561 PRO	<b>rision</b> : 4/19/20. INDUSTRIAL™ Multi-Surfac			Versi SHW	on :18.01 9/

## Section 14. Transport information

and on all actions in case of emergency situations.

Transport in bulk according : Not available. to IMO instruments

Proper shipping name

: Not available.

## Section 15. Regulatory information

This product contains a component that is either subject to a CEPA ministerial condition or an existing/proposed SNAC (Significant New Activity).

International regulations

**Montreal Protocol** 

Not listed.

Stockholm Convention	on Persistent Organic Pollutants
Not listed.	
International lists	: Australia inventory (AIIC): Not determined.
	China inventory (IECSC): Not determined.
	Japan inventory (CSCL): Not determined.
	Japan inventory (ISHL): Not determined.
	Korea inventory (KECI): Not determined.
	New Zealand Inventory of Chemicals (NZIoC): Not determined.
	Philippines inventory (PICCS): Not determined.
	Taiwan Chemical Substances Inventory (TCSI): Not determined.

Thailand inventory: Not determined.

Turkey inventory: Not determined. Vietnam inventory: Not determined.

## Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

	Classification CARCINOGENICITY - Category 2					Justification Calculation method		
CARCINO								
<u>History</u>								
Date of printing Date of issue/Date of revision Date of previous issue Version		:	: 4/19/2024 : 4/19/2024					
		:						
		: 2/4/2024						
		:	18.01					
Date of issue/D	ate of revision		: 4/19/2024	Date of previous issue	: 2/4/2024	Version : 18.01	10/11	
B66W1561	PRO INDUSTF Extra White	RIAL™	Multi-Surface A	crylic Eg-Shel Coating		SHW-85-NA-GHS	G-CA	

## Section 16. Other information

Key to abbreviations	: ATE = Acute Toxicity Estimate
	BCF = Bioconcentration Factor
	GHS = Globally Harmonized System of Classification and Labelling of Chemicals
	IATA = International Air Transport Association
	IBC = Intermediate Bulk Container
	IMDG = International Maritime Dangerous Goods
	LogPow = logarithm of the octanol/water partition coefficient
	MARPOL = International Convention for the Prevention of Pollution From Ships, 1973
	as modified by the Protocol of 1978. ("Marpol" = marine pollution)
	N/A = Not available
	SGG = Segregation Group
	UN = United Nations
<b>— — — — — — — — — —</b>	

Indicates information that has changed from previously issued version.

#### Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.