SAFETY DATA SHEET

B65A110

Section 1. Identifi	cation
Product name	: POLY-COTE™ 110 (Part B) Gray - Fast Set
Product code	: B65A110
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses of t	he substance or mixture and uses advised against
Paint or paint related material.	
Manufacturer	: THE SHERWIN-WILLIAMS COMPANY 101 W. Prospect Avenue Cleveland, OH 44115
Emergency telephone number of the company	: US / Canada: (800) 424-9300 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year
Product Information Telephone Number	: US / Canada: (800) 524-5979 Mexico: Not Available
Regulatory Information Telephone Number	: US / Canada: (216) 566-2902 Mexico: Not Available
Transportation Emergency Telephone Number	: US / Canada: (800) 424-9300 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year

Section 2. Hazards identification

OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	 SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A RESPIRATORY SENSITIZATION - Category 1 SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2 TOXIC TO REPRODUCTION - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
	Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 30% (oral), 30% (dermal), 30% (inhalation)
GHS label elements	
Hazard pictograms	
Signal word	: Danger

Date of issue/Date	e of revision	: 9/17/2023	Date of previous issue	: 6/12/2023	Version : 16	1/14
B65A110	POLY-COTE™ 110 (P Gray <i>-</i> Fast Set	art B)			SHW-85-NA-GHS-US	

Section 2. Hazards identification

Hazard statements	 Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs. May cause damage to organs through prolonged or repeated exposure.
Precautionary statements	
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Wear respiratory protection. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.
Response	: IF exposed or concerned: Call a POISON CENTER or doctor. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER or doctor. Take off contaminated clothing and wash it before reuse. Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
Storage	: Store locked up.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	WARNING: This product contains chemicals known to the State of California to cause cancer. FOR INDUSTRIAL USE ONLY. This product must be mixed with other components before use. Before opening the packages, READ AND FOLLOW WARNING LABELS ON ALL COMPONENTS.
	Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of	: Not available.
identification	

CAS number/other identifiers

Ingredient name	% by weight	CAS number	
Hyrdoxy terminated polyol	≥10 - ≤25	-	
Triol	≥10 - <20	-	
Wollastonite	≤5	13983-17-0	
Amorphous Silica	≤3	7631-86-9	
Aluminum Oxide	≤3	1344-28-1	
Aliphatic Amine	<3	-	
Carbon Black	≤3	1333-86-4	
Organic metallic complex	<1	-	
Titanium Dioxide	≤0.3	13463-67-7	

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Date of issue/Date	of revision	: 9/17/2023	Date of previous issue	: 6/12/2023	Version	:16	2/14
B65A110	POLY-COTE™ 110 (Pa Gray - Fast Set	rt B)			SHW-85-N	IA-GHS-US	

Section 3. Composition/information on ingredients

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In the event of any complaints or symptoms, avoid further exposure.
Skin contact	: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects	
Eye contact	- Causes serious eye irritation.
Inhalation	: May cause damage to organs following a single exposure if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin contact	: May cause damage to organs following a single exposure in contact with skin. Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: May cause damage to organs following a single exposure if swallowed.
Over-exposure signs/sympto	oms
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: wheezing and breathing difficulties asthma reduced fetal weight increase in fetal deaths skeletal malformations

Section 4. First aid measures

Skin contact	: Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Indication of immediate me	dical attention and special treatment needed, if necessary
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
Special protective actions for fire-fighters	 Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist.
	Provide adequate ventilation. Wear appropriate respirator when ventilation is
	inadequate. Put on appropriate personal protective equipment.

Date of issue/Dat	e of revision	: 9/17/2023	Date of previous issue	: 6/12/2023	Version :16	4/14
B65A110	POLY-COTE™ 110 (F Gray - Fast Set	Part B)			SHW-85-NA-GHS-US	

Section 6. Accidental release measures

For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	nt	ainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems or asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Date of previous issue

: 6/12/2023

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

Ingredient name	CAS #	Exposure limits
Hyrdoxy terminated polyol		None.
Triol		None.
Wollastonite	13983-17-0	ACGIH TLV (United States, 1/2023).
		TWA: 1 mg/m ³ 8 hours. Form: Inhalable
		fraction
Amorphous Silica	7631-86-9	NIOSH REL (United States, 10/2020).
		[SILICA, AMORPHOUS]
		TWA: 6 mg/m ³ 10 hours.
Aluminum Oxide	1344-28-1	ACGIH TLV (United States, 1/2023).
		[Aluminum, metal and insoluble
		compounds]
		TWA: 1 mg/m ³ 8 hours. Form: Respirable
		fraction
		OSHA PEL (United States, 5/2018).
		TWA: 5 mg/m ³ 8 hours. Form: Respirable
		fraction
		TWA: 15 mg/m ³ 8 hours. Form: Total dust
Aliphatic Amine		None.
Carbon Black	1333-86-4	NIOSH REL (United States, 10/2020).
		TWA: 3.5 mg/m ³ 10 hours.
		OSHA PEL (United States, 5/2018).
		TWA: 3.5 mg/m ³ 8 hours.
		ACGIH TLV (United States, 1/2023).
		TWA: 3 mg/m ³ 8 hours. Form: Inhalable
		fraction
Organic metallic complex	10,100,07,7	
Titanium Dioxide	13463-67-7	OSHA PEL (United States, 5/2018).
		TWA: 15 mg/m ³ 8 hours. Form: Total dust
		ACGIH TLV (United States, 1/2023).
		TWA: 2.5 mg/m ³ 8 hours. Form: respirable
		fraction, finescale particles

Occupational exposure limits (Canada)

Ingredient name	CAS #	Exposure limits		
Carbon black	1333-86-4	 CA British Columbia Provincial (Canada, 6/2022). TWA: 3 mg/m³ 8 hours. Form: Inhalable CA Ontario Provincial (Canada, 6/2019). TWA: 3 mg/m³ 8 hours. Form: Inhalable particulate matter. CA Quebec Provincial (Canada, 6/2022). TWAEV: 3 mg/m³ 8 hours. Form: inhalable dust CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 3.5 mg/m³ 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 7 mg/m³ 15 minutes. TWA: 3.5 mg/m³ 8 hours. 		

Occupational exposure limits (Mexico)

Date of issue/Date	of revision	: 9/17/2023	Date of previous issue	: 6/12/2023	Version : 16	6/14
B65A110	POLY-COTE™ 110 (P Gray - Fast Set	Part B)			SHW-85-NA-GHS-	US

Section 8. Exposure controls/personal protection

			CAS #	Exposure limits
None.				
Biological exposure indice	s (U	nited States)		
No exposure indices known.				
Biological exposure indice	s (Ca	anada)		
No exposure indices known.				
Biological exposure indice	s (M	exico)		
No exposure indices known.				
Appropriate engineering controls	:	or mist, use process e	nclosures, local e	ser operations generate dust, fumes, gas, vapor exhaust ventilation or other engineering controls ntaminants below any recommended or statutory
Environmental exposure controls	:	they comply with the re	equirements of er s, filters or engine	ess equipment should be checked to ensure nvironmental protection legislation. In some ering modifications to the process equipment o acceptable levels.
Individual protection measu	<u>ures</u>			
Hygiene measures	:	eating, smoking and us Appropriate techniques Contaminated work clo	sing the lavatory s should be used othing should not before reusing.	ghly after handling chemical products, before and at the end of the working period. to remove potentially contaminated clothing. be allowed out of the workplace. Wash Ensure that eyewash stations and safety cation.
Eye/face protection	:	assessment indicates gases or dusts. If con	this is necessary tact is possible, the tact is possible.	oved standard should be used when a risk to avoid exposure to liquid splashes, mists, ne following protection should be worn, unless ee of protection: chemical splash goggles.
Skin protection				
Hand protection	:	worn at all times when necessary. Considerin during use that the glo noted that the time to b	handling chemic ng the parameters ves are still retair preakthrough for In the case of mi	complying with an approved standard should be al products if a risk assessment indicates this is s specified by the glove manufacturer, check hing their protective properties. It should be any glove material may be different for different xtures, consisting of several substances, the accurately estimated.
Body protection	:			ody should be selected based on the task being nould be approved by a specialist before
Other skin protection	:		ng performed and	l skin protection measures should be selected the risks involved and should be approved by a
Respiratory protection	:	appropriate standard of	or certification. R	exposure, select a respirator that meets the espirators must be used according to a e proper fitting, training, and other important

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

<u>Appearance</u>	
Physical state	: Liquid.
Color	: Not available.
Odor	: Paint
Odor threshold	: Not available.
рН	: Not applicable.
Melting point/freezing point	: Not available.
Boiling point, initial boiling point, and boiling range	: 251°C (483.8°F)
Flash point	: Closed cup: 94°C (201.2°F) [Pensky-Martens Closed Cup]
Evaporation rate	: Not available.
Flammability	: Not available.
Lower and upper explosion limit/flammability limit	: Not available.
Vapor pressure	: Not available.
Relative vapor density	: Not available.
Relative density	: 1.1
Solubility(ies)	: · · · · · · · · · · · · · · · · · · ·

	Media		Result	
	cold water		Not soluble	
	artition coefficient: n- ctanol/water	:	Not applicable.	
A	uto-ignition temperature	:	Not available.	
D	ecomposition temperature	:	Not available.	
Vi	scosity	:	Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)	
Μ	olecular weight	:	Not applicable.	

Section 10. Stability and reactivity

Reactivity	1	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	:	The product is stable.
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	:	No specific data.
Incompatible materials	:	No specific data.
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

8/14	:16	Version	: 6/12/2023	Date of previous issue	: 9/17/2023	te of revision	Date of issue/Da
3	NA-GHS-US	SHW-85-1			Part B)	POLY-COTE™ 110	B65A110
,	NA-GH5-U5	5HW-85-0			Part B)	Gray - Fast Set	B65A110

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Aliphatic Amine	LD50 Oral		1000 mg/kg	-
Carbon Black	LD50 Oral	Rat	>15400 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Amorphous Silica	Eyes - Mild irritant	Rabbit	-	24 hours 25	-
Titanium Dioxide	Skin - Mild irritant	Human	-	mg 72 hours 300 ug l	-

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
Wollastonite	-	3	-
Amorphous Silica Carbon Black	-	3 2B	-
Titanium Dioxide	-	2B 2B	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name	• •	Route of exposure	Target organs
Triol	Category 3		Respiratory tract irritation
Aliphatic Amine	Category 3 Category 2	-	Narcotic effects -

Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
Triol Organic metallic complex	Category 2 Category 1	-	-

Aspiration hazard

Not available.

Information on the likely : Not available. routes of exposure

Date of issue/Date	of revision	: 9/17/2023	Date of previous issue	: 6/12/2023	Version : 16	9/14
B65A110	POLY-COTE™ 110 (F Gray <i>-</i> Fast Set	Part B)			SHW-85-NA-GHS-US	

Section 11. Toxicological information

Potential acute health effe	
Eye contact	: Causes serious eye irritation.
Inhalation	: May cause damage to organs following a single exposure if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin contact	: May cause damage to organs following a single exposure in contact with skin. Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: May cause damage to organs following a single exposure if swallowed.
Symptoms related to the p	physical, chemical and toxicological characteristics
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: wheezing and breathing difficulties asthma reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Delayed and immediate ef	fects and also chronic effects from short and long term exposure
<u>Short term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health e	ffects
Not available.	
General	: May cause damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: Suspected of damaging the unborn child.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: Suspected of damaging fertility.

Date of issue/Dat	te of revision	: 9/17/2023	Date of previous issue	: 6/12/2023	Version : 16	10/14
B65A110	POLY-COTE™ 11 Gray <i>-</i> Fast Set	10 (Part B)			SHW-85-NA-GHS-US	

Section 11. Toxicological information

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	70000 mg/kg
Dermal	77000 mg/kg
Inhalation (dusts and mists)	105 mg/l

Section 12. Ecological information

т	oxi	C	itv
-	-	-	

Product/ingredient name	Result	Species	Exposure
Amorphous Silica	Acute EC50 2.2 g/L Fresh water	Daphnia - <i>Daphnia magna</i> - Neonate	48 hours
	Chronic NOEC 12.5 mg/l Fresh water	Daphnia - <i>Daphnia magna</i> - Neonate	21 days
Aluminum Oxide	Acute EC50 114.357 mg/l Fresh water	Daphnia - <i>Daphnia magna</i> - Neonate	48 hours
Aliphatic Amine Titanium Dioxide	LC50 46 mg/l Acute LC50 >1000000 µg/l Marine water	Fish - <i>Leuciscus idis</i> Fish - <i>Fundulus heteroclitus</i>	96 hours 96 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Not available.

<u>Mobility in soil</u>	
Soil/water partition coefficient (Koc)	: Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Date of issue/Date	of revision	: 9/17/2023	Date of previous issue	: 6/12/2023	Version : 16	11/14
B65A110	B65A110 POLY-COTE™ 110 (Part B) Gray - Fast Set			SHW-85-NA-GHS-US		

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	ΙΑΤΑ	IMDG
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.
Additional information	-	-	-	-	-
oecial precautions	conside mode o suitably to shipn of the p dangero and on	odal shipping descript odal shipping descript r container sizes. The f transport (sea, air, f for that mode of transferred of transferred for that mode of transferred nent, and compliance erson offering the propus goods must be to all actions in case of	e presence of a shi etc.), does not indic nsport. All packaging e with the applicable oduct for transport. rained on all of the r	pping description for ate that the produc g must be reviewed regulations is the People loading and isks deriving from t	r a particular t is packaged for suitability prior sole responsibility unloading

Proper shipping name : Not available.

Section 15. Regulatory information

SARA 313

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet.

California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer.

International regulations

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Date of previous issue


: 6/12/2023

Section 15. Regulatory information

International lists	: Australia inventory (AIIC): Not determined.
	China inventory (IECSC): Not determined.
	Japan inventory (CSCL): Not determined.
	Japan inventory (ISHL): Not determined.
	Korea inventory (KECI): Not determined.
	New Zealand Inventory of Chemicals (NZIoC): Not determined.
	Philippines inventory (PICCS): Not determined.
	Taiwan Chemical Substances Inventory (TCSI): Not determined.
	Thailand inventory: Not determined.
	Turkey inventory: Not determined.
	Vietnam inventory: Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

	Classification	Justification		
SKIN CORROSION/IRRIT SERIOUS EYE DAMAGE/ RESPIRATORY SENSITIZ SKIN SENSITIZATION - C CARCINOGENICITY - Cat TOXIC TO REPRODUCTI SPECIFIC TARGET ORG SPECIFIC TARGET ORG	Calculation method Calculation method Calculation method Calculation method Calculation method Calculation method Calculation method Calculation method			
<u>History</u>				
Date of printing	: 9/17/2023			
Date of issue/Date of revision	: 9/17/2023			
Date of previous issue	: 6/12/2023			
Version	: 16			
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition co- MARPOL = International Convention for the Preventi as modified by the Protocol of 1978. ("Marpol" = mar N/A = Not available	efficient ion of Pollution From Ships, 1973		

Date of issue/Da	ate of revision	: 9/17/2023	Date of previous issue	: 6/12/2023	Version : 16	13/14
B65A110	POLY-COTE™ 1 [°] Gray <i>-</i> Fast Set	10 (Part B)			SHW-85-NA-GHS-US	

Section 16. Other information

SGG = Segregation Group UN = United Nations

✓ Indicates information that has changed from previously issued version.

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

14/14