# **SAFETY DATA SHEET**

B65V920

## Section 1. Identification

Product name	: SHERFLEX® S Elastomeric Polyurethane (Part B) Hardener
Product code	: B65V920
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses of t	he substance or mixture and uses advised against
Paint or paint related material.	
Supplier	: Compania Sherwin-Williams S.A. de C.V. Poniente 140 No.595 Col. Industrial Vallejo, Del. Azcapotzalco C.P. 02300, Ciudad de México, México
Emergency telephone number of the company	: US / Canada: (800) 424-9300 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year
Product Information Telephone Number	: US / Canada: (800) 524-5979 Mexico: Not Available
Regulatory Information Telephone Number	: US / Canada: (216) 566-2902 Mexico: Not Available
Transportation Emergency Telephone Number	: US / Canada: (800) 424-9300 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year

## Section 2. Hazards identification

substance or mixture       SKIN CORROSION/IRRITATION - Category 2         SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A         RESPIRATORY SENSITIZATION - Category 1         SKIN SENSITIZATION - Category 1         SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory trac	
RESPIRATORY SENSITIZATION - Category 1 SKIN SENSITIZATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory trac	
SKIN SENSITIZATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory trac	
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory trac	
irritation) - Category 3	t
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2	
Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 18 (oral), 18% (dermal)	3%
GHS label elements	
Hazard pictograms :	
Signal word : Danger	

Date of issue/Date	of revision	: 9/13/2023	Date of previous issue	: 6/10/2023	Version	:11	1/14
B65V920 SHERFLEX® S Elast Hardener		meric Polyureth	ane (Part B)		SHW-85-	NA-GHS-MX	

## Section 2. Hazards identification

Hazard statements	<ul> <li>H315 - Causes skin irritation.</li> <li>H317 - May cause an allergic skin reaction.</li> <li>H319 - Causes serious eye irritation.</li> <li>H332 - Harmful if inhaled.</li> <li>H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.</li> <li>H335 - May cause respiratory irritation.</li> <li>H373 - May cause damage to organs through prolonged or repeated exposure.</li> </ul>
Precautionary statements	
Prevention	<ul> <li>P280 - Wear protective gloves. Wear eye or face protection.</li> <li>P284 - Wear respiratory protection.</li> <li>P271 - Use only outdoors or in a well-ventilated area.</li> <li>P260 - Do not breathe vapor.</li> <li>P264 - Wash thoroughly after handling.</li> <li>P272 - Contaminated work clothing must not be allowed out of the workplace.</li> </ul>
Response	<ul> <li>P314 - Get medical advice or attention if you feel unwell.</li> <li>P304 + P340, P312 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.</li> <li>P342 + P311 - If experiencing respiratory symptoms: Call a POISON CENTER or doctor.</li> <li>P362 + P364 - Take off contaminated clothing and wash it before reuse.</li> <li>P363 - Wash contaminated clothing before reuse.</li> <li>P302 + P352 - IF ON SKIN: Wash with plenty of water.</li> <li>P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention.</li> <li>P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes.</li> <li>Remove contact lenses, if present and easy to do. Continue rinsing.</li> <li>P337 + P313 - If eye irritation persists: Get medical advice or attention.</li> </ul>
Storage	<ul> <li>P405 - Store locked up.</li> <li>P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.</li> </ul>
Disposal	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	<ul> <li>FOR INDUSTRIAL USE ONLY. This product must be mixed with other components before use. Before opening the packages, READ AND FOLLOW WARNING LABELS ON ALL COMPONENTS. VAPOR AND SPRAY MIST HARMFUL. Gives off harmful vapor of solvents and isocyanates. DO NOT USE IF YOU HAVE CHRONIC (LONG-TERM) LUNG OR BREATHING PROBLEMS, OR IF YOU HAVE EVER HAD A REACTION TO ISOCYANATES. USE ONLY WITH ADEQUATE VENTILATION. WHERE OVERSPRAY IS PRESENT, A POSITIVE PRESSURE AIR SUPPLIED RESPIRATOR (NIOSH approved) SHOULD BE WORN TO PREVENT EXPOSURE. IF UNAVAILABLE, AN APPROPRIATE PROPERLY FITTED APPROVED NIOSH VAPOR/PARTICULATE RESPIRATOR MAY BE EFFECTIVE. Follow directions for respirator use. Wear the respirator for the whole time of spraying and until all vapors and mists are gone. If you have any breathing problems during use, LEAVE THE AREA and get fresh air. If problems remain or happen later, IMMEDIATELY call a doctor - If not available get emergency medical treatment. Have this label with you. Reacts with water in closed container to produce pressure which may cause container to burst.</li> <li>Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.</li> </ul>
Hazards not otherwise classified	: None known.

: 6/10/2023

## Section 3. Composition/information on ingredients

#### Substance/mixture

: Mixture

Other means of identification

: Not available.

**CAS number/other identifiers** 

Ingredient name	% by weight	CAS number
4, 4'-Diphenylmethane Diisocyanate	≥50 - ≤75 ≥25 - ≤50 ≥10 - ≤25	9016-87-9 101-68-8 26447-40-5

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

Description of necessary firs	<u>t aid measures</u>
Eye contact	<ul> <li>Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.</li> </ul>
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. In the event of any complaints or symptoms, avoid further exposure.
Skin contact	: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention following exposure or if feeling unwell. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects	
Eye contact	: Causes serious eye irritation.
Inhalation	: Harmful if inhaled. May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.

Date of issue/Date	of revision	: 9/13/2023	Date of previous issue	: 6/10/2023	Version	:11	3/14
B65V920	SHERFLEX® S Elaston Hardener	neric Polyuretha	ane (Part B)		SHW-85-I	NA-GHS-MX	

### Section 4. First aid measures

### Over-exposure signs/symptoms

Over-exposure signs/symp	
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing wheezing and breathing difficulties asthma
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.
Indication of immediate med	dical attention and special treatment needed, if necessary
Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

### Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides
Special protective actions for fire-fighters	<ul> <li>Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.</li> </ul>
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

Personal precautions, protect	ctiv	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	ont	ainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

#### Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems or asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Date of issue/Date	of revision	: 9/13/2023	Date of previous issue	: 6/10/2023
B65V920	SHERFLEX® S Elas Hardener	tomeric Polyureth	ane (Part B)	

## Section 8. Exposure controls/personal protection

#### **Control parameters**

Occupational exposure limits (OSHA United States)

Ingredient name	CAS #	Exposure limits	
Diphenylmethane Diisocyanate Polymer 4, 4'-Diphenylmethane Diisocyanate	9016-87-9 101-68-8	None. ACGIH TLV (United States, 1/2023). TWA: 0.005 ppm 8 hours. NIOSH REL (United States, 10/2020). TWA: 0.05 mg/m <sup>3</sup> 10 hours. TWA: 0.005 ppm 10 hours. CEIL: 0.2 mg/m <sup>3</sup> 10 minutes. CEIL: 0.02 ppm 10 minutes. OSHA PEL (United States, 5/2018). CEIL: 0.02 ppm CEIL: 0.2 mg/m <sup>3</sup>	
Diphenylmethane Diisocyanate	26447-40-5	None.	

Occupational exposure limits (Canada)

Ingredient name	CAS #	Exposure limits	
lsocyanuric acid polymethylene polyphenyl isocyanate	9016-87-9	CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 0.07 mg/m <sup>3</sup> 8 hours. 8 hrs OEL: 0.005 ppm 8 hours. CA Ontario Provincial (Canada, 6/2019). [Isocyanates, organic compounds] Ceiling Limit: 0.02 ppm TWA: 0.005 ppm 8 hours. CA Quebec Provincial (Canada, 6/2022). [Isocyanate oligomers] Skin sensitizer. Inhalation sensitizer.	
4, 4'-Diphenylmethane Diisocyanate	101-68-8	<ul> <li>Inhalation sensitizer.</li> <li>CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 0.005 ppm 8 hours. 8 hrs OEL: 0.05 mg/m<sup>3</sup> 8 hours.</li> <li>CA British Columbia Provincial (Canada, 6/2022). Inhalation sensitizer. TWA: 0.005 ppm 8 hours. C: 0.01 ppm</li> <li>CA Quebec Provincial (Canada, 6/2022).</li> <li>Skin sensitizer. Inhalation sensitizer. TWAEV: 0.005 ppm 8 hours. TWAEV: 0.051 mg/m<sup>3</sup> 8 hours.</li> <li>CA Saskatchewan Provincial (Canada, 7/2013).</li> <li>STEL: 0.015 ppm 15 minutes. TWA: 0.005 ppm 8 hours.</li> <li>CA Ontario Provincial (Canada, 6/2019).</li> <li>[Isocyanates, organic compounds] Ceiling Limit: 0.02 ppm TWA: 0.005 ppm 8 hours.</li> </ul>	
Diphenylmethane Diisocyanate	26447-40-5	CA British Columbia Provincial (Canada, 6/2022). [Diisocyanates, not elsewhere specified, NOS] TWA: 0.005 ppm 8 hours. C: 0.01 ppm CA Ontario Provincial (Canada, 6/2019). [Isocyanates, organic compounds] Ceiling Limit: 0.02 ppm	
ate of issue/Date of revision : 9/13/2023 Date of pre 55V920 SHERFLEX® S Elastomeric Polyurethane (Part B) Hardener	evious issue	CA Ontario Provincial (Canada, 6/2019 [Isocyanates, organic compounds]	

## Section 8. Exposure controls/personal protection

	TWA: 0.005 ppm 8 hours. CA Quebec Provincial (Canada, 6/2022). [Isocyanate oligomers] Skin sensitizer. Inhalation sensitizer.
Occupational exposure limite (Mexico)	

#### **Occupational exposure limits (Mexico)**

Ingredient name	CAS #	Exposure limits	
4, 4'-Diphenylmethane Diisocyanate	101-68-8	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 0.005 ppm 8 hours.	

#### **Biological exposure indices (United States)**

No exposure indices known.

#### **Biological exposure indices (Canada)**

No exposure indices known.

#### **Biological exposure indices (Mexico)**

No exposure indices known.

Appropriate engineering controls Environmental exposure controls	<ul> <li>Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.</li> <li>Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.</li> </ul>
Individual protection measur	<u>95</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Date of issue/Date	e of revision	: 9/13/2023	Date of previous issue	: 6/10/2023	Version : 11	7/14
B65V920	SHERFLEX® S Elasto Hardener	meric Polyureth	nane (Part B)		SHW-85-NA-GHS-MX	

### Section 8. Exposure controls/personal protection

#### Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

### Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

<u>Appearance</u>						
Physical state	:	Liquid.				
Color	:	Not available.				
Odor	:	Not available.				
Odor threshold	:	Not available.				
рН	:	Not applicable.				
Melting point/freezing point	:	Not available.				
Boiling point, initial boiling point, and boiling range	:	Not available.				
Flash point	:	Closed cup: 193°C (379.4°F) [Pensky-Martens Closed Cup]				
Evaporation rate	:	: Not available.				
Flammability	:	: Not available.				
Lower and upper explosion limit/flammability limit	:	Not available.				
Vapor pressure	:	Not available.				
Relative vapor density	:	Not available.				
Relative density	:	1.23				
Solubility(ies)	:					
Media		Result				
cold water		Not soluble				
Partition coefficient: n- octanol/water	:	Not applicable.				
Auto-ignition temperature	:	Not available.				
Decomposition temperature	:	: Not available.				
Viscosity	:	: Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)				
Molecular weight	:	Not applicable.				
Heat of combustion	:	20.976 kJ/g				
	4	· · · · · · · · · · · · · · · · · · ·				

### Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.

Date of issue/Date	of revision	: 9/13/2023	Date of previous issue	: 6/10/2023	Version : 11	8/14
B65V920	SHERFLEX® S Elast Hardener	omeric Polyureth	nane (Part B)		SHW-85-NA-GHS-MX	

## Section 10. Stability and reactivity

**Incompatible materials** 

: No specific data.

## Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

#### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Diphenylmethane Diisocyanate Polymer	LC50 Inhalation Vapor	Rat	490 mg/m³	4 hours
4, 4'-Diphenylmethane	LD50 Dermal LD50 Oral LD50 Oral	Rabbit Rat Rat	>9400 mg/kg 49 g/kg 9200 mg/kg	-
Diisocyanate			0_00g	

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Diphenylmethane Diisocyanate Polymer	Eyes - Mild irritant	Rabbit	-	100 mg	-
4, 4'-Diphenylmethane Diisocyanate	Eyes - Moderate irritant	Rabbit	-	100 mg	-

#### Sensitization

Not available.

#### **Mutagenicity**

Not available.

#### **Carcinogenicity**

Not available.

#### **Classification**

Product/ingredient name	OSHA	IARC	NTP
Diphenylmethane Diisocyanate Polymer 4, 4'-Diphenylmethane Diisocyanate	-	3 3	-

#### **Reproductive toxicity**

Not available.

#### **Teratogenicity**

Not available.

#### Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Diphenylmethane Diisocyanate Polymer	Category 3	-	Respiratory tract irritation
4, 4'-Diphenylmethane Diisocyanate	Category 3	-	Respiratory tract irritation
Diphenylmethane Diisocyanate	Category 3	-	Respiratory tract irritation

Date of issue/Date	of revision	: 9/13/2023	Date of previous issue	: 6/10/2023	Version	:11	9/14
B65V920	SHERFLEX® S Elaston Hardener	neric Polyuretha	nne (Part B)		SHW-85-1	NA-GHS-MX	

## Section 11. Toxicological information

#### Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
Diphenylmethane Diisocyanate Polymer	Category 2	-	-
4, 4'-Diphenylmethane Diisocyanate	Category 2	-	-
Diphenylmethane Diisocyanate	Category 2	-	-

#### Aspiration hazard

Hardener

Not available.

Information on the likely routes of exposure	available.	
Potential acute health effe		
Eye contact	ses serious eye irritation.	
Inhalation	mful if inhaled. May cause respiratory irritation. May cause ptoms or breathing difficulties if inhaled.	e allergy or asthma
Skin contact	ses skin irritation. May cause an allergic skin reaction.	
Ingestion	known significant effects or critical hazards.	

#### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	:	Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	:	Adverse symptoms may include the following: respiratory tract irritation coughing wheezing and breathing difficulties asthma
Skin contact	:	Adverse symptoms may include the following: irritation redness
Ingestion	:	No specific data.

	<ul><li>levels.</li><li>No known significant effects or critical hazards.</li></ul>					
General	: May cause damage to organs through prolonged or repeated sensitized, a severe allergic reaction may occur when subseq		/ low			
Potential chronic health e Not available.	<u>ifects</u>					
Potential delayed effects	: Not available.					
Potential immediate effects	: Not available.					
Long term exposure						
Potential delayed effects	: Not available.					
Potential immediate effects	: Not available.					
Short term exposure	. Not available					

## Section 11. Toxicological information

## Teratogenicity

: No known significant effects or critical hazards.

Developmental effects Fertility effects

- : No known significant effects or critical hazards.
- : No known significant effects or critical hazards.

#### Numerical measures of toxicity

#### Acute toxicity estimates

Route	ATE value
Inhalation (gases)	8653.85 ppm
Inhalation (vapors)	15.71 mg/l
Inhalation (dusts and mists)	1.83 mg/l

## Section 12. Ecological information

#### **Toxicity**

Not available.

#### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
4, 4'-Diphenylmethane Diisocyanate	-	200	Low
Diphenylmethane Diisocyanate	-	200	Low

#### Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	

Other adverse effects : No known significant effects or critical hazards.

### Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Date of issue/Date	of revision	: 9/13/2023	Date of previous issue	: 6/10/2023	Ver
B65V920	SHERFLEX® S Elaston Hardener	neric Polyuretha	ne (Part B)		SH

## Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	ΙΑΤΑ	IMDG
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.
Additional information	-		-		-
Special precautions	conside mode o suitably to shipr of the p danger and on	odal shipping descri or container sizes. The f transport (sea, air, f for that mode of trans nent, and compliance person offering the propus goods must be t all actions in case of able.	he presence of a shi etc.), does not indic nsport. All packagin e with the applicable oduct for transport. rained on all of the r	pping description fo ate that the product g must be reviewed regulations is the s People loading and isks deriving from th	r a particular is packaged for suitability prior sole responsibility unloading
	Proper s	hipping name	: Not available.		

## Section 15. Regulatory information

Hardener


Internation	al regulations									
Montreal F	Protocol									
Not listed.										
<u>Stockholm</u>	n Convention on	Persistent Org	ganic Pollutants							
Not listed.										
Internation	al lists	: Australi	a inventory (AIIC): Not d	letermined.						
		China inventory (IECSC): Not determined. Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined.								
		Korea inventory (KECI): Not determined.								
	New Zealand Inventory of Chemicals (NZIoC): Not determined.									
		Philippines inventory (PICCS): Not determined.								
		Taiwan	Chemical Substances I	nventory (TCSI): No	ot determined.					
		Thailand	d inventory: Not determi	ned.						
		Turkey i	nventory: Not determine	ed.						
Date of issue/Da	ate of revision	: 9/13/2023	Date of previous issue	: 6/10/2023	Version :	11 12/14				
B65V920	SHERFLEX® S Ela	astomeric Polyuret	hane (Part B)		SHW-85-NA	-GHS-MX				

### Section 15. Regulatory information

Vietnam inventory: Not determined.

## Section 16. Other information





The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

#### Procedure used to derive the classification

	Classification Justification	Justification	
RESPIRATORY SENSITIZ SKIN SENSITIZATION - C SPECIFIC TARGET ORGA irritation) - Category 3	TION - Category 2Calculation methodYE IRRITATION - Category 2ACalculation methodTION - Category 1Calculation method		
History			
Date of printing	: 9/13/2023		
Date of issue/Date of revision	: 9/13/2023		
Date of previous issue	: 6/10/2023		
Version	: 11		
Key to abbreviations	<ul> <li>ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 7 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group</li> </ul>		

UN = United Nations

**V** Indicates information that has changed from previously issued version.

#### Notice to reader

Date of issue/Date of revision	: 9/13/2023	Date of previous issue	: 6/10/2023	Version : 11	13/14
B65V920 SHERFLE Hardener	R S Elastomeric Polyuret		SHW-85-NA-GHS-MX		

## Section 16. Other information

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.