# **SAFETY DATA SHEET**

GP3745B01

Section 1. Identification				
Product name	: GENERAL POLYMERS® 3745 Epoxy (Part B) Hardener			
Product code	: GP3745B01			
Other means of identification	: Not available.			
Product type	: Liquid.			
Relevant identified uses of t	the substance or mixture and uses advised against			
Paint or paint related material.	·			
Manufacturer	: THE SHERWIN-WILLIAMS COMPANY 101 W. Prospect Avenue Cleveland, OH 44115			
National contact	: Sherwin-Williams Canada Inc. 180 Brunel Road Mississauga, Ontario L4Z 1T5 Canada			
Emergency telephone number of the company	: US / Canada: (216) 566-2917 Mexico: SETIQ 01-800-00-214-00 / (52) 55-5559-1588 24 hours / 365 days a year			
Product Information Telephone Number	: US / Canada: Not Available Mexico: Not Available			
Regulatory Information Telephone Number	: US / Canada: (216) 566-2902 Mexico: Not Available			
Transportation Emergency Telephone Number	: US / Canada: (216) 566-2917 Mexico: SETIQ 01-800-00-214-00 / (52) 55-5559-1588 24 hours / 365 days a year			
Section 2. Hazard	s identification			
Classification of the	: ACUTE TOXICITY (oral) - Category 4			

substance or mixture	ACUTE TOXICITY (dermal) - Category 4
	ACUTE TOXICITY (inhalation) - Category 4
	SKIN CORROSION/IRRITATION - Category 1
	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
	SKIN SENSITIZATION - Category 1
	TOXIC TO REPRODUCTION (Fertility) - Category 2
	TOXIC TO REPRODUCTION (Unborn child) - Category 2
	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract
	irritation) - Category 3
	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) -
	Category 3
	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
	Percentage of the mixture consisting of ingredient(s) of unknown dermal toxicity: 16.9%
	Percentage of the mixture consisting of ingredient(s) of unknown inhalation toxicity: 47.
	4%
CUS lobal alamanta	
GHS label elements	

Hazard pictograms



Date of issue/Date	of revision	: 11/15/2018	Date of previous issue	:10/26/2018	Vers
GP3745B01	GENERAL POLYMER Hardener	S® 3745 Epoxy	(Part B)		SH

÷

### Section 2. Hazards identification

Signal word	: Danger
Hazard statements	<ul> <li>Harmful if swallowed, in contact with skin or if inhaled. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Suspected of damaging fertility or the unborn child. May cause respiratory irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.</li> </ul>
<b>Precautionary statements</b>	
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Use only outdoors or in a well-ventilated area. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.
Response	: Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or physician. IF SWALLOWED: Immediately call a POISON CENTER or physician. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Wash contaminated clothing before reuse. Immediately call a POISON CENTER or physician. IF ON SKIN: Wash with plenty of soap and water. Call a POISON CENTER or physician if you feel unwell. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician.
Storage	: Store locked up.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. FOR INDUSTRIAL USE ONLY. This product must be mixed with other components before use. Before opening the packages, READ AND FOLLOW WARNING LABELS ON ALL COMPONENTS.
	Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
Hazards not otherwise classified	: None known.

### Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of	: Not available.
identification	

#### **CAS number/other identifiers**

Ingredient name	% by weight	CAS number
Phenylmethanol	33.54	100-51-6
Isophorone Diamine	30.47	2855-13-2
4-Nonylphenol	16.94	84852-15-3

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

Description of necess	ary first aid measures
Eye contact	: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
Inhalation	: Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	: Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband

#### Most important symptoms/effects, acute and delayed

Potential acute health effects	
Eye contact	: Causes serious eye damage.
Inhalation	<ul> <li>Harmful if inhaled. Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.</li> </ul>
Skin contact	: Causes severe burns. Harmful in contact with skin. May cause an allergic skin reaction.
Ingestion	: Harmful if swallowed. Can cause central nervous system (CNS) depression.
Over-exposure signs/sympto	<u>ms</u>
Eye contact	Adverse symptoms may include the following: pain watering redness
Inhalation	Adverse symptoms may include the following: respiratory tract irritation coughing nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness reduced fetal weight increase in fetal deaths skeletal malformations

:10/26/2018

## Section 4. First aid measures

01.1	
Skin contact	: Adverse symptoms may include the following:
	pain or irritation
	redness
	blistering may occur
	reduced fetal weight
	increase in fetal deaths
	skeletal malformations
Ingestion	: Adverse symptoms may include the following:
ingestion	stomach pains
	reduced fetal weight
	increase in fetal deaths
	skeletal malformations
Indication of immediate med	dical attention and special treatment needed, if necessary
Notes to physician	<ul> <li>In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.</li> </ul>
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

### Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides
Special protective actions for fire-fighters	<ul> <li>Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.</li> </ul>
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures					
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.				
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".				

Date of issue/Date	of revision	: 11/15/2018	Date of previous issue	: 10/26/2018	Version	:6	4/12
GP3745B01	GENERAL POLYMERS	S® 3745 Epoxy	(Part B)		SHW-85-	NA-GHS-CA	L

### Section 6. Accidental release measures

Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	ontainment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

### Section 7. Handling and storage

Precautions for safe handling	1	
Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### Section 8. Exposure controls/personal protection

#### **Control parameters**

#### **Occupational exposure limits (OSHA United States)**

Ingredient name	Exposure limits
Phenylmethanol 3-aminomethyl-3,5,5-trimethylcyclohexylamine	AIHA WEEL (United States, 10/2011). TWA: 10 ppm 8 hours. None.
4-Nonylphenol	None.

#### **Occupational exposure limits (Canada)**

Ingredient name	Exposure limits
benzyl alcohol	AIHA WEEL (United States, 10/2011).
	TWA: 10 ppm 8 hours.

#### **Occupational exposure limits (Mexico)**

Date of issue/Date	of revision	: 11/15/2018	Date of previous issue	: 10/26/2018	Version	:6	5/12
GP3745B01	GENERAL POLYMEI Hardener	RS® 3745 Epoxy	(Part B)		SHW-85-	NA-GHS-CA	

## Section 8. Exposure controls/personal protection

Ingredient name	Exposure limits
None.	

Appropriate engineering controls	: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measure	s Wash hands, forearms and face thoroughly after handling chemical products, before

Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/ or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	<ul> <li>Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Other skin protection	<ul> <li>Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## Section 9. Physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Color	: Not available.
Odor	: Not available.
Odor threshold	: Not available.
рН	Not available.
Melting point/freezing point	: Not available.
Boiling point/boiling range	: 202°C (395.6°F)
Flash point	: Closed cup: 94°C (201.2°F) [Pensky-Martens Closed Cup]
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not available.

Date of issue/Date	of revision	: 11/15/2018	Date of previous issue	: 10/26/2018	Version : 6	6/12
GP3745B01	GENERAL POLYMERS Hardener	® 3745 Epoxy	(Part B)		SHW-85-NA-GHS-CA	

### Section 9. Physical and chemical properties

Lower and upper explosive (flammable) limits	: Lower: 1.3% Upper: 13%
Vapor pressure	: 0.02 kPa (0.15 mm Hg) [at 20°C]
Vapor density	: 3.72 [Air = 1]
Relative density	: 1
Solubility	: Not available.
Partition coefficient: n- octanol/water	: Not available.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Viscosity	: Kinematic (40°C (104°F)): >0.205 cm <sup>2</sup> /s (>20.5 cSt)
Molecular weight	: Not applicable.
Aerosol product	
Heat of combustion	: 40.634 kJ/g

### Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### Section 11. Toxicological information

#### Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Phenylmethanol	LD50 Dermal LD50 Oral		2000 mg/kg 1230 mg/kg	-
4-Nonylphenol	LD50 Oral		1300 mg/kg	-

Product/ingredient name	Result	Species	Score	Exposure	Observation
Phenylmethanol	Skin - Mild irritant	Man	-	48 hours 16 milligrams	-
	Skin - Moderate irritant	Pig	-	100 Percent	-
	Skin - Moderate irritant	Rabbit	-	24 hours 100 milligrams	-
4-Nonylphenol	Eyes - Severe irritant	Rabbit	-	100 milligrams	-
	Skin - Severe irritant	Rabbit	-	24 hours 500 milligrams	-

#### **Sensitization**

Not available.

#### **Mutagenicity**

Date of issue/Date	of revision	: 11/15/2018	Date of previous issue	: 10/26/2018	Version	:6	7/12
	GENERAL POLYMEF Hardener	₹S® 3745 Epoxy (	(Part B)		SHW-85-1	NA-GHS-CA	

### Section 11. Toxicological information

#### Not available.

**Carcinogenicity** 

Not available.

**Reproductive toxicity** 

Not available.

#### **Teratogenicity**

Not available.

#### Specific target organ toxicity (single exposure)

Name	• •	Route of exposure	Target organs
Phenylmethanol	Category 3		Respiratory tract irritation and Narcotic effects

#### Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
Phenylmethanol	Category 2	Not determined	Not determined

#### Aspiration hazard

Not available.

Information on routes of expo		Not available.
Potential acute	health effects	
Eye contact	:	Causes serious eye damage.
Inhalation	:	Harmful if inhaled. Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
Skin contact	:	Causes severe burns. Harmful in contact with skin. May cause an allergic skin reaction.
Ingestion	:	Harmful if swallowed. Can cause central nervous system (CNS) depression.
Symptoms rela	ated to the phy	sical, chemical and toxicological characteristics
Eye contact	:	Adverse symptoms may include the following: pain watering redness
Inhalation	:	Adverse symptoms may include the following: respiratory tract irritation coughing nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	:	Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations
Date of issue/Date GP3745B01		: 11/15/2018       Date of previous issue       : 10/26/2018       Version       : 6       8/12         MERS® 3745 Epoxy (Part B)       SHW-85-NA-GHS-CA

In	<b>a</b>	0	c	fi	0	n
	У	C	9	u	U	

: Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations

Delayed and immediate eff	ects and also chronic effects from short and long term exposure
Short term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health ef	<u>fects</u>
Not available.	
General	: May cause damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: Suspected of damaging the unborn child.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: Suspected of damaging fertility.

#### Numerical measures of toxicity

#### Acute toxicity estimates

Route	ATE value
	987.7 mg/kg 1867.7 mg/kg
	17.25 mg/l

### Section 12. Ecological information

<u>Toxicity</u>			
Product/ingredient name	Result	Species	Exposure
Phenylmethanol	Acute LC50 10000 µg/l Fresh water	Fish - Lepomis macrochirus	96 hours
3-aminomethyl-3,5, 5-trimethylcyclohexylamine	Acute EC50 17.4 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
4-Nonylphenol	Acute EC50 0.03 mg/l Marine water	Algae - Skeletonema costatum	72 hours
	Acute EC50 0.027 mg/l Marine water	Algae - Skeletonema costatum	96 hours
	Acute EC50 137 µg/l Marine water	Crustaceans - Eohaustorius estuarius - Adult	48 hours
	Acute LC50 17 µg/l Marine water	Fish - Pleuronectes americanus - Larvae	96 hours
	Chronic EC10 0.012 mg/l Marine water	Algae - Skeletonema costatum	96 hours
	Chronic NOEC 5 µg/l Fresh water	Crustaceans - Gammarus fossarum - Adult	21 days
	Chronic NOEC 7.4 µg/l Fresh water	Fish - Pimephales promelas - Embryo	33 days

#### Persistence and degradability

Date of issue/Date of revision	: 11/15/2018	Date of previous issue	: 10/26/2018	Version : 6	9/12
GP3745B01 GENERAL POLYMER Hardener	RS® 3745 Epoxy	(Part B)		SHW-85-NA-GHS-CA	

Section 12. Ecological information						
Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability			
Phenylmethanol	-	-	Readily			

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
4-Nonylphenol	-	740	high

#### Mobility in soil

Soil/water partition : Not available. coefficient (Koc)

Other adverse effects : No known significant effects or critical hazards.

### Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

### Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	ΙΑΤΑ	IMDG
UN number	UN3066	UN3066	UN3066	UN3066	UN3066
UN proper shipping name	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL. Marine pollutant (4-Nonylphenol)
Transport	8	8	8	8	8
hazard class(es)	CORIGIVI B	a state of the sta	8	8	
Packing group	III	III	III	Ш	Ш
Environmental hazards	No.	No.	No.	No.	Yes.
Additional information	-	Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2. 40-2.42 (Class 8).	-	The environmentally hazardous substance mark may appear if required by other transportation regulations.	The marine pollutant mark is not required wher transported in sizes of ≤5 L or ≤8 kg. <u>Emergency</u> <u>schedules</u> F-A, S B
ate of issue/Date of rev	rision : 11/15/2	018 Date of previous i	i issue : 10/26/20	18 Versi	l on:6 10/
P3745B01 GEN Hard	ERAL POLYMERS® 3745 E ener	Epoxy (Part B)		SHW	-85-NA-GHS-CA

	ERG No.	ERG No.	ERG No.		
	153	153	153		
Special precaution		consider container sizes. mode of transport (sea, a suitably for that mode of t prior to shipment, and con	The presence of a sh ir, etc.), does not indi ransport. All packagir npliance with the app	for informational purposes and hipping description for a particula cate that the product is package ing must be reviewed for suitabilit licable regulations is the sole t for transport. People loading ar	ir d ty
Transport in bulk to Annex II of MA the IBC Code			ds must be trained or	n all of the risks deriving from the	
to Annex II of MA	RPOL and	unloading dangerous goo substances and on all act	ds must be trained or	n all of the risks deriving from the	
to Annex II of MA	RPOL and	unloading dangerous goo substances and on all act Not available.	ds must be trained or ions in case of emerg	n all of the risks deriving from the	

International regulations	
International lists	<ul> <li>Australia inventory (AICS): Not determined.</li> <li>China inventory (IECSC): Not determined.</li> <li>Japan inventory (ENCS): Not determined.</li> <li>Japan inventory (ISHL): Not determined.</li> <li>Korea inventory (KECI): Not determined.</li> <li>Malaysia Inventory (EHS Register): Not determined.</li> <li>New Zealand Inventory of Chemicals (NZIoC): Not determined.</li> <li>Philippines inventory (PICCS): Not determined.</li> <li>Taiwan Chemical Substances Inventory (TCSI): Not determined.</li> <li>Thailand inventory: Not determined.</li> <li>Turkey inventory: Not determined.</li> <li>Vietnam inventory: Not determined.</li> </ul>

### Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

### Section 16. Other information

Classification	Justification
ACUTE TOXICITY (oral) - Category 4	Calculation method
ACUTE TOXICITY (dermal) - Category 4	Calculation method
ACUTE TOXICITY (inhalation) - Category 4	Calculation method
SKIN CORROSION/IRRITATION - Category 1	Calculation method
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1	Calculation method
SKIN SENSITIZATION - Category 1	Calculation method
TOXIC TO REPRODUCTION (Fertility) - Category 2	Calculation method
TOXIC TO REPRODUCTION (Unborn child) - Category 2	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract	Calculation method
irritation) - Category 3	
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) -	Calculation method
Category 3	
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2	Calculation method

<u>History</u>	
Date of printing	: 11/15/2018
Date of issue/Date of revision	: 11/15/2018
Date of previous issue	: 10/26/2018
Version	: 6
Key to abbreviations	<ul> <li>ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations</li> </ul>

#### Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

: 10/26/2018