# **SAFETY DATA SHEET**

GP4410T04

# Section 1. Identification

Product name	: Resutile™ Aqua 4410/4411 Water-Based Urethane (Part A) Clear / Ultra Deep Tint Base
Product code	: GP4410T04
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses of t	he substance or mixture and uses advised against
Paint or paint related material.	
Manufacturer	: THE SHERWIN-WILLIAMS COMPANY 101 W. Prospect Avenue Cleveland, OH 44115
National contact	: Sherwin-Williams Canada Inc. 180 Brunel Road Mississauga, Ontario L4Z 1T5 Canada
Emergency telephone	: US / Canada: (800) 424-9300 Mavian SETIO 800 00 214 00 / 55 5550 1588 Available 24 hours and 265 days a vest
number of the company	Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year
Product Information Telephone Number	: US / Canada: 1-800-524-5979 Mexico: Not Available
Transportation Emergency Telephone Number	: US / Canada: (800) 424-9300 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year

### Section 2. Hazards identification

Classification of the substance or mixture	: SKIN SENSITIZATION - Category 1 TOXIC TO REPRODUCTION - Category 2
	Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 3.3% (oral), 3.3% (dermal), 3.3% (inhalation)
GHS label elements	
Hazard pictograms	
Signal word	: Warning
Hazard statements	: May cause an allergic skin reaction.
	Suspected of damaging fertility or the unborn child.
Precautionary statements	
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Avoid breathing vapor. Contaminated work clothing must not be allowed out of the workplace.

Date of issue/Date	of revision	: 9/21/2023	Date of previous issue	: 6/15/2023	Version	:11
GP4410T04	Resutile™ Aqua 4410/4 Clear / Ultra Deep Tint		sed Urethane (Part A)		SHW-85-	NA-GI

### Section 2. Hazards identification

Response	: IF exposed or concerned: Get medical advice or attention. Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention.
Storage	: Store locked up.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. FOR INDUSTRIAL USE ONLY. This product must be mixed with other components before use. Before opening the packages, READ AND FOLLOW WARNING LABELS ON ALL COMPONENTS. This product contains a component that is either subject to a CEPA ministerial condition or an existing/proposed SNAC (Significant New Activity). See Environmental Data Sheet (EDS) for additional detail.
	Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
Hazards not otherwise classified	: None known.

### Section 3. Composition/information on ingredients

Substance/mixture	1	Mixture
Other means of	:	Not available.
identification		

### **CAS number/other identifiers**

Ingredient name	% by weight	CAS number
	3.34 0.32	716336-43-5 41556-26-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

#### **Description of necessary first aid measures**

Eye contact	<ul> <li>Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.</li> </ul>
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Date of issue/Date	of revision	: 9/21/2023	Date of previous issue	: 6/15/2023	Version	:11	2/12
GP4410T04	Resutile™ Aqua 4410/ Clear / Ultra Deep Tint		sed Urethane (Part A)		SHW-85-	NA-GHS-CA	

# Section 4. First aid measures

Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Most important symptoms/	effects, acute and delayed
Potential acute health effe	ects
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/sym	<u>ptoms</u>
Eye contact	: No specific data.
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Indication of immediate me	dical attention and special treatment needed, if necessary
Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

# Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.

Date of issue/Date	of revision	: 9/21/2023	Date of previous issue	: 6/15/2023	Version	:11	3/12
GP4410T04	Resutile™ Aqua 4410/ Clear / Ultra Deep Tint		sed Urethane (Part A)		SHW-85-	NA-GHS-CA	

### Section 5. Fire-fighting measures

Hazardous thermal decomposition products	: No specific data.
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

Personal precautions, protect	<u>tiv</u>	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	This product contains a component that is either subject to a CEPA ministerial condition or an existing/proposed SNAC (Significant New Activity). See Environmental Data Sheet (EDS) for additional detail.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### Methods and materials for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

#### Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous.
---------------------	---

Date of issue/Date	of revision	: 9/21/2023	Date of previous issue	: 6/15/2023	Version	:11	4/12
GP4410T04	Resutile™ Aqua 4410/4 Clear / Ultra Deep Tint I		sed Urethane (Part A)		SHW-85-	NA-GHS-CA	

### Section 7. Handling and storage

	Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### Section 8. Exposure controls/personal protection

#### **Control parameters**

#### Occupational exposure limits (OSHA United States)

Ingredient name	CAS #	Exposure limits
Hexanedioic acid, polymer with 2-oxiranylmethyl neodecanoate	716336-43-5	None.
Bis(pentamethyl-4-piperidyl)sebacate	41556-26-7	None.

#### **Occupational exposure limits (Canada)**

Ingredient name	CAS #	Exposure limits		
2-Butoxyethanol	111-76-2	<ul> <li>CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 97 mg/m<sup>3</sup> 8 hours. 8 hrs OEL: 20 ppm 8 hours.</li> <li>CA British Columbia Provincial (Canada, 6/2022). TWA: 20 ppm 8 hours.</li> <li>CA Ontario Provincial (Canada, 6/2019). TWA: 20 ppm 8 hours.</li> <li>CA Quebec Provincial (Canada, 6/2022). TWAEV: 20 ppm 8 hours.</li> <li>CA Quebec Provincial (Canada, 6/2022). TWAEV: 20 ppm 8 hours.</li> <li>CA Saskatchewan Provincial (Canada, 7/2013). STEL: 30 ppm 15 minutes. TWA: 20 ppm 8 hours.</li> </ul>		

#### **Occupational exposure limits (Mexico)**

Ingredient name	CAS #	Exposure limits
None.		

#### **Biological exposure indices (United States)**

No exposure indices known.

#### **Biological exposure indices (Canada)**

No exposure indices known.

#### **Biological exposure indices (Mexico)**

No exposure indices known.

GP4410T04

: 9/21/2023 Date of previous issue 1410/4411 Water-Based Urethane (Part A)

# Section 8. Exposure controls/personal protection

Appropriate engineering controls Environmental exposure controls	<ul> <li>If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.</li> <li>This product contains a component that is either subject to a CEPA ministerial condition or an existing/proposed SNAC (Significant New Activity). See Environmental Data Sheet (EDS) for additional detail.</li> </ul>
	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measu	res
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

# Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### **Appearance**

Physical state	: Liquid.
Color	: Not available.
Odor	: Not available.
Odor threshold	: Not available.
рН	: 7

Date of issue/Date	of revision	: 9/21/2023	Date of previous issue	: 6/15/2023	Version : 11	6/12
GP4410T04	Resutile™ Aqua 4410/ Clear / Ultra Deep Tint		sed Urethane (Part A)		SHW-85-NA-GHS-C/	4

### Section 9. Physical and chemical properties

Melting point/freezing point       : Not available.         Boiling point, initial boiling point, and boiling range       : 100°C (212°F)         Flash point       : Closed cup: 99°C (210.2°F) [Pensky-Martens Closed Cup]         Evaporation rate       : 0.09 (butyl acetate = 1)         Flammability       : Not available.         Lower and upper explosion limit/flammability limit       : Not available.         Vapor pressure       : 2.3 kPa (17.5 mm Hg)         Relative density       : 1 [Air = 1]         Relative density       : 1.04         Solubility(ies)       :         Media       Result         cold water       Partially soluble         Partition coefficient: n- octanol/water       : Not available.         Auto-ignition temperature       : Not available.         Viscosity       : Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)         Molecular weight       : Not applicable.         Viscosity       : Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)					
point, and boiling rangeFlash point: Closed cup: 99°C (210.2°F) [Pensky-Martens Closed Cup]Evaporation rate: 0.09 (butyl acetate = 1)Flammability: Not available.Lower and upper explosion: Not available.limit/flammability limit: Not available.Vapor pressure: 2.3 kPa (17.5 mm Hg)Relative vapor density: 1 [Air = 1]Relative density: 1.04Solubility(ies):Partially solublePartition coefficient: n- octanol/water: Not available.Auto-ignition temperature: Not available.Decomposition temperature: Not available.Viscosity: Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)Molecular weight: Not applicable.	Melting point/freezing point	1	Not available.		
Evaporation rate       : 0.09 (butyl acetate = 1)         Flammability       : Not available.         Lower and upper explosion       : Not available.         limit/flammability limit       : Not available.         Vapor pressure       : 2.3 kPa (17.5 mm Hg)         Relative vapor density       : 1 [Air = 1]         Relative density       : 1.04         Solubility(ies)       :         Media       Result         cold water       Partially soluble         Partition coefficient: n-octanol/water       : Not available.         Auto-ignition temperature       : Not available.         Decomposition temperature       : Not available.         Viscosity       : Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)         Molecular weight       : Not applicable.		;	100°C (212°F)		
Flammability       : Not available.         Lower and upper explosion       : Not available.         limit/flammability limit       : Not available.         Vapor pressure       : 2.3 kPa (17.5 mm Hg)         Relative vapor density       : 1 [Air = 1]         Relative density       : 1.04         Solubility(ies)       :         Media       Result         cold water       Partially soluble         Partition coefficient: n-       : Not available.         octanol/water       : Not available.         Auto-ignition temperature       : Not available.         Viscosity       : Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)         Molecular weight       : Not applicable.	Flash point	:	Closed cup: 99°C (210.2°F) [Pensky-Martens Closed Cup]		
Lower and upper explosion       : Not available.         limit/flammability limit       : 2.3 kPa (17.5 mm Hg)         Relative vapor density       : 1 [Air = 1]         Relative density       : 1.04         Solubility(ies)       :         Media       Result         cold water       Partially soluble         Partition coefficient: n-       : Not applicable.         octanol/water       : Not available.         Auto-ignition temperature       : Not available.         Viscosity       : Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)         Molecular weight       : Not applicable.	Evaporation rate	:	0.09 (butyl acetate = 1)		
limit/flammability limit         Vapor pressure       : 2.3 kPa (17.5 mm Hg)         Relative vapor density       : 1 [Air = 1]         Relative density       : 1.04         Solubility(ies)       :         Media       Result         cold water       Partially soluble         Partition coefficient: n- octanol/water       : Not applicable.         Auto-ignition temperature       : Not available.         Decomposition temperature       : Not available.         Viscosity       : Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)         Molecular weight       : Not applicable.	Flammability	:	Not available.		
Relative vapor density       : 1 [Air = 1]         Relative density       : 1.04         Solubility(ies)       :         Media       Result         cold water       Partially soluble         Partition coefficient: n- octanol/water       : Not applicable.         Auto-ignition temperature       : Not available.         Decomposition temperature       : Not available.         Viscosity       : Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)         Molecular weight       : Not applicable.		1	Not available.		
Relative density       : 1.04         Solubility(ies)       :         Media       Result         cold water       Partially soluble         Partition coefficient: n- octanol/water       : Not applicable.         Auto-ignition temperature       : Not available.         Decomposition temperature       : Not available.         Viscosity       : Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)         Molecular weight       : Not applicable.	Vapor pressure	:	2.3 kPa (17.5 mm Hg)		
Solubility(ies)       :         Media       Result         cold water       Partially soluble         Partition coefficient: n- octanol/water       : Not applicable.         Auto-ignition temperature       : Not available.         Decomposition temperature       : Not available.         Viscosity       : Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)         Molecular weight       : Not applicable.	Relative vapor density	: 1 [Air = 1]			
Media     Result       cold water     Partially soluble       Partition coefficient: n- octanol/water     : Not applicable.       Auto-ignition temperature     : Not available.       Decomposition temperature     : Not available.       Viscosity     : Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)       Molecular weight     : Not applicable.	Relative density	: 1.04			
cold water       Partially soluble         Partition coefficient: n- octanol/water       : Not applicable.         Auto-ignition temperature       : Not available.         Decomposition temperature       : Not available.         Viscosity       : Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)         Molecular weight       : Not applicable.	Solubility(ies)	:			
Partition coefficient: n- octanol/water       : Not applicable.         Auto-ignition temperature       : Not available.         Decomposition temperature       : Not available.         Viscosity       : Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)         Molecular weight       : Not applicable.	Media		Result		
octanol/water: Not available.Auto-ignition temperature: Not available.Decomposition temperature: Not available.Viscosity: Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)Molecular weight: Not applicable.	cold water		Partially soluble		
Decomposition temperature: Not available.Viscosity: Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)Molecular weight: Not applicable.		:	Not applicable.		
Viscosity: Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)Molecular weight: Not applicable.	Auto-ignition temperature	:	: Not available.		
Molecular weight : Not applicable.	Decomposition temperature	: Not available.			
	Viscosity	: Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)			
Heat of combustion : 1.113 kJ/g	Molecular weight	: Not applicable.			
	Heat of combustion	:	1.113 kJ/g		

### Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### Section 11. Toxicological information

### Information on toxicological effects

### Acute toxicity

Not available.

#### Irritation/Corrosion

Not available.

#### **Sensitization**

Not available.

Date of issue/Date	of revision	: 9/21/2023	Date of previous issue	: 6/15/2023	Version : 11	7/12
	Resutile™ Aqua 4 Clear / Ultra Deep		used Urethane (Part A)		SHW-85-NA-GHS-	CA

### Section 11. Toxicological information

### **Mutagenicity**

Not available.

**Carcinogenicity** 

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure) Not available.

Specific target organ toxicity (repeated exposure) Not available.

Aspiration hazard

Not available.

Information on the likely routes of exposure	: Not available.
Potential acute health effe	ects
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.

Symptoms related to the	ph	vsical, chemical and toxicological characterist	tics

Eye contact	: No specific data.
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure		
Short term exposure		
Potential immediate effects	: Not available.	
Potential delayed effects	: Not available.	
Long term exposure		

Date of issue/Date	of revision	: 9/21/2023	Date of previous issue	: 6/15/2023	Version : 11	8/12
GP4410T04	Resutile™ Aqua 4410 Clear / Ultra Deep Tin		ased Urethane (Part A)		SHW-85-NA-GHS-C	A

### Section 11. Toxicological information

Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health ef	ects
Not available.	
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: Suspected of damaging fertility.

### Numerical measures of toxicity Acute toxicity estimates Not available.

### Section 12. Ecological information

### **Toxicity**

Not available.

#### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

Not available.

#### Mobility in soil Soil/water partition coefficient (Koc)

: Not available.

#### Other adverse effects

: No known significant effects or critical hazards.

### Section 13. Disposal considerations

Disposal methods

: This product contains a component that is either subject to a CEPA ministerial condition or an existing/proposed SNAC (Significant New Activity). See Environmental Data Sheet (EDS) for additional detail.

Date of issue/Date	of revision	: 9/21/2023	Date of previous issue	: 6/15/2023	Version : 11	9/12
GP4410T04	Resutile™ Aqua 4410/4 Clear / Ultra Deep Tint		ed Urethane (Part A)		SHW-85-NA-GHS-CA	

### Section 13. Disposal considerations

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

### Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	ΙΑΤΑ	IMDG
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.
Additional information	-	-	-	-	-
Special precautions for user       : Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.         Transport in bulk according to IMO instruments       : Not available.					
	Proper s	hipping name	: Not available.		

### Section 15. Regulatory information

This product contains a component that is either subject to a CEPA ministerial condition or an existing/proposed SNAC (Significant New Activity). See Environmental Data Sheet (EDS) for additional detail.

#### International regulations

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

International lists	: Australia inventory (AIIC): Not determined.
	China inventory (IECSC): Not determined.
	Japan inventory (CSCL): Not determined.
	Japan inventory (ISHL): Not determined.
	Korea inventory (KECI): Not determined.
	New Zealand Inventory of Chemicals (NZIoC): Not determined.
	Philippines inventory (PICCS): Not determined.
	Taiwan Chemical Substances Inventory (TCSI): Not determined.
	Thailand inventory: Not determined.
	Turkey inventory: Not determined.
	Vietnam inventory: Not determined.

### Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

Classification	Justification
	Calculation method
TOXIC TO REPRODUCTION - Category 2	Calculation method

<u>History</u>	
Date of printing	: 9/21/2023
Date of issue/Date of revision	: 9/21/2023
Date of previous issue	: 6/15/2023
Version	: 11

Date of issue/Date	of revision	: 9/21/2023	Date of previous issue	: 6/15/2023	Version : 11	11/12
GP4410T04	P4410T04 Resutile™ Aqua 4410/4411 Water-Based Urethane (Part A) Clear / Ultra Deep Tint Base			SHW-85-NA-GHS-CA	<b>`</b>	

### Section 16. Other information

Key to abbreviations	: ATE = Acute Toxicity Estimate
	BCF = Bioconcentration Factor
	GHS = Globally Harmonized System of Classification and Labelling of Chemicals
	IATA = International Air Transport Association
	IBC = Intermediate Bulk Container
	IMDG = International Maritime Dangerous Goods
	LogPow = logarithm of the octanol/water partition coefficient
	MARPOL = International Convention for the Prevention of Pollution From Ships, 1973
	as modified by the Protocol of 1978. ("Marpol" = marine pollution)
	N/A = Not available
	SGG = Segregation Group
	UN = United Nations

Indicates information that has changed from previously issued version.

### Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.