SAFETY DATA SHEET

GP6800V01

Section 1. Identification

Product name	: 6800 Fluorescent Pigment
Product code	: GP6800V01
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses of the	he substance or mixture and uses advised against
Paint or paint related material.	
Manufacturer	: THE SHERWIN-WILLIAMS COMPANY 101 W. Prospect Avenue Cleveland, OH 44115
National contact	: Sherwin-Williams Canada Inc. 180 Brunel Road Mississauga, Ontario L4Z 1T5 Canada
Emergency telephone	: US / Canada: (800) 424-9300
number of the company	Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year
Product Information	: US / Canada: 1-800-524-5979 Mexico: Not Available
Telephone Number	
Transportation Emergency Telephone Number	: US / Canada: (800) 424-9300 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year

Section 2. Hazards identification

Classification of the substance or mixture	: SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A
	Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 1% (dermal), 1% (inhalation)
GHS label elements	
Hazard pictograms	· · •
Signal word	: Warning
Hazard statements	: Causes serious eye irritation.
Precautionary statements	
Prevention	: Wear eye or face protection. Wash thoroughly after handling.
Response	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
Storage	: Not applicable.
Disposal	: Not applicable.

Date of issue/Da	te of revision	: 1/23/2024	Date of previous issue	: 9/13/2023	Version : 9	1/11
GP6800V01	6800 Fluorescent P	Pigment			SHW-85-NA-GHS-CA	۱.

Section 2. Hazards identification

Supplemental label elements	WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. FOR INDUSTRIAL USE ONLY.
	Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of identification	: Not available.

CAS number/other identifiers

Ingredient name	% by weight	CAS number
Barium Sulfate	30	7727-43-7
Ethoxylated Vegetable Oil	1	-
Cyclohexane	0.1	110-82-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	 Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	 Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health eff	ects					
Eye contact	: Causes ser	ious eye irritation.				
Inhalation	: No known s	significant effects or critic	al hazards.			
Skin contact	: No known s	significant effects or critic	al hazards.			
Date of issue/Date of revision	: 1/23/2024	Date of previous issue	: 9/13/2023	Version	:9	2/11

GP6800V01 6800 Fluorescent Pigment

Section 4. First aid measures

Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/symp	<u>otoms</u>
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.
Indication of immediate me	dical attention and special treatment needed, if necessary
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: sulfur oxides metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protec	tive equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions :

Date of issue/Date	of revision	: 1/23/2024	Date of previous issue	: 9/13/2023	Version : 9	3/11
GP6800V01 6800 Fluorescent Pigment				SHW-85-NA-GHS-CA		

Section 6. Accidental release measures

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

Ingredient name	CAS #	Exposure limits
Barium Sulfate	7727-43-	 ACGIH TLV (United States, 1/2023). TWA: 5 mg/m³ 8 hours. Form: Inhalable fraction NIOSH REL (United States, 10/2020). TWA: 5 mg/m³ 10 hours. Form: Respirable fraction TWA: 10 mg/m³ 10 hours. Form: Total OSHA PEL (United States, 5/2018). TWA: 5 mg/m³ 8 hours. Form: Respirable fraction TWA: 15 mg/m³ 8 hours. Form: Total dust
ate of issue/Date of revision : 1/2	/2024 Date of previous issue	: 9/13/2023 Version : 9 4/11
P6800V01 6800 Fluorescent Pigment		SHW-85-NA-GHS-CA

Section 8. Exposure controls/personal protection

Ethoxylated Vegetable Oil		None.
Cyclońexane	110-82-7	ACGIH TLV (United States, 1/2023). TWA: 100 ppm 8 hours. NIOSH REL (United States, 10/2020). TWA: 300 ppm 10 hours. TWA: 1050 mg/m ³ 10 hours. OSHA PEL (United States, 5/2018). TWA: 300 ppm 8 hours. TWA: 1050 mg/m ³ 8 hours.

Occupational exposure limits (Canada)

Ingredient name	CAS #	Exposure limits
None.		

Occupational exposure limits (Mexico)

Ingredient name	CAS #	Exposure limits
None.		

Biological exposure indices (United States)

Ingredient name	Exposure indices
	ACGIH BEI (United States, 1/2023) BEI: 50 mg/g creatinine, 1,2-cyclohexanediol [in urine]. Sampling time: end of shift at end of workweek.

Biological exposure indices (Canada)

No exposure indices known.

Biological exposure indices (Mexico)

No exposure indices known.

controls	Good general ventilation should be sufficient to control worker exposure to airborne contaminants. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measure	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection	

Section 8. Exposure controls/personal protection

Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Physical state: Liquid.Color: Not available.Odor: Not available.Odor threshold: Not available.pH: 6.6Melting point/freezing point: Not available.Boiling point, initial boiling point, and boiling range: 100°C (212°F)Flash point: Closed cup: Not applicable.Evaporation rate: 0.09 (butyl acetate = 1)Flammability: Not available.Lower and upper explosion limit/flammability limit: Not available.Vapor pressure: 2.3 kPa (17.5 mm Hg)Relative density: 1 [Air = 1]Relative density: 2.18Solubility(ies):	<u>Appearance</u>			
Odor: Not available.Odor threshold: Not available.pH: 6.6Melting point/freezing point: Not available.Boiling point, initial boiling point, and boiling range: 100°C (212°F)Flash point: Closed cup: Not applicable.Evaporation rate: 0.09 (butyl acetate = 1)Flammability: Not available.Lower and upper explosion limit/flammability limit: Not available.Vapor pressure: 2.3 kPa (17.5 mm Hg)Relative vapor density: 1 [Air = 1]Relative density: 2.18Solubility(ies):	Physical state		quid.	
Odor threshold: Not available.pH: 6.6Melting point/freezing point: Not available.Boiling point, initial boiling point, and boiling range: 100°C (212°F)Flash point: Closed cup: Not applicable.Evaporation rate: 0.09 (butyl acetate = 1)Flammability: Not available.Lower and upper explosion limit/flammability limit: Not available.Vapor pressure: 2.3 kPa (17.5 mm Hg)Relative vapor density: 1 [Air = 1]Relative density: 2.18Solubility(ies):	Color		ot available.	
pH:6.6Melting point/freezing point:Not available.Boiling point, initial boiling point, and boiling range:100°C (212°F)Flash point:Closed cup: Not applicable.Evaporation rate:0.09 (butyl acetate = 1)Flammability:Not available.Lower and upper explosion limit/flammability limit:Not available.Vapor pressure:2.3 kPa (17.5 mm Hg)Relative vapor density:1 [Air = 1]Relative density:2.18Solubility(ies):	Odor	: No	ot available.	
Melting point/freezing point: Not available.Boiling point, initial boiling point, and boiling range: 100°C (212°F)Flash point: Closed cup: Not applicable.Evaporation rate: 0.09 (butyl acetate = 1)Flammability: Not available.Lower and upper explosion limit/flammability limit: Not available.Vapor pressure: 2.3 kPa (17.5 mm Hg)Relative vapor density: 1 [Air = 1]Relative density: 2.18Solubility(ies):	Odor threshold	: No	ot available.	
Boiling point, initial boiling point, and boiling range: 100°C (212°F)Flash point: Closed cup: Not applicable.Evaporation rate: 0.09 (butyl acetate = 1)Flammability: Not available.Lower and upper explosion limit/flammability limit: Not available.Vapor pressure: 2.3 kPa (17.5 mm Hg)Relative vapor density: 1 [Air = 1]Relative density: 2.18Solubility(ies):	рН	: 6.	6	
point, and boiling rangeFlash point: Closed cup: Not applicable.Evaporation rate: 0.09 (butyl acetate = 1)Flammability: Not available.Lower and upper explosion: Not available.limit/flammability limit: Not available.Vapor pressure: 2.3 kPa (17.5 mm Hg)Relative vapor density: 1 [Air = 1]Relative density: 2.18Solubility(ies):	Melting point/freezing point	: No	ot available.	
Evaporation rate: 0.09 (butyl acetate = 1)Flammability: Not available.Lower and upper explosion: Not available.limit/flammability limit: Not available.Vapor pressure: 2.3 kPa (17.5 mm Hg)Relative vapor density: 1 [Air = 1]Relative density: 2.18Solubility(ies):			00°C (212°F)	
Flammability : Not available. Lower and upper explosion : Not available. limit/flammability limit : Not available. Vapor pressure : 2.3 kPa (17.5 mm Hg) Relative vapor density : 1 [Air = 1] Relative density : 2.18 Solubility(ies) :	Flash point	: CI	Closed cup: Not applicable.	
Lower and upper explosion limit/flammability limit : Not available. Vapor pressure : 2.3 kPa (17.5 mm Hg) Relative vapor density : 1 [Air = 1] Relative density : 2.18 Solubility(ies) : Media Result	Evaporation rate	: 0.	0.09 (butyl acetate = 1)	
limit/flammability limit Vapor pressure : 2.3 kPa (17.5 mm Hg) Relative vapor density : 1 [Air = 1] Relative density : 2.18 Solubility(ies) : Media Result	Flammability	: No	Not available.	
Relative vapor density : 1 [Air = 1] Relative density : 2.18 Solubility(ies) : Media Result			Not available.	
Relative density : 2.18 Solubility(ies) : Media Result	Vapor pressure	: 2.	2.3 kPa (17.5 mm Hg)	
Solubility(ies) : Media Result	Relative vapor density		1 [Air = 1]	
Media Result	Relative density		18	
	Solubility(ies) :			
cold water Not soluble	Media		Result	
	cold water		Not soluble	

cold water		Not soluble
Partition coefficient: n- octanol/water	: Not	applicable.
Auto-ignition temperature	: Not	available.
Decomposition temperature	: Not	available.
Viscosity	: Kin	ematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)
Molecular weight	: Not	applicable.
Heat of combustion	: 0.04	I7 kJ/g

Date of issue/Date	e of revision
GP6800V01	6800 Fluore

Section 10. Stability and reactivity

	,
Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
1	

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Cyclohexane	LD50 Oral	Rat	6240 mg/kg	-

Irritation/Corrosion

Not available.

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name		Route of exposure	Target organs
Cyclohexane	Category 3	-	Narcotic effects

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Name	Result
Cyclohexane	ASPIRATION HAZARD - Category 1

Date of issue/Date	of revision	: 1/23/2024	Date of previous issue	: 9/13/2023	Version : 9	7/11
GP6800V01	6800 Fluorescent Pigm	nent			SHW-85-NA-GHS-CA	

Section 11. Toxicological information

Information on the likely routes of exposure	: Not available.
Potential acute health effe	ects
Eye contact	: Causes serious eye irritation.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Symptoms related to the p	physical, chemical and toxicological characteristics
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.
Defense of a sol because of a factor of	fe ste suid alla subwards affe ste fuerre alla suid la suid terre terre avec
Short term exposure Potential immediate	fects and also chronic effects from short and long term exposure : Not available.
Short term exposure	
Short term exposure Potential immediate effects	: Not available.
<u>Short term exposure</u> Potential immediate effects Potential delayed effects	: Not available.
Short term exposure Potential immediate effects Potential delayed effects Long term exposure Potential immediate effects	Not available.Not available.
Short term exposure Potential immediate effects Potential delayed effects Long term exposure Potential immediate	 Not available. Not available. Not available. Not available.
Short term exposure Potential immediate effects Potential delayed effects Long term exposure Potential immediate effects Potential delayed effects	 Not available. Not available. Not available. Not available.
Short term exposure Potential immediate effects Potential delayed effects Long term exposure Potential immediate effects Potential delayed effects Potential chronic health effects	 Not available. Not available. Not available. Not available.
Short term exposure Potential immediate effects Potential delayed effects Long term exposure Potential immediate effects Potential delayed effects Potential chronic health effects Not available.	 Not available. Not available. Not available. ffects
Short term exposure Potential immediate effects Potential delayed effects Long term exposure Potential immediate effects Potential delayed effects Potential chronic health effects Not available. General	 Not available. Not available. Not available. Not available. ffects No known significant effects or critical hazards.
Short term exposure Potential immediate effects Potential delayed effects Long term exposure Potential immediate effects Potential delayed effects Potential delayed effects Potential chronic health effects Not available. General Carcinogenicity	 Not available. Not available. Not available. Not available. ffects No known significant effects or critical hazards. No known significant effects or critical hazards.
Short term exposure Potential immediate effects Potential delayed effects Long term exposure Potential immediate effects Potential delayed effects Potential delayed effects Potential chronic health er Not available. General Carcinogenicity Mutagenicity	 Not available. Not available. Not available. Not available. ffects No known significant effects or critical hazards. No known significant effects or critical hazards. No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates	
Route	ATE value
Oral	50000 mg/kg

: 1/23/2024 Date of previous issue

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Barium Sulfate	5	Crustaceans - <i>Cypris subglobosa</i> Daphnia - <i>Daphnia magna</i>	48 hours 48 hours
Cyclohexane	Acute LC50 4530 µg/l Fresh water	Fish - Pimephales promelas	96 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Cyclohexane	-	167	Low

Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

```
Disposal methods
```

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.


Section 14. Transport information

UN number No. UN proper shipping name - Transport -	ot regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
shipping name		-	-		
Transport				-	-
hazard class(es)		-	-	-	-
Packing group -		-	-	-	-
Environmental No hazards).	No.	No.	No.	No.

Additional information		-		
pecial precautions	for usor : Multi mod	al shinning descriptions are	provided for informational purposes	and do not
	consider of mode of tr suitably fo to shipme of the per- dangerous	container sizes. The presence ransport (sea, air, etc.), does or that mode of transport. All nt, and compliance with the son offering the product for t s goods must be trained on	e of a shipping description for a part on tindicate that the product is pack packaging must be reviewed for suit applicable regulations is the sole res ransport. People loading and unload all of the risks deriving from the subs	icular kaged ability prior ponsibility ling
ransport in bulk as		actions in case of emergen	cy situations.	
ansport in bulk ac IMO instruments	ording : Not availab	ie.		
	Proper shi	nning name · Not a	vailable.	
Section 15. F	egulatory info			
Section 15. F	egulatory info			
	egulatory info			
International regu	egulatory info			
International regu Montreal Protoco Not listed.	egulatory info	ormation		
International regu Montreal Protoco Not listed.	egulatory info	ormation		

Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Section 16. Other information

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

Classification		Justification
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A		Calculation method
History		
Date of printing	: 1/23/2024	
Date of issue/Date of revision	: 1/23/2024	
Date of previous issue	: 9/13/2023	
Version	: 9	
Key to abbreviations	 ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations 	

✓ Indicates information that has changed from previously issued version.

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.