

Product Description

Dupli-Color® Adhesion Promoter improves adhesion of enamel and lacquer topcoats to all surfaces, including plastic and chrome. This is an all purpose clear primer ideal for both interior and exterior applications.

Product Characteristics

Color: Clear

Properties

Product Weight: 6 lb/gal

Flash Point: Propellant < 0° F

Preferred Application

Dupli-Color Adhesion Promoter provides an optimum performance when this application method is followed.

Prep	PW100	Prep Wipe
	PS100	Prep Spray
	CM541	Grease & Wax
Prime	CP199	Adhesion Promoter

Refer to the application box for more specific instructions!

Uses

Interior and Exterior of Automotive Vehicles.

Surfaces:

Metal & Plastic.

Application

Directions: Prepare surface by removing loose paint, dirt, rust, grease, wax, etc. For best results, use a Dupli-Color Prep Wipe (PW100) or Grease & Wax Remover to clean surface. Rinse well, and dry well with a clean cloth.

Mask-off surrounding areas to protect from overspray. Use temperatures between 60°-92° F, and when humidity is less than 60%.

Shake can vigorously for one full minute. After each full minute of use, shake the can for an additional 10 seconds. To spray, hold can parallel 8-10 inches from the surface to be coated and use in an even, sweeping motion. To avoid runs and sags, apply in 2-3 light coats. Allow primer to dry for 2-3 minutes between coats. Apply color coat within last 10 minutes of primer coat. Covers approximately 12-14 square feet.

The EZ Touch™ Nozzle results in 50% less finger fatigue than a standard nozzle, as well as greater coverage and less overspray.

Packaging

Fill Weight: 11 oz

Per Case: 6 cans

Case Weight: 6 lbs

Cases/Pallet: 156

Units/Pallet: 936 cans