



Protective & Marine Coatings

FIRETEX® SC1 SCRIM CLOTH

Revised 02/2016 Issue 3

PRODUCT INFORMATION

PRODUCT DESCRIPTION

A high temperature fire resistant fabric scrim cloth

RECOMMENDED USE

As a high temperature fire resistant fabric scrim cloth designed to reinforce the insulation 'char' developed when FIRETEX M93/02 reacts in a fire. Suitable for use in hydrocarbon pool fires for the protection of structural steelwork. Installation to be in accordance with the 'FIRETEX M93/02 Application and Use Manual' and per certification requirements.

ENDORSEMENTS

Approved by Underwriters Laboratory for UL1709 external use

RECOMMENDED APPLICATION METHODS

Installed by hand layup in accordance with the 'FIRETEX M93/02 Application and Use Manual'.

PRODUCT CHARACTERISTICS

Colour Availability: Black-white

VOC: None

RECOMMENDED THICKNESS

Cloth thickness is 0.3mm \pm 5%. Nominal weight is 67g/m² \pm 5%

PRACTICAL APPLICATION RATES - MICRONS PER COAT

Required quantity of cloth will depend on the size and shape of the structure to be fire protected.

FIRETEX SC1 cloth is supplied in rolls nominally 50m long and 1.1m wide. Cut cloth to size and install in accordance with the 'FIRETEX M93/02 Application and Use Manual'.

SURFACE PREPARATION

FIRETEX SC1 is intended to be encapsulated within wet applied FIRETEX M93/02. See 'FIRETEX M93/02 Application and Use Manual' for details.

PACKAGE

Pack Size: Supplied on rolls that are nominally 50m long and 1.1m wide.
Shelf Life: Minimum 2 years from date of supply

HEALTH AND SAFETY

Consult Product Health and Safety Data Sheet for information on safe handling of this product

WARRANTY

Any person or company using the product without first making further enquiries as to the suitability of the product for the intended purpose does so at their own risk, and Sherwin-Williams can accept no liability for the performance of the product, or for any loss or damage arising out of such use.

The information detailed in this Data Sheet is liable to modification from time to time in the light of experience and of normal product development, and before using, customers are advised to check with Sherwin-Williams, quoting the reference number, to ensure that they possess the latest issue.