SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

SECTION 1: Identifica	tion of the substance/mixture and of the company/undertaking
1.1 Product identifier	
Product name	: Zinc Clad™ II EU Ethyl Zinc Silicate Primer - Powder
Product code	: D5V2B
1.2 Relevant identified us	es of the substance or mixture and uses advised against
Material uses	Paint or paint related material.
	: Industrial use only.
1.3 Details of the supplier sheet	of the safety data
Sherwin-Williams UK Limit Coatings Division EMEAI Tower Works Kestor Street Bolton BL2 2AL United Kingdom +44 (0) 1204 521771	ed - Protective & Marine
The Sherwin-Williams Con Inver France SAS 2 Rue Jean Revaus - BP 8 Thouars CEDEX France	
e-mail address of person responsible for this SDS	
1.4 Emergency telephone	number
National advisory body/F	<u>Poison Center</u>
Telephone number	: 421 2 5477 4166
<u>Supplier</u>	
Telephone number	: +(44)-870-8200 418
Hours of operation	: Emergency contact available 24 hours a day
SECTION 2: Hazards i	dentification
2.1 Classification of the s	ubstance or mixture
Product definition	: Mixture
Classification according Aquatic Acute 1, H400 Aquatic Chronic 1, H410	to Regulation (EC) No. 1272/2008 [CLP/GHS]
The product is classified as	s hazardous according to Regulation (EC) 1272/2008 as amended.
See Section 16 for the full	text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

:

Zinc Clad™ II EU Ethyl Zinc Silicate Primer - Powder D5V2B

SECTION 2: Hazards identification

Hazard pictograms



Signal word	: Warning
Hazard statements	: Very toxic to aquatic life with long lasting effects.
Precautionary statements	
Prevention	: Avoid release to the environment.
Response	: Collect spillage.
Storage	: Not applicable.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	: FOR INDUSTRIAL USE ONLY
• • • • • •	

Special packaging requirements

Not applicable.

0.0.14

2.3 Other hazards

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Other hazards which do not result in classification

SECTION 3: Composition/information on ingredients

: None known.

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Zinc Powder	REACH #: 01-2119467174-37 EC: 231-175-3 CAS: 7440-66-6 Index: 030-001-01-9	≥75 - ≤90	Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 1	[1] [2]
Kaolin	EC: 310-194-1 CAS: 1332-58-7	≤10	Not classified.	-	[2]
Zinc Oxide	REACH #: 01-2119463881-32 EC: 215-222-5 CAS: 1314-13-2 Index: 030-013-00-7	≤5	Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 1	[1] [2]
			See Section 16 for the full text of the H statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section. <u>Type</u>

Zinc Clad™ II EU Ethyl Zinc Silicate Primer - Powder

D5V2B

SECTION 3: Composition/information on ingredients

[1] Substance classified with a health or environmental hazard[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid me	asures
General	: In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
Eye contact	: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

See toxicological information (Section 11)

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media	: Recommended: alcohol-resistant foam, CO ₂ , powders, water spray or mist.	
Unsuitable extinguishing media	: Do not use water jet.	

5.2 Special hazards arising from the substance or mixture

Hazards from the
substance or mixture: Fire will produce dense black smoke. Exposure to decomposition products may
cause a health hazard.

Date of issue/Date of revision	: 17, Sep, 2023	Date of previous issue	: 12, Jun, 2023	Version : 11	3/14

Zinc Clad™ II EU Ethyl Zinc Silicate Primer - Powder D5V2B

SECTION 5: Firefighting measures

Hazardous combustion products	:	Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.
5.3 Advice for firefighters		
Special protective actions for fire-fighters	:	Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.
Special protective equipment for fire-fighters	:	Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures		
For non-emergency personnel	:	Exclude sources of ignition and ventilate the area. Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8.
		Keep unnecessary and unprotected personnel from entering.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.
6.3 Methods and materials for containment and cleaning up	:	Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe : handling	 Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing and floors should be of the conducting type. Keep away from heat, sparks and flame. No sparking tools should be used. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Put on appropriate personal protective equipment (see Section 8). Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or watercourses. Information on fire and explosion protection Vapors are heavier than air and may spread along floors. Vapors may form
--	---

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II Zinc Clad™ II EU Ethyl Zinc Silicate Primer - Powder

D5V2B

SECTION 7: Handling and storage

explosive mixtures with air.

7.2 Conditions for safe storage, including any incompatibilities	 Store in accordance with local regulations. Notes on joint storage Keep away from: oxidizing agents, strong alkalis, strong acids. Additional information on storage conditions Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking. Prevent unauthorized access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.
	Contaminated absorbent material may pose the same hazard as the spilled product. Store in closed original container at temperatures between 5°C and 25°C.
7.3 Specific end use(s)	
Recommendations	: Not available.
Industrial sector specific solutions	: Not available.

Good housekeeping standards, regular safe removal of waste materials and regular maintenance of spray booth filters will minimise the risks of spontaneous combustion and other fire hazards.

Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
Zinc Powder	Government regulation SR c. 355/2006 (Slovakia, 9/2020). [Zinc and its inorganic compounds] TWA: 2 mg/m ³ , (Zinc and its inorganic compounds) 8 hours. Form: inhalable fraction TWA: 0.1 mg/m ³ , (Zinc and its inorganic compounds) 8 hours. Form: respirable fraction
Kaolin	Government regulation SR c. 355/2006 (Slovakia, 9/2020). TWA: 10 mg/m ³ 8 hours. Form: fibers, total concentration TWA: 10 mg/m ³ / Fr 8 hours. Form: respirable fibers Fr > 5 % TWA: 2 mg/m ³ 8 hours. Form: respirable fibers Fr \leq 5 %
Zinc Oxide	Government regulation SR c. 355/2006 (Slovakia, 9/2020). TWA: 1 mg/m ³ 8 hours. Form: respirable fraction and fumes STEL: 1 mg/m ³ 15 minutes. Form: respirable fraction and fumes

Biological exposure indices

No exposure indices known.

Recommended monitoring procedures	: Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance
	documents for methods for the determination of hazardous substances will also be

Date of issue/Date of revision	: 17, Sep, 2023	Date of previous issue	: 12, Jun, 2023	Version : 11	5/14
				SHW-A4-EU-CLP44-SK	

	required.Regular monitoring of all work areas should be carried out at all times, including areas that may not be equally ventilated.
<u>DNELs/DMELs</u> No DNELs/DMELs available	· · · · · · · · · · · · · · · · · · ·
<u>PNECs</u> No PNECs available.	
2 Exposure controls	
Appropriate engineering controls	: Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapor below the OEL, suitable respiratory protection must be worn.
	: Users are advised to consider national Occupational Exposure Limits or other equivalent values.
Individual protection meas	<u>ures</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Use safety eyewear designed to protect against splash of liquids.
Skin protection	
Hand protection	: Wear suitable gloves tested to EN374.
Gloves	 Gloves for short term exposure/splash protection (less than 10 min.): Nitrile>0.12 mm Gloves for splash protection need to be changed immediately when in contact with chemicals. Gloves for repeated or prolonged exposure (breakthrough time > 240 min.) When the hazardous ingredients in Section 3 contain any of the following: Aromatic solvents (Xylene, Toluene) or Aliphatic solvents or Mineral Oil use: Polyvinyl alcoho (PVA) gloves 0.2-0.3 mm Otherwise use: Butyl gloves >0.3 mm For long term exposure or spills (breakthrough time >480 min.): Use PE laminated gloves as under gloves Due to many conditions (e.g. temperature, abrasion) the practical usage of a chemical protective glove in practice may be much shorter than the permeation tim determined through testing. The recommendation for the type or types of glove to use when handling this product is based on information from the following source: Solvent resin manufacturers and European Solvents Industry Group (ESIG) There is no one glove material or combination of chemicals. The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical/chemica damage and poor maintenance.

SECTION 8: Exposure controls/personal protection

	The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
Body protection	: Personnel should wear antistatic clothing made of natural fibers or of high- temperature-resistant synthetic fibers.
	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Recommended: A2P2 (EN14387). Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	: Do not allow to enter drains or watercourses.

Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

<u>Appearance</u>		
Physical state	: :	Solid.
Color	: (Gray.
Odor	: :	Solvent.
Odor threshold	: 1	Not Available (Not Tested).
pН		Not relevant/applicable due to nature of the product. insoluble in water.
Melting point/freezing point	:	Not relevant/applicable due to nature of the product.
Initial boiling point and boiling range	:	Not relevant/applicable due to nature of the product.
Flash point	: (Closed cup: 499°C [Pensky-Martens Closed Cup]
Evaporation rate	: 1	Not relevant/applicable due to nature of the product.
Flammability	: 1	Not relevant/applicable due to nature of the product.
Lower and upper explosion limit	:	Not relevant/applicable due to nature of the product.
Vapor pressure	: 1	Not relevant/applicable due to nature of the product.
Relative vapor density	: 1	Not applicable.
Relative density	: (6.25
Solubility(ies)	:	
Media		Result
cold water		Not soluble

Partition coefficient: n-octanol/ : Not relevant/applicable due to nature of the product. *water*

SECTION 9: Physical and chemical properties

Auto-ignition temperature	: Not relevant/applicable due to nature of the product.
Decomposition temperature	: Not relevant/applicable due to nature of the product.
Viscosity	: Kinematic (40°C): >20.5 mm²/s
Explosive properties	: Under normal conditions of storage and use, hazardous reactions will not occur.
Oxidizing properties	: Under normal conditions of storage and use, hazardous reactions will not occur.
Particle characteristics	
Median particle size	: Not relevant/applicable due to nature of the product.

9.2 Other information Heat of combustion

: 0 kJ/g

SECTION 10: Stability and reactivity				
10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredie	ents.		
10.2 Chemical stability	Stable under recommended storage and handling conditions (see Section 7).			
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occu	Jr.		
10.4 Conditions to avoid	When exposed to high temperatures may produce hazardous decomposition products.			
10.5 Incompatible materials	Keep away from the following materials to prevent strong exothermic reactions oxidizing agents, strong alkalis, strong acids.	5:		
10.6 Hazardous decomposition products	Decomposition products may include the following materials: carbon monoxide carbon dioxide, smoke, oxides of nitrogen.	Э,		

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Acute toxicity

No data available

Acute toxicity estimates

No data available

Irritation/Corrosion

ti. S

Product/ingredient name	Result	Species	Score	Exposure	Observation
Zinc Powder	Skin - Mild irritant	Human	-	72 hours 300	-
Zinc Oxide	Eyes - Mild irritant	Rabbit	-	ug I 24 hours 500 mg	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 mg	-
Conclusion/Summary	: Not available.				
<u>Sensitization</u> No data available					
Conclusion/Summary	: Not available.				
Mutagenicity					
No data available					
<u>Carcinogenicity</u> No data available					
Reproductive toxicity					
No data available					
<u>Teratogenicity</u>					
No data available					
<u>Specific target organ toxicit</u> No data available	<u>ty (single exposure)</u>				
Specific target organ toxicit	<u>ty (repeated exposure)</u>				
No data available					
Aspiration hazard					
No data available					
1.2 Information on other haz	zards				
11.2.1 Endocrine disrupting	properties				
Not available.					
11.2.2 Other information					
Not available.					

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself. Do not allow to enter drains or watercourses.

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

SHW-A4-EU-CLP44-SK

SECTION 12: Ecological information

Product/ingredient name	Result	Species	Exposure
Zinc Powder	Acute EC50 10000 µg/l Fresh water	Aquatic plants - Lemna minor	4 days 🥄
	Acute EC50 34 µg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute IC50 65 µg/l Marine water	Algae - <i>Nitzschia closterium</i> - Exponential growth phase	4 days
	Acute LC50 68 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 12.21 µg/l Marine water	Fish - <i>Periophthalmus waltoni</i> - Adult	96 hours
	Chronic EC10 6.3 µg/l	Daphnia - <i>Daphnia magna</i> - Neonate	21 days
	Chronic NOEC 0.25 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Chronic NOEC 9 mg/l Fresh water	Aquatic plants - Ceratophyllum demersum	3 days
	Chronic NOEC 178 µg/l Marine water	Crustaceans - Palaemon elegans	21 days
	Chronic NOEC 2.6 µg/l Fresh water	Fish - Cyprinus carpio	4 weeks
Zinc Oxide	Acute IC50 1.85 mg/l Marine water	Algae - Skeletonema costatum	96 hours
	Acute LC50 98 μg/l Fresh water	Daphnia - <i>Daphnia magna -</i> Neonate	48 hours
	Acute LC50 1.1 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours

12.2 Persistence and degradability

Product/ingredient name	Test	Result		Dose		Inoculum
No data available						
Conclusion/Summary	: Not available.					
Product/ingredient name	Aquatic half-life		Photolysis		Biodeg	radability
No data available						

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Zinc Oxide	-	28960	High

12.4 Mobility in soil	
Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

10/14

SECTION 13: Disposal considerations

13.1 Waste treatment methods

	<u></u>
Methods of disposal	 The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: Yes.
European waste catalogue (EWC)	 waste paint and varnish containing organic solvents or other hazardous substances 08 01 11*
Disposal considerations	 Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Disposal considerations	: Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.
European waste catalogue (EWC)	 packaging containing residues of or contaminated by hazardous substances 15 01 10*
Special precautions	This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG	ΙΑΤΑ
14.1 UN number or ID number	UN3077	UN3077	UN3077
14.2 UN proper shipping name	Environmentally hazardous substance, solid, n.o.s. (Zinc Powder, Zinc Oxide)	Environmentally hazardous substance, solid, n.o.s. (Zinc Powder, Zinc Oxide). Marine pollutant (Zinc Powder, Zinc Oxide)	Environmentally hazardous substance, solid, n.o.s. (Zinc Powder, Zinc Oxide)
14.3 Transport Hazard Class(es)/ Label(s)	9	9	9
14.4 Packing group	111	111	111
14.5 Environmental hazards	Yes.	Yes.	Yes.
Date of issue/Date of revi	Date of issue/Date of revision : 17, Sep, 2023 Date of previous issue : 12, Jun, 2023 Version : 11 11/14 SHW-A4-EU-CLP44-SK SHW-A4-EU-CLP44-SK SHW-A4-EU-CLP44-SK SHW-A4-EU-CLP44-SK		

Zinc Clad™ II EU Ethyl Zinc Silicate Primer - Powder D5V2B

SECTION 14: Transport information

Additional information	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. <u>Tunnel code</u> (-)	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. <u>Emergency schedules</u> F-A, S-F	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.		

14.6 Special precautions for	:	Transport within user's premises: always transport in closed containers that are
user		upright and secure. Ensure that persons transporting the product know what to do in
		the event of an accident or spillage.

14.7 Maritime transport in : Not applicable. **bulk according to IMO instruments**

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

<u>Annex XIV</u>

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

No listed substance

Other EU regulations

VOC content (2010/75/EU)	:	0 0	w/w g/l
Industrial emissions (integrated pollution prevention and control) - Air	:	Listed	
Industrial emissions (integrated pollution prevention and control) - Water	:	Listed	

Explosive precursors : Not applicable.

Seveso Directive

This product may add to the calculation for determining whether a site is within the scope of the Seveso Directive on major accident hazards.

National regulations

15.2 Chemical Safety : No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	 ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number vPvB = Very Persistent and Very Bioaccumulative N/A = Not available
Key literature references and sources for data	 Regulation (EC) No. 1272/2008 [CLP] ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 Directive 2012/18/EU, and relative amendments & additions Directive 2008/98/EC, and relative amendments & additions Directive 2009/161/EU, and relative amendments & additions CEPE Guidelines

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classi	ication Justification
Aquatic Acute 1, H400 Aquatic Chronic 1, H410	Calculation method Calculation method
Full text of abbreviated H statements	 H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects.
Full text of classifications [CLP/GHS]	: Aquatic Acute 1 AQUATIC HAZARD (ACUTE) - Category 1 Aquatic Chronic 1 AQUATIC HAZARD (LONG-TERM) - Category 1
Date of printing	: 17, Sep, 2023.
Date of issue/ Date of revision	: 17, Sep, 2023
Date of previous issue	: 12, Jun, 2023
	 If there is no previous validation date please contact your supplier for more information.
Version	: 11

Notice to reader

In accordance with Regulation (EC) 1907/2006, REACH Regulation, Articles 31, 37, any required hazard-related information on the use of substances received as downstream user will be sent forward. Consequently, the safety data sheets for some products will contain a SUMI - Safe Use of Mixture Information - attached to the safety data sheet.

SUMI(s) will be added to the SDS for products if both the following conditions are met:

• The product is classified as hazardous for health

• The product contains one or more REACH-registered substances for which extended safety data sheets (exposure scenarios) have been provided

SECTION 16: Other information

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country. federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.