SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier	
Product name	: FIRETEX FFC250 Water Based Intumescent
Product code	: FFC250
	s of the substance or mixture and uses advised against
Material uses	: Paint or paint related material.
	: Industrial use only.
1.3 Details of the supplier o sheet	f the safety data
Sherwin-Williams UK Limite Coatings Division EMEAI Tower Works Kestor Street Bolton BL2 2AL United Kingdom +44 (0) 1204 521771	1 - Protective & Marine
The Sherwin-Williams Comp Inver France SAS 2 Rue Jean Revaus - BP 80 Thouars CEDEX France	
e-mail address of person responsible for this SDS	: hse.pm.emea@sherwin.com
1.4 Emergency telephone n	umber
National advisory body/Po	ison Center
Telephone number	: 112 - Information center (available 24 hours)
Supplier	
Telephone number	: +(44)-870-8200 418
-	: Emergency contact available 24 hours a day
Hours of operation	. Emergency contact available 24 hours a day
SECTION 2: Hazards id	entification
2.1 Classification of the sub	
Product definition	: Mixture
	D Regulation (EC) No. 1272/2008 [CLP/GHS]
Skin Sens. 1, H317	
Repr. 2, H361 Aquatic Chronic 3, H412	
The product is classified as	hazardous according to Regulation (EC) 1272/2008 as amended.
See Section 16 for the full te	xt of the H statements declared above.
See Section 11 for more det	ailed information on health effects and symptoms.
Date of issue/Date of revision	15, Apr, 2024 Date of previous issue : 17, Sep, 2023 Version : 16

:

SECTION 2: Hazards identification

2.2	Label	elements
	Laver	01011101110



Signal word	: Warning
Hazard statements	: May cause an allergic skin reaction. Suspected of damaging fertility or the unborn child. Harmful to aquatic life with long lasting effects.
Precautionary statements	
Prevention	: Obtain special instructions before use. Wear protective gloves, protective clothing, eye protection, face protection, or hearing protection. Avoid release to the environment. Avoid breathing vapor.
Response	: IF exposed or concerned: Get medical advice or attention. Take off contaminated clothing and wash it before reuse.
Storage	: Not applicable.
Disposal	: Not applicable.
Hazardous ingredients	 Orthoboric Acid, Zinc Salt 2-Methyl-4-isothiazolin-3-one reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)
Supplemental label elements	: FOR INDUSTRIAL USE ONLY
0	

Special packaging requirements

Not applicable.

2.3 Other hazards

	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
Other hazards which do not result in classification	: If mixed with other materials, product may release hydrogen gas - increased storaged temperatures will accelerate this process.

SECTION 3: Composition/information on ingredients

	Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
3-one 01-2120764690-50 Acute Tox. 3, H311 mg/kg CAS: 2682-20-4 Acute Tox. 2, H330 ATE [Dermal] = Index: 613-326-00-9 Skin Corr. 1B, H314 300 mg/kg Kin Sens. 1A, H317 ATE [Inhalation Skin Sens. 1A, H317 Skin Sens. 1A, H317	Orthoboric Acid, Zinc Salt		≥10 - <25	(inhalation) Aquatic Acute 1, H400 Aquatic Chronic 2,	M [Acute] = 1	[1]
		01-2120764690-50 EC: 220-239-6 CAS: 2682-20-4	<0.01	Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317	mg/kg ATE [Dermal] = 300 mg/kg ATE [Inhalation (vapours)] = 0.5	[1]

SECTION 3: Composition/information on ingredients

		- ingrouion			
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3:1)	REACH #: 01-2120764691-48 CAS: 55965-84-9 Index: 613-167-00-5	<0.001	Aquatic Chronic 1, H410 EUH071 Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1,	Skin Sens. 1, H317: $C \ge 0.0015\%$ M [Acute] = 10 M [Chronic] = 1 ATE [Oral] = 53 mg/ kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (vapours)] = 0.5 mg/l Skin Corr. 1C,	[1]
			Aquatic Chronic 1, H410 EUH071		
			See Section 16 for the full text of the H statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section. <u>Type</u>

[1] Substance classified with a health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
 Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
 Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
 If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

FIRETEX FFC250 Water Based Intumescent

FFC250

SECTION 4: First aid measures

There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.	
Specific treatments	: No specific treatment.	

See toxicological information (Section 11)

5.1 Extinguishing media	
Suitable extinguishing media	: Recommended: alcohol-resistant foam, CO ₂ , powders, water spray or mist.
Unsuitable extinguishing media	: Do not use water jet.

J.Z Special hazarus arising h	U	
Hazards from the substance or mixture	:	Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.
Hazardous combustion products	:	Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.
5.3 Advice for firefighters		
Special protective actions for fire-fighters	:	Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.
Special protective	:	Fire-fighters should wear positive pressure self-contained breathing apparatus

(SCBA) and full turnout gear.

SECTION 6: Accidental release measures

Due to the organic solvents content of the mixture:

equipment for fire-fighters

6.1 Personal precautions, protective equipment and emergency procedures For non-emergency personnel Exclude sources of ignition and ventilate the area. Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8. Keep unnecessary and unprotected personnel from entering. For emergency responders If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

SECTION 6: Accidental release measures

6.2 Environmental precautions	: Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.	
6.3 Methods and materials for containment and cleaning up	: Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.	
6.4 Reference to other sections	 See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information. 	

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling	: Due to the organic solvents content of the mixture:
	 Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Keep away from heat, sparks and flame. No sparking tools should be used. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Put on appropriate personal protective equipment (see Section 8). Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one. Comply with the health and safety at work laws. Information on fire and explosion protection Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapors in all cases. In such circumstances, they should wear a compressed-air-fed respirator during the spraying process and until the particulate and solvent vapor
7.2 Conditions for safe storage, including any incompatibilities	 Store in accordance with local regulations. Notes on joint storage Keep away from: oxidizing agents, strong alkalis, strong acids. Additional information on storage conditions Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep container tightly closed. Keep away from sources of ignition. No smoking. Prevent unauthorized access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Contaminated absorbent material may pose the same hazard as the spilled product. Store in closed original container at temperatures between 5°C and 25°C.

7.3 Specific end use(s)

SECTION 7: Handling and storage

Recommendations	: Not available.
Industrial sector specific	: Not available.
solutions	

Good housekeeping standards, regular safe removal of waste materials and regular maintenance of spray booth filters will minimise the risks of spontaneous combustion and other fire hazards.

Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

Biological exposure indices

No exposure indices known.

Recommended monitoring procedures		Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required. Regular monitoring of all work areas should be carried out at all times, including areas that may not be equally ventilated.
DNELs/DMELs		
No DNELs/DMELs available.		
<u>PNECs</u> No PNECs available.		
8.2 Exposure controls		
Appropriate engineering controls	:	Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn.
	:	Users are advised to consider national Occupational Exposure Limits or other equivalent values.
Individual protection measu	re	<u>S</u>
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Use safety eyewear designed to protect against splash of liquids.
Skin protection		
Hand protection	:	Wear suitable gloves tested to EN374.
Gloves	:	-

SECTION 8: Exposure controls/personal protection

	Gloves for short term exposure/splash protection (less than 10 min): Nitrile >0.12 mm
	Gloves for splash protection need to be changed immediately when in contact with chemicals.
	Gloves for repeated or prolonged exposure (breakthrough time > 480 min): Butyl gloves >0.3 mm
	Due to many conditions (e.g. temperature, abrasion) the practical usage of a chemical protective glove in practice may be much shorter than the permeation time determined through testing.
	The recommendation for the type or types of glove to use when handling this product is based on information from the following source: Solvent resin manufacturers and European Solvents Industry Group (ESIG).
	There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.
	The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.
	Gloves should be replaced regularly and if there is any sign of damage to the glove material.
	Always ensure that gloves are free from defects and that they are stored and used correctly.
	The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.
	Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.
	The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
Body protection	: Personnel should wear protective clothing.
	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Application methods: Brush or roller. Approved/certified respirator with organic vapor cartridge. Filter type: A2 P2 (EN14387).
	Manual spraying. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure controls	: Do not allow to enter drains or watercourses.

Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state	:	Liquid.
Color	:	Red.
Odor	:	Paint

SECTION 9: Physical and chemical properties

-		
Odor threshold	: Not Available (Not Tested).	
pН	: 5.1	
Melting point/freezing point	: Not relevant/applicable due to nature of the product.	
Initial boiling point and boiling range	: 100°C	
Flash point	: Closed cup: 499°C [Pensky-Martens Closed Cup]	
Evaporation rate	: 0.09 (butyl acetate = 1)	
Flammability	: Not relevant/applicable due to nature of the product.	
Lower and upper explosion limit	 LEL: 0.8% (2-(2-Butoxyethoxy)ethyl Acetate) UEL: 5% (2-(2-Butoxyethoxy)ethyl Acetate) 	
Vapor pressure	: 2.3 kPa (17.5 mm Hg)	
Relative vapor density	: 1 [Air = 1]	
Relative density	: 1.51	
Solubility(ies)	:	
Media	Result	
cold water	Partially soluble	

Partition coefficient: n-octanol/ : Not relevant/applicable due to nature of the product. *water*

.

Auto-ignition temperature

Ingredient name		°C	°F	Method	
2-(2-Butoxyethoxy)ethyl Acetate		290	554		
Decomposition temperature	: N	ot relevant/applic	cable due to nature	of the product.	
Viscosity	: K	inematic (40°C):	>20.5 mm²/s		
Explosive properties	: U	nder normal con	ditions of storage ar	nd use, hazardous reactions w	ill not occur.
Oxidizing properties	: U	nder normal con	ditions of storage ar	nd use, hazardous reactions w	ill not occur.
Particle characteristics					
Median particle size	: N	ot relevant/applic	able due to nature o	of the product.	
.2 Other information					
Heat of combustion	: 1.	.034 kJ/g			
ECTION 10: Stability and	l react	tivity			
0.1 Reactivity	: No sp	ecific test data r	elated to reactivity a	vailable for this product or its i	ngredients.
0.2 Chemical stability	: Stable	e under recomm	ended storage and l	nandling conditions (see Section	on 7).
0.3 Possibility of azardous reactions	: Unde	r normal conditio	ns of storage and u	se, hazardous reactions will no	ot occur.
0.4 Conditions to avoid	: Wher produ		n temperatures may	produce hazardous decompos	sition
0.5 Incompatible materials			ollowing materials to ng alkalis, strong aci	prevent strong exothermic reads.	actions:

Date of issue/Date of revision	: 15, Apr, 2024	Date of previous issue	:17, Sep, 2023	Version : 16	8/15
				SHW-A4-EU-CLP44-PL	

FIRETEX FFC250 Water Based Intumescent

FFC250

SECTION 10: Stability and reactivity

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	LD50 Oral	Rat	53 mg/kg	-

Acute toxicity estimates

No data available

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	Skin - Severe irritant	Human	-	0.01 %	-
Conclusion/Summary	: Not available.				

Conclusion/Summary

Sensitization

No data available

: Not available. Conclusion/Summary

Mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

Teratogenicity

No data available

Specific target organ toxicity (single exposure)

No data available

SHW-A4-EU-CLP44-PL

SECTION 11: Toxicological information

Specific target organ toxicity (repeated exposure)

No data available

Aspiration hazard

No data available

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself. Do not allow to enter drains or watercourses.

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

Product/ingredient name	Result	Species	Exposure
2-Methyl-4-isothiazolin-3-one	••	1 1 1	48 hours 96 hours

12.2 Persistence and degradability

Product/ingredient name	Test	Result		Dose		Inoculum
No data available						
Conclusion/Summary	: Not available.					
Product/ingredient name	Aquatic half-life		Photolysis		Biodeg	radability
No data available						

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Orthoboric Acid, Zinc Salt	-	60960	High

12.4 Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

Date of issue/Date of revision : 15, Apr, 2024

FIRETEX FFC250 Water Based Intumescent

FFC250

SECTION 12: Ecological information

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	-
Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: Yes.
European waste catalogue (EWC)	 waste paint and varnish containing organic solvents or other hazardous substances 08 01 11*
Disposal considerations	 Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Disposal considerations	: Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.
European waste catalogue (EWC)	 packaging containing residues of or contaminated by hazardous substances 15 01 10*
Special precautions	This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG	ΙΑΤΑ
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport Hazard Class(es)/ Label(s)	-	-	-
14.4 Packing group	-	-	-
14.5 Environmental hazards	No.	No.	No.
Date of issue/Date of rev	rision : 15, Apr, 2024	Date of previous issue : 17, Se	p, 2023 Version : 16 11/ ⁻
			SHW-A4-EU-CLP44-PL

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II FIRETEX FFC250 Water Based Intumescent				
FFC250				
SECTION 14: 1	Fransport inform	ation		
Additional information	-	-	-	

This mixture is not classified as dangerous according to international transport regulations (ADR/RID, IMDG, ICAO/IATA).

14.6 Special precautions for user: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in	: Not applicable.
bulk according to IMO	
instruments	

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

<u>Annex XIV</u>

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name		%	Designation [Usage]
FIRETEX FFC250 Water B octamethylcyclotetrasiloxar		≥90 <0.01	3 70
Labeling	: Not applicable.		
Other EU regulations			
VOC content (2010/75/EU)	: 1 w/w 15 g/l		
Explosive precursors	: Not applicable.		
Seveso Directive			
This product is not controlle	d under the Seveso Directive.		
National regulations			
References	: Obwieszczenie Marszałka Sejmu Rzeczypost sprawie ogłoszenia jednolitego tekstu ustawy 2007.39.252 z późniejszymi zmianami) Obwieszczenie Marszałka Sejmu Rzeczypost sprawie ogłoszenia jednolitego tekstu ustawy 2007.39.252 z późniejszymi zmianami) Rozporządzenie Ministra Gospodarki z dnia szczegółowych wymagań dotyczących ograni organicznych powstających w wyniku wykorzy organicznych w niektórych farbach i lakierach	o produktach politej Polskie o produktach 16 stycznia 20 czenia emisji ystywania rozj	i biobójczych (Dz.U. j z dnia 1 lutego 2007 r. w i biobójczych (Dz.U. 007 r. w sprawie lotnych związków puszczalników

Date of issue/Date of revision	: 15, Apr, 2024	Date of previous issue	:17, Sep, 2023	Version : 16	12/15
				SHW-A4-EU-CLP44-PL	

SECTION 15: Regulatory information

SECTION 15: Regulato	ry information
	pojazdów (Dz.U. 2007.11.72 z późniejszymi zmianami)
	Rozporządzenie Ministra Ochrony Środowiska z dnia 27 lipca 2004 r. w sprawie
	dopuszczalnych mas substancji które mogą być odprowadzane w ściekach
	przemysłowych (Dz.U. 2004.180.1867) Rozporządzenie Ministra Środowiska z dnia 26 stycznia 2010 r. w sprawie wartości
	odniesienia dla niektórych substancji w powietrzu (Dz.U. 2010.16.87)
	Rozporządzenie Ministra Środowiska z dnia 18 listopada 2014 r. w sprawie
	warunków, jakie należy spełnić przy wprowadzaniu ścieków do wód lub do ziemi,
	oraz w sprawie substancji szczególnie szkodliwych dla środowiska wodnego (Dz.U.
	2014.0.1800)
	Rozporządzenie Ministra Środowiska z dnia 9 grudnia 2014 r. w sprawie katalogu
	odpadów (Dz.U. 2014.0.1923)
	Rozporządzenie Ministra Zdrowia z dnia 11 czerwca 2012 r. w sprawie kategorii
	substancji niebezpiecznych i mieszanin niebezpiecznych, których opakowania
	wyposaża się w zamknięcia utrudniające otwarcie przez dzieci i wyczuwalne
	dotykiem ostrzeżenie o niebezpieczeństwie (Dz.U. 2012.0.688 z późniejszymi
	zmianami) Rozporządzenie Ministra Zdrowia z dnia 24 lipca 2012 r. w sprawie substancji
	chemicznych, ich mieszanin, czynników lub procesów technologicznych o działaniu
	rakotwórczym lub mutagennym w środowisku pracy (Dz.U. 2012.0.890)
	Rozporządzenie Ministra Zdrowia z dnia 30 grudnia 2004 r. w sprawie
	bezpieczeństwa i higieny pracy związanej z występowaniem w miejscu pracy
	czynników chemicznych (Dz.U. 2005.11.86 z późniejszymi zmianami)
	Rozporządzenie Ministra Zdrowia z dnia 2 lutego 2011 r. w sprawie badań i
	pomiarów czynników szkodliwych dla zdrowia w środowisku pracy (Dz.U.
	2011.33.166)
	Rozporządzenie Ministra Zdrowia z dnia 20 kwietnia 2012 r. w sprawie oznakowania
	opakowań substancji niebezpiecznych i mieszanin niebezpiecznych oraz niektórych mieszanin (Dz.U. 2012.0.445 z późniejszymi zmianami)
	Rozporządzenie Ministra Zdrowia z dnia 10 sierpnia 2012 r. w sprawie kryteriów i
	sposobu klasyfikacji substancji chemicznych i ich mieszanin (Dz.U. 2012.0.1018 z
	późniejszymi zmianami)
	Rozporządzenie Ministra Spraw Wewnętrznych i Administracji z dnia 7 czerwca
	2010 r. w sprawie ochrony przeciwpożarowej budynków, innych obiektów
	budowlanych i terenów (Dz.U. 2010.109.719)
	Rozporządzenie Ministra Gospodarki, Pracy i Polityki Społecznej z dnia 14 stycznia
	2004 r. w sprawie bezpieczeństwa i higieny pracy przy czyszczeniu powierzchni,
	malowaniu natryskowym i natryskiwaniu cieplnym (Dz.U. 2004.16.156)
	Rozporządzenie Ministra Pracy i Polityki Społecznej z dnia 6 czerwca 2014 r. w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla
	zdrowia w środowisku pracy (Dz.U. 2014.0.817)
	Umowa europejska dotycząca międzynarodowego przewozu drogowego towarów
	niebezpiecznych (ADR) sporządzona w Genevie dnia 30 września 1957 r. (Dz.U.
	1975.35.189 z późniejszymi zmianami)
	Obwieszczenie Marszałka Sejmu Rzeczypospolitej Polskiej z dnia 15 października
	2009 r. w sprawie ogłoszenia jednolitego tekstu ustawy o ochronie
	przeciwpożarowej (Dz.U. 2009.178.1380 z późniejszymi zmianami)
	Ustawa z dnia 13 czerwca 2013 r. o gospodarce opakowaniami i odpadami
	opakowaniowymi (Dz.U. 2013.0.888) Obwieszczenie Ministra Gospodarki, Pracy i Polityki Społecznej z dnia 28 sierpnia
	2003 r. w sprawie ogłoszenia jednolitego tekstu rozporządzenia Ministra Pracy i
	Polityki Socjalnej w sprawie ogólnych przepisów bezpieczeństwa i higieny pracy (Dz.
	U. 2003.169.1650)
	Ustawa z dnia 19 sierpnia 2011 r. o przewozie towarów niebezpiecznych (Dz.U.
	2011.227.1367 z późniejszymi zmianami)
	Ustawa z dnia 14 grudnia 2012 r. o odpadach (Dz.U. 2013.0.21 z późniejszymi
	zmianami)
15.2 Chemical Safety	: No Chemical Safety Assessment has been carried out.
Assessment	·

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	: ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number vPvB = Very Persistent and Very Bioaccumulative N/A = Not available
Key literature references and sources for data	 Regulation (EC) No. 1272/2008 [CLP] ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 Directive 2012/18/EU, and relative amendments & additions Directive 2008/98/EC, and relative amendments & additions Directive 2009/161/EU, and relative amendments & additions CEPE Guidelines

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classi	fication	Justification
Skin Sens. 1, H317 Repr. 2, H361 Aquatic Chronic 3, H412		Calculation method Calculation method Calculation method
Full text of abbreviated H statements	H310 Fa H311 To H314 Ca H317 M H318 Ca H330 Fa H361 Sa H361 Sa H361 Sa H400 Vo H410 Vo H410 Vo H411 To H412 Ha	oxic if swallowed. atal in contact with skin. oxic in contact with skin. auses severe skin burns and eye damage. ay cause an allergic skin reaction. auses serious eye damage. atal if inhaled. uspected of damaging fertility or the unborn child. ery toxic to aquatic life. ery toxic to aquatic life with long lasting effects. oxic to aquatic life with long lasting effects. armful to aquatic life with long lasting effects. orrosive to the respiratory tract.
Full text of classifications [CLP/GHS]	: Acute Tox. 2 Acute Tox. 3 Aquatic Acute 1 Aquatic Chronic 1 Aquatic Chronic 2 Aquatic Chronic 3 Eye Dam. 1 Repr. 2 Skin Corr. 1B Skin Corr. 1C Skin Sens. 1 Skin Sens. 1	ACUTE TOXICITY - Category 2 ACUTE TOXICITY - Category 3 AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 2 AQUATIC HAZARD (LONG-TERM) - Category 3 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 TOXIC TO REPRODUCTION - Category 2 SKIN CORROSION/IRRITATION - Category 1B SKIN CORROSION/IRRITATION - Category 1C SKIN SENSITIZATION - Category 1 SKIN SENSITIZATION - Category 1
Date of printing	: 15, Apr, 2024.	

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II FIRETEX FFC250 Water Based Intumescent FFC250	
SECTION 16: Other in	formation
Date of issue/ Date of revision	: 15, Apr, 2024
Date of previous issue	: 17, Sep, 2023
	. If there is no previous validation date please contact your supplier for more

If there is no previous validation date please contact your supplier for more information.

Version

: 16

Notice to reader

In accordance with Regulation (EC) 1907/2006, REACH Regulation, Articles 31, 37, any required hazard-related information on the use of substances received as downstream user will be sent forward. Consequently, the safety data sheets for some products will contain a SUMI - Safe Use of Mixture Information - attached to the safety data sheet.

SUMI(s) will be added to the SDS for products if both the following conditions are met:

• The product is classified as hazardous for health

• The product contains one or more REACH-registered substances for which extended safety data sheets (exposure scenarios) have been provided

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS. the manufacturer cannot be responsible for SDSs obtained from any other source.