

# SAFETY DATA SHEET

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : MACROPOXY G280 Epoxy Blast Primer - Base

**Product code** : G280B

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Material uses** : Paint or paint related material.

: Industrial use only.

### 1.3 Details of the supplier of the safety data sheet

Sherwin-Williams Protective & Marine  
Tower Works  
Kestor Street  
Bolton  
BL2 2AL  
United Kingdom  
+44 (0) 1204 521771

**e-mail address of person responsible for this SDS** : hse.pm.emea@sherwin.com

### 1.4 Emergency telephone number

#### National advisory body/Poison Centre

**Telephone number** : 111 (general public) /0344 892 111 (Medical professional (NHS) only)

#### Supplier

**Telephone number** : +(44)-870-8200 418

**Hours of operation** : Emergency contact available 24 hours a day

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 2, H225

Skin Irrit. 2, H315

Eye Irrit. 2, H319

Repr. 2, H361d (Unborn child)

STOT SE 3, H336

STOT RE 2, H373

Asp. Tox. 1, H304

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

**SECTION 2: Hazards identification**

**Hazard pictograms**



**Signal word**

: Danger

**Hazard statements**

: Highly flammable liquid and vapour.  
 Causes serious eye irritation.  
 Causes skin irritation.  
 Suspected of damaging the unborn child.  
 May be fatal if swallowed and enters airways.  
 May cause drowsiness or dizziness.  
 May cause damage to organs through prolonged or repeated exposure.  
 Harmful to aquatic life with long lasting effects.

**Precautionary statements**

**Prevention**

: Obtain special instructions before use. Wear protective gloves. Wear protective clothing. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment. Do not breathe vapour.

**Response**

: IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

**Storage**

: Store locked up.

**Disposal**

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Hazardous ingredients**

: Toluene

**Supplemental label elements**

: Contains epoxy constituents. May produce an allergic reaction. FOR INDUSTRIAL USE ONLY

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles**

: Not applicable.

**Special packaging requirements**

Not applicable.

**2.3 Other hazards**

**Other hazards which do not result in classification**

: None known.

The mixture may be a skin sensitizer. It may also be a skin irritant and repeated contact may increase this effect.

**SECTION 3: Composition/information on ingredients**

**3.2 Mixture**

:

| Product/ingredient name | Identifiers | % | Regulation (EC) No. 1272/2008 [CLP] | Type |
|-------------------------|-------------|---|-------------------------------------|------|
|                         |             |   |                                     |      |

**SECTION 3: Composition/information on ingredients**

|            |                                                                                       |           |                                                                                                                                                                                        |         |
|------------|---------------------------------------------------------------------------------------|-----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|
| Toluene    | REACH #:<br>01-2119471310-51<br>EC: 203-625-9<br>CAS: 108-88-3<br>Index: 601-021-00-3 | ≥25 - ≤50 | Flam. Liq. 2, H225<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>Repr. 2, H361d (Unborn child)<br>STOT SE 3, H336<br>STOT RE 2, H373<br>Asp. Tox. 1, H304<br>Aquatic Chronic 3, H412 | [1] [2] |
| 2-Propanol | REACH #:<br>01-2119457558-25<br>EC: 200-661-7<br>CAS: 67-63-0<br>Index: 603-117-00-0  | ≥10 - ≤25 | Flam. Liq. 2, H225<br>Eye Irrit. 2, H319<br>STOT SE 3, H336<br><br><b>See Section 16 for the full text of the H statements declared above.</b>                                         | [1] [2] |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern
- [6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

**SECTION 4: First aid measures**

**4.1 Description of first aid measures**

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

**4.2 Most important symptoms and effects, both acute and delayed**

There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

## **SECTION 4: First aid measures**

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Based on the properties of the epoxy constituent(s) and considering toxicological data on similar mixtures, this mixture may be a skin sensitiser and an irritant. It contains low molecular weight epoxy constituents which are irritating to eyes, mucous membrane and skin. Repeated skin contact may lead to irritation and to sensitisation, possibly with cross-sensitisation to other epoxies. Skin contact with the mixture and exposure to spray mist and vapour should be avoided.

### **4.3 Indication of any immediate medical attention and special treatment needed**

**Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

**Specific treatments** : No specific treatment.

See toxicological information (Section 11)

## **SECTION 5: Firefighting measures**

### **5.1 Extinguishing media**

**Suitable extinguishing media** : Recommended: alcohol-resistant foam, carbon dioxide, powders.

**Unsuitable extinguishing media** : Do not use water jet.

### **5.2 Special hazards arising from the substance or mixture**

**Hazards from the substance or mixture** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

**Hazardous combustion products** : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

### **5.3 Advice for firefighters**

**Special protective actions for fire-fighters** : Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.

**Special protective equipment for fire-fighters** : Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

## **SECTION 6: Accidental release measures**

### **6.1 Personal precautions, protective equipment and emergency procedures**

**For non-emergency personnel** : Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.

Keep unnecessary and unprotected personnel from entering.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### **6.2 Environmental precautions**

: Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

## SECTION 6: Accidental release measures

**6.3 Methods and material for containment and cleaning up** : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.

**6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

**7.1 Precautions for safe handling** : Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing and floors should be of the conducting type. Keep away from heat, sparks and flame. No sparking tools should be used. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Put on appropriate personal protective equipment (see Section 8). Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or watercourses.

### Information on fire and explosion protection

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

**7.2 Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations.

### Notes on joint storage

Keep away from: oxidising agents, strong alkalis, strong acids.

### Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Contaminated absorbent material may pose the same hazard as the spilt product.

Store in closed original container at temperatures between 5°C and 25°C.

### 7.3 Specific end use(s)

**Recommendations** : Not available.

**Industrial sector specific solutions** : Not available.

## SECTION 7: Handling and storage

Good housekeeping standards, regular safe removal of waste materials and regular maintenance of spray booth filters will minimise the risks of spontaneous combustion and other fire hazards.

**Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations.**

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 8.1 Control parameters

#### Occupational exposure limits

| Product/ingredient name | Exposure limit values                                                                                                                                                                                              |
|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Toluene                 | <b>EH40/2005 WELs (United Kingdom (UK), 8/2018). Absorbed through skin.</b><br>STEL: 384 mg/m <sup>3</sup> 15 minutes.<br>TWA: 191 mg/m <sup>3</sup> 8 hours.<br>TWA: 50 ppm 8 hours.<br>STEL: 100 ppm 15 minutes. |
| 2-Propanol              | <b>EH40/2005 WELs (United Kingdom (UK), 8/2018).</b><br>STEL: 1250 mg/m <sup>3</sup> 15 minutes.<br>STEL: 500 ppm 15 minutes.<br>TWA: 999 mg/m <sup>3</sup> 8 hours.<br>TWA: 400 ppm 8 hours.                      |

- Recommended monitoring procedures** :
- If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
  - Regular monitoring of all work areas should be carried out at all times, including areas that may not be equally ventilated.

#### DNELs/DMELs

| Product/ingredient name | Type | Exposure              | Value                  | Population                | Effects  |
|-------------------------|------|-----------------------|------------------------|---------------------------|----------|
| Toluene                 | DNEL | Short term Inhalation | 226 mg/m <sup>3</sup>  | Human via the environment | Systemic |
|                         | DNEL | Short term Inhalation | 226 mg/m <sup>3</sup>  | Human via the environment | Local    |
|                         | DNEL | Long term Dermal      | 226 mg/m <sup>3</sup>  | Human via the environment | Systemic |
|                         | DNEL | Long term Inhalation  | 226 mg/kg bw/day       | Human via the environment | Systemic |
|                         | DNEL | Long term Inhalation  | 56.5 mg/m <sup>3</sup> | Human via the environment | Systemic |
|                         | DNEL | Long term Oral        | 8.13 mg/kg bw/day      | Human via the environment | Systemic |
|                         | DNEL | Long term Inhalation  | 192 mg/m <sup>3</sup>  | Workers                   | Systemic |
|                         | DNEL | Long term Inhalation  | 192 mg/m <sup>3</sup>  | Workers                   | Local    |

**SECTION 8: Exposure controls/personal protection**

|            |      |                       |                        |           |          |
|------------|------|-----------------------|------------------------|-----------|----------|
| 2-Propanol | DNEL | Short term Inhalation | 384 mg/m <sup>3</sup>  | Workers   | Systemic |
|            | DNEL | Short term Inhalation | 384 mg/m <sup>3</sup>  | Workers   | Local    |
|            | DNEL | Long term Dermal      | 384 mg/kg bw/day       | Workers   | Systemic |
|            | DNEL | Long term Inhalation  | 56.5 mg/m <sup>3</sup> | Consumers | Local    |
|            | DNEL | Long term Dermal      | 888 mg/kg bw/day       | Workers   | Systemic |
|            | DNEL | Long term Inhalation  | 500 mg/m <sup>3</sup>  | Workers   | Systemic |
|            | DNEL | Long term Dermal      | 319 mg/kg bw/day       | Consumers | Systemic |
|            | DNEL | Long term Inhalation  | 89 mg/m <sup>3</sup>   | Consumers | Systemic |
|            | DNEL | Long term Oral        | 26 mg/kg bw/day        | Consumers | Systemic |

**PNECs**

| Product/ingredient name | Compartment Detail     | Value           | Method Detail      |
|-------------------------|------------------------|-----------------|--------------------|
| Toluene                 | Fresh water sediment   | 0.68 mg/l       | Assessment Factors |
|                         | Marine water sediment  | 0.68 mg/l       | Assessment Factors |
|                         | Sewage Treatment Plant | 13.61 mg/l      | Assessment Factors |
| 2-Propanol              | Soil                   | 2.89 mg/kg      | Assessment Factors |
|                         | Fresh water sediment   | 16.39 mg/kg dwt | -                  |
|                         | Marine water sediment  | 16.39 mg/kg dwt | -                  |
|                         | Fresh water            | 140.9 mg/l      | -                  |
|                         | Marine water           | 140.9 mg/l      | -                  |
|                         | Sewage Treatment Plant | 2251 mg/l       | -                  |
|                         | Sediment               | 552 mg/kg dwt   | -                  |
|                         | Soil                   | 28 mg/kg        | -                  |
|                         | Secondary Poisoning    | 160 mg/kg       | -                  |

**8.2 Exposure controls**

- Appropriate engineering controls** : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.
- : Users are advised to consider national Occupational Exposure Limits or other equivalent values.

**Individual protection measures**

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Use safety eyewear designed to protect against splash of liquids.
- Skin protection**
- Hand protection** : Wear suitable gloves tested to EN374.
- Gloves** :

## SECTION 8: Exposure controls/personal protection

Gloves for term exposure/splash protection (less than 10 min): Nitrile > 0.12 mm  
Gloves for splash protection need to be changed immediately when in contact with chemicals.

Gloves for repeated or prolonged exposure (breakthrough time > 240 min.) When the hazardous ingredients in Section 3 contain any of the following: Aromatic solvents (Xylene, Toluene) or Aliphatic solvents or Mineral Oil use: Polyvinyl alcohol (PVA) gloves 0.2-0.3 mm Otherwise use: Butyl gloves > 0.3 mm For long term exposure or spills (breakthrough time > 480 min.): Use PE laminated gloves as under gloves

Due to many conditions (e.g. temperature, abrasion) the practical usage of a chemical protective glove in practice may be much shorter than the permeation time determined through testing.

The recommendation for the type or types of glove to use when handling this product is based on information from the following source: Solvent resin manufacturers and European Solvents Industry Group (ESIG).

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

### **Body protection**

- : Personnel should wear antistatic clothing made of natural fibres or of high-temperature-resistant synthetic fibres.
- : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

### **Other skin protection**

- : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

### **Respiratory protection**

- : Application methods:
  - Brush or roller. Approved/certified respirator with organic vapour cartridge. Filter type: A2 P2 (EN14387).
  - Manual spraying. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

### **Environmental exposure controls**

- : Do not allow to enter drains or watercourses.

**Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.**



## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

|                                                     |                                                                                   |
|-----------------------------------------------------|-----------------------------------------------------------------------------------|
| <b>Physical state</b>                               | : Liquid.                                                                         |
| <b>Colour</b>                                       | : Various                                                                         |
| <b>Odour</b>                                        | : Paint                                                                           |
| <b>Odour threshold</b>                              | : Not Available (Not Tested).                                                     |
| <b>pH</b>                                           | : Not relevant/applicable due to nature of the product.                           |
| <b>Melting point/freezing point</b>                 | : Not relevant/applicable due to nature of the product.                           |
| <b>Initial boiling point and boiling range</b>      | : 81°C                                                                            |
| <b>Flash point</b>                                  | : Closed cup: 12°C [Pensky-Martens Closed Cup]                                    |
| <b>Evaporation rate</b>                             | : 2 (butyl acetate = 1)                                                           |
| <b>Flammability (solid, gas)</b>                    | : Not relevant/applicable due to nature of the product.                           |
| <b>Upper/lower flammability or explosive limits</b> | : LEL: 1% (Toluene)<br>UEL: 12.7% (2-Propanol)                                    |
| <b>Vapour pressure</b>                              | : 4.4 kPa [at 20°C]                                                               |
| <b>Vapour density</b>                               | : 2.07 [Air = 1]                                                                  |
| <b>Relative density</b>                             | : 1.22                                                                            |
| <b>Solubility(ies)</b>                              | : Not relevant/applicable due to nature of the product.                           |
| <b>Partition coefficient: n-octanol/ water</b>      | : Not relevant/applicable due to nature of the product.                           |
| <b>Auto-ignition temperature</b>                    | : Not relevant/applicable due to nature of the product.                           |
| <b>Decomposition temperature</b>                    | : Not relevant/applicable due to nature of the product.                           |
| <b>Viscosity</b>                                    | : Kinematic (40°C): <0.205 cm <sup>2</sup> /s                                     |
| <b>Explosive properties</b>                         | : Under normal conditions of storage and use, hazardous reactions will not occur. |
| <b>Oxidising properties</b>                         | : Under normal conditions of storage and use, hazardous reactions will not occur. |

## SECTION 10: Stability and reactivity

|                                                |                                                                                                                                  |
|------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| <b>10.1 Reactivity</b>                         | : No specific test data related to reactivity available for this product or its ingredients.                                     |
| <b>10.2 Chemical stability</b>                 | : Stable under recommended storage and handling conditions (see Section 7).                                                      |
| <b>10.3 Possibility of hazardous reactions</b> | : Under normal conditions of storage and use, hazardous reactions will not occur.                                                |
| <b>10.4 Conditions to avoid</b>                | : When exposed to high temperatures may produce hazardous decomposition products.                                                |
| <b>10.5 Incompatible materials</b>             | : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids. |
| <b>10.6 Hazardous decomposition products</b>   | : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.        |

Refer to Section 7: **HANDLING AND STORAGE** and Section 8: **EXPOSURE CONTROLS/PERSONAL PROTECTION** for additional handling information and protection of employees.

**SECTION 11: Toxicological information**

**11.1 Information on toxicological effects**

There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Based on the properties of the epoxy constituent(s) and considering toxicological data on similar mixtures, this mixture may be a skin sensitizer and an irritant. It contains low molecular weight epoxy constituents which are irritating to eyes, mucous membrane and skin. Repeated skin contact may lead to irritation and to sensitisation, possibly with cross-sensitisation to other epoxies. Skin contact with the mixture and exposure to spray mist and vapour should be avoided.

**Acute toxicity**

| Product/ingredient name | Result                 | Species | Dose                | Exposure |
|-------------------------|------------------------|---------|---------------------|----------|
| Toluene                 | LC50 Inhalation Vapour | Rat     | 49 g/m <sup>3</sup> | 4 hours  |
| 2-Propanol              | LD50 Oral              | Rat     | 636 mg/kg           | -        |
|                         | LD50 Dermal            | Rabbit  | 12800 mg/kg         | -        |
|                         | LD50 Oral              | Rat     | 5000 mg/kg          | -        |

**Acute toxicity estimates**

No data available

**Irritation/Corrosion**

| Product/ingredient name | Result                   | Species | Score | Exposure                 | Observation |
|-------------------------|--------------------------|---------|-------|--------------------------|-------------|
| Toluene                 | Eyes - Mild irritant     | Rabbit  | -     | 0.5 minutes              | -           |
|                         | Eyes - Mild irritant     | Rabbit  | -     | 100 milligrams           | -           |
|                         | Eyes - Severe irritant   | Rabbit  | -     | 870 Micrograms           | -           |
|                         | Skin - Mild irritant     | Pig     | -     | 24 hours 2 milligrams    | -           |
|                         | Skin - Mild irritant     | Rabbit  | -     | 24 hours 250 microliters | -           |
|                         | Skin - Mild irritant     | Rabbit  | -     | 435 milligrams           | -           |
| 2-Propanol              | Skin - Moderate irritant | Rabbit  | -     | 24 hours 20 milligrams   | -           |
|                         | Skin - Moderate irritant | Rabbit  | -     | 500 milligrams           | -           |
|                         | Eyes - Moderate irritant | Rabbit  | -     | 24 hours 100 milligrams  | -           |
|                         | Eyes - Moderate irritant | Rabbit  | -     | 10 milligrams            | -           |
|                         | Eyes - Severe irritant   | Rabbit  | -     | 100 milligrams           | -           |
|                         | Skin - Mild irritant     | Rabbit  | -     | 500 milligrams           | -           |

**Conclusion/Summary** : Not available.

**Sensitisation**

No data available

## SECTION 11: Toxicological information

**Conclusion/Summary** : Not available.

### Mutagenicity

No data available

### Carcinogenicity

No data available

### Reproductive toxicity

No data available

### Teratogenicity

No data available

### Specific target organ toxicity (single exposure)

| Product/ingredient name | Category   | Route of exposure | Target organs    |
|-------------------------|------------|-------------------|------------------|
| Toluene                 | Category 3 | Not applicable.   | Narcotic effects |
| 2-Propanol              | Category 3 | Not applicable.   | Narcotic effects |

### Specific target organ toxicity (repeated exposure)

| Product/ingredient name | Category   | Route of exposure | Target organs  |
|-------------------------|------------|-------------------|----------------|
| Toluene                 | Category 2 | Not determined    | Not determined |

### Aspiration hazard

| Product/ingredient name | Result                         |
|-------------------------|--------------------------------|
| Toluene                 | ASPIRATION HAZARD - Category 1 |

**Other information** : Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

There are no data available on the mixture itself.  
Do not allow to enter drains or watercourses.

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

| Product/ingredient name | Result                               | Species                                       | Exposure |
|-------------------------|--------------------------------------|-----------------------------------------------|----------|
| Toluene                 | Acute EC50 12500 µg/l Fresh water    | Algae - Pseudokirchneriella subcapitata       | 72 hours |
|                         | Acute EC50 11600 µg/l Fresh water    | Crustaceans - Gammarus pseudolimnaeus - Adult | 48 hours |
|                         | Acute EC50 5.56 mg/l Fresh water     | Daphnia - Daphnia magna - Neonate             | 48 hours |
|                         | Acute LC50 5500 µg/l Fresh water     | Fish - Oncorhynchus kisutch - Fry             | 96 hours |
| 2-Propanol              | Chronic NOEC 1000 µg/l Fresh water   | Daphnia - Daphnia magna                       | 21 days  |
|                         | Acute EC50 10100 mg/l Fresh water    | Daphnia - Daphnia magna                       | 48 hours |
|                         | Acute LC50 1400000 µg/l Marine water | Crustaceans - Crangon crangon                 | 48 hours |
|                         | Acute LC50 4200 mg/l Fresh water     | Fish - Rasbora heteromorpha                   | 96 hours |

### 12.2 Persistence and degradability

| Product/ingredient name | Test | Result | Dose | Inoculum |
|-------------------------|------|--------|------|----------|
| No data available       |      |        |      |          |

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II

MACROPOXY G280 Epoxy Blast Primer - Base

G280B

## SECTION 12: Ecological information

**Conclusion/Summary** : Not available.

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|-------------------------|-------------------|------------|------------------|
| Toluene                 | -                 | -          | Readily          |
| 2-Propanol              | -                 | -          | Readily          |

### 12.3 Bioaccumulative potential

| Product/ingredient name | LogP <sub>ow</sub> | BCF | Potential |
|-------------------------|--------------------|-----|-----------|
| Toluene                 | -                  | 90  | low       |

### 12.4 Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Not available.

### 12.5 Results of PBT and vPvB assessment

**PBT** : Not applicable.

**vPvB** : Not applicable.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : Yes.

**European waste catalogue (EWC)** : waste paint and varnish containing organic solvents or other hazardous substances 08 01 11\*

**Disposal considerations** : Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Disposal considerations** : Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.

**European waste catalogue (EWC)** : packaging containing residues of or contaminated by hazardous substances 15 01 10\*

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II




MACROPOXY G280 Epoxy Blast Primer - Base

G280B

## SECTION 13: Disposal considerations

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

|                                           | ADR/RID                                                                                | IMDG                                                                                   | IATA                                                                                     |
|-------------------------------------------|----------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|
| 14.1 UN number                            | UN1263                                                                                 | UN1263                                                                                 | UN1263                                                                                   |
| 14.2 UN proper shipping name              | PAINT                                                                                  | PAINT                                                                                  | PAINT                                                                                    |
| 14.3 Transport Hazard Class(es)/ Label(s) | 3<br> | 3<br> | 3<br> |
| 14.4 Packing group                        | II                                                                                     | II                                                                                     | II                                                                                       |
| 14.5 Environmental hazards                | No.                                                                                    | No.                                                                                    | No.                                                                                      |
| Additional information                    | <b>Special provisions</b> 640 (C)<br><b>Tunnel code</b> D/E                            | <b>Emergency schedules</b> F-E,<br>S-E                                                 | -                                                                                        |

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code** : Not applicable.

**Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.**

## SECTION 15: Regulatory information

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU Regulation (EC) No. 1907/2006 (REACH)**

**Annex XIV - List of substances subject to authorisation**

**Annex XIV**

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

## SECTION 15: Regulatory information

### Other EU regulations

VOC content (2010/75/EU) : 48.9 w/w  
596 g/l

### Seveso Directive

This product may add to the calculation for determining whether a site is within the scope of the Seveso Directive on major accident hazards.

### National regulations

15.2 Chemical safety assessment : No Chemical Safety Assessment has been carried out.

## SECTION 16: Other information

Indicates information that has changed from previously issued version.

### Abbreviations and acronyms

: ATE = Acute Toxicity Estimate  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
EUH statement = CLP-specific Hazard statement  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number  
vPvB = Very Persistent and Very Bioaccumulative

### Key literature references and sources for data

: Regulation (EC) No. 1272/2008 [CLP]  
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road  
IATA = International Air Transport Association  
IMDG = International Maritime Dangerous Goods  
Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2015/830  
Directive 2012/18/EU, and relative amendments & additions  
Directive 2008/98/EC, and relative amendments & additions  
Directive 2009/161/EU, and relative amendments & additions  
CEPE Guidelines

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

| Classification                | Justification         |
|-------------------------------|-----------------------|
| Flam. Liq. 2, H225            | On basis of test data |
| Skin Irrit. 2, H315           | Calculation method    |
| Eye Irrit. 2, H319            | Calculation method    |
| Repr. 2, H361d (Unborn child) | Calculation method    |
| STOT SE 3, H336               | Calculation method    |
| STOT RE 2, H373               | Calculation method    |
| Asp. Tox. 1, H304             | Calculation method    |
| Aquatic Chronic 3, H412       | Calculation method    |

### Full text of abbreviated H statements

: H225 Highly flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H361d Suspected of damaging the unborn child.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H412 Harmful to aquatic life with long lasting effects.

**SECTION 16: Other information**

**Full text of classifications [CLP/GHS]** : Aquatic Chronic 3, H412 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3  
Asp. Tox. 1, H304 ASPIRATION HAZARD - Category 1  
Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2  
Flam. Liq. 2, H225 FLAMMABLE LIQUIDS - Category 2  
Repr. 2, H361d REPRODUCTIVE TOXICITY (Unborn child) - Category 2  
Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2  
STOT RE 2, H373 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2  
STOT SE 3, H336 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Narcotic effects) - Category 3

**Date of printing** : 18, Feb, 2019.

**Date of issue/ Date of revision** : 18, Feb, 2019

**Date of previous issue** : 09, Oct, 2018

: If there is no previous validation date please contact your supplier for more information.

**Version** : 5.04

**Notice to reader**

*It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become make themselves aware of and understand the data contained in this SDS and any hazards that may be associated with the product. This information is provided in good faith and believed to be accurate as of the effective date mentioned herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can may change later the composition, hazards and risks of the product. Products shall should not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to, the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for the use of the product are not under the manufacturer's control of the manufacturer; the customer/buyer/user is responsible to for determine determining the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS, without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be held responsible for SDSs obtained from any other source.*