

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : MACROPOXY M111 Epoxy Wet Blast Primer - Base

Product code : M111B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Material uses : Paint or paint related material.

: Industrial use only.

1.3 Details of the supplier of the safety data sheet

Sherwin-Williams UK Limited - Protective & Marine
Coatings Division EMEA
Tower Works
Kestor Street
Bolton
BL2 2AL
United Kingdom
+44 (0) 1204 521771

The Sherwin-Williams Company
Inver France SAS
2 Rue Jean Revaus - BP 80088 - 79102
Thouars CEDEX
France

e-mail address of person responsible for this SDS : hse.pm.emea@sherwin.com

1.4 Emergency telephone number

National advisory body/Poison Center

Telephone number : 112 - Request Poison Information

Supplier

Telephone number : +(44)-870-8200 418

Hours of operation : Emergency contact available 24 hours a day

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 2, H225

Skin Irrit. 2, H315

Eye Irrit. 2, H319

Skin Sens. 1, H317

STOT SE 3, H336

Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

SECTION 2: Hazards identification

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :   

Signal word : Danger

Hazard statements : Highly flammable liquid and vapor.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
May cause drowsiness or dizziness.
Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention : Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment. Avoid breathing vapor. Wash thoroughly after handling.

Response : Collect spillage.

Storage : Not applicable.

Disposal : Not applicable.

Hazardous ingredients : Methyl Ethyl Ketone
Epoxy Polymer
1-Methoxy-2-propanol

Supplemental label elements : Contains epoxy constituents. May produce an allergic reaction. FOR INDUSTRIAL USE ONLY

Special packaging requirements

Not applicable.

2.3 Other hazards

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Other hazards which do not result in classification : None known.

SECTION 3: Composition/information on ingredients

3.2 Mixture :

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Zinc Phosphate	EC: 231-944-3 CAS: 7779-90-0 Index: 030-011-00-6	≥10 - ≤24	Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 1	[1]
Methyl Ethyl Ketone	REACH #: 01-2119457290-43 EC: 201-159-0 CAS: 78-93-3 Index: 606-002-00-3	≥10 - <20	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066	-	[1] [2]
Epoxy Polymer	CAS: 25036-25-3	≥10 - ≤25	Skin Irrit. 2, H315	-	[1]

SECTION 3: Composition/information on ingredients

1-Methoxy-2-propanol	REACH #: 01-2119457435-35 EC: 203-539-1 CAS: 107-98-2 Index: 603-064-00-3	≤10	Eye Irrit. 2, H319 Skin Sens. 1, H317 Flam. Liq. 3, H226 STOT SE 3, H336	-	[1] [2]
Zinc Oxide	REACH #: 01-2119463881-32 EC: 215-222-5 CAS: 1314-13-2 Index: 030-013-00-7	≤0.75	Aquatic Acute 1, H400 Aquatic Chronic 1, H410 See Section 16 for the full text of the H statements declared above.	M [Acute] = 1 M [Chronic] = 1	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

SECTION 4: First aid measures

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Based on the properties of the epoxy constituent(s) and considering toxicological data on similar mixtures, this mixture may be a skin sensitizer and an irritant. It contains low-molecular weight epoxy constituents which are irritating to eyes, mucous membranes and skin. Repeated skin contact may lead to irritation and to sensitization, possibly with cross-sensitization to other epoxies. Skin contact with the mixture and exposure to spray, mist and vapors should be avoided.

Contains Epoxy Polymer. May produce an allergic reaction.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

See toxicological information (Section 11)

SECTION 5: Firefighting measures**5.1 Extinguishing media**

- Suitable extinguishing media** : Recommended: alcohol-resistant foam, CO₂, powders, water spray or mist.
- Unsuitable extinguishing media** : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.
- Hazardous combustion products** : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.
- Special protective equipment for fire-fighters** : Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

- For non-emergency personnel** : Exclude sources of ignition and ventilate the area. Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8.
- Keep unnecessary and unprotected personnel from entering.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

SECTION 6: Accidental release measures

6.3 Methods and materials for containment and cleaning up : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.

6.4 Reference to other sections : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling : Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing and floors should be of the conducting type. Keep away from heat, sparks and flame. No sparking tools should be used. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Put on appropriate personal protective equipment (see Section 8). Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or watercourses.

Information on fire and explosion protection

Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapors in all cases. In such circumstances, they should wear a compressed-air-fed respirator during the spraying process and until the particulate and solvent vapor concentrations have fallen below the exposure limits.

7.2 Conditions for safe storage, including any incompatibilities : Store in accordance with local regulations.

Notes on joint storage

Keep away from: oxidizing agents, strong alkalis, strong acids.

Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking. Prevent unauthorized access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Contaminated absorbent material may pose the same hazard as the spilled product. Store in closed original container at temperatures between 5°C and 25°C.

7.3 Specific end use(s)

Recommendations

: Not available.

SECTION 7: Handling and storage

Industrial sector specific solutions : Not available.

Good housekeeping standards, regular safe removal of waste materials and regular maintenance of spray booth filters will minimise the risks of spontaneous combustion and other fire hazards.

Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters**Occupational exposure limits**

Product/ingredient name	Exposure limit values
Methyl Ethyl Ketone	Work environment authority Regulation 2018:1 (Sweden, 9/2021). TWA: 50 ppm 8 hours. TWA: 150 mg/m ³ 8 hours. STEL: 300 ppm 15 minutes. STEL: 900 mg/m ³ 15 minutes.
1-Methoxy-2-propanol	Work environment authority Regulation 2018:1 (Sweden, 9/2021). Absorbed through skin. STEL: 150 ppm 15 minutes. STEL: 568 mg/m ³ 15 minutes. TWA: 190 mg/m ³ 8 hours. TWA: 50 ppm 8 hours.

Biological exposure indices

No exposure indices known.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following:
European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

: Regular monitoring of all work areas should be carried out at all times, including areas that may not be equally ventilated.

DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
Methyl Ethyl Ketone	DNEL	Long term Dermal	1161 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	600 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	412 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Long term Inhalation	106 mg/m ³	General population [Consumers]	Systemic
	DNEL	Long term Oral	31 mg/kg bw/day	General population [Consumers]	Systemic

SECTION 8: Exposure controls/personal protection

1-Methoxy-2-propanol	DNEL	Short term Inhalation	553.5 mg/m ³	Workers	Local
	DNEL	Long term Inhalation	369 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	183 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	43.9 mg/m ³	General population [Consumers]	Systemic
	DNEL	Long term Dermal	78 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Long term Oral	33 mg/kg bw/day	General population [Consumers]	Systemic
Zinc Oxide	DNEL	Long term Inhalation	5 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	0.5 mg/m ³	Workers	Local
	DNEL	Long term Dermal	83 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	2.5 mg/m ³	General population	Systemic
	DNEL	Long term Dermal	83 mg/kg bw/day	General population	Systemic
	DNEL	Long term Oral	0.83 mg/kg bw/day	General population	Systemic

PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail
Methyl Ethyl Ketone	Fresh water	55.8 mg/l	-
	Marine water	55.8 mg/l	-
	Sewage Treatment Plant	709 mg/l	-
	Sediment	284.7 mg/kg dwt	-
	Soil	22.5 mg/kg	-
	Secondary Poisoning	1000 mg/kg	-
1-Methoxy-2-propanol	Fresh water	10 mg/l	-
	Fresh water sediment	52.3 mg/kg	-
	Marine water sediment	5.2 mg/kg	-
	Soil	4.59 mg/kg	-
	Sewage Treatment Plant	100 mg/l	-
	Plant		-
Zinc Oxide	Fresh water	0.0206 mg/l	-
	Marine water	0.0061 mg/l	-
	Sewage Treatment Plant	0.1 mg/l	-
	Fresh water sediment	117.8 mg/kg dwt	-
	Marine water sediment	56.5 mg/kg dwt	-
	Soil	35.6 mg/kg dwt	-

8.2 Exposure controls***Appropriate engineering controls***

- : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn.
- : Users are advised to consider national Occupational Exposure Limits or other equivalent values.

Individual protection measures

SECTION 8: Exposure controls/personal protection

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Use safety eyewear designed to protect against splash of liquids.
- Skin protection**
- Hand protection**
- Gloves** : Wear suitable gloves tested to EN374.
- : Gloves for short term exposure/splash protection (less than 10 min.): Nitrile>0.12 mm
Gloves for splash protection need to be changed immediately when in contact with chemicals.
Gloves for repeated or prolonged exposure (breakthrough time > 240 min.)
When the hazardous ingredients in Section 3 contain any of the following: Aromatic solvents (Xylene, Toluene) or Aliphatic solvents or Mineral Oil use: Polyvinyl alcohol (PVA) gloves 0.2-0.3 mm
Otherwise use: Butyl gloves >0.3 mm
For long term exposure or spills (breakthrough time >480 min.): Use PE laminated gloves as under gloves
Due to many conditions (e.g. temperature, abrasion) the practical usage of a chemical protective glove in practice may be much shorter than the permeation time determined through testing.
The recommendation for the type or types of glove to use when handling this product is based on information from the following source: Solvent resin manufacturers and European Solvents Industry Group (ESIG)
There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.
The breakthrough time must be greater than the end use time of the product.
The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.
Gloves should be replaced regularly and if there is any sign of damage to the glove material.
Always ensure that gloves are free from defects and that they are stored and used correctly.
The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.
Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.
The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
- Body protection** : Personnel should wear antistatic clothing made of natural fibers or of high-temperature-resistant synthetic fibers.
- : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

SECTION 8: Exposure controls/personal protection

Respiratory protection : Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Recommended: A2P2 (EN14387). Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Environmental exposure controls : Do not allow to enter drains or watercourses.

Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state	: Liquid.
Color	: Orange.
Odor	: Paint
Odor threshold	: Not Available (Not Tested).
pH	: Not relevant/applicable due to nature of the product. insoluble in water.
Melting point/freezing point	: Not relevant/applicable due to nature of the product.
Initial boiling point and boiling range	: 78°C
Flash point	: Closed cup: 9°C [Pensky-Martens Closed Cup]
Evaporation rate	: 5.6 (butyl acetate = 1)
Flammability	: Flammable liquid.
Lower and upper explosion limit	: LEL: 1.5% (1-Methoxy-2-propanol) UEL: 13.74% (1-Methoxy-2-propanol)
Vapor pressure	: 12.1 kPa (90.6 mm Hg)
Relative vapor density	: 2.48 [Air = 1]
Relative density	: 1.68
Solubility(ies)	:

Media	Result
cold water	Not soluble

Partition coefficient: n-octanol/ water : Not relevant/applicable due to nature of the product.

Auto-ignition temperature :

Ingredient name	°C	°F	Method
1-Methoxy-2-propanol	286	546.8	
Methyl Ethyl Ketone	475	887	

Decomposition temperature : Not relevant/applicable due to nature of the product.

Viscosity : Kinematic (40°C): >20.5 mm²/s

Explosive properties : Under normal conditions of storage and use, hazardous reactions will not occur.

Oxidizing properties : Under normal conditions of storage and use, hazardous reactions will not occur.

Particle characteristics

Median particle size : Not relevant/applicable due to nature of the product.

SECTION 9: Physical and chemical properties

9.2 Other information

Heat of combustion : 7.2 kJ/g

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : Stable under recommended storage and handling conditions (see Section 7).

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition products.

10.5 Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

10.6 Hazardous decomposition products : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Based on the properties of the epoxy constituent(s) and considering toxicological data on similar mixtures, this mixture may be a skin sensitizer and an irritant. It contains low-molecular weight epoxy constituents which are irritating to eyes, mucous membranes and skin. Repeated skin contact may lead to irritation and to sensitization, possibly with cross-sensitization to other epoxies. Skin contact with the mixture and exposure to spray, mist and vapors should be avoided.

Contains Epoxy Polymer. May produce an allergic reaction.

Acute toxicity

SECTION 11: Toxicological information

Product/ingredient name	Result	Species	Dose	Exposure
Methyl Ethyl Ketone 1-Methoxy-2-propanol	LD50 Dermal	Rabbit	6480 mg/kg	-
	LD50 Oral	Rat	2737 mg/kg	-
	LD50 Dermal	Rabbit	13 g/kg	-
	LD50 Oral	Rat	6600 mg/kg	-

Acute toxicity estimates

No data available

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Methyl Ethyl Ketone	Skin - Mild irritant	Rabbit	-	24 hours 14 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-
1-Methoxy-2-propanol	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-
Zinc Oxide	Skin - Mild irritant	Rabbit	-	500 mg	-
	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 mg	-

Conclusion/Summary : Not available.

Sensitization

No data available

Conclusion/Summary : Not available.

Mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

Teratogenicity

No data available

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Methyl Ethyl Ketone	Category 3	-	Narcotic effects
1-Methoxy-2-propanol	Category 3	-	Narcotic effects

Specific target organ toxicity (repeated exposure)

No data available

Aspiration hazard

No data available

11.2 Information on other hazards
11.2.1 Endocrine disrupting properties

SECTION 11: Toxicological information

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information**12.1 Toxicity**

There are no data available on the mixture itself.

Do not allow to enter drains or watercourses.

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

Product/ingredient name	Result	Species	Exposure
Zinc Phosphate Methyl Ethyl Ketone	Acute LC50 90 µg/l Fresh water	Fish - <i>Oncorhynchus mykiss</i>	96 hours
	Acute EC50 >500000 µg/l Marine water	Algae - <i>Skeletonema costatum</i>	96 hours
	Acute EC50 5091000 µg/l Fresh water	Daphnia - <i>Daphnia magna</i> - Larvae	48 hours
Zinc Oxide	Acute LC50 3220000 µg/l Fresh water	Fish - <i>Pimephales promelas</i>	96 hours
	Acute IC50 1.85 mg/l Marine water	Algae - <i>Skeletonema costatum</i>	96 hours
	Acute LC50 98 µg/l Fresh water	Daphnia - <i>Daphnia magna</i> - Neonate	48 hours
	Acute LC50 1.1 ppm Fresh water	Fish - <i>Oncorhynchus mykiss</i>	96 hours

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
No data available				

Conclusion/Summary : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Methyl Ethyl Ketone	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Zinc Phosphate	-	60960	High
Zinc Oxide	-	28960	High

12.4 Mobility in soil**Soil/water partition coefficient (K_{oc})** : Not available.**Mobility** : Not available.**12.5 Results of PBT and vPvB assessment**

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.

European waste catalogue (EWC) : waste paint and varnish containing organic solvents or other hazardous substances 08 01 11*

Disposal considerations : Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

Packaging






Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Disposal considerations : Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.

European waste catalogue (EWC) : packaging containing residues of or contaminated by hazardous substances 15 01 10*

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA
14.1 UN number or ID number	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT. Marine pollutant (Zinc Phosphate, Zinc Oxide)	PAINT
14.3 Transport Hazard Class(es)/ Label(s)	3  	3  	3 
14.4 Packing group	II	II	II
14.5 Environmental hazards	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.

SECTION 14: Transport information

Additional information	The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg. Special provisions 640 (C) Tunnel code D/E	The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg. Emergency schedules F-E, S-E	The environmentally hazardous substance mark may appear if required by other transportation regulations.
-------------------------------	---	--	--

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not applicable.

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
MACROPOXY M111 Epoxy Wet Blast Primer - Base	≥90	3
formaldehyde	<0.1	72
4,4'-isopropylidenediphenol	<0.01	66
toluene	≤0.1	48

Labeling : Not applicable.

Other EU regulations

VOC content (2010/75/EU) : 24.2 w/w
408 g/l

Explosive precursors : Not applicable.

Seveso Directive

This product may add to the calculation for determining whether a site is within the scope of the Seveso Directive on major accident hazards.

National regulations

Ordinance on Thermoset Plastics : Regulation AFS 2014:43 including its amendments is applicable when working with this product.

15.2 Chemical Safety Assessment : No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	: ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number vPvB = Very Persistent and Very Bioaccumulative N/A = Not available
Key literature references and sources for data	: Regulation (EC) No. 1272/2008 [CLP] ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 Directive 2012/18/EU, and relative amendments & additions Directive 2008/98/EC, and relative amendments & additions Directive 2009/161/EU, and relative amendments & additions CEPE Guidelines

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H336 Aquatic Chronic 2, H411	On basis of test data Calculation method Calculation method Calculation method Calculation method Calculation method

Full text of abbreviated H statements	: H225 H226 H315 H317 H319 H336 H400 H410 H411 EUH066	Highly flammable liquid and vapor. Flammable liquid and vapor. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. Toxic to aquatic life with long lasting effects. Repeated exposure may cause skin dryness or cracking.
Full text of classifications [CLP/GHS]	: Aquatic Acute 1 Aquatic Chronic 1 Aquatic Chronic 2 Eye Irrit. 2 Flam. Liq. 2 Flam. Liq. 3 Skin Irrit. 2 Skin Sens. 1 STOT SE 3	AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 FLAMMABLE LIQUIDS - Category 2 FLAMMABLE LIQUIDS - Category 3 SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITIZATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 3
Date of printing	: 15, Apr, 2024.	
Date of issue/ Date of revision	: 15, Apr, 2024	
Date of previous issue	: 21, Jan, 2024	

SECTION 16: Other information

: If there is no previous validation date please contact your supplier for more information.

Version : 18

Notice to reader

In accordance with Regulation (EC) 1907/2006, REACH Regulation, Articles 31, 37, any required hazard-related information on the use of substances received as downstream user will be sent forward. Consequently, the safety data sheets for some products will contain a SUMI - Safe Use of Mixture Information - attached to the safety data sheet.

SUMI(s) will be added to the SDS for products if both the following conditions are met:

- ***The product is classified as hazardous for health***
- ***The product contains one or more REACH-registered substances for which extended safety data sheets (exposure scenarios) have been provided***

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.