# SAFETY DATA SHEET

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier	
Product name	: EPIDEK M153 Epoxy Deck Coating - Aggregate
Product code	: M153C

1.2 Relevant identified uses of the substance or mixture and uses advised against		
Material uses	: Paint or paint related material.	
	: Industrial use only.	
1.3 Details of the supplier o sheet	f the safety data	
Sherwin-Williams Protective	e & Marine	
Tower Works Kestor Street		
Bolton		
BL2 2AL		
United Kingdom +44 (0) 1204 521771		
+44 (0) 1204 521771		

The Sherwin-Williams Company Inver France SAS 2 Rue Jean Revaus - BP 80088 - 79102 Thouars CEDEX France

e-mail address of person : hse.pm.emea@sherwin.com responsible for this SDS

# 1.4 Emergency telephone number

National advisory body/Poison Center			
: +45 82 12 12 12			
: +(44)-870-8200 418			
: Emergency contact available 24 hours a day			

# **SECTION 2: Hazards identification**

2.1 Classification of the s	substance or mixture
Product definition	: Mixture
<b>Classification according</b>	g to Regulation (EC) No. 1272/2008 [CLP/GHS]
The product is not classif	ied as hazardous according to Regulation (EC) 1272/2008 as amended.
See Section 16 for the ful	I text of the H statements declared above.
See Section 11 for more	detailed information on health effects and symptoms.
2.2 Label elements	
Signal word	: No signal word.
Hazard statements	: No known significant effects or critical hazards.

Date of issue/Date of revision	: 23, Apr, 2021	Date of previous issue	:02, Dec, 2020	Version : 1.02	1/13

# **SECTION 2: Hazards identification**

Precautionary statements	
Prevention	: Not applicable.
Response	: Not applicable.
Storage	: Not applicable.
Disposal	: Not applicable.
Supplemental label elements	: FOR INDUSTRIAL USE ONLY
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
Special packaging requirem	ents
Not applicable	

Not applicable.

#### 2.3 Other hazards

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do : None known. not result in classification

# SECTION 3: Composition/information on ingredients

:

#### 3.2 Mixture

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Туре
Crystalline Silica, non- respirable	EC: 238-878-4 CAS: 14808-60-7	≥90	Not classified.	[2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Type</u>

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

[6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

# **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

General	anything by	of doubt, or when sympton mouth to an unconscious p I seek medical advice.				ive
Eye contact		ntact lenses, irrigate copiou rt for at least 10 minutes ar				
Inhalation		fresh air. Keep person war if respiratory arrest occurs, connel.				is
Skin contact		ntaminated clothing and sh e recognized skin cleanser.				
Date of issue/Date of revision	: 23, Apr, 2021	Date of previous issue	:02, Dec, 2020	Version	: 1.02	2/13

# Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II

EPIDEK M153 Epoxy Deck Coating - Aggregate M153C

# **SECTION 4: First aid measures**

Ingestion	

: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training.

# 4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eve contact.

### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	Treat symptomatically. Contact poison treatment specialist immediately quantities have been ingested or inhaled.	if large
Specific treatments	No specific treatment.	

See toxicological information (Section 11)

SECTION 5: Firefighting	measures
5.1 Extinguishing media Suitable extinguishing media	: Recommended: alcohol-resistant foam, carbon dioxide, powders.
Unsuitable extinguishing media	: Do not use water jet.
5.2 Special hazards arising f	rom the substance or mixture
Hazards from the substance or mixture	<ul> <li>Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.</li> </ul>
Hazardous combustion products	: Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.
5.3 Advice for firefighters	
Special protective actions for fire-fighters	: Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.
Special protective equipment for fire-fighters	: Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

# **SECTION 6: Accidental release measures**

6.1 Personal precautions, pro	ote	ctive equipment and emergency procedures
For non-emergency personnel	:	Exclude sources of ignition and ventilate the area. Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8.
		Keep unnecessary and unprotected personnel from entering.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.
6.3 Methods and materials for containment and cleaning up	:	Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.
		-

# SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe : handling	<ul> <li>Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits.</li> <li>In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.</li> <li>Mixture may charge electrostatically: always use earthing leads when transferring from one container to another.</li> <li>Operators should wear antistatic footwear and clothing and floors should be of the conducting type.</li> <li>Keep away from heat, sparks and flame. No sparking tools should be used.</li> <li>Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding.</li> <li>Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.</li> <li>Put on appropriate personal protective equipment (see Section 8).</li> <li>Never use pressure to empty. Container is not a pressure vessel.</li> <li>Always keep in containers made from the same material as the original one.</li> <li>Comply with the health and safety at work laws.</li> <li>Do not allow to enter drains or watercourses.</li> <li>Information on fire and explosion protection</li> <li>Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air.</li> </ul>
7.2 Conditions for safe : storage, including any incompatibilities	<ul> <li>Store in accordance with local regulations.</li> <li>Notes on joint storage</li> <li>Keep away from: oxidizing agents, strong alkalis, strong acids.</li> <li>Additional information on storage conditions</li> <li>Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking.</li> <li>Prevent unauthorized access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.</li> <li>Contaminated absorbent material may pose the same hazard as the spilled product.</li> </ul>

# **SECTION 7: Handling and storage**

## 7.3 Specific end use(s)

Recommendations	: Not available.
Industrial sector specific	: Not available.
solutions	

Good housekeeping standards, regular safe removal of waste materials and regular maintenance of spray booth filters will minimise the risks of spontaneous combustion and other fire hazards.

# Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations.

# **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 8.1 Control parameters

#### **Occupational exposure limits**

Product/ingredi	ent name Exposure limit values
Crystalline Silica, non-respi	rable Working Environment Authority (Denmark, 5/2020).
Recommended monitoring procedures	<ul> <li>If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.</li> <li>Regular monitoring of all work areas should be carried out at all times, including areas that may not be equally ventilated.</li> </ul>
DNELs/DMELs No DNELs/DMELs available	
PNECs No PNECs available.	
8.2 Exposure controls	
Appropriate engineering controls	<ul> <li>Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn.</li> <li>Users are advised to consider national Occupational Exposure Limits or other equivalent values.</li> </ul>
Individual protection meas	
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Use safety eyewear designed to protect against splash of liquids.
Date of issue/Date of revision	23, Apr, 2021         Date of previous issue         : 02, Dec, 2020         Version         : 1.02         5/13

# **SECTION 8: Exposure controls/personal protection**

Skin protection	
Hand protection	: Wear suitable gloves tested to EN374.
Gloves	: Gloves for short term exposure/splash protection (less than 10 min.): Nitrile>0.12 mm
	Gloves for splash protection need to be changed immediately when in contact with chemicals.
	Gloves for repeated or prolonged exposure (breakthrough time > 240 min.) When the hazardous ingredients in Section 3 contain any of the following: Aromatic solvents (Xylene, Toluene) or Aliphatic solvents or Mineral Oil use: Polyvinyl alcohol (PVA) gloves 0.2-0.3 mm Otherwise use: Butyl gloves >0.3 mm
	For long term exposure or spills (breakthrough time >480 min.): Use PE laminated gloves as under gloves
	Due to many conditions (e.g. temperature, abrasion) the practical usage of a chemical protective glove in practice may be much shorter than the permeation time determined through testing.
	The recommendation for the type or types of glove to use when handling this product is based on information from the following source: Solvent resin manufacturers and European Solvents Industry Group (ESIG)
	There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. The breakthrough time must be greater than the end use time of the product.
	The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove
	material. Always ensure that gloves are free from defects and that they are stored and used
	correctly. The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.
	Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.
	The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
Body protection	<ul> <li>Personnel should wear antistatic clothing made of natural fibers or of high- temperature-resistant synthetic fibers.</li> </ul>
	<ul> <li>Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Other skin protection	<ul> <li>Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Respiratory protection	: Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Recommended: A2P2 (EN14387). Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	: Do not allow to enter drains or watercourses.

Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

# **SECTION 9: Physical and chemical properties**

# 9.1 Information on basic physical and chemical properties

#### Appearance

Appearance		
Physical state	:	Solid.
Color	:	Gray.
Odor	:	Solvent.
Odor threshold	:	Not Available (Not Tested).
pН	:	Not applicable.
Melting point/freezing point	:	Not relevant/applicable due to nature of the product.
Initial boiling point and boiling range	:	Not relevant/applicable due to nature of the product.
Flash point	:	Closed cup: 499°C [Pensky-Martens Closed Cup]
Evaporation rate	:	Not relevant/applicable due to nature of the product.
Flammability (solid, gas)	:	Not relevant/applicable due to nature of the product.
Upper/lower flammability or explosive limits	:	Not relevant/applicable due to nature of the product.
Vapor pressure	:	Not relevant/applicable due to nature of the product.
Vapor density	:	Not relevant/applicable due to nature of the product.
Relative density	:	2.64
Solubility(ies)	:	Not relevant/applicable due to nature of the product.
Partition coefficient: n-octanol/ water	:	Not relevant/applicable due to nature of the product.
Auto-ignition temperature	:	Not relevant/applicable due to nature of the product.
Decomposition temperature	:	Not relevant/applicable due to nature of the product.
Viscosity	:	Kinematic (40°C): >0.205 cm <sup>2</sup> /s
Explosive properties	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Oxidizing properties	:	Under normal conditions of storage and use, hazardous reactions will not occur.

# **SECTION 10: Stability and reactivity**

-	-	
10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredie	ents.
10.2 Chemical stability	Stable under recommended storage and handling conditions (see Section 7).	
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occu	ır.
10.4 Conditions to avoid	When exposed to high temperatures may produce hazardous decomposition products.	
10.5 Incompatible materials	Keep away from the following materials to prevent strong exothermic reactions oxidizing agents, strong alkalis, strong acids.	;;
10.6 Hazardous decomposition products	Decomposition products may include the following materials: carbon monoxide carbon dioxide, smoke, oxides of nitrogen.	<b>)</b> ,
Refer to Section 7: HANDLIN	ND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL	

Refer to Section 7: HANDLING AND ONTROLS/PERSONAL STORAGE and Section 8: EXPOSURE PROTECTION for additional handling information and protection of employees.

# **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
No data available				
Acute toxicity estimates No data available				
Irritation/Corrosion No data available				
<b>Conclusion/Summary</b> <u>Sensitization</u> No data available	: Not available.			
<b>Conclusion/Summary</b> <u>Mutagenicity</u> No data available	: Not available.			
<u>Carcinogenicity</u> No data available				
<u>Reproductive toxicity</u> No data available				
<u>Teratogenicity</u> No data available				
Specific target organ toxicity	<u>(single exposure)</u>			
Product/ingre	dient name	Category	Route of exposure	Target organs
No data available				
Specific target organ toxicity	(repeated exposure)			
Product/ingre	dient name	Category	Route of exposure	Target organs
No data available				
Aspiration hazard				
Product/in	gredient name		Result	

No data available

#### M153C

# **SECTION 11: Toxicological information**

Other information

: Not available.

# **SECTION 12: Ecological information**

# 12.1 Toxicity

There are no data available on the mixture itself. Do not allow to enter drains or watercourses.

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

# 12.2 Persistence and degradability

Product/ingredient name	Test	Result		Dose		Inoculum
No data available						
Conclusion/Summary	: Not available.					
Product/ingredient name	Aquatic half-life		Photolysis		Biodeg	radability
No data available						

### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
No data available			

12.4 Mobility in soil	
Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

## 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects	: No known significant effects or critical hazards.
	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# **SECTION 13: Disposal considerations**

13.1 Waste treatment meth	ods
<u>Product</u>	
Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: No.
European waste catalogue (EWC)	: 08 01 12 - waste paint and varnish other than those mentioned in 08 01 11

# **SECTION 13: Disposal considerations**

-	
Disposal considerations	<ul> <li>Do not allow to enter drains or watercourses.</li> <li>Dispose of according to all federal, state and local applicable regulations.</li> <li>If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.</li> <li>For further information, contact your local waste authority.</li> </ul>
<u>Packaging</u>	
Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Disposal considerations	: Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.
European waste catalogue (EWC)	: Plastic articles 15 01 02 - metallic packaging 15 01 04 - mixed packaging 15 01 06.
Special precautions	: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# **SECTION 14: Transport information**

	ADR/RID	IMDG	ΙΑΤΑ
14.1 UN number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport Hazard Class(es)/ Label(s)	-	-	-
14.4 Packing group	-	-	-
14.5 Environmental hazards	No.	No.	No.
Additional information	-	-	-

This mixture is not classified as dangerous according to international transport regulations (ADR/RID, IMDG, ICAO/IATA).

**14.6 Special precautions for user**: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk: Not applicable.according to IMOinstruments

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

# **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>

### Annex XIV - List of substances subject to authorization

#### Annex XIV

None of the components are listed.

Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

#### **Other EU regulations**

VOC content	(2010/75/EU)	:	0	w/w
			0	g/l

#### Seveso Directive

This product is not controlled under the Seveso Directive.

#### National regulations

MAL-code 93 Protection based on MAL	<ul> <li>00-1</li> <li>According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment:</li> <li>General: Gloves must be worn for all work that may result in soiling. Apron/ coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In this case, other recommended use of eye protection is not required.</li> <li>In all spraying operations in which there is return spray, the following must be worn: respiratory protection and arm protectors/apron/coveralls/protective clothing as</li> </ul>
	<ul> <li>appropriate or as instructed.</li> <li>MAL-code: 00-1</li> <li>Application: When spraying in existing* spray booths, if the operator is outside the spray zone.</li> <li>Arm protectors must be worn.</li> <li>During all spraying where atomization occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cabin or booth.</li> <li>Full mask with combined filter, coveralls and hood must be worn.</li> </ul>
	<ul> <li>Drying: Items for drying/drying ovens that are temporarily placed on such things as rack trolleys, etc. must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.</li> <li>Polishing: When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always be worn.</li> </ul>

# **SECTION 15: Regulatory information**

Caution The regulations contain other stipulations in addition to the above.

\*See Regulations.

15.2 Chemical Safety	: No Chemical Safety Assessment has been carried out.
Assessment	

# **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	: ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number vPvB = Very Persistent and Very Bioaccumulative N/A = Not available
Key literature references and sources for data	<ul> <li>Regulation (EC) No. 1272/2008 [CLP] ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2015/830 Directive 2012/18/EU, and relative amendments &amp; additions Directive 2008/98/EC, and relative amendments &amp; additions Directive 2009/161/EU, and relative amendments &amp; additions CEPE Guidelines</li> </ul>

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classi	fication	Justification
Not classified.		
Full text of abbreviated H statements	: Not applicable.	
Full text of classifications [CLP/GHS]	: Not applicable.	
Date of printing	: 23, Apr, 2021.	
Date of issue/ Date of revision	: 23, Apr, 2021	
Date of previous issue	: 02, Dec, 2020	
	: If there is no previous val information.	idation date please contact your supplier for more
Version	: 1.02	
Notice to reader		

# **SECTION 16: Other information**

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory reguirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.