SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier	
Product name	: EPIDEK M153 Epoxy Deck Coating - Dressing Aggregate - HYAGG
Product code	: M153D
EC number	: 215-691-6
CAS number	: 1344-28-1

1.2 Relevant identified uses of the substance or mixture and uses advised against

- : Paint or paint related material.
 - : Industrial use only.

1.3 Details of the supplier of the safety data sheet

Material uses

Sherwin-Williams UK Limited - Protective & Marine Coatings Division EMEAI Tower Works Kestor Street Bolton BL2 2AL United Kingdom +44 (0) 1204 521771

The Sherwin-Williams Company Inver France SAS 2 Rue Jean Revaus - BP 80088 - 79102 Thouars CEDEX France

e-mail address of person : hse.pm.emea@sherwin.com responsible for this SDS

1.4 Emergency telephone number

National advisory body/Poison Center

Telephone number	: 070 245 245
<u>Supplier</u>	
Telephone number	: +(44)-870-8200 418
Hours of operation	: Emergency contact available 24 hours a day

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mono-constituent substance

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Date of issue/Date of revision	: 19, Oct, 2023
--------------------------------	-----------------

Date of previous issue : 18, Sep, 2023

SECTION 2: Hazards identification

Signal word	: No signal word.
Hazard statements	: No known significant effects or critical hazards.
Precautionary statements	
Prevention	: Not applicable.
Response	: Not applicable.
Storage	: Not applicable.
Disposal	: Not applicable.
Supplemental label elements	: FOR INDUSTRIAL USE ONLY

Special packaging requirements

Not applicable.

2.3 Other hazards

Product meets the criteria	: [PBT	Р	В	Т	vPvB	vP	vB
for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII		No	N/A	N/A	No	N/A	N/A	N/A
	c r	The substand disrupting pro regulation (E 0.1% or high	operties acc U) 2017/21	cording to F	REACH Arti	cle 57(f) or C	Commission	
Other hazards which do not result in classification	: 1	None known.						

SECTION 3: Composition/information on ingredients

:

3.1 Substance

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Aluminum Oxide	REACH #: 01-2119529248-35 EC: 215-691-6 CAS: 1344-28-1	100	Not classified.	-	[1]
			See Section 16 for the full text of the H statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier, are classified and contribute to the classification of the substance and hence require reporting in this section.

Туре

[1] Constituent

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

General	 In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
Eye contact	 Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

2/12

SECTION 4: First aid measures

Inhalation	 Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	 If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact. Coating powders can cause localized skin irritation in folds of the skin or under tight clothing.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	No specific treatment.

See toxicological information (Section 11)

SECTION 5: Firefighting	m	easures	
5.1 Extinguishing media			
Suitable extinguishing media	:	Recommended: alcohol-resistant foam, CO_2 blanket, water spray or mist.	
Unsuitable extinguishing media	:	Do not use water jet. Do not use inert gas under high pressure (e.g. CO2).	
5.2 Special hazards arising fi	ron	n the substance or mixture	
Hazards from the substance or mixture	:	Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.	
Hazardous combustion products	:	Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.	
5.3 Advice for firefighters			
Special protective actions for fire-fighters	:	Cool closed containers exposed to fire with water. Do not release runoff from fire drains or watercourses.	to
Special protective equipment for fire-fighters	:	Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.	
SECTION 6: Accidental	rel	ease measures	
6.1 Personal precautions, pre	ote	ctive equipment and emergency procedures	
For non-emergency personnel	:	Exclude sources of ignition and ventilate the area. Avoid breathing dust. Refer to protective measures listed in sections 7 and 8.	
		Keep unnecessary and unprotected personnel from entering.	

For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Date of issue/Date of revision	: 19, Oct, 2023	Date of previous issue	:18, Sep, 2023	Version : 5.04	3/12
				SHW-A4-EU-CLP44-BE	

SECTION 6: Accidental release measures

6.2 Environmental precautions	:	Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.
6.3 Methods and materials for containment and cleaning up	:	Contain and collect spillage with an electrically protected vacuum cleaner or by wet- brushing and place in container for disposal according to local regulations (see section 13). Do not use a dry brush as dust clouds or static can be created.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Advice should be taken from a competent occupational health practitioner on the assessment of employees with skin or respiratory complaints before the individual is exposed to the uncured product.

7.1 Precautions for safe handling	 Precautions should be taken to prevent the formation of dusts in concentrations above flammable, explosive or occupational exposure limits. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing and floors should be of the conducting type. Keep away from heat, sparks and flame. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Put on appropriate personal protective equipment (see Section 8). Always keep in containers made from the same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or watercourses.
7.2 Conditions for safe storage, including any incompatibilities	 Store in accordance with local regulations. Additional information on storage conditions Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep container tightly closed. Keep away from sources of ignition. No smoking. Prevent unauthorized access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Contaminated absorbent material may pose the same hazard as the spilled product.
7.3 Specific end use(s) Recommendations Industrial sector specific solutions	 Not available. Not available.
Good nousekeeping standar	ds, regular safe removal of waste materials and regular maintenance of spray booth

filters will minimise the risks of spontaneous combustion and other fire hazards.

Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
	Limit values (Belgium, 5/2021). [Aluminium (metal and insoluble compounds)] TWA: 1 mg/m ³ 8 hours. Form: respirable fraction

Biological exposure indices

No exposure indices known.

Recommended monitoring procedures	 Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
	. Degular manitaring of all work areas should be carried out at all times, including

: Regular monitoring of all work areas should be carried out at all times, including areas that may not be equally ventilated.

DNELs/DMELs

No DNELs/DMELs available.

PNECs

No PNECs available.

8.2 Exposure controls	
Appropriate engineering controls	: Avoid breathing dust. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain exposure to dusts below the OEL, suitable respiratory protection must be worn.
	: Users are advised to consider national Occupational Exposure Limits or other equivalent values.
Individual protection meas	ires
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear should be used when there is a likelihood of exposure.
Skin protection	
Hand protection	: Wear suitable gloves tested to EN374.
Gloves	 Gloves for short term exposure or repeated or prolonged exposure (480 min): Weak any rubber glove such as Nitrile or Neoprene gloves. Due to many conditions (e.g. temperature, abrasion) the practical usage of a chemical protective glove in practice may be much shorter than the permeation time determined through testing.

SECTION 8: Exposure controls/personal protection

	There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. The breakthrough time must be greater than the end use time of the product.
	The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.
	Gloves should be replaced regularly and if there is any sign of damage to the glove material.
	Always ensure that gloves are free from defects and that they are stored and used correctly.
	The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.
	Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.
	The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
Body protection	: Personnel should wear protective clothing. Care should be taken in the selection of protective clothing to ensure that inflammation and irritation of the skin at the neck and wrists through contact with the powder are avoided.
	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Recommended: particulate filter, P2-P3 (EN14387). Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	: Do not allow to enter drains or watercourses.

Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

<u>Appearance</u>		
Physical state	: Solid.	
Color	: Gray.	
Odor	: None	
Odor threshold	: Not applicable.	
рН	 Not relevant/applicable due to nature of the product. insoluble in water. 	
Melting point/freezing point	: Not relevant/applicable due to nature of the product.	
Initial boiling point and boiling range	: Not relevant/applicable due to nature of the product.	
Flash point	Closed cup: Not applicable.	
Evaporation rate	: Not relevant/applicable due to nature of the product.	
Flammability	: Not relevant/applicable due to nature of the product.	

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II EPIDEK M153 Epoxy Deck Coating - Dressing Aggregate - HYAGG					
M153D					
SECTION 9: Physical and chemical properties					
Lower and upper explosion limit					
Vapor pressure	: Not relevant/applicable due to nature of the product.				
Relative vapor density	: Not applicable.				
Relative density	: 3.99				
Solubility(ies)	:				
Media	Result				
cold water	Not soluble				
Partition coefficient: n-octar water	nol / : Not relevant/applicable due to nature of the product.				
Auto-ignition temperature	: Not relevant/applicable due to nature of the product.				
Decomposition temperature	Not relevant/applicable due to nature of the product.				
Viscosity	: Kinematic (40°C): >20.5 mm²/s				
Explosive properties	: Under normal conditions of storage and use, hazardous reactions will not occur.				
Oxidizing properties	: Under normal conditions of storage and use, hazardous reactions will not occur.				
Particle characteristics					
Median particle size	: Not relevant/applicable due to nature of the product.				
9.2 Other information					
Heat of combustion	: 0 kJ/g				
SECTION 10: Stability and reactivity					
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.				
10.2 Chemical stability	: Stable under recommended storage and handling conditions (see Section 7).				
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.				
10.4 Conditions to avoid	When exposed to high temperatures may produce hazardous decomposition products.				
10.5 Incompatible materials	: Not applicable.				
10.6 Hazardous decomposition products	 Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen. 				
	G AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL andling information and protection of employees.				

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact. Coating powders can cause localized skin irritation in folds of the skin or under tight clothing.

Acute toxicity

No data available

: Not available.

SECTION 11: Toxicological information

Acute toxicity estimates

No data available

Irritation/Corrosion

No data available

Conclusion/Summary

Sensitization

No data available

Conclusion/Summary : Not available.

<u>Mutagenicity</u>

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

Teratogenicity

No data available

Specific target organ toxicity (single exposure)

No data available

Specific target organ toxicity (repeated exposure)

No data available

Aspiration hazard

No data available

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself.

Coating powder residues should not be allowed to enter drains or watercourses or be deposited where they could affect ground or surface waters.

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Product/ingredient name	Result	Species	Exposure
Aluminum Oxide	Acute EC50 114.357 mg/l Fresh water	Daphnia - <i>Daphnia magna</i> - Neonate	48 hours

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
No data available				
Conclusion/Summary	• Not available	·	·	

Conclusion/Summary : Not available.

Date of issue/Date of revision	: 19, Oct, 2023	Date of previous issue	:18, Sep, 2023	Version : 5.04	8/12

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II

EPIDEK M153 Epoxy Deck Coating - Dressing Aggregate - HYAGG M153D

SECTION 12: Ecological information

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
No data available			

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
No data available			

12.4 Mobility in soil	
Soil/water partition	: Not available.
coefficient (Koc)	
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

Product/ingredient name	PBT	Р	В	Т	vPvB	vP	vB
EPIDEK M153 Epoxy Deck Coating - Dressing Aggregate	No	N/A	N/A	No	N/A	N/A	N/A

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations				
13.1 Waste treatment metho	ds			
<u>Product</u>				
Methods of disposal	:	The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.		
Hazardous waste	:	No.		
European waste catalogue (EWC)	:	08 01 12 - waste paint and varnish other than those mentioned in 08 01 11		
Disposal considerations	 Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code ma longer apply and the appropriate code should be assigned. For further information, contact your local waste authority. 			
Packaging				
Methods of disposal	:	The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.		
Disposal considerations	:	Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.		

Date of issue/Date of revision	: 19, Oct, 2023	Date of previous issue	:18, Sep, 2023	Version : 5.04	9/12
				SHW-A4-EU-CLP44-BE	

SECTION 13: Disposal considerations

European waste
catalogue (EWC)
Special precautions

- : Plastic articles 15 01 02 metallic packaging 15 01 04 mixed packaging 15 01 06.
- : This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG	ΙΑΤΑ			
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.			
14.2 UN proper shipping name	-	-	-			
14.3 Transport Hazard Class(es)/ Label(s)	-	-	-			
14.4 Packing group	-	-	-			
14.5 Environmental hazards	No.	No.	No.			
Additional information	-	-	-			

This mixture is not classified as dangerous according to international transport regulations (ADR/RID, IMDG, ICAO/IATA).

14.6 Special precautions for user: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in	: Not applicable.
bulk according to IMO	
instruments	

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>

Annex XIV - List of substances subject to authorization

<u>Annex XIV</u>

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

No listed substance

Other EU regulations

Date of previous issue : 18, Sep, 2023

Conforms to Regulation (EC EPIDEK M153 Epoxy Deck Coating	C) No. 1907/2006 (REACH), Annex II		
M153D	- Dressing Aggregate - HTAOO		
SECTION 15: Regulator	v information		
VOC content (2010/75/EU)	-		
	0 g/l		
Explosive precursors	: Not applicable.		
<u>Seveso Directive</u>			
This product is not controlle	ed under the Seveso Directive.		
National regulations			
15.2 Chemical Safety Assessment	: No Chemical Safety Assessment has been carried out.		
SECTION 16: Other info	ormation		
Indicates information that	has changed from previously issued version.		
Abbreviations and	: ATE = Acute Toxicity Estimate		
acronyms	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]		
	DMEL = Derived Minimal Effect Level		
	DNEL = Derived No Effect Level		
	EUH statement = CLP-specific Hazard statement		
	PBT = Persistent, Bioaccumulative and Toxic		
	PNEC = Predicted No Effect Concentration RRN = REACH Registration Number		
	vPvB = Very Persistent and Very Bioaccumulative		
	N/A = Not available		
Key literature references	: Regulation (EC) No. 1272/2008 [CLP]		
and sources for data	ADR = The European Agreement concerning the International Carriage of		
	Dangerous Goods by Road IATA = International Air Transport Association		
	IMDG = International Maritime Dangerous Goods		
	Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by		
	Commission Regulation (EU) 2020/878		
	Directive 2012/18/EU, and relative amendments & additions		
	Directive 2008/98/EC, and relative amendments & additions Directive 2009/161/EU, and relative amendments & additions		
	CEPE Guidelines		

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classi	fication	Justification	
Not classified.			
Full text of abbreviated H statements	: Not applicable.		
Full text of classifications [CLP/GHS]	: Not applicable.		
Date of printing	: 19, Oct, 2023.		
Date of issue/ Date of revision	: 19, Oct, 2023		
Date of previous issue	: 18, Sep, 2023		
	: If there is no previous va information.	idation date please contact your supplier for more	
Version	: 5.04		
Notice to reader			

11/12

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II EPIDEK M153 Epoxy Deck Coating - Dressing Aggregate - HYAGG M153D

SECTION 16: Other information

In accordance with Regulation (EC) 1907/2006, REACH Regulation, Articles 31, 37, any required hazard-related information on the use of substances received as downstream user will be sent forward. Consequently, the safety data sheets for some products will contain a SUMI - Safe Use of Mixture Information - attached to the safety data sheet.

SUMI(s) will be added to the SDS for products if both the following conditions are met:

• The product is classified as hazardous for health

• The product contains one or more REACH-registered substances for which extended safety data sheets (exposure scenarios) have been provided

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.