# SAFETY DATA SHEET

#### FIRETEX M90/03 Epoxy Intumescent - Additive - Blue

Safety Data Sheet according to GB/T 16483-2008 and GB/T 17519-2013

### **Section 1. Identification**

Hours of operation	: Emergency contact	available 24 hours a day
Emergency telephone number (with hours of operation)	: 400-6267911	
Supplier Telephone number e-mail address of person responsible for this SDS	: 400-6267911 : hse.pm.emea@she	rwin.com
Details of the supplier of the Sherwin-Williams Protective & Tower Works Kestor Street Bolton BL2 2AL United Kingdom +44 (0) 1204 521771	-	<i>National contact</i> Sherwin-Williams (Shanghai) Ltd 188 Wuxiang Road Xu Hang Town Jiading Shanghai 201808
<i>Product use</i> Material uses	<ul><li>Industrial application</li><li>Paint or paint relate</li></ul>	
Product code GHS product identifier	: M90/03A : FIRETEX M90/03 E Blue	poxy Intumescent - Additive

# Section 2. Hazards identification

Classification of the substance or mixture according to GB 13690-2009 and GB 30000-2013

#### **Emergency overview**

Liquid. Blue. May be harmful if swallowed. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious eye damage. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. (urinary tract) Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. None known. Please refer to the SDS for additional information. IF exposed or concerned: Get medical advice or attention. IF INHALED: Immediately call a POISON CENTER or doctor. IE SWALLOWED: Immediately

Immediately call a POISON CENTER or doctor. IF SWALLOWED: Immediately call a POISON CENTER or doctor. IF ON SKIN (or hair): Immediately call a POISON CENTER or doctor. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Immediately call a POISON CENTER or doctor.

# Section 2. Hazards identification

See Section 12 for environmental precautions.

Classification of the substance or mixture	: ACUTE TOXICITY (oral) - Category 5 SKIN CORROSION/IRRITATION - Category 1C SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2 TOXIC TO REPRODUCTION - Category 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1
GHS label elements	
Hazard pictograms	
Signal word	: Danger
Hazard statements	<ul> <li>May be harmful if swallowed.</li> <li>Causes severe skin burns and eye damage.</li> <li>May cause an allergic skin reaction.</li> <li>Causes serious eye damage.</li> <li>Suspected of causing cancer.</li> <li>Suspected of damaging fertility or the unborn child.</li> <li>May cause damage to organs through prolonged or repeated exposure. (urinary tract)</li> <li>Very toxic to aquatic life.</li> <li>Very toxic to aquatic life with long lasting effects.</li> </ul>
Precautionary statements	
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Avoid release to the environment. Do not breathe vapor. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.
Response	: Collect spillage. IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER or doctor. Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
Storage	: Store locked up.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Physical and chemical hazards	: No known significant effects or critical hazards.

M90/03A	FIRETEX M90/03 Epoxy Intumescent - Additive - Blue	
---------	--	--

# Section 2. Hazards identification

Section 2. Hazarus	
Health hazards	: May be harmful if swallowed. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious eye damage. Suspected of causing cancer. Suspected of damaging fertility or the unborn child.
Symptoms related to the phy	vsical, chemical and toxicological characteristics
Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations
Delayed and immediate effect	ts and also chronic effects from short and long term exposure
Short term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure Potential immediate	: Not available.
effects	
Potential delayed effects	: Not available.
Environmental hazards	: Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.
Other hazards which do not result in classification	: None known. Please refer to the SDS for additional information.

# Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

#### Hazardous ingredients

# Section 3. Composition/information on ingredients

Ingredient name	%	CAS number	EC number	Hazard classification
1,3,5-Triazine-2,4,6-triamine	≥25 - ≤50	108-78-1	203-615-4	H303, H320, H351, H361, H373
Fatty acids, tall-oil, reaction products with tetraethylenepentamine	≥25 - ≤50	68953-36-6	273-201-6	H314, H317, H318, H400, H410
2,4,6-tris(dimethylaminomethyl)phenol	≤4.9	90-72-2	202-013-9	H302 + H312, H314, H318
3,6,9-triazaundecamethylenediamine	<1	112-57-2	203-986-2	H303, H314, H317, H318, H401, H411

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

# Section 4. First aid measures

#### **Description of necessary first aid measures**

Eye contact	: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
Inhalation	: Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	: Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a
Date of issue/Date of revision	: 2024/03/05. Date of previous issue : 2023/09/24. Version : 6 4/10

Classification of the substance or mixture according to GB 13690-2009 and GB 30000-2013

M90/03A FIRETEX M90/03 Epoxy Intumescent - Additive - Blue

### Section 4. First aid measures

collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

Potential acute health effects	
Eye contact	: Causes serious eye damage.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes severe burns. May cause an allergic skin reaction.
Ingestion	: May be harmful if swallowed.
Over-exposure signs/sympto	o <u>ms</u>
Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations
Indication of immediate medic	al attention and special treatment needed, if necessary
Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

FIRETEX M90/03 Epoxy Intumescent - Additive - Blue

### Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Recommended: alcohol-resistant foam, CO <sub>2</sub> , powders, water spray or mist.
Unsuitable extinguishing media	: Do not use water jet.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides
Advice for firefighters	
Special protective actions for fire-fighters	<ul> <li>Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.</li> </ul>
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

Personal precautions, protect	tiv	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
Methods and materials for co	nt	ainment and cleaning up

Spill
 Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Date of issue/Date of revision	: 2024/03/05.	Date of previous issue	: 2023/09/24.	Version : 6	6/16
				SHW-A4-AP-GH432-CN	

FIRETEX M90/03 Epoxy Intumescent - Additive - Blue

### Section 7. Handling and storage

#### Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### Section 8. Exposure controls/personal protection

#### **Control parameters**

None.

#### **Biological exposure indices**

No exposure indices known.

Appropriate engineering controls	: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### Individual protection measures

Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Use safety eyewear designed to protect against splash of liquids.
Skin protection	

		Indune a condition Div	
M90/03A	FIREIEX W90/03 EPOX	y Intumescent - Additive - Blu	е

# Section 8. Exposure controls/personal protection

Hand protection	: Wear suitable gloves tested to EN374.
Gloves	: Short Term Exposure less than 10 minutes Continuous use Nitrile gloves. Hazardous ingredients Section 3 For more than 4 hours of protection in the presence of Ethyl methyl ketone or Methyl ethyl ketone Acetone or Methyl isobutyl ketone Butyl gloves 0.7mm For more than 4 hours of protection in the presence of Aromatic solvent use polyvinyl alcohol (PVA) gloves.
	Long Term Exposure Spill / For prolonged or repeated handling, use PE / PE Laminate gloves > 8 hours (breakthrough time) .
	There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.
	The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.
	Gloves should be replaced regularly and if there is any sign of damage to the glove material.
	Always ensure that gloves are free from defects and that they are stored and used correctly.
	The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.
	Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.
	The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
Body protection	<ul> <li>Personnel should wear antistatic clothing made of natural fibers or of high- temperature-resistant synthetic fibers.</li> </ul>
	<ul> <li>Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Other skin protection	<ul> <li>Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Respiratory protection	: If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.

# Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

<u>Appearance</u>		
Physical state	: Liquid.	
Color	: Blue.	
Odor	: Solvent.	
Odor threshold	: Not available.	
рН	: Not applicable.	
Melting point/freezing point	: Not available.	
Boiling point, initial boiling point, and boiling range	: Not available.	
Flash point	: Closed cup: Not applicable.	
Evaporation rate	: Not available.	
Lower and upper explosion limit/flammability limit	: Not available.	
Date of issue/Date of revision	: 2024/03/05. Date of previous issue : 2023/09/24.	Version : 6 8

8/16

### **Section 9. Physical and chemical properties**

-		
Vapor pressure	: No	t available.
Relative vapor density	: No	t available.
Relative density	: 1.2	27
Solubility(ies)	:	
Media		Result
cold water		Not soluble
Partition coefficient: n- octanol/water	: No	t applicable.
Auto-ignition temperature	: No	t available.
Decomposition temperature	: Not available.	
Viscosity	: Kir	nematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)
VOC content	: 0 g	)/L
Heat of combustion	: 1.9	975 kJ/g

# Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	<ul><li>No specific data.</li><li>Avoid high temperature.</li></ul>
Incompatible materials	: No specific data.
Hazardous decomposition products	<ul> <li>Under normal conditions of storage and use, hazardous decomposition products should not be produced.</li> </ul>

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

# Section 11. Toxicological information

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
1,3,5-Triazine-2,4,6-triamine	LD50 Oral	Rat	3161 mg/kg	-
2,4,6-tris	LD50 Dermal	Rat	1280 mg/kg	-
(dimethylaminomethyl)				
phenol				
	LD50 Oral	Rat	1200 mg/kg	-
3,6,9-triazaundecamethylenediamine	LD50 Oral	Rat	3990 mg/kg	-

#### Irritation/Corrosion

#### FIRETEX M90/03 Epoxy Intumescent - Additive - Blue

# Section 11. Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
1,3,5-Triazine-2,4,6-triamine	Eyes - Mild irritant	Rabbit	-	24 hours 500	-
				mg	
2,4,6-tris	Eyes - Severe irritant	Rabbit	-	24 hours 50	-
(dimethylaminomethyl) phenol				ug	
	Skin - Mild irritant	Rat	-	0.025 MI	-
	Skin - Severe irritant	Rabbit	-	24 hours 2	-
				mg	
	Skin - Severe irritant	Rat	-	0.25 MI	-
3,6,9-triazaundecamethylenediamine	Eyes - Moderate irritant	Rabbit	-	24 hours 100	-
				mg	
	Eyes - Moderate irritant	Rabbit	-	5 mg	-
	Skin - Severe irritant	Rabbit	-	495 mg	-
	Skin - Severe irritant	Rabbit	-	24 hours 5	-
				mg	

#### **Sensitization**

Not available.

#### **Mutagenicity**

Not available.

#### Carcinogenicity

Not available.

#### **Classification**

Product/ingredient name	IARC
1,3,5-Triazine-2,4,6-triamine	2B

#### Reproductive toxicity

Not available.

#### **Teratogenicity**

Not available.

#### Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure)

Name	<u>J</u> - J	Route of exposure	Target organs
1,3,5-Triazine-2,4,6-triamine	Category 2	-	urinary tract

#### Information on the likely : Not available. routes of exposure

#### Potential acute health effects

Eye contact	: Causes serious eye damage.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes severe burns. May cause an allergic skin reaction.
Ingestion	: May be harmful if swallowed.

# Section 11. Toxicological information

#### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations

#### Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Long term exposure		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Potential chronic health effe	ect	<u>S</u>
Not available.		
General	:	May cause damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	:	Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	:	No known significant effects or critical hazards.
Teratogenicity	:	Suspected of damaging the unborn child.
<b>Developmental effects</b>	:	No known significant effects or critical hazards.
Fertility effects	:	Suspected of damaging fertility.

#### Numerical measures of toxicity

#### Acute toxicity estimates

# Section 11. Toxicological information

Route	ATE value
Oral	3711.76 mg/kg
Dermal	6522.78 mg/kg

# Section 12. Ecological information

#### <u>Toxicity</u>

Not available.

#### Persistence/degradability

Not available.

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
1,3,5-Triazine-2,4,6-triamine	-	<3.8	Low

#### Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	

**Other adverse effects** : No known significant effects or critical hazards.

Do not allow to enter drains or watercourses.

# Section 13. Disposal considerations

Disposal methods	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
	Do not incinerate closed container. Incinerate in a licensed, high-temperature, hazardous-waste incinerator.

FIRETEX M90/03 Epoxy Intumescent - Additive - Blue

### Section 14. Transport information

Section 14.	ranspo		mation		
	Ch	ina	ADR	IMDG	ΙΑΤΑ
UN number	UN3066		UN3066	UN3066	UN3066
UN proper shipping name	PAINT. Ma pollutant (F tall-oil, read products wi tetraethylen	atty acids, ction	PAINT	PAINT. Marine pollutant (Fatty acids, tall-oil, reaction products with tetraethylenepentamine)	PAINT
Transport Hazard Class(es)/Label(s)	8	¥2	8	8	8
Packing group	Ш		ш	III	III
Environmental hazards/Marine pollutant	Yes.		Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Additional informati	<u>on</u>				
China	:		e pollutant mark is not	required when transported	in sizes of ≤5 L or ≤5
		kg. <b>Emergenc</b>	<b>y schedules</b> F-A, S-E	3	
ADR	:		L or ≤5 kg.	substance mark is not requ	ired when transported in
IMDG	:	kg.	e pollutant mark is not <b>y schedules</b> F-A, S-E	required when transported	in sizes of ≤5 L or ≤5
ΙΑΤΑ	:	The enviro	,	substance mark may appea	ar if required by other
Special precautions	for user :	upright and	-	ses: always transport in clos persons transporting the pro ge.	
Extinguishing media					
Suitable extinguish media	ning :	Use an ext	inguishing agent suita	ble for the surrounding fire.	
Unsuitable extingu media	ishing :	None know	/n.		
Incompatible materi	als :	No specific	; data.		
Transport in bulk ac to IMO instruments	cording :	Not availab	ble.		

Classification of the substance or mixture according to GB 13690-2009 and GB 30000-2013

M90/03A FIRETEX M90/03 Epoxy Intumescent - Additive - Blue

# Section 14. Transport information

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

# Section 15. Regulatory information

National inventory	: Australia inventory (AIIC): Not determined.
	Canada inventory: Not determined.
	China inventory (IECSC): Not determined.
	Japan inventory (CSCL): Not determined.
	Japan inventory (ISHL): Not determined.
	Korea inventory: Not determined.
	Mexico inventory: Not determined.
	New Zealand Inventory of Chemicals (NZIoC): All components are listed or
	exempted.
	Philippines inventory (PICCS): Not determined.
	<b>Russian Federation inventory:</b> All components are listed or exempted.
	Thailand inventory: All components are listed or exempted.
	Turkey inventory: Not determined.
	Taiwan Chemical Substances Inventory (TCSI): All components are listed or exempted.
	United States inventory (TSCA 8b): Not determined.
	Vietnam inventory: All components are listed or exempted.

#### List of Goods banned for Importing

None of the components are listed.

#### Drug Precursors Requiring an Import/Export License

None of the components are listed.

#### **Inventory of Hazardous Chemicals**

Ingredient name	CAS number	Status	Reference number
Tetraethylenepentamine	112-57-2	Listed	2086

#### List of Explosive Precursors

None of the components are listed.

#### List of Goods banned for Exporting

None of the components are listed.

#### List of Toxic Chemicals Severely Restricted for Importing & Exporting by China

None of the components are listed.

#### Catalogue and classification of drug precursor chemicals

None of the components are listed.

#### **Inventory of Highly Toxic Articles**

None of the components are listed.

#### Catalogue of Hazardous Chemicals of Priority Management

None of the components are listed.

:2023/09/24.

Classification of the substance or mixture according to GB 13690-2009 and GB 30000-2013

M90/03A

FIRETEX M90/03 Epoxy Intumescent - Additive - Blue

# Section 15. Regulatory information

#### China MEE12 Registration number

Not applicable.

# Section 16. Other information

History	
Date of printing	: 2024/03/05.
Date of issue/Date of revision	: 2024/03/05.
Date of previous issue	: 2023/09/24.
Version	: 6
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations

#### Procedure used to derive the classification

Classification	Justification
ACUTE TOXICITY (oral) - Category 5	Calculation method
SKIN CORROSION/IRRITATION - Category 1C	Calculation method
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1	Calculation method
SKIN SENSITIZATION - Category 1	Calculation method
CARCINOGENICITY - Category 2	Calculation method
TOXIC TO REPRODUCTION - Category 2	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2	Calculation method
AQUATIC HAZARD (ACUTE) - Category 1	Calculation method
AQUATIC HAZARD (LONG-TERM) - Category 1	Calculation method

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Full text of classifications [CLP/GHS]	: ACUTE TOXICITY (oral) - Category 5 SKIN CORROSION/IRRITATION - Category 1C SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2 TOXIC TO REPRODUCTION - Category 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1
Full text of abbreviated H statements	<ul> <li>H303 - May be harmful if swallowed.</li> <li>H314 - Causes severe skin burns and eye damage.</li> <li>H317 - May cause an allergic skin reaction.</li> <li>H318 - Causes serious eye damage.</li> <li>H351 - Suspected of causing cancer.</li> <li>H361 - Suspected of damaging fertility or the unborn child.</li> <li>H373 - May cause damage to organs through prolonged or repeated exposure. (urinary tract)</li> </ul>

M90/03A	FIRETEX M90/03 Epoxy Intumescent - Additive - Blue
Section 16. Other	information
	H400 - Very toxic to aquatic life. H410 - Very toxic to aquatic life with long lasting effects.
Precautionary statements	<ul> <li>P201 - Obtain special instructions before use.</li> <li>P202 - Do not handle until all safety precautions have been read and understood P280 - Wear protective gloves, protective clothing and eye or face protection.</li> <li>P273 - Avoid release to the environment.</li> <li>P260 - Do not breathe vapor.</li> <li>P264 - Wash thoroughly after handling.</li> <li>P272 - Contaminated work clothing should not be allowed out of the workplace.</li> <li>P391 - Collect spillage.</li> <li>P308 + P313 - IF exposed or concerned: Get medical advice or attention.</li> <li>P304 + P340, P310 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor.</li> <li>P301 + P310, P330, P331 - IF SWALLOWED: Immediately call a POISON</li> </ul>
	<ul> <li>CENTER or doctor. Rinse mouth. Do NOT induce vomiting.</li> <li>P303 + P361 + P353, P310 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER or doctor.</li> <li>P363 - Wash contaminated clothing before reuse.</li> <li>P302 + P352 - IF ON SKIN: Wash with plenty of water.</li> <li>P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention.</li> <li>P305 + P351 + P338, P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</li> <li>Immediately call a POISON CENTER or doctor.</li> <li>P405 - Store locked up.</li> <li>P501 - Dispose of contents and container in accordance with all local, regional,</li> </ul>

Indicates information that has changed from previously issued version.

#### Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buver/user is responsible to ensure that his activities comply with all country. federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS. the manufacturer cannot be responsible for SDSs obtained from any other source.