SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

	· · · · · · · · · · · · · · · · · · ·
1.1 Product identifier	
Product name	: Phoenix 370-60 - WHITE
Product code	: PH370-60
1.2 Relevant identified use	es of the substance or mixture and uses advised against
Material uses	: Paint or paint related material.
	: Industrial use only.
1.3 Details of the supplier of	of the safety data
sheet	d. Desta stirra 9 Mania a
Sherwin-Williams UK Limite Coatings Division EMEAI	a - Protective & Marine
Tower Works	
Kestor Street	
Bolton BL2 2AL	
United Kingdom	
+44 (0) 1204 521771	
The Sherwin-Williams Com	nany
Inver France SAS	pany
2 Rue Jean Revaus - BP 80	088 - 79102
Thouars CEDEX	
France	
e-mail address of person responsible for this SDS	: hse.pm.emea@sherwin.com
1.4 Emergency telephone r	number
National advisory body/Po	bison Center
Telephone number	: 111 (general public) /0344 892 111 (Medical professional (NHS) only)
<u>Supplier</u>	
Telephone number	: +(44)-870-8200 418
Hours of operation	: Emergency contact available 24 hours a day
SECTION 2: Hazards ic	lentification
2.1 Classification of the su	bstance or mixture
Product definition	: Mixture
Classification according t	o Regulation (EC) No. 1272/2008 [CLP/GHS]
Carc. 2, H351	
Repr. 2, H361	
STOT RE 2, H373	hazardous according to Regulation (EC) 1272/2008 as amonded
•	hazardous according to Regulation (EC) 1272/2008 as amended. ext of the H statements declared above.
	tailed information on health effects and symptoms.
Date of issue/Date of revision	: 15, Apr, 2024 Date of previous issue : 23, Sep, 2023 Version : 10 1/1
1	

÷

SECTION 2: Hazards identification

Hazard pictograms



Signal word	:	Warning
Hazard statements	:	Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.
Precautionary statements		
Prevention	:	Obtain special instructions before use. Wear protective gloves, protective clothing, eye protection, face protection, or hearing protection. Do not breathe vapor.
Response	:	IF exposed or concerned: Get medical advice or attention.
Storage	:	Not applicable.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	:	1,3,5-Triazine-2,4,6-triamine
Supplemental label elements	:	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. FOR INDUSTRIAL USE ONLY
Special packaging requirement Not applicable. 2.3 Other hazards	<u>en</u>	<u>ts</u>
		This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
		The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
Other hazards which do not result in classification	:	None known.

SECTION 3: Composition/information on ingredients

:

3.2 Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
1,3,5-Triazine-2,4,6-triamine	REACH #: 01-2119485947-16 EC: 203-615-4 CAS: 108-78-1 Index: 613-345-00-2	≥10 - ≤25	Carc. 2, H351 Repr. 2, H361 STOT RE 2, H373 (urinary tract)	-	[1] [2]
Chloropropanol Phosphate	EC: 237-158-7 CAS: 13674-84-5	≤3	Acute Tox. 4, H302 See Section 16 for the full text of the H statements declared above.	ATE [Oral] = 1500 mg/kg	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section. <u>Type</u>

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II

Phoenix 370-60 - WHITE

PH370-60

SECTION 3: Composition/information on ingredients

[1] Substance classified with a health or environmental hazard

[2] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid me	easures
General	: In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
Eye contact	 Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	 If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.

See toxicological information (Section 11)

SECTION 5: Firefighting measures

5.1 Extinguishing media	
Suitable extinguishing media	: Recommended: alcohol-resistant foam, CO ₂ , powders, water spray or mist.
Unsuitable extinguishing media	: Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the
substance or mixture: Fire will produce dense black smoke. Exposure to decomposition products may
cause a health hazard.

SECTION 5: Firefighting measures

Hazardous combustion products	Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.
5.3 Advice for firefighters Special protective actions for fire-fighters	Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.
Special protective equipment for fire-fighters	Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

SECTION 6: Accidental release measures

Due to the organic solvents content of the mixture:

6.1 Personal precautions, protective equipment and emergency procedures					
For non-emergency personnel	:	Exclude sources of ignition and ventilate the area. Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8.			
		Keep unnecessary and unprotected personnel from entering.			
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".			
6.2 Environmental precautions	:	Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.			
6.3 Methods and materials for containment and cleaning up	:	Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.			
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.			

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling	: Due to the organic solvents content of the mixture:
	Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Keep away from heat, sparks and flame. No sparking tools should be used.
	Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding.
	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.
	Put on appropriate personal protective equipment (see Section 8).
	Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one. Comply with the health and safety at work laws. Information on fire and explosion protection
	Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air.

SECTION 7: Handling and storage When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapors in all cases. In such circumstances, they should wear a compressed-air-fed respirator during the spraying process and until the particulate and solvent vapor concentrations have fallen below the exposure limits. 7.2 Conditions for safe : Store in accordance with local regulations. storage, including any Notes on joint storage incompatibilities Keep away from: oxidizing agents, strong alkalis, strong acids. Additional information on storage conditions Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep container tightly closed. Keep away from sources of ignition. No smoking. Prevent unauthorized access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Contaminated absorbent material may pose the same hazard as the spilled product. Store above 5°C (42°F) Protect from frost. 7.3 Specific end use(s) Recommendations : Not available. Industrial sector specific : Not available. solutions

Good housekeeping standards, regular safe removal of waste materials and regular maintenance of spray booth filters will minimise the risks of spontaneous combustion and other fire hazards.

Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

Biological exposure indices

No exposure indices known.

Recommended monitoring procedures	Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
-----------------------------------	--

: Regular monitoring of all work areas should be carried out at all times, including areas that may not be equally ventilated.

DNELs/DMELs

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II Phoenix 370-60 - WHITE

PH370-60

SECTION 8: Exposure controls/personal protection

		1			
Product/ingredient name	Туре	Exposure	Value	Population	Effects
1,3,5-Triazine-2,4,6-triamine	DNEL	Short term Dermal	117 mg/kg	Workers	Systemic 🥄
	DNEL	Short term Inhalation	82.3 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	11.8 mg/kg	Workers	Systemic
	DNEL	Long term	8.3 mg/m ³	Workers	Systemic
		Inhalation	-		
	DNEL	Long term Dermal	4.2 mg/kg	General	Systemic
				population	
	DNEL	Long term	1.5 mg/m³	General	Systemic
		Inhalation		population	
	DNEL	Long term Oral	0.42 mg/kg	General	Systemic
				population	

PNECs

Product/ingredient name	Compartment Detail	Value	Me	thod Detail
1,3,5-Triazine-2,4,6-triamine	Fresh water	0.5 mg/l	-	
	Marine water	0.05 mg/l	-	
	Sewage Treatment	200 mg/l	-	
	Plant	Ū,		
	Fresh water sediment	2.524 mg/kg	-	

8.2 Exposure controls

o.z Exposure controis	
Appropriate engineering controls	: Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn.
	 Users are advised to consider national Occupational Exposure Limits or other equivalent values.
Individual protection meas	ures
<i>Hygiene measures</i>	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Use safety eyewear designed to protect against splash of liquids.
Skin protection	
Hand protection	: Wear suitable gloves tested to EN374.
Gloves	 Gloves for short term exposure/splash protection (less than 10 min): Nitrile >0.12 mm Gloves for splash protection need to be changed immediately when in contact with chemicals. Gloves for repeated or prolonged exposure (breakthrough time > 480 min): Butyl gloves >0.3 mm Due to many conditions (e.g. temperature, abrasion) the practical usage of a chemical protective glove in practice may be much shorter than the permeation time determined through testing. The recommendation for the type or types of glove to use when handling this product is based on information from the following source: Solvent resin manufacturers and European Solvents Industry Group (ESIG).

SHW-A4-EU-CLP44-UA

SECTION 8: Exposure controls/personal protection

	There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.
	The breakthrough time must be greater than the end use time of the product.
	The instructions and information provided by the glove manufacturer on use,
	storage, maintenance and replacement must be followed.
	Gloves should be replaced regularly and if there is any sign of damage to the glove material.
	Always ensure that gloves are free from defects and that they are stored and used correctly.
	The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.
	Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.
	The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
Body protection	: Personnel should wear protective clothing.
	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	 Application methods: Brush or roller. Approved/certified respirator with organic vapor cartridge. Filter type: A2 P2 (EN14387). Manual spraying. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure controls	Do not allow to enter drains or watercourses.

Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Color	: White.
Odor	: Paint
Odor threshold	: Not Available (Not Tested).
pН	: 8.1
Melting point/freezing point	: Not relevant/applicable due to nature of the product.
Initial boiling point and boiling range	: 100°C
Flash point	: Closed cup: 499°C [Pensky-Martens Closed Cup]
Evaporation rate	: 0.09 (butyl acetate = 1)
Flammability Lower and upper explosion limit	 Not relevant/applicable due to nature of the product. LEL: 0.6% (Trimethylpentanediol Isobutyrate) UEL: 12.5% (Propylene Glycol)

SECTION 9: Physical and chemical properties

Vapor pressure	:	2.3 kPa (17.5	mm Hg)			
Relative vapor density	:	1 [Air = 1]				
Relative density	:	1.35				
Solubility(ies)	:					
Media		Result				
cold water		Partially solu	ıble			
Partition coefficient: n-octar water	ol/ :	Not relevant/a	applicable du	e to nature	e of the pr	oduct.
Auto-ignition temperature	:					
Ingredient name		°C		°F		Method
Trimethylpentanediol Isobutyrate Propylene Glycol		392 400		737.6 752		
Decomposition temperature	:	Not relevant/a	pplicable du	e to nature	e of the pr	oduct.
Viscosity	:	Kinematic (40	°C): >20.5 n	וm²/s		
Explosive properties	:	Under normal	conditions of	of storage a	and use, h	nazardous reactions will not occur.
Oxidizing properties	:	Under normal	conditions of	of storage a	and use, h	nazardous reactions will not occur.
Particle characteristics						
Median particle size	:	Not relevant/a	pplicable du	e to nature	e of the pro	oduct.
9.2 Other information						
Heat of combustion	:	0.943 kJ/g				
SECTION 10: Stability an	d rea	activity				
10.1 Reactivity	: No	o specific test da	ata related to	reactivity	available	for this product or its ingredients.
10.2 Chemical stability	: St	able under reco	mmended s	torage and	d handling	conditions (see Section 7).
10.3 Possibility of hazardous reactions	: Ur	nder normal cor	nditions of st	orage and	use, haza	rdous reactions will not occur.
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.					
10.5 Incompatible materials		eep away from t idizing agents, s				t strong exothermic reactions:
10.6 Hazardous decomposition products	 Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen. 					
Refer to Section 7: HANDLIN	ANI	D STORAGE al	nd Section	B: EXPOSU	URE CON	ITROLS/PERSONAL

PROTECTION for additional handling information and protection of employees.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

SHW-A4-EU-CLP44-UA

Phoenix 370-60 - WHITE

PH370-60

SECTION 11: Toxicological information

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
1,3,5-Triazine-2,4,6-triamine	LD50 Oral	Rat	3161 mg/kg	-
Chloropropanol Phosphate	LD50 Oral	Rat	1500 mg/kg	-

Acute toxicity estimates

Route	ATE value		
Oral	51932.11 mg/kg		

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
1,3,5-Triazine-2,4,6-triamine	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-
Conclusion/Summary	: Not available.				

Conclusion/Summary

Sensitization

No data available

: Not available. Conclusion/Summary

Mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

Teratogenicity

No data available

Specific target organ toxicity (single exposure)

No data available

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
1,3,5-Triazine-2,4,6-triamine	Category 2	-	urinary tract

Aspiration hazard

No data available

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties Not available. 11.2.2 Other information Not available.

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II Phoenix 370-60 - WHITE

PH370-60

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself. Do not allow to enter drains or watercourses.

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

12.2 Persistence and degradability

Product/ingredient name	Test	Result		Dose		Inoculum
No data available						
Conclusion/Summary	: Not available.					•
Product/ingredient name	Aquatic half-life		Photolysis		Biodeg	radability
No data available						

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
1,3,5-Triazine-2,4,6-triamine		<3.8	Low
Chloropropanol Phosphate		0.8 to 2.8	Low

12.4 Mobility in soil	
Soil/water partition coefficient (K _{oc})	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	
Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: Yes.
European waste catalogue (EWC)	 waste paint and varnish containing organic solvents or other hazardous substances 08 01 11*

SECTION 13: Disposal considerations

-	
Disposal considerations	 Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.
<u>Packaging</u>	
Methods of disposal	The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Disposal considerations	Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.
European waste catalogue (EWC)	: packaging containing residues of or contaminated by hazardous substances 15 01 10*
Special precautions	This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG	ΙΑΤΑ
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport Hazard Class(es)/ Label(s)	-	-	-
14.4 Packing group	-	-	-
14.5 Environmental hazards	No.	No.	No.
Additional information	-	-	-

This mixture is not classified as dangerous according to international transport regulations (ADR/RID, IMDG, ICAO/IATA).

14.6 Special precautions for user: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in	: Not applicable.
bulk according to IMO	
instruments	

SECTION 14: Transport information

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

Ingredient name	Intrinsic property	Status	Reference number	Date of revision
1,3,5-Triazine-2,4,6-triamine	Substance of equivalent concern for human health	Candidate	D(2022) 9120-DC	1/17/2023
1,3,5-Triazine-2,4,6-triamine	Substance of equivalent concern for environment	Candidate	D(2022) 9120-DC	1/17/2023

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]	
Phoenix 370-60	≥90	3	
Labeling Other EU regulations	: Not applicable.		
VOC content (2010/75/EU)	: 1.2 w/w 17 g/l		
Explosive precursors <u>Seveso Directive</u>	: Not applicable.		
This product is not controlled National regulations	under the Seveso Directive.		
15.2 Chemical Safety Assessment	: No Chemical Safety Assessment has been carried out		

SECTION 16: Other information

Indicates information that has changed from previously issued version.				
Abbreviations and acronyms : ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Ref 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number vPvB = Very Persistent and Very Bioaccumulative N/A = Not available	egulation (EC) No.			

SECTION 16: Other information

Key literature references	: Regulation (EC) No. 1272/2008 [CLP]
and sources for data	ADR = The European Agreement concerning the International Carriage of
	Dangerous Goods by Road
	IATĂ = International Air Transport Association
	IMDG = International Maritime Dangerous Goods
	Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by
	Commission Regulation (EU) 2020/878
	Directive 2012/18/EU, and relative amendments & additions
	Directive 2008/98/EC, and relative amendments & additions
	Directive 2009/161/EU, and relative amendments & additions
	CEPE Guidelines

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification		Justification
Carc. 2, H351 Repr. 2, H361 STOT RE 2, H373		Calculation method Calculation method Calculation method
Full text of abbreviated H statements	H351 Susp H361 Susp	nful if swallowed. ected of causing cancer. ected of damaging fertility or the unborn child. cause damage to organs through prolonged or repeated sure.
Full text of classifications [CLP/GHS]	: Acute Tox. 4 Carc. 2 Repr. 2 STOT RE 2	ACUTE TOXICITY - Category 4 CARCINOGENICITY - Category 2 TOXIC TO REPRODUCTION - Category 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
Date of printing	: 15, Apr, 2024.	
Date of issue/ Date of revision	: 15, Apr, 2024	
Date of previous issue	: 23, Sep, 2023	
	: If there is no previous information.	validation date please contact your supplier for more
Version	: 10	

Notice to reader

In accordance with Regulation (EC) 1907/2006, REACH Regulation, Articles 31, 37, any required hazard-related information on the use of substances received as downstream user will be sent forward. Consequently, the safety data sheets for some products will contain a SUMI - Safe Use of Mixture Information - attached to the safety data sheet.

SUMI(s) will be added to the SDS for products if both the following conditions are met:

• The product is classified as hazardous for health

• The product contains one or more REACH-registered substances for which extended safety data sheets (exposure scenarios) have been provided

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the

SECTION 16: Other information

manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.