SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : Resuflor HB Clear Hardener

Product code : TOSTCLA

1.2 Relevant identified uses of the substance or mixture and uses advised against

Material uses : Paint or paint related material.

: Industrial use only.

1.3 Details of the supplier of the safety data

sheet

Sherwin-Williams UK Limited - Protective & Marine

Coatings Division EMEAI

Tower Works Kestor Street Bolton BL2 2AL

United Kingdom +44 (0) 1204 521771

The Sherwin-Williams Company Inver France SAS 2 Rue Jean Revaus - BP 80088 - 79102

Thouars CEDEX

France

e-mail address of person responsible for this SDS

: hse.pm.emea@sherwin.com

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : 111 (general public) /0344 892 111 (Medical professional (NHS) only)

Supplier

Telephone number : +(44)-870-8200 418

Hours of operation : Emergency contact available 24 hours a day

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition: Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Repr. 1B, H360Fd Aquatic Chronic 1, H410

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

Date of issue/Date of revision : 07, Mar, 2024 Date of previous issue : 22, Sep, 2023 Version : 11 1/16

Resuflor HB Clear Hardener

TOSTCLA

SECTION 2: Hazards identification

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms









Signal word Danger

Hazard statements : Harmful if swallowed.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

May damage fertility. Suspected of damaging the unborn child.

Very toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention : Obtain special instructions before use. Wear protective gloves, protective clothing,

eye protection, face protection, or hearing protection. Avoid release to the

environment.

Response : Collect spillage. IF exposed or concerned: Get medical advice or attention. IF

INHALED: Immediately call a POISON CENTER or doctor.

Storage Not applicable. Disposal : Not applicable. Hazardous ingredients : Isophorone Diamine

Phenylmethanol

1,3-Benzenedimethanamine

4,4'-Isopropylidenediphenol : FOR INDUSTRIAL USE ONLY

Supplemental label

elements

Special packaging requirements

Not applicable.

2.3 Other hazards

This mixture does not contain any substances that are assessed to be a PBT or a

vPvB.

Other hazards which do not result in classification This substance/mixture contains components considered to have endocrine disrupting properties affecting human health, according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100. This substance/mixture contains components considered to have endocrine disrupting properties for environment, according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

SECTION 3: Composition/information on ingredients

3.2 Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Isophorone Diamine	EC: 220-666-8 CAS: 2855-13-2 Index: 612-067-00-9	≥25 - ≤50	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317	ATE [Oral] = 1030 mg/kg Skin Sens. 1, H317: C ≥ 0.001%	[1]
Phenylmethanol	REACH #: 01-2119492630-38 EC: 202-859-9	≥25 - ≤50	Acute Tox. 4, H302 Acute Tox. 4, H332 Eye Irrit. 2, H319	ATE [Oral] = 1230 mg/kg ATE [Inhalation	[1]

Date of issue/Date of revision : 07, Mar, 2024 Date of previous issue 2/16 : 22, Sep, 2023 Version

Resuflor HB Clear Hardener

TOSTCLA

SECTION 3: Composition/information on ingredients

1	CAC. 100 E1 C			(vanauna)1 = 44 ·/	1
	CAS: 100-51-6			(vapours)] = 11 mg/	
	Index: 603-057-00-5				
Cyclohexanemethanamine,	REACH #:	≥10 - ≤16	Acute Tox. 4, H302	ATE [Oral] = 500	[1]
5-amino-1,3,3-trimethyl-,	01-2120770776-40		Skin Corr. 1C, H314	mg/kg	
reaction products with	EC: 291-130-9		Eye Dam. 1, H318	M [Acute] = 1	
glycidyl tolyl ether	CAS: 90341-97-2		Aquatic Acute 1, H400		
			Aquatic Chronic 2,		
			H411		
1,3-Benzenedimethanamine	EC: 216-032-5	≤10	Acute Tox. 4, H302	ATE [Oral] = 930	[1]
,	CAS: 1477-55-0		Acute Tox. 4, H332	mg/kg	
			Skin Corr. 1B, H314	ATE [Inhalation	
			Eye Dam. 1, H318	(gases)] = 4500	
			Skin Sens. 1, H317	ppm	
			Aquatic Chronic 3,	PF	
			H412		
4,4'-Isopropylidenediphenol	REACH #:	≤8.8	Eye Dam. 1, H318	M [Acute] = 1	[1] [2]
,,	01-2119457856-23		Skin Sens. 1, H317	M [Chronic] = 10	[3]
	EC: 201-245-8		Repr. 1B, H360F	[0010]	[0]
	CAS: 80-05-7		STOT SE 3, H335		
	Index: 604-030-00-0		Aquatic Acute 1, H400		
	III GOX: 00 000 00 0		Aquatic Chronic 1,		
			H410		
Salicylic Acid	EC: 200-712-3	≤5	Acute Tox. 4, H302	ATE [Oral] = 500	[1]
Cancyno / tota	CAS: 69-72-7		Eye Dam. 1, H318	mg/kg	[,1
	Index: 607-732-00-5		Repr. 2, H361d	1119/119	
	mack. 001-102-00-0		See Section 16 for		
			the full text of the H		
			statements declared		
			above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

General	: In all cases of doubt, or when symptoms persist, seek medical attention. Never give	
	anything by mouth to an unconscious person. If unconscious, place in recovery	

position and seek medical advice.

Eye contact : Check for and remove any contact lenses. Immediately flush eyes with running

water for at least 15 minutes, keeping eyelids open. Seek immediate medical

attention.

Inhalation: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

Skin contact: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use recognised skin cleanser. Do NOT use solvents or thinners.

If swallowed, seek medical advice immediately and show the container or label.

Keep person warm and at rest. Do NOT induce vomiting.

Date of issue/Date of revision : 07, Mar, 2024 Date of previous issue : 22, Sep, 2023 Version : 11 3/16

Resuflor HB Clear Hardener

TOSTCLA

SECTION 4: First aid measures

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 3-aminomethyl-3,5,5-trimethylcyclohexylamine, m-phenylenebis(methylamine), 4,4'-isopropylidenediphenol. May produce an allergic reaction.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments: No specific treatment.

See toxicological information (Section 11)

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

9

: Recommended: alcohol-resistant foam, CO2, powders, water spray or mist.

Unsuitable extinguishing

media

: Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

: Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

Hazardous combustion

products

: Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

5.3 Advice for firefighters

Special protective actions for fire-fighters

: Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.

Special protective equipment for fire-fighters

: Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

Date of issue/Date of revision: 07, Mar, 2024Date of previous issue: 22, Sep, 2023Version: 114/16

Resuflor HB Clear Hardener

TOSTCLA

SECTION 6: Accidental release measures

Due to the organic solvents content of the mixture:

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.

Keep unnecessary and unprotected personnel from entering.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

: Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.

6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

: Due to the organic solvents content of the mixture:

Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.

Keep away from heat, sparks and flame. No sparking tools should be used. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.

Put on appropriate personal protective equipment (see Section 8). Never use pressure to empty. Container is not a pressure vessel.

Always keep in containers made from the same material as the original one.

Comply with the health and safety at work laws. Information on fire and explosion protection

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

Date of issue/Date of revision Version : 11 : 07, Mar, 2024 Date of previous issue : 22, Sep, 2023 5/16

Resuflor HB Clear Hardener

TOSTCLA

SECTION 7: Handling and storage

7.2 Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations.

Notes on joint storage

Keep away from: oxidising agents, strong alkalis, strong acids.

Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away

from heat and direct sunlight. Keep container tightly closed.

Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Contaminated absorbent material may pose the same hazard as the spilt product.

7.3 Specific end use(s)

Recommendations
Industrial sector specific solutions

Not available.Not available.

Good housekeeping standards, regular safe removal of waste materials and regular maintenance of spray booth filters will minimise the risks of spontaneous combustion and other fire hazards.

Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values	
4,4'-Isopropylidenediphenol	EH40/2005 WELs (United Kingdom (UK), 1/2020). TWA: 2 mg/m ³ 8 hours.	

Biological exposure indices

No exposure indices known.

Recommended monitoring procedures

- : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
- : Regular monitoring of all work areas should be carried out at all times, including areas that may not be equally ventilated.

DNELs/DMELs

No DNELs/DMELs available.

PNECs

No PNECs available

8.2 Exposure controls

Date of issue/Date of revision: 07, Mar, 2024Date of previous issue: 22, Sep, 2023Version: 116/16

Resuflor HB Clear Hardener

TOSTCLA

SECTION 8: Exposure controls/personal protection

Appropriate engineering controls

- : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.
- : Users are advised to consider national Occupational Exposure Limits or other equivalent values.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection Skin protection

: Use safety eyewear designed to protect against splash of liquids.

Hand protection

: Wear suitable gloves tested to EN374.

Gloves

: Gloves for short term exposure/splash protection (less than 10 min.): Nitrile>0.12 mm

Gloves for splash protection need to be changed immediately when in contact with chemicals.

Gloves for repeated or prolonged exposure (breakthrough time>480 min.): Butyl gloves>0.3 mm

Due to many conditions (e.g. temperature, abrasion) the practical usage of a chemical protective glove in practice may be much shorter than the permeation time determined through testing.

The recommendation for the type or types of glove to use when handling this product is based on information from the following source: Solvent resin manufacturers and European Solvents Industry Group (ESIG)

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Body protection

- : Personnel should wear protective clothing.
- : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Application methods:

Brush or roller. Approved/certified respirator with organic vapour cartridge. Filter type: A2 P2 (EN14387).

Manual spraying. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Date of issue/Date of revision : 07, Mar, 2024 Date of previous issue : 22, Sep, 2023 Version : 11 7/16

Resuflor HB Clear Hardener

TOSTCLA

SECTION 8: Exposure controls/personal protection

Environmental exposure

: Do not allow to enter drains or watercourses.

controls

Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid. Colour : Colourless. Odour : Paint

Odour threshold : Not Available (Not Tested).

pН : Not relevant/applicable due to nature of the product.

insoluble in water.

Melting point/freezing point : Not relevant/applicable due to nature of the product.

: 202°C Initial boiling point and

boiling range

Flash point : Closed cup: 100°C [Pensky-Martens Closed Cup] Evaporation rate : Not relevant/applicable due to nature of the product. : Not relevant/applicable due to nature of the product. **Flammability**

Lower and upper explosion

: LEL: 1.1% (Salicylic Acid) UEL: 13% (Phenylmethanol) limit

Vapour pressure : 0.02 kPa (0.15 mm Hg)

Relative vapour density : 3.72 [Air = 1]

Relative density : 1.04

Solubility(ies)

Media	Result
cold water	Partially soluble

Partition coefficient: n-octanol/: Not relevant/applicable due to nature of the product.

water

Auto-ignition temperature

Ingredient name	°C	°F	Method
Phenylmethanol	436 500	816.8 932	
4,4'-lsopropylidenediphenol Salicylic Acid	540	1004	

Decomposition temperature : Not relevant/applicable due to nature of the product.

Viscosity : Kinematic (40°C): >20.5 mm²/s

Explosive properties : Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising properties : Under normal conditions of storage and use, hazardous reactions will not occur.

Particle characteristics

Median particle size : Not relevant/applicable due to nature of the product.

9.2 Other information

Heat of combustion : 36.111 kJ/g

Date of issue/Date of revision : 07, Mar, 2024 Date of previous issue : 22, Sep, 2023 Version :11 8/16

Resuflor HB Clear Hardener

TOSTCLA

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : Stable under recommended storage and handling conditions (see Section 7).

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition

products.

10.5 Incompatible materials: Keep away from the following materials to prevent strong exothermic reactions:

oxidising agents, strong alkalis, strong acids.

10.6 Hazardous decomposition products

Decomposition products may include the following materials: carbon monoxide,

carbon dioxide, smoke, oxides of nitrogen.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 3-aminomethyl-3,5,5-trimethylcyclohexylamine, m-phenylenebis(methylamine), 4,4'-isopropylidenediphenol. May produce an allergic reaction.

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Phenylmethanol	LD50 Dermal	Rabbit	2000 mg/kg	-
	LD50 Oral	Rat	1230 mg/kg	-
1,3-Benzenedimethanamine	LC50 Inhalation Gas.	Rat	700 ppm	1 hours
	LD50 Dermal	Rabbit	2 g/kg	-
	LD50 Oral	Rat	930 mg/kg	-
4,4'-lsopropylidenediphenol	LD50 Oral	Rat	1200 mg/kg	-

Acute toxicity estimates

Route	ATE value	
Oral Inhalation (gases) Inhalation (vapours)	970.3 mg/kg 50000 ppm 37.93 mg/l	

Date of issue/Date of revision: 07, Mar, 2024Date of previous issue: 22, Sep, 2023Version: 119/16

Resuflor HB Clear Hardener

TOSTCLA

SECTION 11: Toxicological information

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Phenylmethanol	Skin - Mild irritant	Man	-	48 hours 16	-
				mg	
	Skin - Moderate irritant	Pig	-	100 %	-
	Skin - Moderate irritant	Rabbit	-	24 hours 100	-
				mg	
1,3-Benzenedimethanamine	Eyes - Severe irritant	Rabbit	-	24 hours 50	-
				ug	
	Skin - Severe irritant	Rabbit	-	24 hours 750	-
				ug	
4,4'-Isopropylidenediphenol	Eyes - Severe irritant	Rabbit	-	24 hours 250	-
				ug	
	Skin - Mild irritant	Rabbit	-	250 mg	-
	Skin - Mild irritant	Rabbit	-	24 hours 500	-
				mg	

Conclusion/Summary

: Not available.

Sensitisation

No data available

Conclusion/Summary

: Not available.

Mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

Teratogenicity

No data available

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
4,4'-lsopropylidenediphenol	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

No data available

Aspiration hazard

No data available

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

This substance/mixture contains components considered to have endocrine disrupting properties affecting human health, according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

11.2.2 Other information

Not available.

Date of issue/Date of revision : 07, Mar, 2024 Date of previous issue : 22, Sep, 2023 Version : 11 10/16

Resuflor HB Clear Hardener

TOSTCLA

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself.

Do not allow to enter drains or watercourses.

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

Product/ingredient name	Result	Species	Exposure
Isophorone Diamine	Acute EC50 17.4 mg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
Phenylmethanol	Acute LC50 10 ppm Fresh water	Fish - Lepomis macrochirus	96 hours
4,4'-Isopropylidenediphenol	Acute EC50 1.506 mg/l Marine water	Algae - <i>Prorocentrum minimum</i> - Exponential growth phase	72 hours
	Acute EC50 1800 µg/l Marine water	Algae - Skeletonema costatum	96 hours
	Acute EC50 7.3 mg/l Fresh water	Daphnia - <i>Daphnia magna</i> - Neonate	48 hours
	Acute LC50 1.34 mg/l Marine water	Crustaceans - Americamysis bahia - Larvae	48 hours
	Acute LC50 3.5 mg/l Marine water	Fish - <i>Rivulus marmoratus</i> - Embryo	96 hours
	Chronic NOEC 2 mg/l Fresh water	Algae - <i>Chlorolobion braunii</i> - Exponential growth phase	4 days
	Chronic NOEC 10 µg/l Marine water	Crustaceans - Tigriopus japonicus - Nauplii	21 days
	Chronic NOEC 30 µg/l Fresh water	Daphnia - <i>Daphnia magna</i> - Neonate	21 days
	Chronic NOEC 0.2 µg/l Fresh water	Fish - Carassius auratus - Adult	90 days
Salicylic Acid	Acute LC50 111.7 mg/l Fresh water	Daphnia - <i>Daphnia magna</i> - Neonate	48 hours
	Chronic NOEC 5.6 mg/l Fresh water	Daphnia - <i>Daphnia magna</i> - Neonate	21 days

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
No data available				

Conclusion/Summary: Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Phenylmethanol	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
1,3-Benzenedimethanamine 4,4'-Isopropylidenediphenol		2.69 20 to 67	Low Low

12.4 Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Date of issue/Date of revision	: 07, Mar, 2024	Date of previous issue	: 22, Sep, 2023	Version :11	11/16

Resuflor HB Clear Hardener

TOSTCLA

SECTION 12: Ecological information

12.6 Endocrine disrupting properties

This substance/mixture contains components considered to have endocrine disrupting properties for environment, according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal

The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste

European waste catalogue (EWC) : Yes.

waste paint and varnish containing organic solvents or other hazardous substances

08 01 11*

Disposal considerations

: Do not allow to enter drains or watercourses.

Dispose of according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no

longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

Packaging

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Disposal considerations

: Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.

European waste catalogue (EWC)

Special precautions

packaging containing residues of or contaminated by hazardous substances 15 01 10*

This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA
14.1 UN number or ID number	UN3066	UN3066	UN3066
14.2 UN proper shipping name	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL. Marine pollutant (4,4'- Isopropylidenediphenol)	PAINT RELATED MATERIAL
14.3 Transport Hazard Class(es)/ Label(s)	8	8	8

Date of issue/Date of revision : 07, Mar, 2024 Date of previous issue : 22, Sep, 2023 Version : 11 12/16

Resuflor HB Clear Hardener

TOSTCLA

SECTION 14: Transport information

14.4 Packing group	II	II	II
14.5 Environmental hazards	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Additional information	The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg. Tunnel code E	The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg. Emergency schedules F-A, S-B	The environmentally hazardous substance mark may appear if required by other transportation regulations.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

: Not applicable.

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

Ingredient name	Intrinsic property	Status	Reference number	Date of revision
4,4'-Isopropylidenediphenol 4,4'-Isopropylidenediphenol	Toxic to reproduction Endocrine disrupting properties for human health	Recommended Recommended	ED/01/2018 ED/01/2018	10/1/2019 10/1/2019
4,4'-Isopropylidenediphenol	Endocrine disrupting properties for environment	Recommended	ED/01/2018	10/1/2019

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

0
3
30
30 66

Labelling : Restricted to professional users.

Other EU regulations

VOC content (2010/75/EU) : 40 w/w

Date of issue/Date of revision : 07, Mar, 2024 Date of previous issue : 22, Sep. 2023 Version : 11 13/16

Resuflor HB Clear Hardener

TOSTCLA

SECTION 15: Regulatory information

418 g/l

Explosive precursors

: Not applicable.

Seveso Directive

This product may add to the calculation for determining whether a site is within the scope of the Seveso Directive on major accident hazards.

National regulations

15.2 Chemical safety

: No Chemical Safety Assessment has been carried out.

assessment

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and

: ATE = Acute Toxicity Estimate

acronyms CLF

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

vPvB = Very Persistent and Very Bioaccumulative

N/A = Not available

Key literature references and sources for data : Regulation (EC) No. 1272/2008 [CLP]

ADR = The European Agreement concerning the International Carriage of

Dangerous Goods by Road

IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by

Commission Regulation (EU) 2020/878

Directive 2012/18/EU, and relative amendments & additions Directive 2008/98/EC, and relative amendments & additions Directive 2009/161/EU, and relative amendments & additions

CEPE Guidelines

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Acute Tox. 4, H302	Calculation method
Skin Corr. 1B, H314	Calculation method
Eye Dam. 1, H318	Calculation method
Skin Sens. 1, H317	Calculation method
Repr. 1B, H360Fd	Calculation method
Aquatic Chronic 1, H410	Calculation method

Full text of abbreviated H statements

: H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H360F May damage fertility.

H360Fd May damage fertility. Suspected of damaging the unborn child.

H361d Suspected of damaging the unborn child.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.H411 Toxic to aquatic life with long lasting effects.

Date of issue/Date of revision : 07, Mar, 2024 Date of previous issue : 22, Sep, 2023 Version : 11 14/16

Resuflor HB Clear Hardener

TOSTCLA

SECTION 16: Other information

H412 Harmful to aquatic life with long lasting effects.

Full text of classifications

[CLP/GHS]

: Acute Tox. 4 ACUTE TOXICITY - Category 4

Aquatic Acute 1 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category

1

Aquatic Chronic 1 LONG-TERM (CHRONIC) AQUATIC HAZARD -

Category 1

Aquatic Chronic 2 LONG-TERM (CHRONIC) AQUATIC HAZARD -

Category 2

Aquatic Chronic 3 LONG-TERM (CHRONIC) AQUATIC HAZARD -

Category 3

Eye Dam. 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2

Repr. 1B REPRODUCTIVE TOXICITY - Category 1B
Repr. 2 REPRODUCTIVE TOXICITY - Category 2
Skin Corr. 1B SKIN CORROSION/IRRITATION - Category 1B
Skin Corr. 1C SKIN CORROSION/IRRITATION - Category 1C

Skin Sens. 1 SKIN SENSITISATION - Category 1
Skin Sens. 1A SKIN SENSITISATION - Category 1A

STOT SE 3 SPECIFIC TARGET ORGAN TOXICITY - SINGLE

EXPOSURE - Category 3

Date of printing : 07, Mar, 2024.

Date of issue/ Date of

revision

: 07, Mar, 2024

Date of previous issue : 22, Sep, 2023

: If there is no previous validation date please contact your supplier for more

information.

Version : 11

Notice to reader

In accordance with Regulation (EC) 1907/2006, REACH Regulation, Articles 31, 37, any required hazard-related information on the use of substances received as downstream user will be sent forward. Consequently, the safety data sheets for some products will contain a SUMI - Safe Use of Mixture Information - attached to the safety data sheet.

SUMI(s) will be added to the SDS for products if both the following conditions are met:

- The product is classified as hazardous for health
- The product contains one or more REACH-registered substances for which extended safety data sheets (exposure scenarios) have been provided

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become make themselves aware of and understand the data contained in this SDS and any hazards that may be associated with the product. This information is provided in good faith and believed to be accurate as of the effective date mentioned herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can may change later the composition, hazards and risks of the product. Products shall should not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to, the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for the use of the product are not under the manufacturer's control of the manufacturer; the customer/buyer/user is responsible to for determine determining the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS, without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be held responsible for SDSs obtained from any other source.

Date of issue/Date of revision : 07, Mar, 2024 Date of previous issue : 22, Sep, 2023 Version : 11 15/16

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II
Resuflor HB Clear Hardener

TOSTCLA

Date of issue/Date of revision: 07, Mar, 2024Date of previous issue: 22, Sep, 2023Version: 1116/16