# SAFETY DATA SHEET

## **SECTION 1:** Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier	
Product name	: DEGREASER W500
Product code	: W500

	of the substance or mixture and uses advised against
Material uses	Paint or paint related material.
	: Industrial use only.
1.3 Details of the supplier of sheet	the safety data
Sherwin-Williams Protective & Tower Works Kestor Street Bolton BL2 2AL United Kingdom +44 (0) 1204 521771	& Marine
The Sherwin-Williams Compa Inver France SAS 2 Rue Jean Revaus - BP 800 Thouars CEDEX France	
e-mail address of person responsible for this SDS	: hse.pm.emea@sherwin.com
1.4 Emergency telephone nu	ımber
National advisory body/Poi	son Center
Telephone number	: +45 82 12 12 12
<u>Supplier</u>	
Telephone number	: +(44)-870-8200 418
Hours of operation	: Emergency contact available 24 hours a day
SECTION 2: Hazards ide	
2.1 Classification of the subs	
Product definition	: Mixture

## Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS] Skin Irrit. 2, H315 Eye Irrit. 2, H319 The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended. See Section 16 for the full text of the H statements declared above. See Section 11 for more detailed information on health effects and symptoms.

## 2.2 Label elements

1/14

SECTION 2: Hazards identification		
Hazard pictograms		
Signal word	: Warning	
Hazard statements	: Causes skin irritation. Causes serious eye irritation.	
Precautionary statements		
Prevention	: Wear protective gloves. Wear eye or face protection. Wash thoroughly after handling.	
Response	: Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.	
Storage	: Not applicable.	
Disposal	: Not applicable.	
Hazardous ingredients	: Potassium Hydroxide	
Supplemental label elements	: FOR INDUSTRIAL USE ONLY	
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.	
Special packaging requirem Not applicable.	<u>ients</u>	

# 2.3 Other hazards

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do : None known. not result in classification

## **SECTION 3: Composition/information on ingredients**

:

#### 3.2 Mixture

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Туре
Triethanolamine	EC: 203-049-8 CAS: 102-71-6	≥25 - ≤50	Not classified.	[2] 🥄
Potassium Hydroxide	REACH #: 01-2119487136-33 EC: 215-181-3 CAS: 1310-58-3 Index: 019-002-00-8	<2	Acute Tox. 3, H301 Skin Corr. 1A, H314 Eye Dam. 1, H318	[1] [2]
			See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

DEGREASER W500

#### W500

## **SECTION 3: Composition/information on ingredients**

#### <u>Type</u>

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern
- [6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

## SECTION 4: First aid measures

#### 4.1 Description of first aid measures

General	<ul> <li>In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.</li> </ul>
Eye contact	<ul> <li>Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.</li> </ul>
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	<ul> <li>Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.</li> </ul>
Ingestion	<ul> <li>If swallowed, seek medical advice immediately and show this container or label.</li> <li>Keep person warm and at rest. Do NOT induce vomiting.</li> </ul>
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

## 4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

## 4.3 Indication of any immediate medical attention and special treatment needed

*Notes to physician* : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments : No specific treatment.

See toxicological information (Section 11)

## SECTION 5: Firefighting measures

: Recommended: alcohol-resistant foam, carbon dioxide, powders.
: Do not use water jet.
om the substance or mixture
: Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.
: Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.
: Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.
: Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

# **SECTION 6: Accidental release measures**

#### Due to the organic solvents content of the mixture:

6.1 Personal precautions, protective equipment and emergency procedures		
For non-emergency personnel	:	Exclude sources of ignition and ventilate the area. Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8.
For emergency responders	:	Keep unnecessary and unprotected personnel from entering. If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.
6.3 Methods and materials for containment and cleaning up	:	Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

# SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling	: Due to the organic solvents content of the mixture:
<b>y</b>	Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Keep away from heat, sparks and flame. No sparking tools should be used. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or
	······································

Date of issue/Date of revision	: 27, Sep, 2021	Date of previous issue	: 16, Apr, 2021	Version : 3.03	4/14
				SHW-A4-EU-CLP44-DK	

## SECTION 7: Handling and storage mist arising from the application of this mixture. Avoid inhalation of dust from sanding. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Put on appropriate personal protective equipment (see Section 8). Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one. Comply with the health and safety at work laws. Information on fire and explosion protection Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. 7.2 Conditions for safe : Store in accordance with local regulations. storage, including any Notes on joint storage Keep away from: oxidizing agents, strong alkalis, strong acids. incompatibilities Additional information on storage conditions Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep container tightly closed. Keep away from sources of ignition. No smoking. Prevent unauthorized access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Contaminated absorbent material may pose the same hazard as the spilled product. Store in closed original container at temperatures between 5°C and 25°C. 7.3 Specific end use(s)

Recommendations	: Not available.
Industrial sector specific	: Not available.
solutions	

Good housekeeping standards, regular safe removal of waste materials and regular maintenance of spray booth filters will minimise the risks of spontaneous combustion and other fire hazards.

Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

## 8.1 Control parameters

## **Occupational exposure limits**

Product/ingredient name	Exposure limit values	
Triethanolamine	Working Environment Authority (Denmark, 2/2021). TWA: 0.5 ppm 8 hours.	
Potassium Hydroxide	TWA: 0.5 ppm 8 hours. TWA: 3.1 mg/m <sup>3</sup> 8 hours. Working Environment Authority (Denmark, 2/2021). CEIL: 2 mg/m <sup>3</sup>	

## **SECTION 8: Exposure controls/personal protection**

Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
	. Describer reprisering of all work areas about the permised out at all times, including

: Regular monitoring of all work areas should be carried out at all times, including areas that may not be equally ventilated.

#### **DNELs/DMELs**

Product/ingredient name	Туре	Exposure	Value	Population	Effects
,	DNEL	Long term Inhalation Long term Inhalation	5	Workers Workers	Local Local

#### PNECs

No PNECs available.

#### 8.2 Exposure controls

Appropriate engineering controls		Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn. Users are advised to consider national Occupational Exposure Limits or other equivalent values.
Individual protection measu	re	<u>S</u>
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Use safety eyewear designed to protect against splash of liquids.
Skin protection		
Hand protection	:	Wear suitable gloves tested to EN374.
Gloves		Gloves for short term exposure/splash protection (less than 10 min): Nitrile >0.12 mm Gloves for splash protection need to be changed immediately when in contact with chemicals. Gloves for repeated or prolonged exposure (breakthrough time > 480 min): Butyl gloves >0.3 mm Due to many conditions (e.g. temperature, abrasion) the practical usage of a chemical protective glove in practice may be much shorter than the permeation time determined through testing. The recommendation for the type or types of glove to use when handling this product is based on information from the following source: Solvent resin manufacturers and European Solvents Industry Group (ESIG).

## **SECTION 8: Exposure controls/personal protection**

	There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used
	The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.
	Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.
	The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
Body protection	: Personnel should wear protective clothing.
	<ul> <li>Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Other skin protection	<ul> <li>Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Respiratory protection	: Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Recommended: A2P2 (EN14387). Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	: Do not allow to enter drains or watercourses.

Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

## **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### 9.1 Information on basic physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Color	: Colorless.
Odor	: Paint
Odor threshold	: Not Available (Not Tested).
pН	: 10.5
Melting point/freezing point	: Not relevant/applicable due to nature of the product.
Initial boiling point and boiling range	: 100°C
Flash point	: Closed cup: Not applicable.
Evaporation rate	: 0.09 (butyl acetate = 1)
Flammability (solid, gas)	: Not relevant/applicable due to nature of the product.
Upper/lower flammability or explosive limits	: LEL: 1.3% (Triethanolamine) UEL: 8.5% (Triethanolamine)

## **SECTION 9: Physical and chemical properties**

Vapor pressure	:	2.3 kPa (17.5 mm Hg)
Vapor density	:	1 [Air = 1]
Relative density	:	0.97
Solubility(ies)	:	Not relevant/applicable due to nature of the product.
Partition coefficient: n-octanol/ water	:	Not relevant/applicable due to nature of the product.
Auto-ignition temperature	:	Not relevant/applicable due to nature of the product.
Decomposition temperature		Not relevant/applicable due to nature of the product.
Viscosity	:	Kinematic (40°C): >20.5 mm <sup>2</sup> /s
Explosive properties	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Oxidizing properties	:	Under normal conditions of storage and use, hazardous reactions will not occur.

### **SECTION 10: Stability and reactivity** : No specific test data related to reactivity available for this product or its ingredients. 10.1 Reactivity : Stable under recommended storage and handling conditions (see Section 7). 10.2 Chemical stability 10.3 Possibility of : Under normal conditions of storage and use, hazardous reactions will not occur. hazardous reactions 10.4 Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition products. 10.5 Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids. Decomposition products may include the following materials: carbon monoxide, 10.6 Hazardous carbon dioxide, smoke, oxides of nitrogen. decomposition products

# Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

## **SECTION 11: Toxicological information**

11.1 Information on toxicological effects

There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Potassium Hydroxide	LD50 Oral	Rat	273 mg/kg	-

### Acute toxicity estimates

Date of issue/Date of revision	: 27, Sep, 2021	Date of previous issue	: 16, Apr, 2021	Version

:303

8/14

# **SECTION 11: Toxicological information**

Route	ATE value
Oral	17062.5 mg/kg

# Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
		•	Score		Observation
Potassium Hydroxide	Eyes - Moderate irritant	Rabbit	-	24 hours 1	-
	Skin - Severe irritant	Guinea pig	_	mg 24 hours 50	_
		Curred pig		mg	
	Skin - Severe irritant	Human	-	24 hours 50	-
	Chin Course initent	Data		mg	
	Skin - Severe irritant	Rabbit	-	24 hours 50 mg	-
0				ing	
Conclusion/Summary	: Not available.				
<u>Sensitization</u>					
No data available					
Conclusion/Summary	: Not available.				
Mutagenicity					
No data available					
<u>Carcinogenicity</u> No data available					
NO Uala avaliable					
Reproductive toxicity					
No data available					
<u>Teratogenicity</u>					
No data available					
	<i>.</i>				
Specific target organ toxicit	<u>y (single exposure)</u>			,	
Product/ing	redient name	Category			larget organs
			exp	osure	
No data available					

#### Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
No data available			

Aspiration hazard

	Product/ingredient name	Result
No data available		

Other information

# : Not available.

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

There are no data available on the mixture itself. Do not allow to enter drains or watercourses.

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

# **SECTION 12: Ecological information**

Product/ingredient name	Result	Species	Exposure
Potassium Hydroxide	Acute LC50 80 ppm Fresh water	Fish - Gambusia affinis - Adult	96 hours

# 12.2 Persistence and degradability

Product/ingredient name	Test	Result		Dose		Inoculum
No data available						
Conclusion/Summary	: Not available.					
Product/ingredient name	Aquatic half-life		Photolysis		Biodeg	radability
No data available						

## 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
No data available			

12.4 Mobility in soil	
Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

## 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects	:	No known significant effects or critical hazards.
	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# **SECTION 13: Disposal considerations**

## 13.1 Waste treatment methods

<u>Product</u>	
Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: Yes.
European waste catalogue (EWC)	<ul> <li>waste paint and varnish containing organic solvents or other hazardous substances 08 01 11*</li> </ul>
Disposal considerations	<ul> <li>Do not allow to enter drains or watercourses.</li> <li>Dispose of according to all federal, state and local applicable regulations.</li> <li>If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.</li> <li>For further information, contact your local waste authority.</li> </ul>
Packaging	

# SECTION 13: Disposal considerations

•		
Methods of disposal	The generation of waste should be avoided or minimized wherever possible. Was packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.	te
Disposal considerations	: Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminate by the product in accordance with local or national legal provisions.	
European waste catalogue (EWC)	<ul> <li>packaging containing residues of or contaminated by hazardous substances 15 0 10*</li> </ul>	1
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.	

## **SECTION 14: Transport information**

	ADR/RID	IMDG	ΙΑΤΑ
14.1 UN number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport Hazard Class(es)/ Label(s)	-	-	-
14.4 Packing group	-	-	-
14.5 Environmental hazards	No.	No.	No.
Additional information	-	-	-

This mixture is not classified as dangerous according to international transport regulations (ADR/RID, IMDG, ICAO/IATA).

**14.6 Special precautions for user**: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk : Not applicable.according to IMO instruments

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

11/14

## **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>

#### Annex XIV - List of substances subject to authorization

#### Annex XIV

None of the components are listed.

Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

#### Other EU regulations

VOC content	(2010/75/EU)	:	0	w/w
			0	g/l

#### Seveso Directive

This product is not controlled under the Seveso Directive.

#### National regulations

MAL-code 93	:	00-4
Protection based on MAL	:	According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment:

**General:** Gloves must be worn for all work that may result in soiling. Apron/ coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In this case, other recommended use of eye protection is not required.

In all spraying operations in which there is return spray, the following must be worn: respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed.

#### MAL-code: 00-4

**Application:** When using scraper or knife, brush, roller etc. for pre- and posttreatments in a spray booth where the operator is outside the spray zone and when working in similar new\* facilities of the combined-cabin, spray-cabin and spraybooth type where the operator is working inside the spray zone. When spraying in new\* booths and cabins with non-atomizing guns. When spraying in existing\* spray booths, if the operator is outside the spray zone. During downtimes, cleaning and repair of closed facilities, spray booths or cabins, if there is a risk of contact with wet paint or organic solvents. During non-atomizing spraying in existing\* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone. When using scraper or knife, brush, roller, etc. for pre- and post-treatments in cabins or booths of the existing\* facility type, if the operator is inside the spray zone. When using scraper or knife, brush, roller, etc. for pre- and post-treatments outside a closed facility, spray booth or spray cabin.

- Protective clothing must be worn.

During all spraying where atomization occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cabin or booth.

021
(

# SECTION 15: Regulatory information

- Air-supplied full mask, protective clothing and hood must be worn.

Restrictions on use	Not to be used by professional users below 18 years of age. See the National Working Environment Authorities Executive Order regarding Young People At Work
	*See Regulations.
	<b>Caution</b> The regulations contain other stipulations in addition to the above.
	<b>Polishing:</b> When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always be worn.
	<b>Drying:</b> Items for drying/drying ovens that are temporarily placed on such things as rack trolleys, etc. must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.

#### SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	<ul> <li>ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number vPvB = Very Persistent and Very Bioaccumulative N/A = Not available</li> </ul>
Key literature references and sources for data	<ul> <li>Regulation (EC) No. 1272/2008 [CLP] ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2015/830 Directive 2012/18/EU, and relative amendments &amp; additions Directive 2008/98/EC, and relative amendments &amp; additions Directive 2009/161/EU, and relative amendments &amp; additions CEPE Guidelines</li> </ul>

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Irrit. 2, H315 Eye Irrit. 2, H319	Calculation method  Calculation method

#### **SECTION 16: Other information**

Full text of abbreviated H statements	<ul> <li>H301 Toxic if swallowed.</li> <li>H314 Causes severe skin burns and eye damage.</li> <li>H315 Causes skin irritation.</li> <li>H318 Causes serious eye damage.</li> <li>H319 Causes serious eye irritation.</li> </ul>
Full text of classifications [CLP/GHS]	: Acute Tox. 3ACUTE TOXICITY - Category 3Eye Dam. 1SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1Eye Irrit. 2SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2Skin Corr. 1ASKIN CORROSION/IRRITATION - Category 1ASkin Irrit. 2SKIN CORROSION/IRRITATION - Category 2
Date of printing	: 27, Sep, 2021.
Date of issue/ Date of revision	: 27, Sep, 2021
Date of previous issue	: 16, Apr, 2021
	<ul> <li>If there is no previous validation date please contact your supplier for more information.</li> </ul>
Version	: 3.03

#### Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.