

ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation
Dec 9, 2018

17 00 [3438]

PRODUCT NUMBER

P002

PRODUCT NAME

Vapor Barrier Interior Acrylic Primer/Finish

MANUFACTURER'S NAME

Conco Paints
101 Prospect Avenue N.W.
Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

Product Weight

10.31 lb/gal

Specific Gravity

1.24

FLASH POINT

N.A.

Hazard Category (for SARA 311.312)

| Acute | Chronic |

Volatile Ingredients

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Water 7732-18-5	N	N	N	N	58	72

Volatile Organic Compounds - U.S. EPA

A.	Coating Density	10.31 lb/gal	1235 g/l	
B.	Total Volatiles	59.7% by wt.	74.2% by vol.	
C.	Federally exempt solvents:			
	Water	58.1% by wt.	72.2% by vol.	
	2-Amino-2-Methyl-1-Propanol	0.2% by wt.	0.3% by vol.	
D.	Organic Volatiles	1.4% by wt.	1.7% by vol.	
E.	Percent Non-Volatile	40.3% by wt.	25.8% by vol.	
F.	VOC Content	0.14 lb/gal	16 g/l	total
		0.51 lb/gal	61 g/l	less exempt solvents
		0.54 lb/gal	65 g/l	of solids
		0.03 lb/lb	0.03 kg/kg	of solids
		0.0%		by wt LVP-VOC
	Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009)			
		0.02		

Volatile Organic Compounds - California

A.	Coating Density	10.31 lb/gal	1235 g/l	
B.	Total Volatiles	59.7% by wt.	74.2% by vol.	
C.	Exempt solvents:			
	Water	58.1% by wt.	72.2% by vol.	
D.	Organic Volatiles	1.6% by wt.	2.0% by vol.	
E.	Percent Non-Volatile	40.3% by wt.	25.8% by vol.	
F.	VOC Content	0.16 lb/gal	20 g/l	total
		0.60 lb/gal	71 g/l	less exempt solvents
		0.64 lb/gal	77 g/l	of solids
		0.04 lb/lb	0.04 kg/kg	of solids
		0.2%		by wt LVP-VOC
	Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010)			
		0.02		

Volatile Organic Compounds - South Coast Air Quality Management District, California, US

A. Coating Density	10.31 lb/gal	1235 g/l	
B. Total Volatiles	59.7% by wt.	74.2% by vol.	
C. Exempt solvents:			
Water	58.1% by wt.	72.2% by vol.	
D. Organic Volatiles	1.6% by wt.	2.0% by vol.	
E. Percent Non-Volatile	40.3% by wt.	25.8% by vol.	
F. VOC Content	0.16 lb/gal	20 g/l	total
	0.60 lb/gal	71 g/l	less exempt solvents
	0.64 lb/gal	77 g/l	of solids
	0.04 lb/lb	0.04 kg/kg	of solids
	0.2%		by wt LVP-VOC

Volatile Organic Compounds - EU Directive 2010/75/EU

Total Volatiles	59.1% by wt.	73.4% by vol.
VOC Content	0.10 lb/gal	12 g/l

Hazardous Air Pollutants (Clean Air Act, Section 112(b))

Volatile HAPS	0.00 lb/gal	0.000 kg/l
	0.00 lb/gal	0.000 kg/l of solids
	0.00 lb/lb	0.00 kg/kg of solids

Air Quality Data

Density of Organic Solvent Blend
8.24 lb/gal
Photochemically Reactive
No

Additional Regulatory Information

US EPA TSCA:
Not Applicable
Relevant identified uses of the substance or mixture and uses advised against:
Not Applicable

Waste Disposal

Waste from this product is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Addition of reducers or other additives to this product may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.