

# ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation  
Feb 19, 2024

29 00 [0344]

## PRODUCT NUMBER

5500(30)

## PRODUCT NAME

Elastomeric Stucco & Masonry Interior/Exterior Flat, Deep Base

## MANUFACTURER'S NAME

CONCO PAINTS

101 Prospect Avenue N.W.

Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

## Hazard Category (for SARA 311.312)

5500(30) = | Acute | Chronic |

## Product Weight

10.80 lb/gal

## Specific Gravity

1.30

## FLASH POINT

N.A.

## Volatile Ingredients

| Chemical / Compound                            | SARA 302 EHS | CERCLA | SARA 313 TC | HAPS 112 | % by Weight | % by Volume |
|------------------------------------------------|--------------|--------|-------------|----------|-------------|-------------|
| Trimethylpentanediol Isobutyrate<br>25265-77-4 | N            | N      | N           | N        | 2           | 2           |
| Water<br>7732-18-5                             | N            | N      | N           | N        | 40          | 53          |

## Regulated Compounds

|               | SARA 302 EHS | CERCLA | SARA 313 TC | HAPS 112 | % by Weight | % by Volume |
|---------------|--------------|--------|-------------|----------|-------------|-------------|
| Zinc (as Zn)  | N            | Y      | Y           | N        | 1           |             |
| Zinc Compound | N            | N      | Y           | N        | 1           |             |

**Volatile Organic Compounds - U.S. EPA / Canada**

|                           | 5500(30)   |            |
|---------------------------|------------|------------|
|                           | LB/Gal     | g/L        |
| Coating Density           | 10.80      | 1293       |
|                           | By wt      | By vol     |
| Total Volatiles           | 42.0%      | 55.9%      |
| Federally exempt solvents |            |            |
| Water                     | 40.1%      | 53.1%      |
| Non-Organic Volatiles     |            |            |
| Ammonium Hydroxide        | 0.2%       | 0.3%       |
| Organic Volatiles         | 1.8%       | 2.4%       |
| Percent Non-Volatile      | 58.0%      | 44.1%      |
| VOC Content               | LB/Gal     | g/L        |
| Total                     | 0.19       | 22         |
| Less exempt solvents      | 0.40       | 48         |
| Of solids                 | 0.43       | 51         |
| Of solids                 | 0.03 lb/lb | 0.03 kg/kg |
|                           | By wt      |            |
| By wt LVP-VOC             | 0.0%       |            |

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) **0.02**

**Volatile Organic Compounds - California**

|                       | 5500(30)   |            |
|-----------------------|------------|------------|
|                       | LB/Gal     | g/L        |
| Coating Density       | 10.80      | 1293       |
|                       | By wt      | By vol     |
| Total Volatiles       | 42.0%      | 55.9%      |
| Exempt solvents       |            |            |
| Water                 | 40.1%      | 53.1%      |
| Non-Organic Volatiles |            |            |
| Ammonium Hydroxide    | 0.2%       | 0.3%       |
| Organic Volatiles     | 1.8%       | 2.4%       |
| Percent Non-Volatile  | 58.0%      | 44.1%      |
| VOC Content           | LB/Gal     | g/L        |
| Total                 | 0.19       | 22         |
| Less exempt solvents  | 0.40       | 48         |
| Of solids             | 0.43       | 51         |
| Of solids             | 0.03 lb/lb | 0.03 kg/kg |
|                       | By wt      |            |
| By wt LVP-VOC         | 0.0%       |            |

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) **0.01**

**Volatile Organic Compounds - South Coast Air Quality Management District, California, US**

|                       | 5500(30)   |            |
|-----------------------|------------|------------|
|                       | LB/Gal     | g/L        |
| Coating Density       | 10.80      | 1293       |
|                       | By wt      | By vol     |
| Total Volatiles       | 42.0%      | 55.9%      |
| Exempt solvents       |            |            |
| Water                 | 40.1%      | 53.1%      |
| Non-Organic Volatiles |            |            |
| Ammonium Hydroxide    | 0.2%       | 0.3%       |
| Organic Volatiles     | 1.8%       | 2.4%       |
| Percent Non-Volatile  | 58.0%      | 44.1%      |
| VOC Content           | LB/Gal     | g/L        |
| Total                 | 0.19       | 22         |
| Less exempt solvents  | 0.40       | 48         |
| Of solids             | 0.43       | 51         |
| Of solids             | 0.03 lb/lb | 0.03 kg/kg |

**Volatile Organic Compounds - EU Directive 2004/42/EC**

|                 | 5500(30) |        |
|-----------------|----------|--------|
|                 | By wt    | By vol |
| Total Volatiles | 40.5%    | 53.8%  |
| VOC Content     | LB/Gal   | g/L    |
| Total           | 0.02     | 3      |

**Volatile Organic Compounds - EU Directive 2010/75/EU**

|                 | 5500(30) |        |
|-----------------|----------|--------|
|                 | By wt    | By vol |
| Total Volatiles | 40.5%    | 53.8%  |
| VOC Content     | LB/Gal   | g/L    |
| Total           | 0.02     | 3      |

**Volatile Organic Compounds - Mexico**

|                       | 5500(30)   |            |
|-----------------------|------------|------------|
|                       | LB/Gal     | g/L        |
| Coating Density       | 10.80      | 1293       |
|                       | By wt      | By vol     |
| Total Volatiles       | 42.0%      | 55.9%      |
| Exempt solvents       |            |            |
| Water                 | 40.1%      | 53.1%      |
| Non-Organic Volatiles |            |            |
| Ammonium Hydroxide    | 0.2%       | 0.3%       |
| Organic Volatiles     | 1.8%       | 2.4%       |
| Percent Non-Volatile  | 58.0%      | 44.1%      |
| VOC Content           | LB/Gal     | g/L        |
| Total                 | 0.19       | 22         |
| Less exempt solvents  | 0.40       | 48         |
| Of solids             | 0.43       | 51         |
| Of solids             | 0.03 lb/lb | 0.03 kg/kg |

**Hazardous Air Pollutants (Clean Air Act, Section 112(b))**

|               | 5500(30)   |            |
|---------------|------------|------------|
|               | LB/Gal     | kg/L       |
| Volatile HAPS | 0.00       | 0.000      |
| Of solids     | 0.00       | 0.000      |
| Of solids     | 0.00 lb/lb | 0.00 kg/kg |

**Air Quality Data****Density of Organic Solvent Blend**

7.68 lb/gal

**Photochemically Reactive**

No

**Waste Disposal**

Waste from this product is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Addition of reducers or other additives to this product may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.