

ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation
Sep 10, 2021

22 00 [2101]

PRODUCT NUMBER

5500(40)

PRODUCT NAME

Elastomeric Stucco & Masonry Interior/Exterior Flat, Accent Base

MANUFACTURER'S NAME

Conco Paints
101 Prospect Avenue N.W.
Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

Hazard Category (for SARA 311.312)

5500(40) = | Chronic |

Product Weight

10.85 lb/gal

Specific Gravity

1.31

FLASH POINT

N.A.

Volatile Ingredients

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Trimethylpentanediol Isobutyrate 25265-77-4	N	N	N	N	1	2
Water 7732-18-5	N	N	N	N	40	54

Volatile Organic Compounds - U.S. EPA / Canada

	5500(40)	
	LB/Gal	g/L
Coating Density	10.85	1300
	By wt	By vol
Total Volatiles	42.4%	56.5%
Federally exempt solvents		
Water	40.5%	53.8%
Non-Organic Volatiles		
Ammonium Hydroxide	0.2%	0.3%
Organic Volatiles	1.7%	2.3%
Percent Non-Volatile	57.6%	43.5%
VOC Content	LB/Gal	g/L
Total	0.18	22
Less exempt solvents	0.40	48
Of solids	0.43	51
Of solids	0.03 lb/lb	0.03 kg/kg
	By wt	
By wt LVP-VOC	0.0%	

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) **0.01**

Volatile Organic Compounds - California

	5500(40)	
	LB/Gal	g/L
Coating Density	10.85	1300
	By wt	By vol
Total Volatiles	42.4%	56.5%
Exempt solvents		
Water	40.5%	53.8%
Non-Organic Volatiles		
Ammonium Hydroxide	0.2%	0.3%
Organic Volatiles	1.7%	2.3%
Percent Non-Volatile	57.6%	43.5%
VOC Content	LB/Gal	g/L
Total	0.18	22
Less exempt solvents	0.40	48
Of solids	0.43	51
Of solids	0.03 lb/lb	0.03 kg/kg
	By wt	
By wt LVP-VOC	0.0%	

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) **0.01**

Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	5500(40)	
	LB/Gal	g/L
Coating Density	10.85	1300
	By wt	By vol
Total Volatiles	42.4%	56.5%
Exempt solvents		
Water	40.5%	53.8%
Non-Organic Volatiles		
Ammonium Hydroxide	0.2%	0.3%
Organic Volatiles	1.7%	2.3%
Percent Non-Volatile	57.6%	43.5%
VOC Content	LB/Gal	g/L
Total	0.18	22
Less exempt solvents	0.40	48
Of solids	0.43	51
Of solids	0.03 lb/lb	0.03 kg/kg

Volatile Organic Compounds - EU Directive 2004/42/EC

	5500(40)	
	By wt	By vol
Total Volatiles	40.9%	54.4%
VOC Content	LB/Gal	g/L
Total	0.02	3

Volatile Organic Compounds - EU Directive 2010/75/EU

	5500(40)	
	By wt	By vol
Total Volatiles	40.9%	54.4%
VOC Content	LB/Gal	g/L
Total	0.02	3

Volatile Organic Compounds - Mexico

	5500(40)	
	LB/Gal	g/L
Coating Density	10.85	1300
	By wt	By vol
Total Volatiles	42.4%	56.5%
Exempt solvents		
Water	40.5%	53.8%
Non-Organic Volatiles		
Ammonium Hydroxide	0.2%	0.3%
Organic Volatiles	1.7%	2.3%
Percent Non-Volatile	57.6%	43.5%
VOC Content	LB/Gal	g/L
Total	0.18	22
Less exempt solvents	0.40	48
Of solids	0.43	51
Of solids	0.03 lb/lb	0.03 kg/kg

Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	5500(40)	
	LB/Gal	kg/L
Volatile HAPS	0.00	0.000
Of solids	0.00	0.000
Of solids	0.00 lb/lb	0.00 kg/kg

Air Quality Data

Density of Organic Solvent Blend

7.71 lb/gal

Photochemically Reactive

No

Additional Regulatory Information

US EPA TSCA:

Not Applicable

Relevant identified uses of the substance or mixture and uses advised against:

Not Applicable

Waste Disposal

Waste from this product is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Addition of reducers or other additives to this product may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.