



SERIES 8950 Latex Flat Dry Fall

Conco® Latex Dry Fall is an industrial grade dry fall with high hiding and high reflectance properties. Conco® Latex Dry Fall, when applied to properly prepared steel, aluminum, and galvanized substrates, produces an intense white finish which increases the lighting efficiency in the area and promotes a safe working environment.

Recommended Uses

- Interior Ceilings, Walls and Structural Surfaces
- Mills, Manufacturing Facilities, Gymnasiums and other places requiring a high reflective finish
- Ferrous Metal Ceiling Decking
- Bar Joists
- Aluminum Ductwork
- Tilt-up Concrete Walls

Performance Benefits

- Resists Flash Rusting
- Offers an Intense White Finish to Properly Prepared Steel, Aluminum and Galvanized Substrates
- Increases Lighting Efficiency

Recommended Systems

Ferrous Metal

1 or 2 coats Conco® Latex Dry Fall

Ferrous Metal Or Aged Galvanizing (with rust stains present)

1 coat Conco® Acrylic Prime and Finish

1 or 2 coats Conco® Latex Dry Fall

Aluminum, Galvanizing, Tiltup Concrete Walls, Dry Wall

1 or 2 coats Conco® Latex Dry Fall

Technical Information

Finish:	Flat
Colors:	White & Black
Drying Time (@ 77°)	
To Touch:	30 Min
Tack Free:	45 Min
To Recoat:	1 Hr
Fall Dry (@ 77°):	8-10 Feet
Spread Rate:	135 - 225 Sq. Ft. /Gal (dependent upon surface texture and porosity)
Film Thickness:	7.0 – 11.0 mils wet 3.0 – 5.0 mils dry
Volume Solids:	42% ± 2%
Light Reflectance Value:	83% ± 2%
Vehicle Type:	Modified Acrylic
Flash Point:	155°F, PMCC
V.O.C. Level:	VOC: 84 g/l- .70 lb/gal as per 40 CFR 59.406
Reduction:	Not Recommended
Cleanup:	Soap and Water
Shelf Life:	36 Months
Size:	Available in Fives & 53-Gallon Drums

Warranty:

20 YEAR LIMITED WARRANTY: If this product, when applied according to label instructions, fails to perform to your complete satisfaction, upon presentation of proof of purchase to the store where the product was purchased we will, as your exclusive remedy, either replace an equivalent quantity of product free of charge or refund the purchase price. This warranty covers paint that is applied according to label instructions and excludes failure due to improper surface preparation, structural defects, or failure of the previous paint. This warranty does not include (1) labor or costs associated with labor for the application of any product and/or (2) any indirect, special, incidental or consequential damages with labor for the application of any product and/or (2) any indirect, special, incidental or consequential damages.

Surface Preparation

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

Preparation

Surface must be free of dirt, oil, moisture, grease, and other contaminants. Ferrous Metal should be cleaned according to SSPC SP-2 or SP-3. For optimum protection in corrosive environments, apply over a primer. Galvanizing should be cleaned according to SSPC SP-1 followed by SP-2 or SP-3. Chromate pretreatments must be removed by abrasive blasting. Do not use hydrocarbon solvents for cleaning.

Cleanup Information

Clean spills and spatters immediately with soap and warm water. Clean hands and tools immediately after use with soap and warm water. Follow manufacturer's safety recommendations when using mineral spirits.



CONCO PAINTS
Pro Technology... Engineered For The Job™

**SERIES
8950**

Latex Flat Dry Fall

Application

Not intended for immersion service. Do not apply when surface temperature is less than 5°F above the dew point. Do not apply to surface temperatures less than 50°F. Tinting of the product may affect the dry fall properties of the coating.

Spray – Airless

Pressure.....2000-3000 psi
Tip.....0.017"-0.019"
Filter.....60 Mesh

Do not thin.

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of Conco Paints. Information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Conco Paint retailer or sales representative to obtain the most recent Product Data Sheet.