







# Classic One® Int Latex Paint + Primer

DB452XX Series - Flat  
DB455XX Series - Eggshell  
DB456XX Series - Satin  
DB457XX Series - Semi-Gloss

## Product Data Sheet

<b>COVERAGE:</b>  400 sq. ft./gal (smooth) 125 - 300 sq. ft./gal (rough surface)	<b>DRY TIME (@77°F, 50% R.H.):</b>  Touch: 1 hour Recoat: 2-4 hours	<b>APPLICATION:</b>  Brush: nylon/polyester Roller: 1/4" - 1/2" synthetic nap Spray (Airless): 2000 PSI Tip .015"-.019"	<b>CLEAN UP:</b>  Warm, soapy water
---	--	---	---

<b>Features</b> <ul style="list-style-type: none"> <li>• Ultra-Durable 100% Acrylic Paint + Primer</li> <li>• Long-lasting, premium finish</li> <li>• Exceptional coverage and hide</li> <li>• Outstanding touch-up</li> <li>• Spatter-resistant formula</li> <li>• Easy, soap-and-water cleanup</li> <li>• Provides a mildew-resistant coating</li> <li>• GREENGUARD Gold Certified for low chemical emissions</li> <li>• Lifetime limited warranty</li> </ul>
---

<b>Where To Use</b> Properly prepared interior walls, trim and ceilings of previously painted or bare drywall, plaster, masonry, wood and primed metal.
--

<b>Recommended Systems</b> The Paint + Primer feature enables Classic One® coating to be applied directly to most previously painted or uncoated drywall, plaster, masonry and non-bleeding wood without the use of a separate primer. <p><b>Previously Painted Surfaces:</b></p> <ul style="list-style-type: none"> <li>• Use Classic One® Paint + Primer to spot prime bare areas, allow to dry, then paint entire surface.</li> <li>• 1-2 coats of Classic One® Paint + Primer</li> </ul> <p><b>Bare Surfaces: Drywall, Plaster, Masonry, Non-Ferrous Metal, and Wood:</b></p> <ul style="list-style-type: none"> <li>• 1-2 coats of Classic One® Paint + Primer</li> <li>• The first coat of Classic One® Paint + Primer serves as a priming coat and the second coat provides final appearance and performance.</li> </ul> <p><b>Severely Stained/Bleeding Surfaces:</b></p> <ul style="list-style-type: none"> <li>• Extreme household stains, watermarks, wood knots, bleeding woods such as cedar and redwood, or other surfaces where paint adhesion or stain suppression is a particular problem, use an appropriate primer.</li> <li>• 1-2 coats of Classic One® Paint + Primer</li> </ul>
--

<b>Technical Data</b>	
<b>Vehicle:</b>	Acrylic
<b>Finish:</b>	
Flat	0-6 units @ 85°
Eggshell	10-20 units @ 85°
Satin	22-32 units @ 85°
Semi-Gloss	30-40 units @ 60°
<b>Flash Point:</b>	N/A
<b>Weight Solids*:</b>	
Flat	53% ± 2%
Eggshell	54% ± 2%
Satin	49% ± 2%
Semi-Gloss	45% ± 2%
<b>Volume Solids*:</b>	
Flat	37% ± 2%
Eggshell	38% ± 2%
Satin	35% ± 2%
Semi-Gloss	34% ± 2%
<b>Weight per gallon*:</b>	
Flat	11.1 lbs/gal
Eggshell	11.2 lbs/gal
Satin	10.7 lbs/gal
Semi-Gloss	10.1 lb/gal
<b>VOC:</b>	<50 g/L as per 40 CFR 59.406
<b>Film Thickness:</b>	
Flat	@4 mils wet; 1.9 mils dry
Eggshell	@4 mils wet; 1.7 mils dry
Satin	@4 mils wet; 1.6 mils dry
Semi-Gloss	@4 mils wet; 1.4 mils dry
<b>Sizes:</b>	Gallon 5-Gallon (Ultra-White only)
*Product data calculated on Ultra White	

## Surface Prep

**WARNING!** Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (In US) or contact your local health authority.

Thoroughly clean the surface and allow to dry. Remove wallpaper and loose, peeling paint. Scrape and sand peeled or damaged paint. Sand glossy surfaces dull.

**Drywall:** Fill cracks and holes with patching paste and sand smooth.

**Plaster, Masonry, Block:** New surfaces must cure at least 30 days. Fill rough surfaces if desired.

**Wood:** Sand to a fresh surface. Patch imperfections with wood filler.

**Priming:** This paint can be used to prime patched areas, bare surfaces and lightly stained areas before applying the finish coat. For best results on heavily stained areas, use a coat of an appropriate stain-blocking primer. For drastic color changes or deep, vivid colors, prime with an appropriate tintable primer for optimal color accuracy and coverage.

### **Clean Mildew From the Surface:**

Mildew is a fungus that looks like dirt, but won't wash off. Mildew must be removed before painting or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub surface before painting with a commercial mildew remover or a solution of 1 part liquid chlorine bleach to 3 parts water. Rinse thoroughly. Avoid contact with skin and eyes. Protect skin and eyes by wearing rubber gloves and eye goggles when working with bleach solution.

## Application

- Apply product when surface, air and product temperatures are between 50-90°F
- Stir paint thoroughly. Inter-mix containers for uniformity.
- Thinning not required.
- Certain deep or bright colors may require an additional coat for complete hide. Surface conditions and application technique may impact coverage.

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of Dutch Boy Paints. Information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Dutch Boy Paint Retailer or sales representative to obtain the most recent Product Data Sheet.

## Clean Up/Disposal

- Clean up with warm, soapy water.
- Do not pour unused contents down the drain.
- Consult with local authorities for proper method of disposal and recycling.

## Maintenance

Wait at least 7 days before washing with a mild detergent and soft sponge.

## Cautions

Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**