

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II

DUPLI-COLOR® Premium Acrylic Enamel - Gloss Black

PAE100

# SAFETY DATA SHEET

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : DUPLI-COLOR® Premium Acrylic Enamel - Gloss Black

**Product code** : PAE100

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Material uses** : Paint or paint related material.

### 1.3 Details of the supplier of the safety data sheet

Mfg. in U.S.A and exported by:  
The Sherwin-Williams Company  
101 Prospect Avenue N.W.  
Cleveland, OH 44115

EU Only Representative: Valspar B.V.  
Zuiveringweg 89  
8243 PE Lelystad  
P.O. Box 2139  
The Netherlands  
Phone: +31 (0)320 29 22 00

**e-mail address of person responsible for this SDS** : sds@sherwin.com

### 1.4 Emergency telephone number

#### National advisory body/Poison Center

**Telephone number** : +431 406 43 43

#### Supplier

**Telephone number** : +1 703-741-5970

**Hours of operation** : Emergency contact available 24 hours a day

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Aerosol 1, H222, H229

Eye Irrit. 2, H319

STOT SE 3, H336

Asp. Tox. 1, H304

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

## SECTION 2: Hazards identification

**Hazard pictograms** :



**Signal word** :

Danger

**Hazard statements** :

Extremely flammable aerosol. Pressurized container: may burst if heated.  
May be fatal if swallowed and enters airways.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.  
Harmful to aquatic life with long lasting effects.

**Precautionary statements**

**Prevention** :

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Use only outdoors or in a well-ventilated area. Do not pierce or burn, even after use.

**Response** :

IF SWALLOWED: Immediately call a POISON CENTER or doctor.

**Storage** :

Not applicable.

**Disposal** :

Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Hazardous ingredients** :

Acetone  
Lt. Aliphatic Hydrocarbon Solvent

**Supplemental label elements** :

Contains 2-butanone oxime and maleic anhydride. May produce an allergic reaction.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** :

Not applicable.

**Special packaging requirements**

**Containers to be fitted with child-resistant fastenings** :

Not applicable.

**Tactile warning of danger** :

Yes, applicable.

### 2.3 Other hazards

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**Other hazards which do not result in classification** :

Risk of spontaneous combustion. Spraydust, cloth and other contaminated organic material should be wetted and placed in a sealed metal container. Store in a fire-proof place.

## SECTION 3: Composition/information on ingredients

**3.2 Mixture** :

| Product/ingredient name | Identifiers  | %         | Regulation (EC) No. 1272/2008 [CLP]                                   | Type    |
|-------------------------|--|-----------|---|---------|
| Acetone                 | REACH #:<br>01-2119471330-49<br>EC: 200-662-2<br>CAS: 67-64-1<br>Index: 606-001-00-8 | ≥10 - ≤25 | Flam. Liq. 2, H225<br>Eye Irrit. 2, H319<br>STOT SE 3, H336<br>EUH066 | [1] [2] |
| Propane                 | EC: 200-827-9<br>CAS: 74-98-6  | ≥10 - ≤25 | Flam. Gas 1A, H220<br>Press. Gas (Comp.), H280                        | [2]     |

**SECTION 3: Composition/information on ingredients**

|                                   |  |           |  |         |
|-----------------------------------|--|-----------|--|---------|
| n-Butyl Acetate                   | Index: 601-003-00-5<br>REACH #:<br>01-2119485493-29<br>EC: 204-658-1<br>CAS: 123-86-4  | ≥10 - ≤25 | Flam. Liq. 3, H226<br>STOT SE 3, H336<br>EUH066  | [1] [2] |
| Lt. Aliphatic Hydrocarbon Solvent | Index: 607-025-00-1<br>EC: 265-192-2<br>CAS: 64742-89-8                                | ≥10 - ≤25 | Flam. Liq. 2, H225<br>Asp. Tox. 1, H304  | [1]     |
| Butane                            | Index: 649-267-00-0<br>EC: 203-448-7<br>CAS: 106-97-8                                  | ≤10       | Flam. Gas 1A, H220<br>Press. Gas (Comp.), H280   | [2]     |
| Ethyl 3-Ethoxypropionate          | Index: 601-004-00-0<br>REACH #:<br>01-2119463267-34<br>EC: 212-112-9<br>CAS: 763-69-9  | ≤5        | Flam. Liq. 3, H226<br>EUH066   | [1] [2] |
| Xylene, mixed isomers             | REACH #:<br>01-2119488216-32<br>EC: 215-535-7<br>CAS: 1330-20-7<br>Index: 601-022-00-9 | ≤3        | Flam. Liq. 3, H226<br>Acute Tox. 4, H312<br>Acute Tox. 4, H332<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>STOT SE 3, H335<br>STOT RE 2, H373<br>Asp. Tox. 1, H304   | [1] [2] |
| Zinc Phosphate                    | EC: 231-944-3<br>CAS: 7779-90-0<br>Index: 030-011-00-6                                 | ≤2.2      | Aquatic Acute 1, H400 (M=1)<br>Aquatic Chronic 1, H410 (M=1)   | [1]     |
| Methyl Ethyl Ketoxime             | REACH #:<br>01-2119539477-28<br>EC: 202-496-6<br>CAS: 96-29-7<br>Index: 616-014-00-0   | ≤0.3      | Acute Tox. 4, H312<br>Eye Dam. 1, H318<br>Skin Sens. 1, H317<br>Carc. 2, H351  | [1] [2] |
| Zinc Hydroxide                    | EC: 243-814-3<br>CAS: 20427-58-1   | ≤0.3      | Aquatic Acute 1, H400 (M=1)<br>Aquatic Chronic 2, H411   | [1]     |
| Zinc Oxide                        | REACH #:<br>01-2119463881-32<br>EC: 215-222-5<br>CAS: 1314-13-2<br>Index: 030-013-00-7 | ≤0.25     | Aquatic Acute 1, H400 (M=1)<br>Aquatic Chronic 1, H410 (M=1)   | [1]     |
| Maleic Anhydride                  | REACH #:<br>01-2119472428-31<br>EC: 203-571-6<br>CAS: 108-31-6<br>Index: 607-096-00-9  | <0.001    | Acute Tox. 4, H302<br>Skin Corr. 1B, H314<br>Eye Dam. 1, H318<br>Resp. Sens. 1, H334<br>Skin Sens. 1A, H317<br>STOT RE 1, H372 (respiratory system)<br>(inhalation)<br>EUH071<br><br><b>See Section 16 for the full text of the H statements declared above.</b> | [1] [2] |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

[6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

## **SECTION 4: First aid measures**

### **4.1 Description of first aid measures**

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

### **4.2 Most important symptoms and effects, both acute and delayed**

There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 2-butanone oxime. May produce an allergic reaction.

### **4.3 Indication of any immediate medical attention and special treatment needed**

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

See toxicological information (Section 11)

## **SECTION 5: Firefighting measures**

### **5.1 Extinguishing media**

- Suitable extinguishing media** : Recommended: alcohol-resistant foam, carbon dioxide, powders.
- Unsuitable extinguishing media** : Do not use water jet.

### **5.2 Special hazards arising from the substance or mixture**

- Hazards from the substance or mixture** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

## SECTION 5: Firefighting measures

**Hazardous combustion products** : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

### 5.3 Advice for firefighters

**Special protective actions for fire-fighters** : Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.

**Special protective equipment for fire-fighters** : Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : Exclude sources of ignition and ventilate the area. Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8.

Keep unnecessary and unprotected personnel from entering.

**For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

: Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

### 6.3 Methods and materials for containment and cleaning up

: Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.

### 6.4 Reference to other sections

: See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

: Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.

Mixture may charge electrostatically: always use earthing leads when transferring from one container to another.

Operators should wear antistatic footwear and clothing and floors should be of the conducting type.

Keep away from heat, sparks and flame. No sparking tools should be used.

Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.

Put on appropriate personal protective equipment (see Section 8).

Never use pressure to empty. Container is not a pressure vessel.

Always keep in containers made from the same material as the original one.

Comply with the health and safety at work laws.

Do not allow to enter drains or watercourses.

#### **Information on fire and explosion protection**

Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air.

**SECTION 7: Handling and storage**

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapors in all cases. In such circumstances, they should wear a compressed-air-fed respirator during the spraying process and until the particulate and solvent vapor concentrations have fallen below the exposure limits.

**7.2 Conditions for safe storage, including any incompatibilities**

: Store in accordance with local regulations.

**Notes on joint storage**

Keep away from: oxidizing agents, strong alkalis, strong acids.

**Additional information on storage conditions**

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking. Prevent unauthorized access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Contaminated absorbent material may pose the same hazard as the spilled product.

**7.3 Specific end use(s)**

**Recommendations**

: Not available.

**Industrial sector specific solutions**

: Not available.

Good housekeeping standards, regular safe removal of waste materials and regular maintenance of spray booth filters will minimise the risks of spontaneous combustion and other fire hazards.

**Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations.**

**SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

**8.1 Control parameters**

**Occupational exposure limits**

| Product/ingredient name  | Exposure limit values   |
|--------------------------|---|
| Acetone                  | <p><b>Regulation on Limit Values - MAC (Austria, 9/2020).</b><br/>                     TWA: 500 ppm 8 hours.<br/>                     TWA: 1200 mg/m<sup>3</sup> 8 hours.<br/>                     PEAK: 2000 ppm, 4 times per shift, 15 minutes.<br/>                     PEAK: 4800 mg/m<sup>3</sup>, 4 times per shift, 15 minutes.</p>  |
| Propane                  | <p><b>Regulation on Limit Values - MAC (Austria, 9/2020).</b><br/>                     TWA: 1000 ppm 8 hours.<br/>                     TWA: 1800 mg/m<sup>3</sup> 8 hours.<br/>                     CEIL: 2000 ppm, 3 times per shift, 60 minutes.<br/>                     CEIL: 3600 mg/m<sup>3</sup>, 3 times per shift, 60 minutes.</p> |
| n-Butyl Acetate          | <p><b>Regulation on Limit Values - MAC (Austria, 9/2020).</b><br/>                     CEIL: 480 mg/m<sup>3</sup><br/>                     CEIL: 100 ppm<br/>                     TWA: 480 mg/m<sup>3</sup> 8 hours.<br/>                     TWA: 100 ppm 8 hours.</p>   |
| Butane                   | <p><b>Regulation on Limit Values - MAC (Austria, 9/2020).</b><br/>                     TWA: 800 ppm 8 hours.<br/>                     CEIL: 3800 mg/m<sup>3</sup>, 3 times per shift, 60 minutes.<br/>                     CEIL: 1600 ppm, 3 times per shift, 60 minutes.<br/>                     TWA: 1900 mg/m<sup>3</sup> 8 hours.</p>  |
| Ethyl 3-Ethoxypropionate | <p><b>Regulation on Limit Values - MAC (Austria, 9/2020). Absorbed</b></p>  |

**SECTION 8: Exposure controls/personal protection**

|                       |  |
|-----------------------|--|
| Xylene, mixed isomers | <p><b>through skin.</b><br/>                 CEIL: 610 mg/m<sup>3</sup> 15 minutes.<br/>                 CEIL: 100 ppm 15 minutes.<br/>                 TWA: 610 mg/m<sup>3</sup> 8 hours.<br/>                 TWA: 100 ppm 8 hours.</p> <p><b>Regulation on Limit Values - MAC (Austria, 9/2020).</b><br/>                 PEAK: 442 mg/m<sup>3</sup>, 4 times per shift, 15 minutes.<br/>                 TWA: 50 ppm 8 hours.<br/>                 PEAK: 100 ppm, 4 times per shift, 15 minutes.<br/>                 TWA: 221 mg/m<sup>3</sup> 8 hours.</p> |
| Methyl Ethyl Ketoxime | <p><b>Regulation on Limit Values - MAC (Austria, 9/2020). Skin sensitizer.</b></p>   |
| Maleic Anhydride      | <p><b>Regulation on Limit Values - MAC (Austria, 9/2020). Skin sensitizer. Inhalation sensitizer.</b><br/>                 TWA: 0.1 ppm 8 hours.<br/>                 TWA: 0.4 mg/m<sup>3</sup> 8 hours.<br/>                 CEIL: 0.2 ppm, 8 times per shift, 5 minutes.<br/>                 CEIL: 0.8 mg/m<sup>3</sup>, 8 times per shift, 5 minutes.</p>  |

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

**DNELs/DMELs**

| Product/ingredient name | Type | Exposure              | Value                   | Population                     | Effects  |
|-------------------------|------|-----------------------|-------------------------|--------------------------------|----------|
| Acetone                 | DNEL | Long term Dermal      | 186 mg/kg bw/day        | Workers                        | Systemic |
|                         | DNEL | Long term Inhalation  | 1210 mg/m <sup>3</sup>  | Workers                        | Systemic |
|                         | DNEL | Short term Inhalation | 2420 mg/m <sup>3</sup>  | Workers                        | Local    |
|                         | DNEL | Long term Dermal      | 62 mg/kg bw/day         | General population [Consumers] | Systemic |
|                         | DNEL | Long term Inhalation  | 200 mg/m <sup>3</sup>   | General population [Consumers] | Systemic |
|                         | DNEL | Long term Oral        | 62 mg/kg bw/day         | General population [Consumers] | Systemic |
| n-Butyl Acetate         | DNEL | Short term Inhalation | 960 mg/m <sup>3</sup>   | Workers                        | Systemic |
|                         | DNEL | Short term Inhalation | 960 mg/m <sup>3</sup>   | Workers                        | Local    |
|                         | DNEL | Long term Inhalation  | 480 mg/m <sup>3</sup>   | Workers                        | Systemic |
|                         | DNEL | Long term Inhalation  | 480 mg/m <sup>3</sup>   | Workers                        | Local    |
|                         | DNEL | Short term Inhalation | 859.7 mg/m <sup>3</sup> | General population [Consumers] | Systemic |

**SECTION 8: Exposure controls/personal protection**

|                       |      |                       |                          |  |          |
|-----------------------|------|-----------------------|--------------------------|--|----------|
| Xylene, mixed isomers | DNEL | Short term Inhalation | 859.7 mg/m <sup>3</sup>  | General population [Consumers]                 | Local    |
|                       | DNEL | Long term Inhalation  | 102.34 mg/m <sup>3</sup> | General population [Consumers]                 | Systemic |
|                       | DNEL | Long term Inhalation  | 102.34 mg/m <sup>3</sup> | General population [Consumers]                 | Local    |
|                       | DNEL | Long term Dermal      | 180 mg/kg bw/day         | Workers  | Systemic |
|                       | DNEL | Long term Dermal      | 108 mg/kg bw/day         | General population [Human via the environment] | Systemic |
|                       | DNEL | Long term Inhalation  | 77 mg/m <sup>3</sup>     | Workers  | Systemic |
|                       | DNEL | Short term Inhalation | 289 mg/m <sup>3</sup>    | Workers  | Systemic |
|                       | DNEL | Short term Inhalation | 289 mg/m <sup>3</sup>    | Workers  | Local    |
|                       | DNEL | Long term Inhalation  | 14.8 mg/m <sup>3</sup>   | General population [Human via the environment] | Systemic |
|                       | DNEL | Short term Inhalation | 174 mg/m <sup>3</sup>    | General population [Consumers]                 | Systemic |
| Zinc Oxide            | DNEL | Short term Inhalation | 174 mg/m <sup>3</sup>    | General population [Consumers]                 | Local    |
|                       | DNEL | Long term Dermal      | 83 mg/kg bw/day          | Workers  | Systemic |
|                       | DNEL | Long term Inhalation  | 5 mg/m <sup>3</sup>      | Workers  | Systemic |

**PNECs**

| Product/ingredient name | Compartment Detail     | Value        | Method Detail |
|-------------------------|------------------------|--------------|---------------|
| Acetone                 | Fresh water            | 10.6 mg/l    | -             |
|                         | Marine water           | 1.06 mg/l    | -             |
|                         | Sewage Treatment Plant | 100 mg/l     | -             |
|                         | Fresh water sediment   | 30.4 mg/kg   | -             |
|                         | Sediment               | 3.04 mg/kg   | -             |
|                         | Soil                   | 29.5 mg/kg   | -             |
| n-Butyl Acetate         | Fresh water            | 0.18 mg/l    | -             |
|                         | Marine water           | 0.018 mg/l   | -             |
|                         | Fresh water sediment   | 0.981 mg/kg  | -             |
|                         | Marine water sediment  | 0.0981 mg/kg | -             |
|                         | Soil                   | 0.0903 mg/kg | -             |
|                         | Sewage Treatment Plant | 35.6 mg/l    | -             |
| Xylene, mixed isomers   | Fresh water            | 0.327 mg/l   | -             |
|                         | Marine water           | 0.327 mg/l   | -             |
|                         | Fresh water sediment   | 12.46 mg/l   | -             |
|                         | Sewage Treatment Plant | 6.58 mg/l    | -             |
|                         | Soil                   | 2.31 mg/kg   | -             |
|                         | Marine water sediment  | 12.46 mg/l   | -             |

**8.2 Exposure controls**



## SECTION 8: Exposure controls/personal protection

- Appropriate engineering controls** : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn.
- : Users are advised to consider national Occupational Exposure Limits or other equivalent values.

### Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

- Eye/face protection** : Use safety eyewear designed to protect against splash of liquids.

### Skin protection

- Hand protection** : Wear suitable gloves tested to EN374.

### **Gloves**

- :  
There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.  
The breakthrough time must be greater than the end use time of the product.  
The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.  
Gloves should be replaced regularly and if there is any sign of damage to the glove material.  
Always ensure that gloves are free from defects and that they are stored and used correctly.  
The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.  
Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.  
The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

- Body protection** : Personnel should wear antistatic clothing made of natural fibers or of high-temperature-resistant synthetic fibers.
- : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

- Respiratory protection** : Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Recommended: A2P2 (EN14387). Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

- Environmental exposure controls** : Do not allow to enter drains or watercourses.

**Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.**

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

|   |   |
|---|---|
| <b>Physical state</b>                               | : Liquid.   |
| <b>Color</b>  | : Not available.  |
| <b>Odor</b>   | : Solvent.  |
| <b>Odor threshold</b>                               | : Not Available (Not Tested).   |
| <b>pH</b>   | : 7   |
| <b>Melting point/freezing point</b>                 | : Not relevant/applicable due to nature of the product.                           |
| <b>Initial boiling point and boiling range</b>      | : Not relevant/applicable due to nature of the product.                           |
| <b>Flash point</b>                                  | : Closed cup: -29°C [Pensky-Martens Closed Cup]                                   |
| <b>Evaporation rate</b>                             | : 5.6 (butyl acetate = 1)   |
| <b>Flammability (solid, gas)</b>                    | : Not relevant/applicable due to nature of the product.                           |
| <b>Upper/lower flammability or explosive limits</b> | : LEL: 0.9% (Lt. Aliphatic Hydrocarbon Solvent)<br>UEL: 12.8% (Acetone)           |
| <b>Vapor pressure</b>                               | : 101.3 kPa [at 20°C]   |
| <b>Vapor density</b>                                | : 1.55 [Air = 1]  |
| <b>Relative density</b>                             | : 0.73  |
| <b>Solubility(ies)</b>                              | : Not relevant/applicable due to nature of the product.                           |
| <b>Partition coefficient: n-octanol/water</b>       | : Not relevant/applicable due to nature of the product.                           |
| <b>Auto-ignition temperature</b>                    | : Not relevant/applicable due to nature of the product.                           |
| <b>Decomposition temperature</b>                    | : Not relevant/applicable due to nature of the product.                           |
| <b>Viscosity</b>                                    | : Kinematic (40°C): <0.205 cm <sup>2</sup> /s                                     |
| <b>Explosive properties</b>                         | : Under normal conditions of storage and use, hazardous reactions will not occur. |
| <b>Oxidizing properties</b>                         | : Under normal conditions of storage and use, hazardous reactions will not occur. |
| <b>Type of aerosol</b>                              | : Spray   |

## SECTION 10: Stability and reactivity

|  |  |
|--|--|
| <b>10.1 Reactivity</b>                         | : No specific test data related to reactivity available for this product or its ingredients.                                     |
| <b>10.2 Chemical stability</b>                 | : Stable under recommended storage and handling conditions (see Section 7).  |
| <b>10.3 Possibility of hazardous reactions</b> | : Under normal conditions of storage and use, hazardous reactions will not occur.  |
| <b>10.4 Conditions to avoid</b>                | : When exposed to high temperatures may produce hazardous decomposition products.  |
| <b>10.5 Incompatible materials</b>             | : Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids. |
| <b>10.6 Hazardous decomposition products</b>   | : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.        |

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

**SECTION 11: Toxicological information**

**11.1 Information on toxicological effects**

There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 2-butanone oxime. May produce an allergic reaction.

**Acute toxicity**

| Product/ingredient name    | Result               | Species | Dose         | Exposure |
|----------------------------|----------------------|---------|--------------|----------|
| Acetone<br>n-Butyl Acetate | LD50 Oral            | Rat     | 5800 mg/kg   | -        |
|                            | LD50 Dermal          | Rabbit  | >17600 mg/kg | -        |
|                            | LD50 Oral            | Rat     | 10768 mg/kg  | -        |
| Xylene, mixed isomers      | LC50 Inhalation Gas. | Rat     | 6700 ppm     | 4 hours  |
|                            | LD50 Oral            | Rat     | 4300 mg/kg   | -        |
| Methyl Ethyl Ketoxime      | LD50 Oral            | Rat     | 930 mg/kg    | -        |
|                            | LD50 Dermal          | Rabbit  | 2620 mg/kg   | -        |
| Maleic Anhydride           | LD50 Oral            | Rat     | 400 mg/kg    | -        |

**Acute toxicity estimates**

| Route              | ATE value      |
|--------------------|----------------|
| Dermal             | 74611.61 mg/kg |
| Inhalation (gases) | 454452.53 ppm  |

**Irritation/Corrosion**

| Product/ingredient name | Result                   | Species | Score | Exposure        | Observation |
|-------------------------|--------------------------|---------|-------|-----------------|-------------|
| Acetone                 | Eyes - Mild irritant     | Human   | -     | 186300 ppm      | -           |
|                         | Eyes - Mild irritant     | Rabbit  | -     | 10 uL           | -           |
|                         | Eyes - Moderate irritant | Rabbit  | -     | 24 hours 20 mg  | -           |
|                         | Eyes - Severe irritant   | Rabbit  | -     | 20 mg           | -           |
|                         | Skin - Mild irritant     | Rabbit  | -     | 24 hours 500 mg | -           |
| n-Butyl Acetate         | Skin - Mild irritant     | Rabbit  | -     | 395 mg          | -           |
|                         | Eyes - Moderate irritant | Rabbit  | -     | 100 mg          | -           |
|                         | Skin - Moderate irritant | Rabbit  | -     | 24 hours 500 mg | -           |
| Xylene, mixed isomers   | Eyes - Mild irritant     | Rabbit  | -     | 87 mg           | -           |
|                         | Eyes - Severe irritant   | Rabbit  | -     | 24 hours 5 mg   | -           |
|                         | Skin - Mild irritant     | Rat     | -     | 8 hours 60 uL   | -           |
|                         | Skin - Moderate irritant | Rabbit  | -     | 24 hours 500 mg | -           |
|                         | Skin - Moderate irritant | Rabbit  | -     | 100 %           | -           |
| Methyl Ethyl Ketoxime   | Eyes - Severe irritant   | Rabbit  | -     | 100 uL          | -           |
|                         | Eyes - Mild irritant     | Rabbit  | -     | 24 hours 500 mg | -           |
|                         | Skin - Mild irritant     | Rabbit  | -     | 24 hours 500 mg | -           |
| Maleic Anhydride        | Eyes - Severe irritant   | Rabbit  | -     | 1 %             | -           |

## SECTION 11: Toxicological information

**Conclusion/Summary** : Not available.

### Sensitization

No data available

**Conclusion/Summary** : Not available.

### Mutagenicity

No data available

### Carcinogenicity

No data available

### Reproductive toxicity

No data available

### Teratogenicity

No data available

### Specific target organ toxicity (single exposure)

| Product/ingredient name | Category   | Route of exposure | Target organs                |
|-------------------------|------------|-------------------|------------------------------|
| Acetone                 | Category 3 | -                 | Narcotic effects             |
| n-Butyl Acetate         | Category 3 | -                 | Narcotic effects             |
| Xylene, mixed isomers   | Category 3 | -                 | Respiratory tract irritation |

### Specific target organ toxicity (repeated exposure)

| Product/ingredient name | Category   | Route of exposure | Target organs      |
|-------------------------|------------|-------------------|--------------------|
| Xylene, mixed isomers   | Category 2 | -                 | -                  |
| Maleic Anhydride        | Category 1 | inhalation        | respiratory system |

### Aspiration hazard

| Product/ingredient name           | Result                         |
|-----------------------------------|--------------------------------|
| Lt. Aliphatic Hydrocarbon Solvent | ASPIRATION HAZARD - Category 1 |
| Xylene, mixed isomers             | ASPIRATION HAZARD - Category 1 |

**Other information** : Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

There are no data available on the mixture itself.

Do not allow to enter drains or watercourses.

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

| Product/ingredient name | Result                               | Species                                 | Exposure |
|-------------------------|--------------------------------------|---|----------|
| Acetone                 | Acute EC50 7200000 µg/l Fresh water  | Algae - Selenastrum sp.                 | 96 hours |
|                         | Acute LC50 4.42589 ml/L Marine water | Crustaceans - Acartia tonsa - Copepodid | 48 hours |
|                         | Acute LC50 7460000 µg/l Fresh water  | Daphnia - Daphnia cucullata             | 48 hours |
|                         | Acute LC50 5600 ppm Fresh water      | Fish - Poecilia reticulata              | 96 hours |
|                         | Chronic NOEC 4.95 mg/l Marine water  | Algae - Ulva pertusa                    | 96 hours |
|                         | Chronic NOEC 0.016 ml/L Fresh water  | Crustaceans - Daphniidae                | 21 days  |
|                         | Chronic NOEC 0.1 ml/L Fresh water    | Daphnia - Daphnia magna - Neonate       | 21 days  |
|                         | Chronic NOEC 5 µg/l Marine water     | Fish - Gasterosteus aculeatus -         | 42 days  |

**Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II**

DUPLI-COLOR® Premium Acrylic Enamel - Gloss Black

PAE100

**SECTION 12: Ecological information**

|  |  |  |  |
|--|--|--|--|
| n-Butyl Acetate  | Acute LC50 32 mg/l Marine water<br>Acute LC50 18000 µg/l Fresh water   | Larvae<br>Crustaceans - Artemia salina<br>Fish - Pimephales promelas<br>Fish - Oncorhynchus mykiss   | 48 hours<br>96 hours<br>96 hours                                     |
| Lt. Aliphatic Hydrocarbon Solvent<br>Xylene, mixed isomers | Acute LC50 >100000 ppm Fresh water<br>Acute LC50 8500 µg/l Marine water  |  |  |
| Zinc Phosphate<br>Methyl Ethyl Ketoxime<br>Zinc Oxide      | Acute LC50 13400 µg/l Fresh water<br>Acute LC50 90 µg/l Fresh water<br>Acute LC50 843000 µg/l Fresh water<br>Acute IC50 1.85 mg/l Marine water<br>Acute IC50 46 µg/l Fresh water | Crustaceans - Palaemonetes pugio<br>Fish - Pimephales promelas<br>Fish - Oncorhynchus mykiss<br>Fish - Pimephales promelas<br>Algae - Skeletonema costatum<br>Algae - Pseudokirchneriella subcapitata - Exponential growth phase | 48 hours<br>96 hours<br>96 hours<br>96 hours<br>96 hours<br>72 hours |
|  | Acute LC50 98 µg/l Fresh water   | Daphnia - Daphnia magna - Neonate  | 48 hours   |
| Maleic Anhydride   | Acute LC50 1.1 ppm Fresh water<br>Acute LC50 230 ppm Fresh water   | Fish - Oncorhynchus mykiss<br>Fish - Gambusia affinis - Adult  | 96 hours<br>96 hours   |

**12.2 Persistence and degradability**

| Product/ingredient name | Test | Result | Dose | Inoculum |
|-------------------------|------|--------|------|----------|
| No data available       |      |        |      |          |

**Conclusion/Summary** : Not available.

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|-------------------------|-------------------|------------|------------------|
| Acetone                 | -                 | -          | Readily          |
| n-Butyl Acetate         | -                 | -          | Readily          |
| Xylene, mixed isomers   | -                 | -          | Readily          |

**12.3 Bioaccumulative potential**

| Product/ingredient name           | LogP <sub>ow</sub> | BCF         | Potential |
|-----------------------------------|--------------------|-------------|-----------|
| Lt. Aliphatic Hydrocarbon Solvent | -                  | 10 to 2500  | high      |
| Xylene, mixed isomers             | -                  | 8.1 to 25.9 | low       |
| Zinc Phosphate                    | -                  | 60960       | high      |
| Methyl Ethyl Ketoxime             | -                  | 2.5 to 5.8  | low       |
| Zinc Hydroxide                    | -                  | 60960       | high      |
| Zinc Oxide                        | -                  | 28960       | high      |

**12.4 Mobility in soil****Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.**Mobility** : Not available.**12.5 Results of PBT and vPvB assessment**

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**12.6 Other adverse effects**

: No known significant effects or critical hazards.

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : Yes.

**European waste catalogue (EWC)** : waste paint and varnish containing organic solvents or other hazardous substances 08 01 11\*

**Disposal considerations** : Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

#### Packaging




**Methods of disposal** : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Disposal considerations** : Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.

**European waste catalogue (EWC)** : packaging containing residues of or contaminated by hazardous substances 15 01 10\*

**Special precautions** : This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

## SECTION 14: Transport information

|   | ADR/RID  | IMDG   | IATA   |
|---|--|--|--|
| 14.1 UN number                            | UN1950   | UN1950   | UN1950   |
| 14.2 UN proper shipping name              | AEROSOLS   | AEROSOLS   | AEROSOLS, flammable  |
| 14.3 Transport Hazard Class(es)/ Label(s) | 2<br> | 2.1<br> | 2.1<br> |
| 14.4 Packing group                        | -  | -  | -  |
| 14.5 Environmental hazards                | No.  | No.  | No.  |
| Additional information                    | <u>Tunnel code</u> D   | <u>Emergency schedules</u> F-D, S-U  | -  |

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II**

DUPLI-COLOR® Premium Acrylic Enamel - Gloss Black

PAE100

## SECTION 14: Transport information

**14.7 Transport in bulk according to IMO instruments** : Not applicable.

**Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.**

## SECTION 15: Regulatory information

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU Regulation (EC) No. 1907/2006 (REACH)**

**Annex XIV - List of substances subject to authorization**

**Annex XIV**

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

**Other EU regulations**

**VOC content (2010/75/EU)** : 82.7 w/w  
606 g/l

**Industrial emissions (integrated pollution prevention and control) - Air** : Listed

**Seveso Directive**

This product may add to the calculation for determining whether a site is within the scope of the Seveso Directive on major accident hazards.

**National regulations**

**15.2 Chemical Safety Assessment** : No Chemical Safety Assessment has been carried out.

## SECTION 16: Other information

🔍 Indicates information that has changed from previously issued version.

**Abbreviations and acronyms** : ATE = Acute Toxicity Estimate  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
EUH statement = CLP-specific Hazard statement  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number  
vPvB = Very Persistent and Very Bioaccumulative  
N/A = Not available

**SECTION 16: Other information**

**Key literature references and sources for data** : Regulation (EC) No. 1272/2008 [CLP]  
 ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road  
 IATA = International Air Transport Association  
 IMDG = International Maritime Dangerous Goods  
 Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2015/830  
 Directive 2012/18/EU, and relative amendments & additions  
 Directive 2008/98/EC, and relative amendments & additions  
 Directive 2009/161/EU, and relative amendments & additions  
 CEPE Guidelines

**Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]**

| Classification          | Justification         |
|-------------------------|-----------------------|
| Aerosol 1, H222, H229   | On basis of test data |
| Eye Irrit. 2, H319      | Calculation method    |
| STOT SE 3, H336         | Calculation method    |
| Asp. Tox. 1, H304       | Calculation method    |
| Aquatic Chronic 3, H412 | Calculation method    |

|  |                      |  |
|--|----------------------|--|
| <b>Full text of abbreviated H statements</b> | : H220<br>H222, H229 | Extremely flammable gas.<br>Extremely flammable aerosol. Pressurized container: may burst if heated. |
|  | H225                 | Highly flammable liquid and vapor.   |
|  | H226                 | Flammable liquid and vapor.  |
|  | H280                 | Contains gas under pressure; may explode if heated.  |
|  | H302                 | Harmful if swallowed.  |
|  | H304                 | May be fatal if swallowed and enters airways.  |
|  | H312                 | Harmful in contact with skin.  |
|  | H314                 | Causes severe skin burns and eye damage.   |
|  | H315                 | Causes skin irritation.  |
|  | H317                 | May cause an allergic skin reaction.   |
|  | H318                 | Causes serious eye damage.   |
|  | H319                 | Causes serious eye irritation.   |
|  | H332                 | Harmful if inhaled.  |
|  | H334                 | May cause allergy or asthma symptoms or breathing difficulties if inhaled.                           |
|  | H335                 | May cause respiratory irritation.  |
|  | H336                 | May cause drowsiness or dizziness.   |
|  | H351                 | Suspected of causing cancer.   |
|  | H372                 | Causes damage to organs through prolonged or repeated exposure.                                      |
|  | H373                 | May cause damage to organs through prolonged or repeated exposure.                                   |
|  | H400                 | Very toxic to aquatic life.  |
|  | H410                 | Very toxic to aquatic life with long lasting effects.  |
|  | H411                 | Toxic to aquatic life with long lasting effects.   |
|  | H412                 | Harmful to aquatic life with long lasting effects.   |
|  | EUH066               | Repeated exposure may cause skin dryness or cracking.  |
|  | EUH071               | Corrosive to the respiratory tract.  |

|   |   |  |
|---|---|--|
| <b>Full text of classifications [CLP/GHS]</b> | : Acute Tox. 4<br>Aerosol 1<br>Aquatic Acute 1<br>Aquatic Chronic 1<br>Aquatic Chronic 2<br>Aquatic Chronic 3<br>Asp. Tox. 1<br>Carc. 2<br>Eye Dam. 1<br>Eye Irrit. 2 | ACUTE TOXICITY - Category 4<br>AEROSOLS - Category 1<br>AQUATIC HAZARD (ACUTE) - Category 1<br>AQUATIC HAZARD (LONG-TERM) - Category 1<br>AQUATIC HAZARD (LONG-TERM) - Category 2<br>AQUATIC HAZARD (LONG-TERM) - Category 3<br>ASPIRATION HAZARD - Category 1<br>CARCINOGENICITY - Category 2<br>SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1<br>SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 |
|---|---|--|



**SECTION 16: Other information**

|                    |   |
|--------------------|---|
| Flam. Gas 1A       | FLAMMABLE GASES - Category 1A                                   |
| Flam. Liq. 2       | FLAMMABLE LIQUIDS - Category 2                                  |
| Flam. Liq. 3       | FLAMMABLE LIQUIDS - Category 3                                  |
| Press. Gas (Comp.) | GASES UNDER PRESSURE - Compressed gas                           |
| Resp. Sens. 1      | RESPIRATORY SENSITIZATION - Category 1                          |
| Skin Corr. 1B      | SKIN CORROSION/IRRITATION - Category 1B                         |
| Skin Irrit. 2      | SKIN CORROSION/IRRITATION - Category 2                          |
| Skin Sens. 1       | SKIN SENSITIZATION - Category 1                                 |
| Skin Sens. 1A      | SKIN SENSITIZATION - Category 1A                                |
| STOT RE 1          | SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1 |
| STOT RE 2          | SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 |
| STOT SE 3          | SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 3   |

**Date of printing** : 13, Apr, 2021.

**Date of issue/ Date of revision** : 13, Apr, 2021

**Date of previous issue** : 01, Apr, 2021

: If there is no previous validation date please contact your supplier for more information.

**Version** : 10.01

**Notice to reader**

*It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.*