



TECHNICAL BULLETIN

DURA SEAL® Dura Finish Liquid Floor Wax

PRODUCT DESCRIPTION:

DURA SEAL® Dura Finish Liquid Floor Wax is a rich, durable, liquid wax blend that adds a satin lustre to natural and previously sealed or stained wood floors. May be used as a finish coat or as a maintenance product to restore color and shine to worn wax finishes. Available in 210 Neutral and 223 Coffee Brown. May also be used on unglazed tile.

WARNING! Removal of old paint by sanding, scraping, or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

DIRECTIONS:

1. Apply a thin coat of **DURA SEAL® Dura Finish Liquid Floor Wax**, at a coverage rate of 2,000 square feet per gallon using a cloth, lambswool applicator or a fine steel wool pad.
2. Allow to dry and buff to a satin lustre using a cloth or a floor polishing machine. NOTE: Drying time may be affected by high humidity, low temperature or applying too heavily.

CAUTION: Do not varnish over **DURA SEAL® Dura Finish Liquid Floor Wax**. Do not thin or adulterate. Do not use over rubber or asphalt tile. Do not allow product to freeze.

DRYING TIME: Overnight drying is recommended before subjecting floor to traffic or replacing rugs and furniture

CLEAN UP: Clean equipment using paint thinner, turpentine or mineral spirits

MAINTENANCE: Regularly remove dust and dirt with a vacuum, dry cloth or dust mop. Periodic buffing will renew the lustre. Areas receiving exceptionally heavy wear may require an additional application of **DURA SEAL® Dura Finish Liquid Floor Wax**. When complete reconditioning is desired, clean surface using **DURA SEAL® Renovator Cleaner and Reconditioner**.

COVERAGE: 2,000 square feet per gallon.

SOLVENT: Non-photochemically reactive

CAUTION: CONTAINS ALIPHATIC HYDROCARBONS Contents are COMBUSTIBLE.
Keep away from heat and open flame. DO NOT TAKE INTERNALLY.

KEEP OUT OF REACH OF CHILDREN.

DANGER: HARMFUL OR FATAL IF SWALLOWED. COMBUSTIBLE. VAPOR HARMFUL. IRRITATES EYES, SKIN AND RESPIRATORY TRACT.

VAPOR HARMFUL. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area.

Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

FIRST AID: In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician. If swallowed, do NOT induce vomiting. Call Poison Control Center, hospital emergency room, or physician immediately. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.

Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

COLOR	SIZE	SKU #	CASE/PACK
210 NEUTRAL	Gal	81410	6
223 COFFEE BROWN	Gal	81423	6