



## TECHNICAL BULLETIN

### DURA SEAL Paste Wax

#### PRODUCT DESCRIPTION:

**DURA SEAL® Paste Wax** is a special blend of five waxes that gives hardwood floors the hand-rubbed lustre of fine furniture. This classic product protects and beautifies with minimal maintenance. Available in Neutral for light surfaces and Coffee Brown for dark surfaces.

**WARNING! Removal of old paint by sanding, scraping, or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.**

#### DIRECTIONS:

##### New Floor Preparation:

1. Prepare floor according to NOFMA or NWFA approved methods.
2. Stain and seal with **DURA SEAL® Penetrating Wood Finish, DURA SEAL®Fast Dry Wood Stain, or DURA SEAL® 500 Penetrating Fast Dry Sealer**, according to label directions.

##### Old Floor Preparation:

1. Clean flooring using **DURA SEAL® Renovator® Cleaner and Reconditioner**, according to label directions

##### Application:

1. Place a small amount of **DURA SEAL Paste Wax** in the center of a piece of cheese cloth. Fold the cloth so the Paste Wax will not come in direct contact with the floor.
2. Wipe floor with the cheese cloth in a circular motion applying light pressure to the cloth. This will force the **DURA SEAL Paste Wax** through the cloth onto the floor yielding a more even application. **NOTE:** Apply **DURA SEAL Paste Wax** in small enough areas so that the surface can be buffed before the wax has set and hardened, approximately five minutes.
3. After applying, buff each area to a soft sheen with a soft, dry cloth, weighted buffer or polisher.

**PRECAUTIONS:** Do not use on surfaces other than wood. Do not apply polyurethane over wax. Do not store in warm area.

**CLEAN UP:** Clean equipment using paint thinner, turpentine or mineral spirits

**COVERAGE:** 500 square feet per pound

**STORAGE:** Keep containers tightly closed. Isolate from heat, sparks or open flame,

**PHYSICAL PROPERTIES:**

SOLVENT: Mineral Spirits (NON-PHOTOCHEMICALLY REACTIVE)  
PRODUCT WEIGHT (LBS/GAL); 6.8 (Typical)  
% SOLIDS: 29.5 (Typical)  
VOC WGT %: 71.0  
VISCOSITY: Solid at room temperature  
FLASH POINT (SETA FLASH): 105°

**MAINTENANCE:** Periodically remove dust and grit by sweeping or vacuuming. Wipe up spills as soon as possible. Periodic buffing will renew lustre. Exceptionally worn areas will require an additional coat of DURA SEAL Paste Wax. When complete reconditioning is desired, clean surface using **DURA SEAL Renovator** Cleaner and Reconditioner.

SOLVENT: Non-photochemically reactive.

**CAUTION: COMBUSTIBLE MIXTURE DANGER!**

**KEEP OUT OF REACH OF CHILDREN.**

**DANGER:** Contains mineral spirits. Harmful or fatal if swallowed. Do not take internally. Skin irritant. Avoid contact with skin and eyes. Wear rubber gloves and safety glasses when handling. Avoid inhalation and use only with adequate ventilation. If adequate ventilation cannot be maintained, wear respiratory protection [NIOSH/MSHA TC23C or equivalent] or leave the area. Do not use or store near heat, sparks, flame or other sources of ignition. Close container after each use.

**SAFETY - HMIS RATING:**

Health	2
Flammability	2
Reactivity	0

**HEALTH:** Effects of overexposure: irritation of eyes, skin and respiratory system.

**FIRST AID:** If swallowed, do not induce vomiting. **CALL PHYSICIAN IMMEDIATELY.** For skin contact, wash thoroughly with soap and water. If irritation persists, get medical attention. In case of eye contact, immediately flush eyes thoroughly with water, then remove any contact lenses. Continue to flush eyes with water for at least 15 minutes. If irritation persists, **CONTACT A PHYSICIAN.** If affected by inhalation, remove to fresh air and **CALL PHYSICIAN.**

<b>COLOR</b>	<b>SIZE</b>	<b>SKU #</b>	<b>CASE/PACK</b>
NEUTRAL	1LB	81710	12
COFFEE BROWN	1 LB	81723	12
NEUTRAL	6 LB	86710	4
COFFEE BROWN	6 LB	86723	4