



Dutch Boy® Dimensions® Chalky Finish

Product Data Sheet

DBC100 Series – Chalky Finish

COVERAGE:  Up to 100 sq. ft./quart	DRY TIME (@77°F, 50% R.H.):  Touch: 30 minutes Recoat or distress: 1 hour	APPLICATION:  Brush: nylon/polyester	CLEAN UP:  Warm soapy water
-----------------------------------------------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------------------------------------	--------------------------------------------------------------------------------------------------------------------------

Features <ul style="list-style-type: none"> • Unique decorator interior finish allows you to create a distressed, velvety matte finish that transforms ordinary items into one-of-a-kind treasures • Palette features 42 designer colors • Instructions are easy to follow and are supported by online content • Use on properly prepared interior furniture and decorative accessories • Backed by a satisfaction guaranteed warranty

Technical Data	
Vehicle:	Vinyl Acrylic
Finish:	0-2 @85°
Flash Point:	N/A
Weight Solids*:	48 ± 2%
Volume Solids*:	29% ± 2%
Weight per gallon:	11.25 lbs/gal
VOC:	VOC <50 g/L as per 40 CFR 59.406
Film Thickness:	@ 4 mils wet; 1.16 mils dry
Sizes:	Quart
Product data calculated on White /Base A	

Where To Use
Use on properly prepared interior furniture and decorative accessories.

Surface Prep

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (In US) or contact your local health authority.

All surfaces should be sound, clean, dull and dry. Remove loose paint. Wash with a mild, non-abrasive, non-oily cleanser and water. Rinse completely, let dry. Patch cracks and holes and sand smooth. Sand glossy surfaces dull. Remove sanding dust with a damp cloth.

Application

- Apply when surface, air and product temperatures are above 50°F. Paint dries best between 65°F and 85°F.
- Stir paint thoroughly. Mix containers together when using more than one of the same product.
- Thinning not required.
- Apply Chalky Finish with brush.

Painting:

- Test paint on a small area. If paint beads up on the surface, sand the surface and test again.
- Coat surface using a nylon/polyester brush.
- Allow to dry at least 1 hour. Apply second coat if desired and allow to dry.

Distressing (optional):

- If a distressed look is desired, use medium grit sandpaper to distress areas of the surface that would be naturally worn over time such as edges, corners and legs.
- Remove all sanding dust with a tack cloth.

Finishing:

- Remove any sanding dust from the surface.
- Finish the surface by rubbing on Minwax® Paste Finishing Wax with a lint-free cloth.
- Allow Finishing Wax to cure 24 hours before using.

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of Dutch Boy Paints. Information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Dutch Boy Paint Retailer or sales representative to obtain the most recent Product Data Sheet.

Clean Up/Disposal

Clean up with warm, soapy water. Do not pour unused contents down the drain. Consult with local authorities for proper method of disposal and recycling.

Maintenance

Freshly painted surfaces may be washed after 30 days. Clean with mild, non-abrasive, non-oily cleanser and water. Do not place objects on painted surfaces until thoroughly dry

Cautions

CONTAINS CRYSTALLINE SILICA. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (**NIOSH** approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (**NIOSH** approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.** Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

16 (1/10)