



# Dutch Boy® Dimensions® Chalky Finish

DBC100 Series – Chalky Finish

## Product Data Sheet

Turn your next furniture find into a treasured favorite with the decorative paint finish that allows you to transform everyday furniture into new works of art. **Dutch Boy® Dimensions® Chalky Finish** offers rich, dimensional color with a matte finish — perfect for a distressed boho-chic look, or a polished, lustrous finish. For color inspiration and how-to advice, check out the Dutch Boy Faux Real brochure. Dimensions Chalky Finish is available in the easy-to-use Dutch Boy Twist & Pour® container.

## Features

- Unique decorator interior finish allows you to create a distressed, velvety matte finish that transforms ordinary items into one-of-a-kind treasures
- Palette features 42 designer colors
- Instructions are easy to follow and are supported by online content
- Use on properly prepared interior furniture and decorative accessories
- Backed by a satisfaction guaranteed warranty

## Where To Use

Use on properly prepared interior furniture and decorative accessories.

## Clean Up/Disposal

- Clean hands and tools with warm, soapy water.
- Promptly wipe up spills and spatters with a damp cloth.
- In event of a spill, absorb with inert material such as sand or kitty litter.
- Dispose of empty container or unused portion in accordance with local, state, and federal regulations.

## Surface Preparation

**WARNING!** Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (In US) or contact your local health authority.

All surfaces should be sound, clean, dull and dry. Remove loose paint. Wash with a mild, non-abrasive, non-oily cleanser and water. Rinse completely, let dry. Patch cracks and holes and sand smooth. Sand glossy surfaces dull. Remove sanding dust with a damp cloth.

## COVERAGE:



Up to 100 sq. ft./quart

## DRYING TIME (@77°F, 50% R.H.):



Touch: 30 minutes  
Recoat or distress: 1 hour

## APPLICATION:



Brush: nylon/polyester

## CLEAN UP:



Warm soapy water

## Application

- Apply when surface, air and product temperatures are above 50°F. Paint dries best between 65°F and 85°F.
- Stir paint thoroughly. Mix containers together when using more than one of the same product.
- Thinning not required.
- Apply Chalky Finish with brush.

### Painting:

- Test paint on a small area. If paint beads up on the surface, sand the surface and test again.
- Coat surface using a nylon/polyester brush.
- Allow to dry at least 1 hour. Apply second coat if desired and allow to dry.

### Distressing (optional):

- If a distressed look is desired, use medium grit sandpaper to distress areas of the surface that would be naturally worn over time such as edges, corners and legs.
- Remove all sanding dust with a tack cloth.

### Finishing:

- Remove any sanding dust from the surface.
- Finish the surface by rubbing on Minwax® Paste Finishing Wax with a lint-free cloth.
- Allow Finishing Wax to cure 24 hours before using.

Brush:

Nylon/Polyester

## Maintenance

Freshly painted surfaces may be washed after 30 days. Clean with mild, non-abrasive, non-oily cleanser and water. Do not place objects on painted surfaces till thoroughly dry.

## Cautions

- Protect from freezing
- For interior use only

## Technical Data

<b>Vehicle:</b>	Vinyl Acrylic
<b>Finish:</b>	
White/Base A	0-2 @85°
Accent/Base D	0-10 @85°
<b>Flash Point:</b>	N/A
<b>Weight Solids*:</b>	48 ± 2%
<b>Volume Solids*:</b>	29% ± 2%
<b>Dry Time(@77°F and 50% R.H):</b>	
To Touch:	30 minutes
To Recoat or Distress:	1 hour
<b>Weight per gallon:</b>	11.3 lb/gal
<b>VOC:</b>	VOC <50 g/L - 0.42lb/gal as per 40 CFR 59.406
<b>Spread Rate:</b>	
Smooth surface:	Up to 100 - sq. ft. per quart
<b>Film Thickness:</b>	@ 4 mils wet; 1.16 mils dry
<b>Sizes:</b>	Quart

Product data calculated on White /Base A

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of Dutch Boy Paints. Information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Dutch Boy Paint Retailer or sales representative to obtain the most recent Product Data Sheet.