




# Ceiling Solution® Interior Ceiling Latex Paint + Primer


DB15060 - Flat


## Product Data Sheet

**Dura Clean® Ceiling Solution® Interior Paint + Primer with Color-Changing Technology** ensures you never miss a spot by appearing pink when wet and drying white. This unique formula makes it easy to see your progress and make any necessary adjustments right away. What's more, it provides excellent hide and spatter resistance.

**COVERAGE:**  
 400 sq. ft./gal (smooth)  
 125 - 300 sq. ft./gal (rough surface)

**DRY TIME (@77°F, 50% R.H.):**  
 **Touch: 1 hour**  
**Recoat: 4 hours**

**APPLICATION:**  
 Brush: nylon/polyester  
 Roller: 3/8" - 1/2" synthetic nap  
 Spray (Airless): 2000 psi Tip .017" - .021"

**CLEAN UP:**  
 Warm soapy water

## Application

- Apply when surface, air and product temperatures are above 50°F. Paint dries best between 65°F and 85°F.
- Stir paint thoroughly. Mix gallons together when using more than one gallon of the same product.
- Brush a 3" border around all edges.
- Fill the roller completely. Apply paint in the form of an "N". Fill the center of the "N" with horizontal strokes from side to side.
- Lightly smooth out with vertical strokes. Repeat "N" pattern with a freshly loaded roller, continuing to work in 2' by 2' sections.
- Always roll from the dry, unpainted area into the wet edge.
- Other methods may require multiple coats for a professional-looking finish.

**Brush:** Nylon/Polyester  
**Roller:** Synthetic, 3/8" – 1/2" Nap  
**Sprayer – Airless:** 2000 psi, .017" – .021" Tip

## Clean Up/Disposal

- Clean hands and tools with warm, soapy water.
- Promptly wipe up spills and spatters with a damp cloth.
- In event of a spill, absorb with inert material such as sand or kitty litter.
- Dispose of empty container or unused portion in accordance with local, state, and federal regulations.
- After cleaning, flush spray equipment with mineral spirits to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using mineral spirits.

## Maintenance

Freshly painted surfaces may be washed after 30 days. Clean with mild, non-abrasive, non-oily cleanser and water. Do not place objects on painted surfaces until thoroughly dry. **Note: Some cleaning solutions may cause pink to reappear, color will return to white when dry.**

## Cautions

- Protect from freezing
- For interior use only

## Features

- Dura Clean® Ceiling Solution® Paint + Primer with Color-Changing Technology ensures you never miss a spot
- Paint + Primer feature enables Dura Clean® Ceiling Solution® coating to be applied directly to most previously painted or uncoated drywall and acoustical tile without the use of a separate primer
- Convenient color-changing technology makes it easy to see your progress and make any necessary adjustments right away
- Exceptional hide for smooth, even coverage
- Excellent spatter resistance to help protect floors and walls
- Award-winning Twist & Pour® container is easy to hold, easy to open, easy to pour and easy to store
- Backed by a lifetime warranty

## Where To Use

Use on properly prepared, previously painted or bare interior ceilings of textured or smooth drywall, plaster, masonry, wood and acoustical tile.

## Recommended Systems

The Paint + Primer feature enables Dura Clean® Ceiling Solution® coating to be applied directly to most previously painted or uncoated drywall and acoustical tile without the use of a separate primer.

### Previously Painted Surfaces:

- No primer necessary on previously painted surfaces or drywall.
- 1-2 coats Dura Clean® Ceiling Solution® Paint + Primer

### Bare Surfaces: Plaster, Masonry, and Wood:

- 1-2 coats Dura Clean® Ceiling Solution® Paint + Primer.
- Apply an appropriate primer over bare surfaces and stained areas, and allow to dry according to label instructions.

### Bare Surfaces: Drywall and Acoustical Tile:

- 1-2 coats Dura Clean® Ceiling Solution® Paint + Primer.
- Do not primer Acoustical Tile

### Severely Stained/Bleeding Surfaces:

- Extreme household stains, watermarks, wood knots, bleeding woods such as cedar and redwood, or other surfaces where paint adhesion or stain suppression is a particular problem, use an appropriate primer.
- 1-2 coats Dura Clean® Ceiling Solution® Paint + Primer

## Surface Prep

**WARNING!** Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (In US) or contact your local health authority.

All surfaces should be sound, clean, dull and dry. Remove loose paint. Wash with a mild, non-abrasive, non-oily cleanser and water. Rinse completely, let dry. Fill cracks and holes with patching/spackling paste and sand smooth. Sand glossy surfaces dull. Remove sanding dust with a damp cloth.

**Drywall:** Wipe with a damp cloth to remove dust. Allow to dry. Fill cracks & holes with spackling compound and sand smooth. Joint compound must be cured and sanded smooth. Remove all sanding dust.

**Plaster:** All new surfaces must be hard and cured according to the supplier's recommendations—usually at least 30 days. Treat textured, soft, porous, or powdery plaster with a solution of 1 pint household vinegar to 1 gallon of water. Repeat until the surface is hard, rinse with water and allow to dry.

**Wood:** Sand any exposed wood to a fresh smooth surface. Patch all holes and imperfections with a wood filler or putty and sand smooth. Remove all sanding dust.

**Acoustical Tile:** Remove dust from tiles with a vacuum or by dusting. In order to maintain the tile's acoustical properties, apply paint directly to the tiles; do not prime.

**Masonry:** Allow new masonry to cure at least 30 days. pH should be less than 9. Clean old masonry with a wire bristle brush to remove all loose concrete and efflorescence. Rinse thoroughly and allow to dry. Fill rough surfaces, if desired, with block filler.

**Caulking:** Fill gaps between walls, ceilings, crown moldings, and other trim with latex or siliconized latex caulk after priming the surface.

**Mildew:** Remove mildew before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the mildewed area for 10 minutes. Rinse thoroughly with water and allow surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. **DO NOT ADD DETERGENTS OR AMMONIA TO THE BLEACH/WATER SOLUTION.**

## Technical Data

<b>Vehicle:</b>	Vinyl Acrylic
<b>Finish:</b>	0-5 units @ 85°
<b>Flash Point:</b>	N/A
<b>Weight Solids:</b>	54% ± 2%
<b>Volume Solids:</b>	35% ± 2%
<b>Dry Time(@77°F and 50% R.H.):</b>	
To Touch:	1 hour
To Recoat:	4 hours
<b>Weight per gallon:</b>	11.73 lb/gal
<b>VOC:</b>	VOC <50 g/L - 0.42lb/gal as per 40 CFR 59.406
<b>Spread Rate:</b>	
Smooth surface:	400 sq. ft. per gal
Rough or textured surfaces:	125-300 sq. ft. per gal
<b>Film Thickness:</b>	@ 4 mils wet; 1.40 mils dry
<b>Sizes:</b>	Quart, Gallon

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of Dutch Boy Paints. Information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Dutch Boy Paint Retailer or sales representative to obtain the most recent Product Data Sheet.