52-010 Breeze Interior Flat Latex



INTENDED USES:

A quick drying flat finish suitable for interior use on drywall and other prepared surfaces. Suitable for painting bedrooms, living rooms and other low traffic areas. Has spatter free application properties.

PRODUCT DESCRIPTION

A high quality latex vehicle pigmented with inert pigments. Formulated to be low in VOC (less than 50 g/L)

TECHNICAL INFORMATION:

Finish:

Flat

Tint Range:

Full range of Millennium colours

Theoretical Coverage:

22-29 m²/3.7L (230-310 ft²/3.7L)

Typical Specific Gravity: 1.4

Application Thinner:

Not normally required. Up to 10% water if needed for spraying.

Standard Colours: White

Recommended # of coats: 1-2 at recommended coverage

Typical Volume Solids: 29%

Flash point: Not Applicable

Clean-up Thinner:

Water

SURFACE PREPARATION:

Surfaces must be clean, dry and free from dust, grease, mildew and wax. Remove any loose and peeling paint and repair with patching compound. Prime as required. Surface repairs should be spot primed. New Drywall: Seal with Latex Sealer.

New Wood: Prime with Alkyd Primer Sealer or Latex Wood Primer. Previously Painted Surfaces: Glossy surfaces should be sanded to a dull finish or primed with Latex Plastic Primer to provide good adhesion. Metal and Other Surfaces: Consult your GP Paint Pro.

APPLICATION:

Brush, Roller, Air Spray, Airless Spray.

Airless Tips: .013" - .017"

Dry times at 21°C / 70°F and 40%-60% R.H.:

| To Touch: | 15-60 minutes |
|--------------|---------------------------------------|
| To Handle: | 1-2 hours |
| To Overcoat: | 4 hours (takes 28 days to fully cure) |

PRODUCT HAZARDS AND SAFETY INFORMATION:

See Material Safety Data Sheet for complete Health and Safety information.

ADDITIONAL DATA:

For optimum adhesion and application performance, ensure that the temperature and relative humidity are between 15-25°C and 40-60% respectively, at the time of application and for four hours afterward.

Complies with the requirements of MPI #53.

Legal Details

The information contained herein is true and accurate to the best of our knowledge. However, no guarantee or warranty of any kind, express or implied, is given with respect to the accuracy or completeness of the said information and data or to the products described herein and we assume no risk or liability for the performance or coverage of or for injury resulting from the handling, use or application of the said information, data or products.