52-060

Ceiling Latex

INTENDED USES:

A very high opacity flat finish for use on new or previously painted ceilings. The product has virtually no low angle sheen and will not flash.

PRODUCT DESCRIPTION:

A very highly pigmented latex.

TECHNICAL INFORMATION: Finish:	
1 111311.	Standard Colours:
Flat	White
Tint Range:	Recommended # of coats:
Light colours	1-2 at recommended coverage
Theoretical Coverage:	Typical Volume Solids:
22-29 m ² /3.7L (240-320 ft ² /3.7L)	30%
Typical Specific Gravity:	Flash point:
1.4	Not Applicable
Application Thinner:	Clean-up Thinner:
Water, if required for spraying.	Water

SURFACE PREPARATION:

Surfaces must be clean, dry and free from dust, grease, mildew and wax. New Drywall: Seal with Latex Sealer Metal and Other Surfaces: Consult your GP Paint Pro.

APPLICATION:

Brush, Roller*, Air or Airless Spray *A split foam roller is most suitable for coarse textured ceilings.

Airless Tips: .015" - .021"

Dry times at 21°C / 70°F and 40%-60% R.H.:

To Touch:	15 to 30 minutes
To Handle:	2 hours
To Overcoat:	3 hours minimum

PRODUCT HAZARDS SAFETY INFORMATION:

See Material Safety Data Sheet for complete Health and Safety information.

ADDITIONAL DATA:

For optimum adhesion and application performance, ensure that the temperature and relative humidity are between 15-25°C and 40-60% respectively, at the time of application and for four hours afterward. Before painting a texture ceiling, test for water sensitivity. Many texture ceilings are water-soluble and require a coat of an alkyd paint to stabilize the substrate.

Legal Details

The information contained herein is true and accurate to the best of our knowledge. However, no guarantee or warranty of any kind, express or implied, is given with respect to the accuracy or completeness of the said information and data or to the products described herein and we assume no risk or liability for the performance or coverage of or for injury resulting from the handling, use or application of the said information, data or products.

