

# 56-030



Monocoat Interior / Exterior Eggshell Finish

## INTENDED USES:

A premium eggshell finish designed to be self-priming on most residential and light commercial applications. The 100% acrylic formula provides a hard, durable finish for both interior and exterior walls and trim, while eliminating the usual requirement of first priming the surface. Monocoat is a one-step solution without compromise on durability or weatherability.

## PRODUCT DESCRIPTION

A premium quality, self-priming coating formulated with 100% acrylics.

---

## TECHNICAL INFORMATION:

### Finish:

Eggshell

### Tint Range:

Full Range of Colours

### Theoretical Coverage:

27-36 m<sup>2</sup>/3.7L (290-390 ft<sup>2</sup>/3.7L)

### Typical Specific Gravity:

1.3

### Application Thinner:

Not required for brush or roller application.  
Use water if required for spraying

### Standard Colours:

White

### Recommended # of coats:

2 minimum at recommended coverage

### Typical Volume Solids:

37%

### Flash point:

Not Applicable

### Clean-up Thinner:

Water

---

## SURFACE PREPARATION:

Surfaces must be clean, dry and free from dust, grease, mildew and wax. Remove any loose and / or peeling paint and repair with patching compound. Glossy surfaces should be sanded to a matte finish to improve adhesion of the first coat. This self-priming finishing product has been designed to be used over many surfaces but in cases where stain migration / bleeding (tannin, ink, felt, pen) may occur, the following primers are recommended. In addition, coverage and application properties can also be enhanced by utilizing the following primer systems:

New Wood: Primer with Oil Wood Primer or Latex Wood Primer

New Drywall: Prime with Latex Sealer

Previously Painted Surfaces: Glossy surfaces should be sanded to a dull finish to provide good adhesion.

Concrete and Masonry: Allow to age 28 days. No primer required provided pH is below 9.

Latex Block Filler can be used to reduce texture on rough surfaces.

Metal and other surfaces: Consult your GP Paint Pro.

## APPLICATION:

Brush, Roller, Air Spray or Airless Spray

Airless Tips: .013" - .017"

Dry times at 21°C / 70°F and 40%-60% R.H.:

To Touch: 15 to 30 minutes

To Handle: 2 hours

To Overcoat: 4 hours minimum

## PRODUCT HAZARDS AND SAFETY INFORMATION:

See Material Safety Data Sheet for complete Health and Safety information.

## ADDITIONAL DATA:

### Legal Details

The information contained herein is true and accurate to the best of our knowledge. However, no guarantee or warranty of any kind, express or implied, is given with respect to the accuracy or completeness of the said information and data or to the products described herein and we assume no risk or liability for the performance or coverage of or for injury resulting from the handling, use or application of the said information, data or products.

56030

DATE OF ISSUE: Nov 2, 2016.

If mildew is present, the surface should be washed with a chlorine bleach solution (20% household bleach and 1% liquid detergent in warm water) and thoroughly rinsed prior to painting. For optimum adhesion and application performance, ensure that the temperature and relative humidity are between 15-25°C and 40-60% respectively, at the time of application and for four hours afterward.

#### **Legal Details**

The information contained herein is true and accurate to the best of our knowledge. However, no guarantee or warranty of any kind, express or implied, is given with respect to the accuracy or completeness of the said information and data or to the products described herein and we assume no risk or liability for the performance or coverage of or for injury resulting from the handling, use or application of the said information, data or products.

**56030**

**DATE OF ISSUE: Nov 2, 2016.**