

57-030



Kitchen & Bath Eggshell Finish

INTENDED USES:

A fast drying eggshell finish with excellent adhesion to new surfaces and to previously painted latex and alkyd finishes. Specially formulated for kitchens, laundry rooms and bathrooms where moisture and condensation occur. May also be used in other areas where a very durable eggshell finish is required.

PRODUCT DESCRIPTION

A suitably pigmented, high quality, 100% acrylic latex. Contains a fungicidal agent to inhibit mildew growth on the surface of the coating.

TECHNICAL INFORMATION:

Finish:

Eggshell

Tint Range:

Full range of colours

Theoretical Coverage:

31-41 m²/3.7L (330-440 ft²/3.7L)

Typical Specific Gravity:

1.4

Application Thinner:

Not required for brush or roller application.
Use water if required for spraying

Standard Colours:

White

Recommended # of coats:

1-2 at recommended coverage

Typical Volume Solids:

41%

Flash point:

Not Applicable

Clean-up Thinner:

Water

SURFACE PREPARATION:

Surfaces must be clean, dry and free from dust, grease, mildew and wax. Remove any loose and peeling paint and repair with patching compound. Prime as required below. Surface repairs should be spot primed.

New Drywall: Seal with Latex Primer Sealer.

New Wood: Prime with Alkyd Primer Sealer or Latex Wood Primer.

Previously Painted Surfaces: Can be applied directly onto most surfaces but if glossy surfaces are sanded to a dull finish or primed with Latex Plastic Primer the adhesion and application properties will be optimized.

Metal and Other Surfaces: Consult your GP Paint Pro.

APPLICATION:

Brush, Roller, Air Spray or Airless Spray

Airless Tips: .013" - .017"

Dry times at 21°C / 70°F and 40%-60% R.H.:

To Touch: 15 to 30 minutes

To Handle: 2 hours

To Overcoat: 4 hours minimum

PRODUCT HAZARDS AND SAFETY INFORMATION:

See Material Safety Data Sheet for complete Health and Safety information.

Legal Details

The information contained herein is true and accurate to the best of our knowledge. However, no guarantee or warranty of any kind, express or implied, is given with respect to the accuracy or completeness of the said information and data or to the products described herein and we assume no risk or liability for the performance or coverage of or for injury resulting from the handling, use or application of the said information, data or products.

57030

DATE OF ISSUE: Nov 2, 2016.

ADDITIONAL DATA:

For optimum adhesion and application performance, ensure that the temperature and relative humidity are between 15-25°C and 40-60% respectively, at the time of application and for four hours afterward. If mildew is present, the surface should be washed with a chlorine bleach solution (20% household bleach and 1% liquid detergent in warm water) and thoroughly rinsed prior to painting. The coating should be allowed to dry for a minimum of 48 hours before subjecting to condensation and cured for 30 days before washing. Consult your GP Paint Pro.

Legal Details

The information contained herein is true and accurate to the best of our knowledge. However, no guarantee or warranty of any kind, express or implied, is given with respect to the accuracy or completeness of the said information and data or to the products described herein and we assume no risk or liability for the performance or coverage of or for injury resulting from the handling, use or application of the said information, data or products.