

# 60-026

## Baseline Drywall Sealer



### INTENDED USES:

A interior undercoat for new drywall for use under a flat or low sheen eggshell finish.

### PRODUCT DESCRIPTION

A high opacity pigmented latex undercoat designed for professional painters.

---

### TECHNICAL INFORMATION:

#### Finish:

Flat

#### Tint Range:

Light Colours

#### Theoretical Coverage:

23-32 m<sup>2</sup>/3.7L (250-340 ft<sup>2</sup>/3.7L)

#### Typical Specific Gravity:

1.5

#### Application Thinner:

Not normally required. Up to 10% water may be used, if required, for spraying.

#### Standard Colours:

White

#### Recommended # of coats:

1-2 at recommended coverage

#### Typical Volume Solids:

32%

#### Flash point:

Not Applicable

#### Clean-up Thinner:

Water

---

### SURFACE PREPARATION:

Surfaces must be clean, dry and free from loose material. Drywall joints and patched areas must be dry and free from sanding dust.

### APPLICATION:

Brush, Roller, Air Spray or Airless Spray

Airless Tips: .013" - .019"

Dry times at 21°C / 70°F and 40%-60% R.H.:

To Touch: 60 minutes

To Handle: 1 to 2 hours

To Overcoat: 2 to 4 hours

### PRODUCT HAZARDS AND SAFETY INFORMATION:

See Material Safety Data Sheet for complete Health and Safety information.

### ADDITIONAL DATA:

Designed for use on new drywall and under flat or low sheen latex topcoats only. Not recommended on previously painted surfaces, or for use under an alkyd or a pearl, semi-gloss or gloss latex topcoat.

### Legal Details

The information contained herein is true and accurate to the best of our knowledge. However, no guarantee or warranty of any kind, express or implied, is given with respect to the accuracy or completeness of the said information and data or to the products described herein and we assume no risk or liability for the performance or coverage of or for injury resulting from the handling, use or application of the said information, data or products.