

## X-TERMINATOR2

## **INTENDED USES:**

Quick drying interior/exterior primer with exceptional sealing, adhesion and stain killing/blocking properties. Recommended for use on drywall, plaster, hardboard, masonry, wood and previously painted interior walls, ceilings and trim. Will block stains, seal surfaces and provide excellent adhesion on most substrates.

## **PRODUCT DESCRIPTION:**

A fast drying waterborne acrylic resin pigmented with inert pigments.

TECHNICAL INFORMATION:	
Finish:	Standard Colours:
Flat	Off-White
Tint Range:	Recommended # of coats:
Light colours	1-2 at recommended coverage
Theoretical Coverage:	Typical Volume Solids:
28-38 m <sup>2</sup> /3.7L (300-410 ft <sup>2</sup> /3.7L)	38%
Typical Specific Gravity:	Flash point:
1.3	Not Applicable
Application Thinner:	Clean-up Thinner:
Not required	Water

#### SURFACE PREPARATION:

Surface must be clean, dry free from dust, dirt, chalk, grease, oil, wax, mildew, loose paint or other contaminants.

#### **APPLICATION:**

Brush, Roller, or Airless Spray Airless Tips: .013" - .017"

Dry times at 21°C / 70°F and 40%-60% R.H.:

To Touch:	40 Minutes
To Handle:	1 Hour
To Overcoat:	2 Hours

#### **PRODUCT HAZARDS SAFETY INFORMATION:**

See Material Safety Data Sheet for complete Health and Safety information.

## ADDITIONAL DATA:

Apply coating evenly while maintaining a "wet edge" to prevent lapping. When thoroughly dry X-Terminator2 may be sanded lightly with 180 or 220 grit sanding paper to achieve the most appropriate finish on smooth surfaces. Some stains may require two coats to cover.

Due to the exceptional adhesion level of this product it is suitable for use on many substrates that are typically considered difficult to paint like melamine, tile, galvanized metal and aged alkyd, however a test patch is recommended to ensure that the adhesion is adequate.

Complies with the requirements of MPI #17, 39, 134 and #137.

60 200 DATE OF ISSUE: Nov 2, 2016.



# Legal Details

The information contained herein is true and accurate to the best of our knowledge. However, no guarantee or warranty of any kind, express or implied, is given with respect to the accuracy or completeness of the said information and data or to the products described herein and we assume no risk or liability for the performance or coverage of or for injury resulting from the handling, use or application of the said information, data or products.