

71-LINE



Siding Re-Nu

INTENDED USES:

A quick drying, extremely weather-resistant finish for repainting weathered vertical siding. May be applied over aged alkyd, latex stain or paint.

PRODUCT DESCRIPTION:

A high quality, 100% acrylic latex pigmented to give a semi-gloss finish.

TECHNICAL INFORMATION:

Finish:

Semi-Gloss

Tint Range:

Light and Medium colours

Theoretical Coverage:

25-33 m²/3.7L (270-350 ft²/3.7L)

Typical Specific Gravity:

1.2

Application Thinner:

Not normally required. Up to 10% water if needed for spraying.

Standard Colours:

White

Recommended # of coats:

1-2 at recommended coverage

Typical Volume Solids:

33%

Flash point:

Not Applicable

Clean-up Thinner:

Water

SURFACE PREPARATION:

Siding must be clean, dry and free from dust, grease, mildew and wax. If the siding is not weathered the siding should be abraded to reduce the sheen.

APPLICATION:

Brush, Roller, Air Spray or Airless Spray.

Airless Tips: .015" - .021"

Dry times at 21°C / 70°F and 40%-60% R.H.:

To Touch:	15-60 minutes
To Handle:	1-2 hours
To Overcoat:	4 hours (takes 28 days to fully cure)

PRODUCT HAZARDS SAFETY INFORMATION:

See Material Safety Data Sheet for complete Health and Safety information.

ADDITIONAL DATA:

For optimum adhesion and application performance, ensure that the temperature and relative humidity are between 15-25°C and 40-60% respectively, at the time of application and for four hours afterward. If mildew is present, the surface should be washed with a chlorine bleach solution (20% household bleach and 1% liquid detergent in warm water) and thoroughly rinsed prior to painting.

NOTE: Darker colours on vinyl siding could potentially lead to warpage if in direct sunlight.

Legal Details

The information contained herein is true and accurate to the best of our knowledge. However, no guarantee or warranty of any kind, express or implied, is given with respect to the accuracy or completeness of the said information and data or to the products described herein and we assume no risk or liability for the performance or coverage of or for injury resulting from the handling, use or application of the said information, data or products.