# **SAFETY DATA SHEET**

### GC43511

# Section 1. Identification

Product name	: Geocel® 4350 Metal Roof Sealant Saddle Tan
Product code	: GC43511
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses of t	the substance or mixture and uses advised against
Paint or paint related material.	
Manufacturer	: Geocel Products Group A Business Unit of the Sherwin-Williams Company 101 W. Prospect Avenue Cleveland, Ohio 44115
National contact	: Sherwin-Williams Canada Inc. 180 Brunel Road Mississauga, Ontario L4Z 1T5 Canada
Emergency telephone number of the company Product Information Telephone Number	<ul> <li>US / Canada: (800) 424-9300 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year</li> <li>US / Canada: (800) 348-7615 Mexico: Not Available</li> </ul>
Transportation Emergency Telephone Number	: US / Canada: (800) 424-9300 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year

### Section 2. Hazards identification

Classification of the	: SKIN CORROSION/IRRITATION - Category 2
substance or mixture	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A
	SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 1A
	TOXIC TO REPRODUCTION - Category 1B SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract
	irritation) - Category 3

**GHS label elements** 

**Hazard pictograms** 



Signal word	: Danger
Hazard statements	: Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause respiratory irritation. May cause cancer. May damage fertility or the unborn child.

Date of issue/Date	of revision	: 4/25/2025	Date of previous issue	: 1/9/2025	Version : 14	1/15
GC43511	Geocel® 4350 Metal Ro Saddle Tan	oof Sealant			SHW-85-NA-GHS-CA	

# Section 2. Hazards identification

Precautionary statements	
General	: Keep out of reach of children. If medical advice is needed, have product container or label at hand.
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing, eye protection, face protection, or hearing protection. Use only outdoors or in a well-ventilated area. Avoid breathing vapor. Wash thoroughly after handling.
Response	: IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
Storage	: Store locked up. Store in a well-ventilated place. Keep container tightly closed.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. Adequate ventilation required when sanding or abrading the dried film. If Adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Abrading or sanding of the dry film may release Crystalline Silica which has been shown to cause lung damage and cancer under long term exposure.
	Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
Hazards not otherwise classified	: None known.

# Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of	: Not available.
identification	

### **CAS number/other identifiers**

Ingredient name	% by weight	Identifiers
Calcium Carbonate	57.83	1317-65-3
Aminoethylaminopropyltrimethoxysilane	0.78	1760-24-3
Dibutylbis(pentadionate)tin	0.41	22673-19-4
Crystalline Silica, respirable powder	0.15	14808-60-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

# Section 4. First aid measures

Description of necessary f	irst aid measures
Eye contact	<ul> <li>Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.</li> </ul>
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Most important symptoms/effects, acute and delayed

Potential acute health effects	
Eye contact :	Causes serious eye irritation.
Inhalation :	May cause respiratory irritation.
Skin contact :	Causes skin irritation. May cause an allergic skin reaction.
Ingestion :	No known significant effects or critical hazards.
Over-exposure signs/symptom	<u>15</u>
Eye contact :	Adverse symptoms may include the following: pain or irritation watering redness
Inhalation :	Adverse symptoms may include the following: respiratory tract irritation coughing reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact :	Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion :	Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations

Date of issue/Date	of revision	: 4/25/2025	Date of previous issue	: 1/9/2025	Version	:14	3/15
GC43511	Geocel® 4350 Metal Ro Saddle Tan	oof Sealant			SHW-85-	NA-GHS-CA	

### Section 4. First aid measures

Indication of immediate med	dical attention and special treatment needed, if necessary
Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

### Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Date of issue/Date	of revision	: 4/25/2025	Date of previous issue	: 1/9/2025	Version : 14	4/15
GC43511	Geocel® 4350 Metal Roof Sealant Saddle Tan				SHW-85-NA-GHS-CA	

### Section 6. Accidental release measures

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

# Section 7. Handling and storage

#### Precautions for safe handling

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### Section 8. Exposure controls/personal protection

#### **Control parameters**

Occupational exposure limits (OSHA United States)

Ingredient	name	CAS #	Exposure limits
Calcium Ca	arbonate	1317-65-3	NIOSH REL (United States, 10/2020) [calcium carbonate] TWA 10 hours: 10 mg/m <sup>3</sup> . Form: Total. TWA 10 hours: 5 mg/m <sup>3</sup> . Form: Respirable fraction. OSHA PEL (United States, 5/2018) TWA 8 hours: 15 mg/m <sup>3</sup> . Form: Total dust. TWA 8 hours: 5 mg/m <sup>3</sup> . Form: Respirable fraction.
-	laminopropyltrimethoxysilane pentadionate)tin	1760-24-3 22673-19-4	None. ACGIH TLV (United States, 1/2024) [Tin, organic compounds] A4. Absorbed through skin. TWA 8 hours: 0.1 mg/m <sup>3</sup> (as Sn). STEL 15 minutes: 0.2 mg/m <sup>3</sup> (as Sn). NIOSH REL (United States, 10/2020) [tin organic compounds] Absorbed through skin.
ate of issue/D	ate of revision : 4/25/2025	Date of previous issue	: 1/9/2025 Version : 14 5/15
GC43511 Geocel® 4350 Metal Roof Sealant Saddle Tan			SHW-85-NA-GHS-CA

# Section 8. Exposure controls/personal protection

		TWA 10 hours: 0.1 mg/m <sup>3</sup> (as Sn). OSHA PEL (United States, 5/2018) [Tin, organic compounds] TWA 8 hours: 0.1 mg/m <sup>3</sup> (as Sn).
Crystalline Silica, respirable powder	14808-60-7	ACGIH TLV (United States, 1/2024) [Silica, crystalline] A2. TWA 8 hours: 0.025 mg/m <sup>3</sup> . Form: Respirable fraction. NIOSH REL (United States, 10/2020) [SILICA, CRYSTALLINE] NIA. TWA 10 hours: 0.05 mg/m <sup>3</sup> . Form: respirable dust. OSHA PEL (United States, 5/2018) [Silica, crystalline] TWA 8 hours: 50 $\mu$ g/m <sup>3</sup> . Form: Respirable dust. OSHA PEL Z3 (United States, 6/2016) TWA 8 hours: 250 / (%SiO <sub>2</sub> +5) mppcf. Form: Respirable. TWA 8 hours: 10 / (%SiO <sub>2</sub> +2) mg/m <sup>3</sup> . Form: Respirable.

### **Occupational exposure limits (Canada)**

ngredient name	CAS #	Exposure limits
Dibutylbis(pentadionate)tin	22673-19-4	<ul> <li>CA Saskatchewan Provincial (Canada, 4/2021) [Tin organic compounds]</li> <li>Absorbed through skin.</li> <li>STEL 15 minutes: 0.2 mg/m<sup>3</sup> (measured as Sn).</li> <li>TWA 8 hours: 0.1 mg/m<sup>3</sup> (measured as Sn).</li> <li>CA British Columbia Provincial (Canada, 4/2024) [tin - organic compounds]</li> <li>Absorbed through skin.</li> <li>TWA 8 hours: 0.1 mg/m<sup>3</sup> (as Sn).</li> <li>STEL 15 minutes: 0.2 mg/m<sup>3</sup> (as Sn).</li> <li>STEL 15 minutes: 0.2 mg/m<sup>3</sup> (as Sn).</li> <li>CA Ontario Provincial (Canada, 6/2019)</li> <li>[Tin (Organic compounds)] Absorbed through skin.</li> <li>TWA 8 hours: 0.1 mg/m<sup>3</sup> (as Sn).</li> <li>CA Alberta Provincial (Canada, 3/2023)</li> <li>[Tin Organic compounds] Absorbed through skin.</li> <li>OEL 15 minutes: 0.2 mg/m<sup>3</sup> (as Sn).</li> <li>OEL 15 minutes: 0.1 mg/m<sup>3</sup> (as Sn).</li> </ul>
Quartz	14808-60-7	<ul> <li>CA Saskatchewan Provincial (Canada, 4/2021)</li> <li>TWA 8 hours: 0.05 mg/m<sup>3</sup>. Form: respirable fraction.</li> <li>CA British Columbia Provincial (Canada, 4/2024) [silica, crystalline - alpha quartz and cristobalite] Carc 2A, Carc 1.</li> <li>TWA 8 hours: 0.025 mg/m<sup>3</sup>. Form: Respirable.</li> <li>CA Ontario Provincial (Canada, 6/2019)</li> </ul>
te of issue/Date of revision : 4/25/2025 43511 Geocel® 4350 Metal Roof Sealant	Date of previous issue	: 1/9/2025 Version : 14 6 SHW-85-NA-GHS-CA

### Section 8. Exposure controls/personal protection

	[Silica, Crystalline (Quartz/Tripoli)] TWA 8 hours: 0.1 mg/m <sup>3</sup> . Form: Respirable particulate matter CA Quebec Provincial (Canada, 2/2024) [Silica Crystalline -Quartz] C2. TWAEV 8 hours: 0.1 mg/m <sup>3</sup> . Form: respirable aerosol fraction. CA Alberta Provincial (Canada, 3/2023) A2. OEL 8 hours: 0.025 mg/m <sup>3</sup> . Form: Respirable particulate.
--	--

#### **Occupational exposure limits (Mexico)**

Ingredient name	CAS #	Exposure limits
Dibutylbis(pentadionate)tin	22673-19-4	NOM-010-STPS-2014 (Mexico, 4/2016) [Estaño, compuestos orgánicos] A4. Absorbed through skin. TWA 8 hours: 0.1 mg/m <sup>3</sup> (as Sn). STEL 15 minutes: 0.2 mg/m <sup>3</sup> (as Sn).

#### **Biological exposure indices (United States)**

No exposure indices known.

#### **Biological exposure indices (Canada)**

No exposure indices known.

#### **Biological exposure indices (Mexico)**

No exposure indices known.

Appropriate engineering controls	:	Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	•	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measur	es	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection		

### Section 8. Exposure controls/personal protection

Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

# Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### **Appearance**

Physical state	: Li	quid.	
Color	: Ta	in.	
Odor	: N	ot available.	
Odor threshold	: N	ot available.	
рН	: N	ot applicable.	
Melting point/freezing point	: N	ot available.	
Boiling point or initial boiling point and boiling range	: N	ot available.	
Flash point	: C	osed cup: Not applicable.	
Evaporation rate	: N	ot available.	
Flammability	: N	ot available.	
Lower and upper explosion limit/flammability limit	: N	ot available.	
Vapor pressure	: N	ot available.	
Relative vapor density	: N	ot available.	
Relative density	: 1.	57	
Density	: 1.	56 g/cm <sup>3</sup>	
Solubility(ies)	:		
Media		Result	]
cold water		Not soluble	]
Partition coefficient: n- octanol/water	: N	bt applicable.	L
Auto-ignition temperature	: N	ot available.	

**Decomposition temperature** : Not available.

# Section 9. Physical and chemical properties

Viscosity	: Dynamic (room temperature): Not available. Kinematic (room temperature): Not available. Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)	
Molecular weight	: Not applicable.	
Particle characteristics		
Median particle size	: Not applicable.	
Heat of combustion	: 8.197 kJ/g	

# Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# Section 11. Toxicological information

Saddle Tan

Information on toxicological effects		
Acute toxicity		
Product/ingredient name	Result	
Aminoethylaminopropyltrimethoxysilane	<b>Rat - Oral - LD50</b> 2413 mg/kg <u>Toxic effects</u> : Behavioral - Tremor Gastrointestin diarrhea Gastrointestinal - Other changes	nal - Hypermotility,
Conclusion/Summary [Product] : Not av	ailable.	
Skin corrosion/irritation		
Product/ingredient name	Result	
Aminoethylaminopropyltrimethoxysilane	Rabbit - Skin - Mild irritant Amount/concentration applied: 500 mg	
Conclusion/Summary [Product] : Not av	vailable.	
Serious eye damage/eye irritation		
Product/ingredient name	Result	
Aminoethylaminopropyltrimethoxysilane	Rabbit - Eyes - Severe irritant Amount/concentration applied: 15 mg	
Conclusion/Summary [Product] : Not av	ailable.	
Date of issue/Date of revision: 4/25/2025DateGC43511Geocel® 4350 Metal Roof Sealant		n : 14 9/15 8 <b>5-NA-GHS-CA</b>

## Section 11. Toxicological information

### **Respiratory corrosion/irritation** Not available. **Conclusion/Summary [Product]** : Not available. Respiratory or skin sensitization Not available. Skin **Conclusion/Summary [Product]** : Not available. Respiratory **Conclusion/Summary [Product]** : Not available. Germ cell mutagenicity Not available. **Conclusion/Summary [Product]** : Not available. **Carcinogenicity** Not available. **Conclusion/Summary [Product]** : Not available. **Classification OSHA Product/ingredient name** IARC NTP Crystalline Silica, respirable + 1 Known to be a human carcinogen. powder

#### Reproductive toxicity

Not available.

### **Conclusion/Summary [Product]** : Not available.

#### Specific target organ toxicity (single exposure)

Product/ingredient name	Result
Calcium Carbonate	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) 🥄
	(Respiratory tract irritation) - Category 3
Dibutylbis(pentadionate)tin	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) -
	Category 1

#### Specific target organ toxicity (repeated exposure)

Product/ingredient name

Result

Date of issue/Da	ate of revision	: 4/25/2025	Date of previous issue	: 1/9/2025	Version : 14	10/15
GC43511	Geocel® 4350 Me	etal Roof Sealant			SHW-85-NA-GHS-CA	
	Saddle Tan					

# Section 11. Toxicological information

Aminoethylaminopropyltrimethoxysilane

Dibutylbis(pentadionate)tin

Crystalline Silica, respirable powder

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (immune system) - Category 1 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (inhalation) - Category 1

#### Aspiration hazard

Not available.

### Information on the likely routes of exposure

Not available.

#### Potential acute health effects

Eye contact	: Causes serious eye irritation.
Inhalation	: May cause respiratory irritation.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness	
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing reduced fetal weight increase in fetal deaths skeletal malformations	
Skin contact	: Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations	
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations	

#### Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure		
Potential immediate effects	: Not available	
Potential delayed effects	: Not available	
Long term exposure		
Potential immediate effects	: Not available	
Potential delayed effects	: Not available	
Potential chronic health effe	ects	

Date of issue/Date of	of revision	: 4/25/2025	Date of previous issue	: 1/9/2025	Version : 14	11/15
	Geocel® 4350 Metal Ro Saddle Tan	oof Sealant			SHW-85-NA-GHS-CA	

# Section 11. Toxicological information

Not available.

Conclusion/Summary [P	Product] : Not available.
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: May cause cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: May damage fertility or the unborn child.

### Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name		Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
Aminoethylaminopropyltrimethoxysilane	2413	N/A	N/A		N/A 📃
Dibutylbis(pentadionate)tin	500	2500	N/A		N/A

# Section 12. Ecological information

#### **Toxicity**

Not available.

**Conclusion/Summary [Product]** : Not available.

### Persistence and degradability

Not available.

Conclusion/Summary [Product] : Not available.

### **Bioaccumulative potential**

Not available.

### Mobility in soil

Soil/Water partition : No coefficient

: Not available.

### Other adverse effects

No known significant effects or critical hazards.

Date of issue/Date	e of revision	: 4/25/2025	Date of previous issue
GC43511	Geocel® 4350 Metal Saddle Tan	Roof Sealant	

# Section 13. Disposal considerations

#### **Disposal methods**

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# Section 14. Transport information

	•				1
	DOT Classification	TDG Classification	Mexico Classification	ΙΑΤΑ	IMDG
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.
Additional information	-	-	-	-	-
Special precautions	conside mode o suitably to shipn of the p dangero and on	odal shipping descrip r container sizes. The f transport (sea, air, for that mode of trans nent, and compliance erson offering the propus goods must be tr all actions in case of	e presence of a ship etc.), does not indic nsport. All packaging e with the applicable oduct for transport. rained on all of the ri	pping description for ate that the product g must be reviewed to regulations is the se People loading and sks deriving from th	a particular s packaged for suitability prior ble responsibility unloading
ransport in bulk ac o IMO instruments	ccording : Not avail	able.			

Proper shipping name : Not av

: Not available.

### Section 15. Regulatory information

### International regulations

#### **Montreal Protocol**

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

List name	Ingredient name	Status
Annex A - Elimination - Production	UV-328	
Annex A - Elimination - Use	UV-328	Listed

International lists : Australia inventory (AIIC): Not determined. China inventory (IECSC): Not determined. Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined. Korea inventory (KECI): Not determined. New Zealand Inventory of Chemicals (NZIoC): Not determined. Philippines inventory (PICCS): Not determined. Taiwan Chemical Substances Inventory (TCSI): Not determined. Thailand inventory: Not determined. Turkey inventory: Not determined. Vietnam inventory: Not determined.

### Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

	Justification	
SKIN SENSITIZATION - C CARCINOGENICITY - Cat TOXIC TO REPRODUCTI	EYE IRRITATION - Category 2A ategory 1 egory 1A	Calculation method Calculation method Calculation method Calculation method Calculation method Calculation method
<u>History</u> Date of printing	: 4/25/2025	
Date of issue/Date of revision	: 4/25/2025	
Date of previous issue	: 1/9/2025	
Version	: 14	

Date of issue/	Date of revision	: 4/25/2025	Date of previous issue	: 1/9/2025	Version : 14	14/15
GC43511	Geocel® 4350 M	Geocel® 4350 Metal Roof Sealant			SHW-85-NA-GHS-CA	
	Saddle Tan					

### Section 16. Other information

Key to abbreviations	: ATE = Acute Toxicity Estimate
	BCF = Bioconcentration Factor
	GHS = Globally Harmonized System of Classification and Labelling of Chemicals
	IATA = International Air Transport Association
	IBC = Intermediate Bulk Container
	IMDG = International Maritime Dangerous Goods
	LogPow = logarithm of the octanol/water partition coefficient
	MARPOL = International Convention for the Prevention of Pollution From Ships, 1973
	as modified by the Protocol of 1978. ("Marpol" = marine pollution)
	N/A = Not available
	SGG = Segregation Group
	UN = United Nations

Indicates information that has changed from previously issued version.

#### Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.