# SAFETY DATA SHEET

GC43561

### **Section 1. Identification**

Product name : Geocel® 4350 Metal Roof Sealant

Evergreen

Product code : GC43561
Other means of : Not available.

identification Product type

: Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Paint or paint related material.

Manufacturer : Geocel Products Group

A Business Unit of the Sherwin-Williams Company

101 W. Prospect Avenue Cleveland, Ohio 44115

National contact : Sherwin-Williams Canada Inc.

180 Brunel Road

Mississauga, Ontario L4Z 1T5 Canada

**Emergency telephone** number of the company

: US / Canada: (800) 424-9300

Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year

Product Information Telephone Number

: US / Canada: (800) 348-7615 Mexico: Not Available

Transportation Emergency

: US / Canada: (800) 424-9300

Telephone Number Mexico: SET

Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year

### Section 2. Hazards identification

Classification of the substance or mixture

: SKIN CORROSION/IRRITATION - Category 2

SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A

SKIN SENSITIZATION - Category 1
CARCINOGENICITY - Category 1A

TOXIC TO REPRODUCTION - Category 1B

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract

irritation) - Category 3

**GHS label elements** 

Hazard pictograms :





Signal word

: Danger

**Hazard statements**: Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation. May cause respiratory irritation.

May cause cancer.

May damage fertility or the unborn child.

Date of issue/Date of revision : 1/9/2025 Date of previous issue : 11/19/2024 Version : 13.04 1/14

GC43561 Geocel® 4350 Metal Roof Sealant

Evergreen

### Section 2. Hazards identification

### **Precautionary statements**

**General** 

: Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

**Prevention** 

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Use only outdoors or in a well-ventilated area. Avoid breathing vapor. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

Response

: IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. Take off contaminated clothing and wash it before reuse. Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

Storage Disposal

: Store locked up. Store in a well-ventilated place. Keep container tightly closed.

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label elements

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. Adequate ventilation required when sanding or abrading the dried film. If Adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Abrading or sanding of the dry film may release Crystalline Silica which has been shown to cause lung damage and cancer under long term exposure. Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.

Hazards not otherwise classified

: None known.

## Section 3. Composition/information on ingredients

Substance/mixture
Other means of
identification

: Mixture: Not available.

#### **CAS** number/other identifiers

Ingredient name	% by weight	CAS number
Calcium Carbonate	57.64	1317-65-3
Aminoethylaminopropyltrimethoxysilane	0.75	1760-24-3
Dibutylbis(pentadionate)tin	0.4	22673-19-4
Crystalline Silica, respirable powder	0.15	14808-60-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Date of issue/Date of revision: 1/9/2025Date of previous issue: 11/19/2024Version: 13.042/14GC43561Geocel® 4350 Metal Roof SealantSHW-85-NA-GHS-CA

Evergreen

### Section 4. First aid measures

### **Description of necessary first aid measures**

**Eye contact**: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10

minutes. Get medical attention.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it

is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open

airway. Loosen tight clothing such as a collar, tie, belt or waistband.

**Skin contact**: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash

contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean

shoes thoroughly before reuse.

Ingestion : Wash out mouth with water. Remove dentures if any. If material has been swallowed

and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing

such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

### Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : May cause respiratory irritation.

Skin contact : Causes skin irritation. May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

**Eye contact**: Adverse symptoms may include the following:

pain or irritation watering redness

**Inhalation** : Adverse symptoms may include the following:

respiratory tract irritation

coughing

reduced fetal weight increase in fetal deaths skeletal malformations

**Skin contact**: Adverse symptoms may include the following:

irritation redness

reduced fetal weight increase in fetal deaths skeletal malformations

**Ingestion**: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Date of issue/Date of revision : 1/9/2025 Date of previous issue : 11/19/2024 Version : 13.04 3/14

GC43561 Geocel® 4350 Metal Roof Sealant

Evergreen

### Section 4. First aid measures

### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

**Specific treatments** 

: No specific treatment.

**Protection of first-aiders** 

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### See toxicological information (Section 11)

### Section 5. Fire-fighting measures

### **Extinguishing media**

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

: None known.

Specific hazards arising

from the chemical
Hazardous thermal
decomposition products

: In a fire or if heated, a pressure increase will occur and the container may burst.

 Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### Methods and materials for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Date of issue/Date of revision : 1/9/2025 Date of previous issue : 11/19/2024 Version : 13.04 4/14

GC43561 Geocel® 4350 Metal Roof Sealant Evergreen

### Section 6. Accidental release measures

### Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

### Section 7. Handling and storage

### **Precautions for safe handling**

#### **Protective measures**

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

# Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

# Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### Section 8. Exposure controls/personal protection

### **Control parameters**

Occupational exposure limits (OSHA United States)

Ingredient name	CAS#	Exposure limits
Calcium Carbonate	1317-65-3	OSHA PEL (United States, 5/2018).  TWA: 5 mg/m³ 8 hours. Form: Respirable fraction  TWA: 15 mg/m³ 8 hours. Form: Total dust NIOSH REL (United States, 10/2020).  [calcium carbonate]  TWA: 5 mg/m³ 10 hours. Form: Respirable fraction  TWA: 10 mg/m³ 10 hours. Form: Total
Aminoethylaminopropyltrimethoxysilane Dibutylbis(pentadionate)tin	1760-24-3 22673-19-4	None.  ACGIH TLV (United States, 1/2024). [Tin, organic compounds] Absorbed through skin.  TWA: 0.1 mg/m³, (as Sn) 8 hours.  STEL: 0.2 mg/m³, (as Sn) 15 minutes.  NIOSH REL (United States, 10/2020). [tin

Date of issue/Date of revision: 1/9/2025Date of previous issue: 11/19/2024Version: 13.045/14GC43561Geocel® 4350 Metal Roof SealantSHW-85-NA-GHS-CA

GC43561 Geocel® 4350 Metal Roof Sealant Evergreen

# Section 8. Exposure controls/personal protection

	organic compounds] Absorbed through skin.  TWA: 0.1 mg/m³, (as Sn) 10 hours.  OSHA PEL (United States, 5/2018). [Tin, organic compounds]  TWA: 0.1 mg/m³, (as Sn) 8 hours.
14808-60-7	OSHA PEL Z3 (United States, 6/2016). TWA: 250 mppcf / (%SiO <sub>2</sub> +5) 8 hours. Form: Respirable
	TWA: 10 mg/m³ / (%SiO <sub>2</sub> +2) 8 hours. Form: Respirable
	OSHA PEL (United States, 5/2018). [Silica, crystalline]
	TWA: 50 μg/m³ 8 hours. Form: Respirable dust
	ACGIH TLV (United States, 1/2024). [Silica, crystalline]
	TWA: 0.025 mg/m³ 8 hours. Form: Respirable fraction
	NIOSH REL (United States, 10/2020). [SILICA, CRYSTALLINE]
	TWA: 0.05 mg/m³ 10 hours. Form: respirable dust
	14808-60-7

### Occupational exposure limits (Canada)

Evergreen

Ingredient name	CAS#	Exposure limits
Dibutylbis(pentadionate)tin	22673-19-4	CA Alberta Provincial (Canada, 3/2023). [Tin Organic compounds] Absorbed through skin.  OEL: 0.2 mg/m³, (as Sn) 15 minutes. OEL: 0.1 mg/m³, (as Sn) 8 hours.  CA British Columbia Provincial (Canada, 8/2023). [Tin - Organic compounds] Absorbed through skin.  TWA: 0.1 mg/m³, (as Sn) 8 hours. STEL: 0.2 mg/m³, (as Sn) 15 minutes.  CA Ontario Provincial (Canada, 6/2019). [Tin (Organic compounds)] Absorbed through skin.  TWA: 0.1 mg/m³, (as Sn) 8 hours.  CA Saskatchewan Provincial (Canada, 4/2021). [Tin organic compounds] Absorbed through skin.  STEL: 0.2 mg/m³, (measured as Sn) 15 minutes.  TWA: 0.1 mg/m³, (measured as Sn) 8 hours.
Quartz	14808-60-7	CA British Columbia Provincial (Canada, 8/2023). [Silica, Crystalline - alpha quartz and Cristobalite]  TWA: 0.025 mg/m³ 8 hours. Form: Respirable CA Alberta Provincial (Canada, 3/2023).  OEL: 0.025 mg/m³ 8 hours. Form: Respirable particulate CA Ontario Provincial (Canada, 6/2019). [Silica, Crystalline (Quartz/Tripoli)]

Date of issue/Date of revision: 1/9/2025Date of previous issue: 11/19/2024Version: 13.046/14GC43561Geocel® 4350 Metal Roof SealantSHW-85-NA-GHS-CA

### Section 8. Exposure controls/personal protection

TWA: 0.1 mg/m³ 8 hours. Form: Respirable
particulate matter.
CA Quebec Provincial (Canada, 2/2024).
[Silica Crystalline -Quartz]
TWAEV: 0.1 mg/m <sup>3</sup> 8 hours. Form:
respirable aerosol fraction
CA Saskatchewan Provincial (Canada,
4/2021).
TWA: 0.05 mg/m³ 8 hours. Form: respirable
fraction

### Occupational exposure limits (Mexico)

Ingredient name	CAS#	Exposure limits
Dibutylbis(pentadionate)tin		NOM-010-STPS-2014 (Mexico, 4/2016). [Estaño, compuestos orgánicos] Absorbed through skin. TWA: 0.1 mg/m³, (as Sn) 8 hours. STEL: 0.2 mg/m³, (as Sn) 15 minutes.

#### **Biological exposure indices (United States)**

No exposure indices known.

### **Biological exposure indices (Canada)**

No exposure indices known.

#### **Biological exposure indices (Mexico)**

No exposure indices known.

# Appropriate engineering controls

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits

# **Environmental exposure** controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### **Individual protection measures**

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

### **Eye/face protection**

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

#### **Skin protection**

GC43561

Date of issue/Date of revision : 1/9/2025 Date of previous issue : 11/19/2024 Version : 13.04 7/14

### Section 8. Exposure controls/personal protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be

worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the

protection time of the gloves cannot be accurately estimated.

: Personal protective equipment for the body should be selected based on the task being **Body protection** 

performed and the risks involved and should be approved by a specialist before

handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected

based on the task being performed and the risks involved and should be approved by a

specialist before handling this product.

: Based on the hazard and potential for exposure, select a respirator that meets the Respiratory protection

appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important

aspects of use.

### Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### **Appearance**

Physical state : Liquid. Color Green.

: Not available. Odor **Odor threshold** Not available. : Not applicable. **Melting point/freezing point** : Not available. **Boiling point, initial boiling** : Not available.

point, and boiling range

Flash point : Closed cup: Not applicable.

**Evaporation rate** : Not available. : Not available. **Flammability** Lower and upper explosion : Not available.

limit/flammability limit

: Not available. Vapor pressure Relative vapor density Not available.

Relative density : 1.57

Solubility(ies)

Media	Result
cold water	Not soluble

Partition coefficient: n-

octanol/water

: Not applicable.

**Auto-ignition temperature** : Not available. **Decomposition temperature** : Not available.

**Viscosity** Kinematic (40°C (104°F)): >20.5 mm<sup>2</sup>/s (>20.5 cSt)

Molecular weight Not applicable.

Heat of combustion : 7.94 kJ/g

Date of issue/Date of revision : 1/9/2025 Date of previous issue : 11/19/2024 Version: 13.04 8/14

GC43561 Geocel® 4350 Metal Roof Sealant

Evergreen

### Section 10. Stability and reactivity

: No specific test data related to reactivity available for this product or its ingredients. Reactivity

**Chemical stability** : The product is stable.

**Possibility of hazardous** 

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** : No specific data.

Incompatible materials : No specific data.

**Hazardous decomposition** 

products

: Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

### Section 11. Toxicological information

### Information on toxicological effects

### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Aminoethylaminopropyltrimethoxysilane	LD50 Oral	Rat	2413 mg/kg	-

### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Aminoethylaminopropyltrimethoxysilane	Eyes - Severe irritant	Rabbit	-	15 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-

### **Sensitization**

Not available.

### **Mutagenicity**

Not available.

#### Carcinogenicity

Not available.

#### Classification

Product/ingredient name	OSHA	IARC	NTP
Crystalline Silica, respirable	+	1	Known to be a human carcinogen.
powder			

### Reproductive toxicity

Not available.

### **Teratogenicity**

Not available.

#### Specific target organ toxicity (single exposure)

Name	•	Route of exposure	Target organs
Calcium Carbonate	Category 3		Respiratory tract irritation
Dibutylbis(pentadionate)tin	Category 1	-	-

Date of issue/Date of revision 9/14 : 1/9/2025 Date of previous issue :11/19/2024 Version: 13.04 GC43561 SHW-85-NA-GHS-CA

Geocel® 4350 Metal Roof Sealant

Evergreen

### Section 11. Toxicological information

### Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
Aminoethylaminopropyltrimethoxysilane Dibutylbis(pentadionate)tin	Category 2 Category 1	-	- immune system
Crystalline Silica, respirable powder	• •	inhalation	-

#### **Aspiration hazard**

Not available.

Information on the likely

: Not available.

routes of exposure

Potential acute health effects

Eye contact : Causes serious eye irritation.Inhalation : May cause respiratory irritation.

**Skin contact**: Causes skin irritation. May cause an allergic skin reaction.

**Ingestion** : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:

pain or irritation

watering redness

**Inhalation** : Adverse symptoms may include the following:

respiratory tract irritation

coughing

reduced fetal weight increase in fetal deaths skeletal malformations

**Skin contact**: Adverse symptoms may include the following:

irritation redness

reduced fetal weight increase in fetal deaths skeletal malformations

**Ingestion** : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Date of issue/Date of revision : 1/9/2025 Date of previous issue : 11/19/2024 Version : 13.04 10/14

GC43561 Geocel® 4350 Metal Roof Sealant

Evergreen

### Section 11. Toxicological information

General

: Once sensitized, a severe allergic reaction may occur when subsequently exposed to

very low levels.

**Carcinogenicity** : May cause cancer. Risk of cancer depends on duration and level of exposure.

**Mutagenicity**: No known significant effects or critical hazards.

**Teratogenicity**: May damage the unborn child.

**Developmental effects**: No known significant effects or critical hazards.

Fertility effects : May damage fertility.

### **Numerical measures of toxicity**

**Acute toxicity estimates** 

Not available.

### Section 12. Ecological information

#### **Toxicity**

Not available.

### Persistence and degradability

Not available.

### **Bioaccumulative potential**

Not available.

### **Mobility in soil**

Soil/water partition coefficient (K<sub>oc</sub>)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

### Section 13. Disposal considerations

#### **Disposal methods**

GC43561

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Date of issue/Date of revision : 1/9/2025 Date of previous issue : 11/19/2024 Version : 13.04 11/14

Geocel® 4350 Metal Roof Sealant

Evergreen

### **Section 14. Transport information**

	DOT Classification	TDG Classification	Mexico Classification	IATA	IMDG
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.
Additional information	-	-	-	-	-

Special precautions for user:

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Transport in bulk according: Not available.

to IMO instruments

Proper shipping name : Not available.

### Section 15. Regulatory information

### International regulations

#### **Montreal Protocol**

Not listed.

### Stockholm Convention on Persistent Organic Pollutants

List name	Ingredient name	Status
Annex A - Elimination - Production	UV-328	Listed
Annex A - Elimination - Use	UV-328	Listed

#### International lists

: Australia inventory (AIIC): Not determined. China inventory (IECSC): Not determined. Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined. Korea inventory (KECI): Not determined.

New Zealand Inventory of Chemicals (NZIoC): Not determined.

Philippines inventory (PICCS): Not determined.

Date of issue/Date of revision 12/14 : 1/9/2025 Date of previous issue : 11/19/2024 Version: 13.04

GC43561 Geocel® 4350 Metal Roof Sealant Evergreen


### Section 15. Regulatory information

Taiwan Chemical Substances Inventory (TCSI): Not determined.

Thailand inventory: Not determined. Turkey inventory: Not determined. Vietnam inventory: Not determined.

### Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them, HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

Classification	Justification
SKIN CORROSION/IRRITATION - Category 2	Calculation method
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A	Calculation method
SKIN SENSITIZATION - Category 1	Calculation method
CARCINOGENICITY - Category 1A	Calculation method
TOXIC TO REPRODUCTION - Category 1B	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3	Calculation method

### **History**

**Date of printing** : 1/9/2025 1/9/2025 Date of issue/Date of

revision

Date of previous issue : 11/19/2024 **Version** 13.04

**Key to abbreviations** : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not availableSGG = Segregation Group UN = United Nations

✓ Indicates information that has changed from previously issued version.

**Notice to reader** 

Date of issue/Date of revision : 1/9/2025 Date of previous issue : 11/19/2024 Version: 13.04 13/14 GC43561

Geocel® 4350 Metal Roof Sealant Evergreen

### Section 16. Other information

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buver/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buver/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

Date of issue/Date of revision : 1/9/2025 Date of previous issue : 11/19/2024 Version : 13.04 14/14