SAFETY DATA SHEET

GC46105

Section 1. Identification		
Product name	: GEOCEL® 4600 Structural Adhesive Sealant Bronze	
Product code	: GC46105	
Other means of identification	: Not available.	
Product type	: Liquid.	
Relevant identified uses of t	the substance or mixture and uses advised against	
Paint or paint related material.		
Manufacturer	: Geocel Products Group A Business Unit of the Sherwin-Williams Company 101 W. Prospect Avenue Cleveland, Ohio 44115	
National contact	: Sherwin-Williams Canada Inc. 180 Brunel Road Mississauga, Ontario L4Z 1T5 Canada	
Emergency telephone number of the company	: US / Canada: (800) 424-9300 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year	
Product Information Telephone Number	: US / Canada: (800) 348-7615 Mexico: Not Available	
Transportation Emergency Telephone Number	: US / Canada: (800) 424-9300 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year	

Section 2. Hazards identification

Classification of the substance or mixture	 SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 1A TOXIC TO REPRODUCTION - Category 1B
	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
	Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 2.8% (dermal), 1.8% (inhalation)
GHS label elements	
Hazard pictograms	

Signal word

: Danger

Date of issue/Date	of revision	: 4/15/2025	Date of previous issue	: 12/10/2024	Version : 17
GC46105	GEOCEL® 4600 Struc Bronze	tural Adhesive S	Sealant		SHW-85-NA-GHS-CA

1/16

Section 2. Hazards identification

Hazard statements	 Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause respiratory irritation. May cause cancer. May damage fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.
Precautionary statements	
General	: Keep out of reach of children. If medical advice is needed, have product container or label at hand.
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing, eye protection, face protection, or hearing protection. Use only outdoors or in a well-ventilated area. Do not breathe vapor. Wash thoroughly after handling.
Response	: IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
Storage	: Store locked up. Store in a well-ventilated place. Keep container tightly closed.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. Adequate ventilation required when sanding or abrading the dried film. If Adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Abrading or sanding of the dry film may release Crystalline Silica which has been shown to cause lung damage and cancer under long term exposure. Please refer to the SDS for additional information. Keep out of reach of children. Do not
	transfer contents to other containers for storage.
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of identification	: Not available.

CAS number/other identifiers

Ingredient name	% by weight	Identifiers
Calcium Carbonate	63	1317-65-3
Aminoethylaminopropyltrimethoxysilane	1.01	1760-24-3
Dibutylbis(pentadionate)tin	0.39	22673-19-4
Light Stabilizer	0.19	52829-07-9
Crystalline Silica, respirable powder	0.16	14808-60-7
Hydrocarbon Polymer	0.13	71302-83-5
Carbon Black	0.13	1333-86-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Date of issue/Da	ate of revision	: 4/15/2025	Date of previous issue	: 12/10/2024	Version : 17	2/16
GC46105	GEOCEL® 4600 \$ Bronze	Structural Adhesive	Sealant		SHW-85-NA-GHS-CA	

Section 3. Composition/information on ingredients

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	 Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Bronze

Potential acute health effe	icts
Eye contact	: Causes serious eye irritation.
Inhalation	: May cause respiratory irritation.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/sym	<u>ptoms</u>
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations
Date of issue/Date of revision	: 4/15/2025 Date of previous issue : 12/10/2024 Versi
GC46105 GEOCEL® 4600	0 Structural Adhesive Sealant SHW

: 12/10/2024	Version : 17
	SHW-85-NA-GHS-CA

Section 4. First aid measures

Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Indication of immediate me	lical attention and special treatment needed, if necessary
Notes to physician	 In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
1	

Section 6. Accidental release measures

Personal precautions, protec	tiv	equipment and emergency proced	<u>ures</u>				
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel fror entering. Do not touch or walk through spilled material. Avoid breathing vapor o Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.					
For emergency responders	:	If specialized clothing is required to de Section 8 on suitable and unsuitable m emergency personnel".					
Environmental precautions	:	Avoid dispersal of spilled material and and sewers. Inform the relevant author pollution (sewers, waterways, soil or a	prities if the product has o				
Date of issue/Date of revision		· 4/15/2025 Date of previous issue	: 12/10/2024	Version	: 17	4/16	

Date of issue/Date of	revision	4/15/2025	Date of previous issue	: 12/10/2024	Version :17	4/
	EOCEL® 4600 Structu ronze	ral Adhesive S	ealant		SHW-85-NA-GHS-CA	

Methods and materials for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Absorb with an inert materia and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

Ingredient name	CAS #	Exposure limits		
Calcium Carbonate	1317-65-3	 NIOSH REL (United States, 10/2020) [calcium carbonate] TWA 10 hours: 10 mg/m³. Form: Total. TWA 10 hours: 5 mg/m³. Form: Respirable fraction. OSHA PEL (United States, 5/2018) TWA 8 hours: 15 mg/m³. Form: Total dust. TWA 8 hours: 5 mg/m³. Form: Respirable fraction. 		
Aminoethylaminopropyltrimethoxysila Dibutylbis(pentadionate)tin	ne 1760-24-3 22673-19-4	None. ACGIH TLV (United States, 1/2024) [Tin, organic compounds] A4. Absorbed through		
Date of issue/Date of revision : 4/1	5/2025 Date of previous issue	: 12/10/2024 Version : 17 5/16		
GC46105 GEOCEL® 4600 Structural A Bronze	Adhesive Sealant	SHW-85-NA-GHS-CA		

Section 8. Exposure controls/personal protection

Coolion of Expectate controls per		
		skin. TWA 8 hours: 0.1 mg/m ³ (as Sn). STEL 15 minutes: 0.2 mg/m ³ (as Sn). NIOSH REL (United States, 10/2020) [tin organic compounds] Absorbed through skin. TWA 10 hours: 0.1 mg/m ³ (as Sn). OSHA PEL (United States, 5/2018) [Tin, organic compounds] TWA 8 hours: 0.1 mg/m ³ (as Sn).
Light Stabilizer Crystalline Silica, respirable powder	52829-07-9 14808-60-7	None. ACGIH TLV (United States, 1/2024) [Silica, crystalline] A2. TWA 8 hours: 0.025 mg/m ³ . Form: Respirable fraction. NIOSH REL (United States, 10/2020) [SILICA, CRYSTALLINE] NIA. TWA 10 hours: 0.05 mg/m ³ . Form: respirable dust. OSHA PEL (United States, 5/2018) [Silica, crystalline] TWA 8 hours: 50 μ g/m ³ . Form: Respirable dust. OSHA PEL Z3 (United States, 6/2016) TWA 8 hours: 250 / (%SiO ₂ +5) mppcf. Form: Respirable. TWA 8 hours: 10 / (%SiO ₂ +2) mg/m ³ . Form: Respirable.
Hydrocarbon Polymer Carbon Black	71302-83-5 1333-86-4	None. ACGIH TLV (United States, 1/2024) A3. TWA 8 hours: 3 mg/m ³ . Form: Inhalable fraction. NIOSH REL (United States, 10/2020) NIA. TWA 10 hours: 3.5 mg/m ³ . TWA 10 hours: 0.1 mg/m ³ (as cyclohexane- extractable fraction). OSHA PEL (United States, 5/2018) TWA 8 hours: 3.5 mg/m ³ .

Occupational exposure limits (Canada)

Ingredient name	CAS #	Exposure limits
Dibutylbis(pentadionate)tin	22673-19-4	 CA Saskatchewan Provincial (Canada, 4/2021) [Tin organic compounds] Absorbed through skin. STEL 15 minutes: 0.2 mg/m³ (measured as Sn). TWA 8 hours: 0.1 mg/m³ (measured as Sn). CA British Columbia Provincial (Canada, 4/2024) [tin - organic compounds] Absorbed through skin. TWA 8 hours: 0.1 mg/m³ (as Sn). STEL 15 minutes: 0.2 mg/m³ (as Sn). STEL 15 minutes: 0.2 mg/m³ (as Sn). CA Ontario Provincial (Canada, 6/2019) [Tin (Organic compounds)] Absorbed through skin.
ate of issue/Date of revision : 4/15/2025 C46105 GEOCEL® 4600 Structural Adhesive	Date of previous issue e Sealant	: 12/10/2024 Version : 17 6/1 SHW-85-NA-GHS-CA

Section 8. Exposure controls/personal protection

Quartz	14808-60-7	TWA 8 hours: 0.1 mg/m ³ (as Sn). CA Alberta Provincial (Canada, 3/2023) [Tin Organic compounds] Absorbed through skin. OEL 15 minutes: 0.2 mg/m ³ (as Sn). OEL 8 hours: 0.1 mg/m ³ (as Sn). CA Saskatchewan Provincial (Canada,
		 4/2021) TWA 8 hours: 0.05 mg/m³. Form: respirable fraction. CA British Columbia Provincial (Canada, 4/2024) [silica, crystalline - alpha quartz and cristobalite] Carc 2A, Carc 1. TWA 8 hours: 0.025 mg/m³. Form: Respirable. CA Ontario Provincial (Canada, 6/2019) [Silica, Crystalline (Quartz/Tripoli)] TWA 8 hours: 0.1 mg/m³. Form: Respirable particulate matter CA Quebec Provincial (Canada, 2/2024) [Silica Crystalline -Quartz] C2. TWAEV 8 hours: 0.1 mg/m³. Form: respirable aerosol fraction. CA Alberta Provincial (Canada, 3/2023) A2. OEL 8 hours: 0.025 mg/m³. Form:
Carbon black	1333-86-4	 CA Saskatchewan Provincial (Canada, 4/2021) STEL 15 minutes: 7 mg/m³. TWA 8 hours: 3.5 mg/m³. CA British Columbia Provincial (Canada, 4/2024) Carc 2B. TWA 8 hours: 3 mg/m³. Form: Inhalable. CA Ontario Provincial (Canada, 6/2019) TWA 8 hours: 3 mg/m³. Form: Inhalable particulate matter CA Quebec Provincial (Canada, 2/2024) C3. TWAEV 8 hours: 3 mg/m³. Form: inhalable aerosol fraction. CA Alberta Provincial (Canada, 3/2023) OEL 8 hours: 3.5 mg/m³.

Occupational exposure limits (Mexico)

Ingredient name	CAS #	Exposure limits
Dibutylbis(pentadionate)tin	22673-19-4	NOM-010-STPS-2014 (Mexico, 4/2016) [Estaño, compuestos orgánicos] A4. Absorbed through skin. TWA 8 hours: 0.1 mg/m ³ (as Sn). STEL 15 minutes: 0.2 mg/m ³ (as Sn).

Biological exposure indices (United States)

No exposure indices known.

Biological exposure indices (Canada)

Date of issue/Date	of revision	: 4/15/2025	Date of previous issue	: 12/10/2024	Version : 17	7/16
GC46105 GEOCEL® 4600 Structural Adhesi Bronze		tural Adhesive	Sealant		SHW-85-NA-GHS-C	A

Section 8. Exposure controls/personal protection

No exposure indices known.

Biological exposure indices (Mexico)

No exposure indices known.

Appropriate engineering controls Environmental exposure controls	 Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measu	
Hygiene measures	 Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance						
Physical state		: Liquid.				
Color		: Various				
Odor		: Not available.				
Odor threshold		: Not available.				
рН		: Not applicable.				
Melting point/fre	ezing point	: Not availab	le.			
Date of issue/Date o	f revision	: 4/15/2025	Date of previous issue	: 12/10/2024	Version : 1	17 8/16
GC46105 GEOCEL® 4600 S Bronze		Structural Adhesive	Sealant		SHW-85-NA	-GHS-CA

Section 9. Physical and chemical properties

: Not	available.	
: Clo	sed cup: Not applicable.	
: Not	available.	
: 1.69	9	
Density : 1.69 g/cm ³		
:		
	Result]
	Not soluble]
: Not	applicable.	
: Not	available.	
: Not	available.	
 Dynamic (room temperature): Not available. Kinematic (room temperature): Not available. Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt) 		
: No	t applicable.	
: Not	applicable.	
• 170	95 k.l/a	
	: Clos : Not : Not : Not : Not : 1.69 : 1.69 : 1.69 : 1.69 : 1.69 : Not : Not : Not : Not : Not : Not : Not	 Result Not soluble Not applicable. Not available. Not available. Dynamic (room temperature): Not available.

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Bronze

Information on toxicological effects	
Acute toxicity	
Product/ingredient name	Result
Aminoethylaminopropyltrimethoxysilane	Rat - Oral - LD50 2413 mg/kg <u>Toxic effects</u> : Behavioral - Tremor Gastrointestinal - Hypermotilit diarrhea Gastrointestinal - Other changes
Light Stabilizer	Rat - Inhalation - LC50 Vapor 500 mg/m ³ [4 hours] <u>Toxic effects</u> : Behavioral - Tremor Lung, Thorax, or Respiration Dyspnea Gastrointestinal - Changes in structure or function of salivary glands
Carbon Black	Rat - Oral - LD50 >15400 mg/kg <u>Toxic effects</u> : Behavioral - Somnolence (general depressed activity)
Conclusion/Summary [Product]	: Not available.
Skin corrosion/irritation	
Product/ingredient name	Result
Aminoethylaminopropyltrimethoxysilane	Rabbit - Skin - Mild irritant Amount/concentration applied: 500 mg
Conclusion/Summary [Product]	: Not available.
Serious eye damage/eye irritation	
Product/ingredient name	Result
Aminoethylaminopropyltrimethoxysilane	Rabbit - Eyes - Severe irritant Amount/concentration applied: 15 mg
Conclusion/Summary [Product]	: Not available.
Respiratory corrosion/irritation Not available.	
Conclusion/Summary [Product]	: Not available.
Respiratory or skin sensitization	
Not available.	
Skin	
Conclusion/Summary [Product]	: Not available.
Respiratory Conclusion/Summary [Product]	: Not available.
Germ cell mutagenicity	
Date of issue/Date of revision : 4/15/20 GC46105 GEOCEL® 4600 Structural Adhe Bronze Bronze	

Not available.

Conclusion/Summary [Product] : Not available.

Carcinogenicity

Not available.

Conclusion/Summary [Product] : Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
Crystalline Silica, respirable powder	+	1	Known to be a human carcinogen.
Carbon Black	-	2B	-

Reproductive toxicity

Not available.

Conclusion/Summary [Product] : Not available.

Specific target organ toxicity (single exposure)	
Product/ingredient name	Result
Calcium Carbonate	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE)
Dibutylbis(pentadionate)tin	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Result
Aminoethylaminopropyltrimethoxysilane	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
Dibutylbis(pentadionate)tin	SPECIFIC TARGET ORGAN TOXICITY (REPEATED
Crystalline Silica, respirable powder	EXPOSURE) (immune system) - Category 1 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (inhalation) - Category 1

Aspiration hazard

Not available.

Information on the likely routes of exposure

Not available.

Potential acute health effects

Eye contact	: Causes serious eye irritation.
Inhalation	: May cause respiratory irritation.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.

Date of issue/D	ate of revision	: 4/15/2025	Date of previous issue	: 12/10/2024	Version : 17	11/16
GC46105	GEOCEL® 4600 \$ Bronze	Structural Adhesive	Sealant		SHW-85-NA-GHS-CA	

	<u> </u>	
Symptoms related to the phy	sical, chemical and toxicological characteristics	1
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness	
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing reduced fetal weight increase in fetal deaths skeletal malformations	
Skin contact	: Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations	
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations	

Delayed and immediate effe	cts and also chronic effects from short and long term exposure
Short term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health effe	ects
Not available.	

Conclusion/Summary [Product] : Not available.				
General	: May cause damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.			
Carcinogenicity	: May cause cancer. Risk of cancer depends on duration and level of exposure.			
Mutagenicity	: No known significant effects or critical hazards.			
Reproductive toxicity	: May damage fertility or the unborn child.			

Numerical measures of toxicity Acute toxicity estimates

 $\overline{}$

	v				
Prod	uct/ingredient name	 Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
Amine	CEL® 4600 Structural Adhesive Sealant oethylaminopropyltrimethoxysilane ylbis(pentadionate)tin	N/A N/A 2500	N/A N/A N/A	1085.8 11 N/A	N/A N/A N/A

Section 12. Ecological information

Toxicity

Not available.

Conclusion/Summary [Pro	duct]	:	Not available.
Persistence and degradability Not available.			
Conclusion/Summary [Pro	duct]	:	Not available.
Bioaccumulative potential Not available.			
<u>Mobility in soil</u> Soil/Water partition coefficient	: Not avai	lat	ble.

Other adverse effects

No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	ΙΑΤΑ	IMDG
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.
Additional information	-	-	-	_	-
Special precautions	conside mode o suitably to shipn of the p dangero and on	l odal shipping descrip or container sizes. Th f transport (sea, air, for that mode of tran nent, and compliance erson offering the pr ous goods must be tr all actions in case of able.	te presence of a shi etc.), does not indic nsport. All packaging e with the applicable oduct for transport. rained on all of the r	pping description for ate that the product g must be reviewed regulations is the s People loading and isks deriving from th	a particular is packaged for suitability prior ole responsibility unloading
	Proper s	hipping name	: Not available.		

Section 15. Regulatory information

International regulations

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

List name	Ingredient name	Status
Annex A - Elimination - Production	UV-328	Listed 🥄
Annex A - Elimination - Use	UV-328	Listed

Inte	erna	atio	nal	lists

Australia inventory (AIIC): Not determined.
 China inventory (IECSC): Not determined.
 Japan inventory (CSCL): Not determined.
 Japan inventory (ISHL): Not determined.
 Korea inventory (KECI): Not determined.
 New Zealand Inventory of Chemicals (NZIoC): Not determined.
 Philippines inventory (PICCS): Not determined.

Date of issue/Date	of revision	: 4/15/2025	Date of previous issue	: 12/10/2024	Version : 17	14/16
GC46105	GEOCEL® 4600 Struct Bronze	tural Adhesive S	Sealant		SHW-85-NA-GHS-CA	

Section 15. Regulatory information

Taiwan Chemical Substances Inventory (TCSI): Not determined. Thailand inventory: Not determined. Turkey inventory: Not determined. Vietnam inventory: Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

Classification	Justification
SKIN CORROSION/IRRITATION - Category 2	Calculation method
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A	Calculation method
SKIN SENSITIZATION - Category 1	Calculation method
CARCINOGENICITY - Category 1A	Calculation method
TOXIC TO REPRODUCTION - Category 1B	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract	Calculation method
irritation) - Category 3	
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2	Calculation method

Date of printing	: 4/15/2025
Date of issue/Date of revision	: 4/15/2025
Date of previous issue	: 12/10/2024
Version	: 17
Key to abbreviations	 ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations

Indicates information that has changed from previously issued version.

Notice to reader

Date of issue/Date	of revision	: 4/15/2025	Date of previous issue	:12/10/2024
GC46105	GEOCEL® 4600 Struc	ctural Adhesive S	Sealant	
	Bronze			

Section 16. Other information

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.