# **SAFETY DATA SHEET**

GC54102

## Section 1. Identification

Product name	: Geocel® Pro™ Gutter Seal Scypolymer® Sealant Aluminum Gray
Product code	: GC54102
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses of t	he substance or mixture and uses advised against
Paint or paint related material.	
Manufacturer	: Geocel Products Group A Business Unit of the Sherwin-Williams Company 101 W. Prospect Avenue Cleveland, Ohio 44115
National contact	: Sherwin-Williams Canada Inc. 180 Brunel Road Mississauga, Ontario L4Z 1T5 Canada
Emergency telephone number of the company	: US / Canada: (800) 424-9300 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year
Product Information Telephone Number	: US / Canada: (800) 348-7615 Mexico: Not Available
Transportation Emergency Telephone Number	: US / Canada: (800) 424-9300 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year

## Section 2. Hazards identification

Aluminum Gray

GHS label elements Hazard pictograms	
	SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 1A TOXIC TO REPRODUCTION - Category 1B SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
substance or mixture	: SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 1A

## Section 2. Hazards identification

Precautionary statements	
General	: Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Use only outdoors or in a well-ventilated area. Avoid breathing vapor. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.
Response	: IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. Take off contaminated clothing and wash it before reuse. Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
Storage	: Store locked up. Store in a well-ventilated place. Keep container tightly closed.
Disposal	<ul> <li>Dispose of contents and container in accordance with all local, regional, national and international regulations.</li> </ul>
Supplemental label elements	WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. Adequate ventilation required when sanding or abrading the dried film. If Adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Abrading or sanding of the dry film may release Crystalline Silica which has been shown to cause lung damage and cancer under long term exposure.
	This product contains a component that is either subject to a CEPA ministerial condition or an existing/proposed SNAC (Significant New Activity).
	Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
Hazards not otherwise classified	: None known.

## Section 3. Composition/information on ingredients

Substance/mixture	
Other means of	
identification	

: Mixture

: Not available.

#### **CAS number/other identifiers**

Ingredient name	% by weight	CAS number
Calcium Carbonate	58.29	1317-65-3
Titanium Dioxide	0.97	13463-67-7
Aminoethylaminopropyltrimethoxysilane	0.69	1760-24-3
Crystalline Silica, respirable powder	0.44	14808-60-7
Dibutylbis(pentadionate)tin	0.23	22673-19-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

Description of necessary first	st aid measures
Eye contact	<ul> <li>Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.</li> </ul>
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effe	ects, acute and delayed
Potential acute health effects	
Eye contact	: Causes serious eye irritation.
Inhalation	: May cause respiratory irritation.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/sympto	<u>ms</u>
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations

Date of issue/Date	of revision	: 5/24/2024	Date of previous issue	: 5/20/2024	Version	:16.03
GC54102	Geocel® Pro™ Gutter Aluminum Gray	Seal Scypolyme	r® Sealant		SHW-85-	NA-GHS-CA

3/14

## Section 4. First aid measures

Indication of immediate med	dical attention and special treatment needed, if necessary
Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	This product contains a component that is either subject to a CEPA ministerial condition or an existing/proposed SNAC (Significant New Activity).
		Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### Methods and materials for containment and cleaning up

Date of issue/Date	te of revision	: 5/24/2024	Date of previous issue	: 5/20/2024	Version	:16.03	4/14
GC54102	Geocel® Pro™ Gut Aluminum Gray	tter Seal Scypolym	er® Sealant		SHW-85-N	NA-GHS-CA	

## Section 6. Accidental release measures

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

#### Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

#### **Control parameters**

#### Occupational exposure limits (OSHA United States)

Ingredient name			CAS #	Exposure limi	its	
Calcium Carbonate		1317-65-3	OSHA PEL (United States, 5/2018). TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Respirable fraction TWA: 15 mg/m <sup>3</sup> 8 hours. Form: Total dust NIOSH REL (United States, 10/2020). [calcium carbonate] TWA: 5 mg/m <sup>3</sup> 10 hours. Form: Respirable fraction			
Titanium Dioxide		13463-67-7	OSHA PEL (U TWA: 15 mg	g/m³ 10 hours. Form: Total Jnited States, 5/2018). g/m³ 8 hours. Form: Total dust United States, 7/2023).		
∣ Date of issue/	Date of revision	: 5/24/2024	Date of previous issue	: 5/20/2024	Version : 16.03 5/14	
GC54102	Geocel® Pro™ G Aluminum Gray	utter Seal Scypolym	er® Sealant		SHW-85-NA-GHS-CA	

# Section 8. Exposure controls/personal protection

	•	
Aminoethylaminopropyltrimethoxysilane Crystalline Silica, respirable powder	1760-24-3 14808-60-7	<ul> <li>TWA: 2.5 mg/m<sup>3</sup> 8 hours. Form: respirable fraction, finescale particles None.</li> <li>OSHA PEL Z3 (United States, 6/2016).</li> <li>TWA: 250 mppcf / (%SiO<sub>2</sub>+5) 8 hours. Form: Respirable</li> <li>TWA: 10 mg/m<sup>3</sup> / (%SiO<sub>2</sub>+2) 8 hours. Form: Respirable</li> <li>OSHA PEL (United States, 5/2018). [Silica, crystalline]</li> <li>TWA: 50 µg/m<sup>3</sup> 8 hours. Form: Respirable dust</li> <li>ACGIH TLV (United States, 7/2023). [Silica, crystalline]</li> <li>TWA: 0.025 mg/m<sup>3</sup> 8 hours. Form: Respirable fraction</li> <li>NIOSH REL (United States, 10/2020).</li> <li>[SILICA, CRYSTALLINE]</li> <li>TWA: 0.05 mg/m<sup>3</sup> 10 hours. Form: respirable dust</li> </ul>
Dibutylbis(pentadionate)tin	22673-19-4	ACGIH TLV (United States, 7/2023). [Tin, organic compounds] Absorbed through skin. TWA: 0.1 mg/m <sup>3</sup> , (as Sn) 8 hours. STEL: 0.2 mg/m <sup>3</sup> , (as Sn) 15 minutes. NIOSH REL (United States, 10/2020). [tin organic compounds] Absorbed through skin. TWA: 0.1 mg/m <sup>3</sup> , (as Sn) 10 hours. OSHA PEL (United States, 5/2018). [Tin, organic compounds] TWA: 0.1 mg/m <sup>3</sup> , (as Sn) 8 hours.

#### **Occupational exposure limits (Canada)**

Exposure limits		
itish Columbia Provincial (Canada, b). [Silica, Crystalline - alpha quartz ristobalite] c 0.025 mg/m <sup>3</sup> 8 hours. Form: able rebec Provincial (Canada, 7/2023). Crystalline -Quartz] EV: 0.1 mg/m <sup>3</sup> 8 hours. Form: able dust. Derta Provincial (Canada, 3/2023). 0.025 mg/m <sup>3</sup> 8 hours. Form: able particulate tario Provincial (Canada, 6/2019). , Crystalline (Quartz/Tripoli)] c 0.1 mg/m <sup>3</sup> 8 hours. Form: Respirable late matter. skatchewan Provincial (Canada, ). c 0.05 mg/m <sup>3</sup> 8 hours. Form: respirable		
perta Provincial (Canada, 3/2023).		
24 Version : 16.03 6/1 SHW-85-NA-GHS-CA		

## Section 8. Exposure controls/personal protection

[Tin Organic compounds] Absorbed
through skin.
OEL: 0.2 mg/m <sup>3</sup> , (as Sn) 15 minutes.
OEL: 0.1 mg/m <sup>3</sup> , (as Sn) 8 hours.
CA British Columbia Provincial (Canada,
8/2023). [Tin - Organic compounds]
Absorbed through skin.
TWA: 0.1 mg/m³, (as Sn) 8 hours.
STEL: 0.2 mg/m³, (as Sn) 15 minutes.
CA Quebec Provincial (Canada, 7/2023).
[Tin Organic compounds] Absorbed
through skin.
TWAEV: 0.1 mg/m³, (as Sn) 8 hours.
STEV: 0.2 mg/m <sup>3</sup> , (as Sn) 15 minutes.
CA Ontario Provincial (Canada, 6/2019).
[Tin (Organic compounds)] Absorbed
through skin.
TWA: 0.1 mg/m³, (as Sn) 8 hours.
CA Saskatchewan Provincial (Canada,
7/2013). [Tin organic compounds]
Absorbed through skin.
STEL: 0.2 mg/m³, (measured as Sn) 15
minutes.
TWA: 0.1 mg/m³, (measured as Sn) 8 hours.

#### **Occupational exposure limits (Mexico)**

Ingredient name	CAS #	Exposure limits
Dibutylbis(pentadionate)tin	22673-19-4	NOM-010-STPS-2014 (Mexico, 4/2016). [Estaño, compuestos orgánicos] Absorbed through skin. TWA: 0.1 mg/m³, (as Sn) 8 hours. STEL: 0.2 mg/m³, (as Sn) 15 minutes.

#### **Biological exposure indices (United States)**

No exposure indices known.

#### **Biological exposure indices (Canada)**

No exposure indices known.

#### **Biological exposure indices (Mexico)**

No exposure indices known.

Appropriate engineering controls	: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	: This product contains a component that is either subject to a CEPA ministerial condition or an existing/proposed SNAC (Significant New Activity).
	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

Date of issue/Date	e of revision	: 5/24/2024	Date of previous issue	: 5/20/2024	Version	:16.03	7/14
GC54102			er® Sealant		SHW-85-	NA-GHS-CA	

## Section 8. Exposure controls/personal protection

Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### **Appearance**

Physical state	: Liquid.
Color	: Gray.
Odor	: Not available.
Odor threshold	: Not available.
рН	: Not applicable.
Melting point/freezing point	: Not available.
Boiling point, initial boiling point, and boiling range	: Not available.
Flash point	: Closed cup: Not applicable.
Evaporation rate	: Not available.
Flammability	: Not available.
Lower and upper explosion limit/flammability limit	: Not available.
Vapor pressure	: Not available.
Relative vapor density	: Not available.
Relative density	: 1.59
Solubility(ies)	:

Date of issue/Date	of revision	: 5/24/2024	Date of previous issue	: 5/20/2024	Version	: 16.03
	Geocel® Pro™ Gutter S Aluminum Gray	eal Scypolymer	® Sealant		SHW-85-1	NA-GHS-CA

8/14

## **Section 9. Physical and chemical properties**

	Media cold water		Result	
			Not soluble	
Partition coefficient: n- : Not octanol/water		: Not	applicable.	
Αυ	Auto-ignition temperature : Not		available.	
De	Decomposition temperature : Not available.			
Vi	Viscosity : Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)			
Molecular weight : Not		: No	t applicable.	
Н	Heat of combustion : 10.095 kJ/g			

## Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

#### Information on toxicological effects

Acute toxicity				
	Δ		tox	icity.
		ulu	LUA	CILY

Product/ingredient name	Result	Species	Dose	Exposure
Aminoethylaminopropyltrimethoxysilane	LD50 Oral	Rat	2413 mg/kg	-

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Titanium Dioxide	Skin - Mild irritant	Human	-	72 hours 300 ug l	-
Aminoethylaminopropyltrimethoxysilane	Eyes - Severe irritant Skin - Mild irritant	Rabbit Rabbit	-	15 mg 500 mg	-

#### Sensitization

Not available.

#### **Mutagenicity**

Not available.

#### **Carcinogenicity**

Not available.

#### **Classification**

Date of issue/Date	of revision	: 5/24/2024	Date of previous issue	: 5/20/2024	Ve
GC54102	Geocel® Pro™ Gutter Aluminum Gray	Seal Scypolyme	r® Sealant		S

## Section 11. Toxicological information

	- <u>-</u>		
Product/ingredient name	OSHA	IARC	NTP
Titanium Dioxide Crystalline Silica, respirable powder	-+	2B 1	- Known to be a human carcinogen.

#### **Reproductive toxicity**

Not available.

#### Teratogenicity

Not available.

#### Specific target organ toxicity (single exposure)

Name	•••	Route of exposure	Target organs
Calcium Carbonate	Category 3		Respiratory tract irritation
Dibutylbis(pentadionate)tin	Category 1	-	-

#### Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
Aminoethylaminopropyltrimethoxysilane	Category 2	-	-
Crystalline Silica, respirable powder	Category 1	inhalation	-
Dibutylbis(pentadionate)tin	Category 1	-	immune system

#### Aspiration hazard

Not available.

### Information on the likely : Not available.

routes o	f exposure
----------	------------

Potential acute health effects

Eye contact	Causes serious eye irritation.
Inhalation	May cause respiratory irritation.
Skin contact	Causes skin irritation. May cause an allergic skin reaction.
Ingestion	No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	Adverse symptoms may include the following: respiratory tract irritation coughing reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations

Date of issue/Date	of revision	: 5/24/2024	Date of previous issue	: 5/20/2024	Version	:16.03	10/14
GC54102	Geocel® Pro™ Gutter S Aluminum Gray	Seal Scypolyme	r® Sealant		SHW-85-	NA-GHS-CA	

## Section 11. Toxicological information

Ingestion	: Adverse symptoms may include the following: reduced fetal weight
	increase in fetal deaths
	skeletal malformations
Delayed and immediate ef	fects and also chronic effects from short and long term exposure
Short term exposure	
Potential immediate	: Not available.
effects	
Potential delayed effects	: Not available.
<u>Long term exposure</u>	
Potential immediate	: Not available.
effects	
Potential delayed effects	: Not available.
Potential chronic health ef	ffects
Not available.	
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: May cause cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: May damage the unborn child.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: May damage fertility.

Numerical measures of toxicity Acute toxicity estimates Not available.

## Section 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
Titanium Dioxide	Acute LC50 >1000000 μg/l Marine water	Fish - Fundulus heteroclitus	96 hours

#### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

Not available.

#### Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Date of issue/Date	of revision	: 5/24/2024	Date of previous issue	: 5/20/2024	Version	:16.03	11/14
GC54102	Geocel® Pro™ Gutter S Aluminum Gray	Seal Scypolyme	r® Sealant		SHW-85-	NA-GHS-CA	

## Section 13. Disposal considerations

**Disposal methods** 

#### : This product contains a component that is either subject to a CEPA ministerial condition or an existing/proposed SNAC (Significant New Activity).

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

	•				
	DOT Classification	TDG Classification	Mexico Classification	ΙΑΤΑ	IMDG
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.
Additional information	-	-	-	-	-

Multi-modal shipping descriptions are provided for informational purposes and do not Special precautions for user : consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Transport in bulk according : Not available. to IMO instruments

**Proper shipping name** 

: Not available.

Date of issue/Date	of revision	: 5/24/2024	Date of previous issue	: 5/20/2024	Version	:16.03	12/14
GC54102	Geocel® Pro™ Gutter Aluminum Gray	Seal Scypolyme	er® Sealant		SHW-85-	NA-GHS-CA	

### Section 15. Regulatory information

This product contains a component that is either subject to a CEPA ministerial condition or an existing/proposed SNAC (Significant New Activity).

#### International regulations

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

International lists : Australia inventory (AIIC): Not determined. China inventory (IECSC): Not determined. Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined. Korea inventory (KECI): Not determined. New Zealand Inventory of Chemicals (NZIoC): Not determined. Philippines inventory (PICCS): Not determined. Taiwan Chemical Substances Inventory (TCSI): Not determined. Thailand inventory: Not determined. Turkey inventory: Not determined. Vietnam inventory: Not determined.

### Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

	Justification			
SKIN SENSITIZATION - C CARCINOGENICITY - Cat TOXIC TO REPRODUCTION	EYE IRRITATION - Category 2A ategory 1 egory 1A	Calculation method Calculation method Calculation method Calculation method Calculation method Calculation method		
History Data of printing	: 5/24/2024			
Date of printing Date of issue/Date of revision	: 5/24/2024			
Date of previous issue	of previous issue : 5/20/2024			
Version	: 16.03			

Date of issue/Date of revision		: 5/24/2024	Date of previous issue	: 5/20/2024	Version	:16.03	13/14
GC54102	Geocel® Pro™ Gutter S Aluminum Gray	Seal Scypolyme	r® Sealant		SHW-85-	NA-GHS-CA	

## Section 16. Other information

Key to abbreviations	: ATE = Acute Toxicity Estimate
	BCF = Bioconcentration Factor
	GHS = Globally Harmonized System of Classification and Labelling of Chemicals
	IATA = International Air Transport Association
	IBC = Intermediate Bulk Container
	IMDG = International Maritime Dangerous Goods
	LogPow = logarithm of the octanol/water partition coefficient
	MARPOL = International Convention for the Prevention of Pollution From Ships, 1973
	as modified by the Protocol of 1978. ("Marpol" = marine pollution)
	N/A = Not available
	SGG = Segregation Group
	UN = United Nations

Indicates information that has changed from previously issued version.

#### Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.