



**1. PRODUCT NAME:**

Instant Gutter Seal Gutter and Narrow Seam Sealant

**2. MANUFACTURER:**

Geocel Products Group A Business Unit of The Sherwin-Williams Company (“Geocel Products Group”) Cleveland, OH 44115  
Phone: (800) 348-7615  
Fax: (800) 348-7009  
www.GeocelUSA.com

**3. PRODUCT DESCRIPTION:**

Instant Gutter and Narrow Seam Sealant is a single component, semi-self-leveling, high-performance tripolymer sealant designed to prevent the passage of air and moisture through small joints or seams.

**Product Benefits:**

- Excellent adhesion to many building surfaces, even when damp or oily
- UV resistant
- Paintable
- Semi-self-leveling
- Cleans up easily
- Asphalt shingle component

**Basic Uses:** For sealing aluminum, galvanized and vinyl-clad gutters, end caps, and downspouts. It is also recommended for lap joints, storm windows, metal awnings, vents, flashing, side corner joints, and thresholds when a small joint sealant is required.

**Adheres to:** Aluminum, Kynar 500®, concrete, galvanized steel, wood, and other common building substrates.

**Primer:** Not required on most surfaces. If primerless adhesion to a particular surface substrate is a question, a test application is recommended. Contact our Technical Service Department for further information.

**Packaging:** 5 fl. oz. squeeze tube and 10 fl. oz. cartridge.

**Colors:** White, aluminum, gray, and clear

**Limitations:**

- Do not use on joints larger than 1/4" x 1/4".
- Do not use on traffic-bearing surfaces.
- Do not use in contact with Styrofoam®

Kynar 500® is a registered trade mark of Arkema Inc.

**4. INSTALLATION:**

**Surface Preparation:** For best results, Instant Gutter Seal should be applied to a clean, dry surface which is free of foreign matter. When resealing over old existing sealant, remove sealant before applying Instant Gutter Seal.

**Elongation:** 900%

**Tack Free:** 15 minutes

**Cure:** 5 days

**Application Temperature:** 0° F to 140° F. -18° C to 60° C

**Application and Tooling:** Instant Gutter Seal may be applied at any working temperature. When temperature is below 40° F (4° C), application of sealant will be easier if sealant is warmed. Level or remove excess sealant with wet tooling stick or knife.

To seal gutter lap joints, apply bead of sealant along inside edge of all joints and around rivets. When rivets are not used on lap joints, apply adequate sealant between 4" overlap to ensure full contact between both surfaces.

To seal gutter end caps and slip joints, apply liberal amounts of sealant to these surfaces before the use of rivets.

**Painting:** Instant Gutter Seal may be painted in 24 hours with latex or most oil-based paints.

**Cleaning:** Remove Instant Gutter Seal from gun and tools before it cures. This may be done by scraping and use of solvents such as MEK (lacquer thinner), xylene, Toluol or chlorinated solvents. Observe manufacturer's precautions when using toxic or flammable solvents. Cured materials may be removed by cutting with sharp tools.

**Storage Life:** One year

**Cautions:** CONTAINS VOLATILE ORGANIC COMPOUNDS. VAPOR HARMFUL Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NOISH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

**First Aid:** In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.** Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure.

**Warning:** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN**

**5. AVAILABILITY AND COST:** May not be sold in the State of California. Available from lumber yards, hardware stores, and home centers. Cost and further technical data are available from your local Geocel Products Group representative or from our offices.

**6. LIMITED WARRANTY:** If when applied according to label directions this product fails to perform in accordance with its published literature, upon satisfactory evidence of product failure, and as your sole remedy, we will either replace the product at no cost or refund the original purchase price for that portion of product that fails to perform in accordance with this limited warranty.

Labor or costs associated with labor are not included. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, WHICH ARE ALL DISCLAIMED AND/OR LIMITED IN DURATION TO THE EXTENT PERMITTED BY LAW. WE SHALL NOT BE LIABLE FOR INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES (INCLUDING LOST PROFITS) FROM ANY CAUSE WHATSOEVER AND SUCH DAMAGES ARE EXPRESSLY EXCLUDED. Some states do not allow the exclusion or limitation of incidental or consequential damages or how long an implied warranty lasts, so the above limitation or exclusion may not apply to you. This limited warranty gives you specific legal rights, and you may also have other rights which vary from state to state

## **7. MAINTENANCE:**

No maintenance should be required. If the sealant is damaged, either remove the bead and reseal, or apply additional sealant over the damaged area.

## **8. TECHNICAL SERVICES:**

Geocel Products Group representatives throughout the U.S. are available to provide technical assistance. Our in-house technical staff and laboratory facilities are equipped to respond to specific requests for further information.

### **THEORETICAL YIELD**

#### **Per 5 fl. oz. Squeeze Tube**

Joint Size	Linear Feet
1/4" x 1/4"	12

#### **Per 10 fl. oz. Cartridge**

Joint Size	Linear Feet
1/4" x 1/4"	24.1

For additional product information, refer to the product spec sheet located at [www.GeocelUSA.com](http://www.GeocelUSA.com) and/or application testing.