



H&C® CONCRETEREADY® CONCENTRATED CLEANER/DEGREASER



PRODUCT DESCRIPTION

H&C® CONCRETEREADY® Concentrated Cleaner/Degreaser is a concentrated heavy-duty cleaner that will remove most automotive fluids (oil, grease, brake fluid, transmission fluid, gear fluid and antifreeze) from concrete and masonry surfaces. Its primary use is to degrease and prepare concrete, block, rick, and masonry prior to applying H&C® COLORTOP™ Water or Solvent- Based Concrete Stains or Sealers and other coatings.

FEATURES & BENEFITS

- Removes grease and oil stains
- Prepares surfaces for paints, stains, and sealers
- Increases any coating's ability to bond with the surface by providing a clean substrate

RECOMMENDED USES

H&C CONCRETEREADY Concentrated Cleaner/Degreaser is formulated for use on concrete and masonry surfaces including Stadium Supports, Bridges and Bridge Structures, Parking Garages, Pavers, Patios and Walkways, Pool Decks, Concrete Driveways, Garage Floors, Block & stucco walls, Athletic courts and other concrete surfaces.

COVERAGE RATES

Coverage: 100 sq. ft. per gallon at 50/50 dilution. Coverage will vary depending on the texture and porosity of the surface.

JOBSITE TEST SECTION

Due to the wide variety of substrates, preparation methods, application methods and environments, it is important to create a test sample.

LIMITATIONS

H&C CONCRETEREADY Concentrated Cleaner/Degreaser is not recommended for asphalt.

TOOLS REQUIRED

- Stiff broom
- Garden hose with a pressure washer nozzle
- Bucket
- Eye Protection
- Respiratory Protection
- Gloves

INSTRUCTIONS

Mixing Instructions: H&C CONCRETEREADY Concentrated Cleaner/Degreaser is highly concentrated. For best results, dilute with hot water. This will improve the product's effectiveness and reduce clean-up time. Dilute product based on the condition of the surface to be cleaned. For light to moderately soiled surfaces dilute 64 oz. (1/2 gal.) of H&C CONCRETEREADY Degreaser with 64 oz. (1/2 gal.) of water. For more heavily soiled areas, use product at full strength.

Application Method:

Sweep away loose dirt and scrape off excess grease and oil Dilute solution according to surface condition. Sprinkle solution onto surface in 10'x10' sections (a standard garden sprinkling can works well)

Allow to penetrate for 5-6 minutes. Scrub the entire concrete surface with a stiff bristle broom or deck brush. Thoroughly rinse the surface using clean water and a garden hose. After the surface has dried, check for any trouble spots (glossy, oily, etc.) by applying a few drops of water. (If the water does not penetrate quickly, repeat the application over these spots.)

Thoroughly rinse H&C CONCRETEREADY Etching Solution off of the Allow surface to dry completely (18-24 hours recommended) before applying any stains or sealers.

PHYSICAL PROPERTIES

Physical Properties and Characteristics		
Property	Test Method	Value
VOC	EPA Method 24	0 g/L
Boiling Point		215-405°F
Flash Point		141°F
Weight per Gallon	ASTM D1475	7.59 lb ± 2%

ORDERING INFORMATION

Clear	Part Number/SMIS
1/2 Gallon	50.170015-15/6507-12318

CAUTIONS

CAUTIONS CONTAINS ALIPHATIC HYDROCARBONS, BUTOXYPROPANOL. Contents are COMBUSTIBLE. Keep away from heat and open flame. VAPOR HARMFUL. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

FIRST AID: In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician. If swallowed do not induce vomiting. Call Poison Control Center, hospital emergency room, or physician immediately. **DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.** Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

LIMITED WARRANTY

Seller's and manufacturers only obligations shall be to replace such quantity of product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising from the applicator's inability to use the product for his/her intended use. The user assumes all risk and liability.

TECHNICAL SERVICES

The information and recommendations set forth in this product data sheet are based on tests conducted by or on behalf of H&C Products Group and The Sherwin-Williams® Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your H&C or Sherwin-Williams representative to obtain the most recent product data sheet.

For technical assistance, call 1-800-867-8246 or visit www.hcconcrete.com.