



KRYLON® HIGH HEAT™ AEROSOL

Heat resistant up to 600°F.

PRODUCT DESCRIPTION	APPLICATION	CAUTIONS
Restores the finish on grills and wood-burning stoves; protects against rust. Paint withstands temperatures up to 600°F. Not for use on kitchen stoves; DO NOT USE ON SURFACES DIRECTLY EXPOSED TO FLAMES.	Shake can for 1–2 minutes and during use. Test an inconspicuous area first. Hold can 10"–12" from surface, spray in sweeping motion from side to side with slight overlap. Apply multiple thin coats to avoid runs and drips.	CONTAINS KETONES, TOLUENE and XYLENE. DANGER! EXTREMELY FLAMMABLE. Keep away from heat, sparks and open flame. Vapors will accumulate readily and may ignite explosively. Keep area ventilated during use and until all vapors are gone. DO NOT SMOKE — Extinguish all flames, pilot lights and heaters — Turn off stoves, electric tools and appliances, and any other sources of ignition. CONTENTS UNDER PRESSURE. Avoid prolonged exposure to sunlight or heat from radiators, stoves, hot water and other heat sources that may cause bursting. Do not puncture, incinerate, burn or store above 120°F. Keep upright in a cool, dry place. Do not discard empty can in trash compactor. VAPOR HARMFUL. Use with adequate ventilation. Avoid continuous breathing of vapor and spray mist. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician. DELAYED EFFECTS FROM LONG-TERM OVEREXPOSURE. Contains solvents that can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.
PAINTING CONDITIONS		
Use outdoors or in a well-ventilated area. For best results, use when air and surface temperatures are 55°F (12°C)-75°F (24°C) and humidity is below 60%.		
	CHARACTERISTICS	
	Colors: Available In 5 Colors.	
	Coverage: Estimated 25 Square Feet on a solid non-porous surface.	
	Drying Time, @ 77°F, 50% RH: <i>Drying time and recoat times are temperature, humidity, and film thickness dependent.</i>	
	Touch: 15 Minutes or Less To Handle: 1 Hour Recoat: Any time.	
	Net Wt.: 12 oz. / 340g	
	Volume Solids: 3-14%	
	Weight Solids: 7 - 25%	
SURFACE PREPARATION		PERFORMANCE TESTING
WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead . Surface should be clean, dull and dry. Remove loose paint, rust, dirt, grease and oil. To improve adhesion, sand glossy or rough surfaces until smooth.		Technical data furnished herein is accurate and true to the best of our knowledge. However, no guarantee of accuracy is expressed or implied. We assume no responsibility or liability as a result of purchase, coverage, application or injuries resulting in misuse. To contact us call 1-800-247-3268 or ask@krylon.com.