

# ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation

May 3, 2025

09 00 [1235]

## PRODUCT NUMBER

B37579

## PRODUCT NAME

CODA™ Interior 2K Hybrid Polyurethane, Black Primer

## MANUFACTURER'S NAME

M. L. CAMPBELL

101 W. Prospect Avenue

Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED and rely on information provided to us by our raw material suppliers. Our suppliers often provide an estimated value or range less than a certain upper limit. We calculate MAXIMUM THEORETICAL VALUES using defined values, if provided, or the upper limit reported by our supplier. Additionally, the suppliers' information may include amounts present in the product as unintentional byproducts or impurities. Variations may occur in individual batches due to adjustments made during production.

## Hazard Category (for SARA 311.312)

B37579 = | Acute | Chronic | Fire | Pressure |

## Product Weight

9.12 lb/gal

## Specific Gravity

1.10

## FLASH POINT

24 °F PMCC

## Volatile Ingredients

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Diacetone Alcohol 123-42-2	N	N	N	N	2	2
Methyl Ethyl Ketone 78-93-3	N	Y	N	N	7	10
n-Butyl Acetate 123-86-4	N	Y	N	N	35	44
1-Methoxy-2-Propanol Acetate 108-65-6	N	N	N	N	4	4

## Regulated Compounds

	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Mercury (as Hg)	N	N	Y	N	0.000002	
Lead (as Pb)	N	N	Y	N	0.00002	
Zinc Compound	N	N	Y	N	2	

**Volatile Organic Compounds - U.S. EPA / Canada**

	B37579	
	LB/Gal	g/L
Coating Density	9.12	1092
	By wt	By vol
Total Volatiles	50.6%	63.2%
Federally exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	50.6%	63.2%
Percent Non-Volatile	49.4%	36.8%
VOC Content	LB/Gal	g/L
Total	4.61	552
Less exempt solvents	4.61	552
Of solids	12.52	1500
Of solids	1.02 lb/lb	1.02 kg/kg
	By wt	
By wt LVP-VOC	50.4%	

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) **0.57**

**Volatile Organic Compounds - California**

	B37579	
	LB/Gal	g/L
Coating Density	9.12	1092
	By wt	By vol
Total Volatiles	50.6%	63.2%
Exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	50.6%	63.2%
Percent Non-Volatile	49.4%	36.8%
VOC Content	LB/Gal	g/L
Total	4.61	552
Less exempt solvents	4.61	552
Of solids	12.52	1500
Of solids	1.02 lb/lb	1.02 kg/kg
	By wt	
By wt LVP-VOC	50.4%	

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) **0.54**

**Volatile Organic Compounds - South Coast Air Quality Management District, California, US**

	B37579	
	LB/Gal	g/L
Coating Density	9.12	1092
	By wt	By vol
Total Volatiles	50.6%	63.2%
Exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	50.6%	63.2%
Percent Non-Volatile	49.4%	36.8%
VOC Content	LB/Gal	g/L
Total	4.61	552
Less exempt solvents	4.61	552
Of solids	12.52	1500
Of solids	1.02 lb/lb	1.02 kg/kg

**Volatile Organic Compounds - EU Directive 2004/42/EC**

	B37579	
	By wt	By vol
Total Volatiles	50.6%	63.2%
VOC Content	LB/Gal	g/L
Total	4.61	552

**Volatile Organic Compounds - EU Directive 2010/75/EU**

	B37579	
	By wt	By vol
Total Volatiles	50.6%	63.1%
VOC Content	LB/Gal	g/L
Total	4.61	552

**Volatile Organic Compounds - Mexico**

	B37579	
	LB/Gal	g/L
Coating Density	9.12	1092
	By wt	By vol
Total Volatiles	50.6%	63.2%
Exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	50.6%	63.2%
Percent Non-Volatile	49.4%	36.8%
VOC Content	LB/Gal	g/L
Total	4.61	552
Less exempt solvents	4.61	552
Of solids	12.52	1500
Of solids	1.02 lb/lb	1.02 kg/kg

**Hazardous Air Pollutants (Clean Air Act, Section 112(b))**

	B37579	
	LB/Gal	kg/L
Volatile HAPS	0.00	0.000
Of solids	0.00	0.000
Of solids	0.00 lb/lb	0.00 kg/kg

**Air Quality Data****Density of Organic Solvent Blend**

7.31 lb/gal

**Photochemically Reactive**

No

**Waste Disposal**

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

The addition of any material to this product can change the composition, hazards and risks of the product and may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.