ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

14 00 [1235]

Date of Preparation May 3, 2025

PRODUCT NUMBER

C35572

PRODUCT NAME

POLARION® Interior 2K Acrylic Polyurethane, Dull

MANUFACTURER'S NAME

M. L. CAMPBELL

101 W. Prospect Avenue Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED and rely on information provided to us by our raw material suppliers. Our suppliers often provide an estimated value or range less than a certain upper limit. We calculate MAXIMUM THEORETICAL VALUES using defined values, if provided, or the upper limit reported by our supplier. Additionally, the suppliers' information may include amounts present in the product as unintentional byproducts or impurities. Variations may occur in individual batches due to adjustments made during production.

Hazard Category (for SARA 311.312)

C35572 = | Acute | Chronic | Fire |

Product Weight 7.93 lb/gal	Specific Gravity 0.95			FLASH POINT 29 °F PMCC		
Volatile Ingredients						
Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Ethylbenzene 100-41-4	N	Y	Y	Υ	0.2	0.2
Light Aromatic Hydrocarbons 64742-95-6	N	N	N	Ν	2	2
Methyl n-Amyl Ketone 110-43-0	N	N	N	Ν	30	35
n-Butyl Propionate 590-01-2	N	N	N	Ν	7	7
n-Butyl Acetate 123-86-4	N	Y	N	Ν	22	24

Regulated Compounds

	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Mercury (as Hg)	N	Ν	Y	Ν	0.000004	
Lead (as Pb)	Ν	Ν	Y	Ν	0.0000003	

Volatile Organic Compounds - U.S. EPA / Canada

	C35572		
	LB/Gal	g/L	
Coating Density	7.93	950	
	By wt	By vol	
Total Volatiles	64.0%	72.1%	
Federally exempt solvents			
Water	0.1%	0.1%	
Organic Volatiles	64.0%	72.0%	
Percent Non-Volatile	36.0%	27.9%	
VOC Content	LB/Gal	g/L	
Total	5.07	608	
Less exempt solvents	5.07	608	
Of solids	18.18	2179	
Of solids	1.77 lb/lb	1.77 kg/kg	
	By wt		
By wt LVP-VOC	63.8%		

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) 1.37

Volatile Organic Compounds - California

	C35572		
	LB/Gal	g/L	
Coating Density	7.93	950	
	By wt	By vol	
Total Volatiles	64.0%	72.1%	
Exempt solvents			
Water	0.1%	0.1%	
Organic Volatiles	64.0%	72.0%	
Percent Non-Volatile	36.0%	27.9%	
VOC Content	LB/Gal	g/L	
Total	5.07	608	
Less exempt solvents	5.07	608	
Of solids	18.18	2179	
Of solids	1.77 lb/lb	1.77 kg/kg	
	By wt		
By wt LVP-VOC	63.8%		

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) 1.21

Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	C35572		
	LB/Gal	g/L	
Coating Density	7.93	950	
	By wt	By vol	
Total Volatiles	64.0%	72.1%	
Exempt solvents			
Water	0.1%	0.1%	
Organic Volatiles	64.0%	72.0%	
Percent Non-Volatile	36.0%	27.9%	
VOC Content	LB/Gal	g/L	
Total	5.07	608	
Less exempt solvents	5.07	608	
Of solids	18.18	2179	
Of solids	1.77 lb/lb	1.77 kg/kg	

Volatile Organic Compounds - EU Directive 2004/42/EC

	C35572		
	By wt	By vol	
Total Volatiles	64.0%	72.1%	
VOC Content	LB/Gal	g/L	
Total	5.07	608	

Volatile Organic Compounds - EU Directive 2010/75/EU

	C35572		
	By wt	By vol	
Total Volatiles	64.0%	72.1%	
VOC Content	LB/Gal	g/L	
Total	5.07	608	

Volatile Organic Compounds - Mexico

	C35572		
	LB/Gal	g/L	
Coating Density	7.93	950	
	By wt	By vol	
Total Volatiles	64.0%	72.1%	
Exempt solvents			
Water	0.1%	0.1%	
Organic Volatiles	64.0%	72.0%	
Percent Non-Volatile	36.0%	27.9%	
VOC Content	LB/Gal	g/L	
Total	5.07	608	
Less exempt solvents	5.07	608	
Of solids	18.18	2179	
Of solids	1.77 lb/lb	1.77 kg/kg	

Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	C35572		
	LB/Gal	kg/L	
Volatile HAPS	0.01	0.001	
Of solids	0.04	0.005	
Of solids	0.00 lb/lb	0.00 kg/kg	

Air Quality Data

Density of Organic Solvent Blend 7.05 lb/gal Photochemically Reactive No

Waste Disposal

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

The addition of any material to this product can change the composition, hazards and risks of the product and may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.