ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation

Oct 11, 2025

16 00 [3394]

PRODUCT NUMBER

V41121

PRODUCT NAME

TURINO™ Conversion Varnish Clear Tint Base, Flat Sheen

MANUFACTURER'S NAME

M. L. CAMPBELL 101 W. Prospect Avenue Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED and rely on information provided to us by our raw material suppliers. Our suppliers often provide an estimated value or range less than a certain upper limit. We calculate MAXIMUM THEORETICAL VALUES using defined values, if provided, or the upper limit reported by our supplier. Additionally, the suppliers' information may include amounts present in the product as unintentional byproducts or impurities. Variations may occur in individual batches due to adjustments made during production.

Hazard Category (for SARA 311.312)

V41121 = | Acute | Chronic | Fire |

Product WeightSpecific GravityFLASH POINT8.04 lb/gal0.9725 °F PMCC

Volatile Ingredients

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Polycyclic Aromatic Compounds Proprietary	N	N	Υ	N	0.0005	0.0005
Toluene 108-88-3	N	Υ	Υ	Υ	3	4
Ethanol 64-17-5	N	N	N	N	3	4
2-Propanol 67-63-0	N	N	N	N	4	5
2-Methyl-1-propanol 78-83-1	N	Υ	N	N	6	6
Acetone 67-64-1	N	Υ	N	N	6	7
Methyl n-Amyl Ketone 110-43-0	N	N	N	N	2	3
Ethyl Acetate 141-78-6	N	Υ	N	N	6	6
n-Butyl Acetate 123-86-4	N	Υ	N	N	22	24

Volatile Organic Compounds - U.S. EPA / Canada

	V41121	
	LB/Gal	g/L
Coating Density	8.04	963
	By wt	By vol
Total Volatiles	54.1%	61.1%
Federally exempt solvents		
Water	0.0%	0.0%
Acetone	6.0%	7.3%
Organic Volatiles	48.1%	53.8%
Percent Non-Volatile	45.9%	38.9%
VOC Content	LB/Gal	g/L
Total	3.86	462
Less exempt solvents	4.16	499
Of solids	9.92	1189
Of solids	1.04 lb/lb	1.04 kg/kg
	By wt	
By wt LVP-VOC	48.1%	

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) 0.75

Volatile Organic Compounds - California

	V41121		
	LB/Gal	g/L	
Coating Density	8.04	963	
	By wt	By vol	
Total Volatiles	54.1%	61.1%	
Exempt solvents			
Water	0.0%	0.0%	
Acetone	6.0%	7.3%	
Organic Volatiles	48.1%	53.8%	
Percent Non-Volatile	45.9%	38.9%	
VOC Content	LB/Gal	g/L	
Total	3.86	462	
Less exempt solvents	4.16	499	
Of solids	9.92	1189	
Of solids	1.04 lb/lb	1.04 kg/kg	
	By wt		
By wt LVP-VOC	48.1%	_	

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) 0.73

Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	V41121	
	LB/Gal	g/L
Coating Density	8.04	963
	By wt	By vol
Total Volatiles	54.1%	61.1%
Exempt solvents		
Water	0.0%	0.0%
Acetone	6.0%	7.3%
Organic Volatiles	48.1%	53.8%
Percent Non-Volatile	45.9%	38.9%
VOC Content	LB/Gal	g/L
Total	3.86	462
Less exempt solvents	4.16	499
Of solids	9.92	1189
Of solids	1.04 lb/lb	1.04 kg/kg

Volatile Organic Compounds - EU Directive 2004/42/EC

	V41121	
	By wt	By vol
Total Volatiles	54.1%	61.1%
VOC Content	LB/Gal	g/L
Total	4.34	520

Volatile Organic Compounds - EU Directive 2010/75/EU

	V41121	
	By wt	By vol
Total Volatiles	54.1%	61.1%
VOC Content	LB/Gal	g/L
Total	4.34	520

Volatile Organic Compounds - Mexico

	V41121		
	LB/Gal	g/L	
Coating Density	8.04	963	
	By wt	By vol	
Total Volatiles	54.1%	61.1%	
Exempt solvents			
Water	0.0%	0.0%	
Acetone	6.0%	7.3%	
Organic Volatiles	48.1%	53.8%	
Percent Non-Volatile	45.9%	38.9%	
VOC Content	LB/Gal	g/L	
Total	3.86	462	
Less exempt solvents	4.16	499	
Of solids	9.92	1189	
Of solids	1.04 lb/lb	1.04 kg/kg	

Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	V41121	
	LB/Gal	kg/L
Volatile HAPS	0.25	0.031
Of solids	0.66	0.079
Of solids	0.07 lb/lb	0.07 kg/kg

Air Quality Data

Density of Organic Solvent Blend

7.11 lb/gal

Photochemically Reactive

No

Waste Disposal

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability and extractability to determine the applicable EPA hazardous waste numbers.

The addition of any material to this product can change the composition, hazards and risks of the product and may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.