### **ENVIRONMENTAL DATA SHEET**

(Certified Product Data Sheet)

**Date of Preparation** 

Feb 24, 2024

14 00 [0554]

### **PRODUCT NUMBER**

V41128

#### PRODUCT NAME

TURINO™ Conversion Varnish Clear Tint Base, Gloss Sheen

#### **MANUFACTURER'S NAME**

M. L. CAMPBELL 101 W. Prospect Avenue Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

#### Hazard Category (for SARA 311.312)

V41128 = | Acute | Chronic | Fire |

Product WeightSpecific GravityFLASH POINT7.95 lb/gal0.9625 °F PMCC

#### **Volatile Ingredients**

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	<b>HAPS 112</b>	% by Weight	% by Volume
Toluene 108-88-3	N	Υ	Υ	Υ	3	4
Ethanol 64-17-5	N	N	N	N	4	4
2-Propanol 67-63-0	N	N	N	N	4	5
2-Methyl-1-propanol 78-83-1	N	Υ	N	N	6	7
Acetone 67-64-1	N	Υ	N	N	6	8
Methyl n-Amyl Ketone 110-43-0	N	N	N	N	2	3
Ethyl Acetate 141-78-6	N	Υ	N	N	6	6
n-Butyl Acetate 123-86-4	N	Υ	N	N	23	25

# Volatile Organic Compounds - U.S. EPA / Canada

	V41128	
	LB/Gal	g/L
Coating Density	7.95	952
	By wt	By vol
Total Volatiles	56.4%	63.6%
Federally exempt solvents		
Water	0.0%	0.0%
Acetone	6.2%	7.5%
Organic Volatiles	50.1%	56.1%
Percent Non-Volatile	43.6%	36.4%
VOC Content	LB/Gal	g/L
Total	3.98	477
Less exempt solvents	4.30	516
Of solids	10.94	1311
Of solids	1.14 lb/lb	1.14 kg/kg
	By wt	
By wt LVP-VOC	50.1%	

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) 0.76

# Volatile Organic Compounds - California

	V41128	
	LB/Gal	g/L
Coating Density	7.95	952
	By wt	By vol
Total Volatiles	56.4%	63.6%
Exempt solvents		
Water	0.0%	0.0%
Acetone	6.2%	7.5%
Organic Volatiles	50.1%	56.1%
Percent Non-Volatile	43.6%	36.4%
VOC Content	LB/Gal	g/L
Total	3.98	477
Less exempt solvents	4.30	516
Of solids	10.94	1311
Of solids	1.14 lb/lb	1.14 kg/kg
	By wt	
By wt LVP-VOC	50.1%	

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) 0.74

# Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	V41128	
	LB/Gal	g/L
Coating Density	7.95	952
	By wt	By vol
Total Volatiles	56.4%	63.6%
Exempt solvents		
Water	0.0%	0.0%
Acetone	6.2%	7.5%
Organic Volatiles	50.1%	56.1%
Percent Non-Volatile	43.6%	36.4%
VOC Content	LB/Gal	g/L
Total	3.98	477
Less exempt solvents	4.30	516
Of solids	10.94	1311
Of solids	1.14 lb/lb	1.14 kg/kg

# Volatile Organic Compounds - EU Directive 2004/42/EC

	V41128	
	By wt	By vol
Total Volatiles	56.4%	63.6%
VOC Content	LB/Gal	g/L
Total	4.47	536

## Volatile Organic Compounds - EU Directive 2010/75/EU

	V41128	
	By wt	By vol
Total Volatiles	56.4%	63.6%
VOC Content	LB/Gal	g/L
Total	4.47	536

# **Volatile Organic Compounds - Mexico**

	V41128		
	LB/Gal	g/L	
Coating Density	7.95	952	
	By wt	By vol	
Total Volatiles	56.4%	63.6%	
Exempt solvents			
Water	0.0%	0.0%	
Acetone	6.2%	7.5%	
Organic Volatiles	50.1%	56.1%	
Percent Non-Volatile	43.6%	36.4%	
VOC Content	LB/Gal	g/L	
Total	3.98	477	
Less exempt solvents	4.30	516	
Of solids	10.94	1311	
Of solids	1.14 lb/lb	1.14 kg/kg	

### Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	V41128	
	LB/Gal	kg/L
Volatile HAPS	0.26	0.031
Of solids	0.73	0.087
Of solids	0.07 lb/lb	0.07 kg/kg

### **Air Quality Data**

**Density of Organic Solvent Blend** 

7.04 lb/gal

**Photochemically Reactive** 

No

### **Waste Disposal**

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Addition of reducers or other additives to this product may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.