ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation
Dec 11, 2025

19 00 [3445]

PRODUCT NUMBER

C133724

PRODUCT NAME

KRYSTAL® SL High-Solids Conversion Varnish, Satin

MANUFACTURER'S NAME

M. L. CAMPBELL
101 W. Prospect Avenue
Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED and rely on information provided to us by our raw material suppliers. Our suppliers often provide an estimated value or range less than a certain upper limit. We calculate MAXIMUM THEORETICAL VALUES using defined values, if provided, or the upper limit reported by our supplier. Additionally, the suppliers' information may include amounts present in the product as unintentional byproducts or impurities. Variations may occur in individual batches due to adjustments made during production.

Hazard Category (for SARA 311.312)

C133724 = | Acute | Chronic | Fire |

Product Weight	Specific Gravity	FLASH POINT
7.80 lb/gal	0.94	7 °F PMCC

Volatile Ingredients

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Ethylbenzene **100-41-4**	N	Y	Y	Y	0.2	0.2
p-Chlorobenzotrifluoride **98-56-6**	N	N	N	N	9	6
1-Butanol **71-36-3**	N	Y	Y	N	4	5
2-Methyl-1-propanol **78-83-1**	N	Y	N	N	2	2
Acetone **67-64-1**	N	Y	N	N	44	52
n-Butyl Acetate **123-86-4**	N	Y	N	N	1	1

Volatile Organic Compounds - U.S. EPA / Canada

	C133724	
	LB/Gal	g/L
Coating Density	7.80	934
	By wt	By vol
Total Volatiles	63.0%	69.8%
Federally exempt solvents		
Water	0.1%	0.0%
Acetone	43.6%	51.7%
P-Chlorobenzotrifluoride	8.9%	6.2%
Organic Volatiles	10.4%	11.9%
Percent Non-Volatile	37.0%	30.2%
VOC Content	LB/Gal	g/L
Total	0.80	97
Less exempt solvents	1.92	230
Of solids	2.68	321
Of solids	0.28 lb/lb	0.28 kg/kg
	By wt	
By wt LVP-VOC	10.3%	

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) **0.50**

Volatile Organic Compounds - California

	C133724	
	LB/Gal	g/L
Coating Density	7.80	934
	By wt	By vol
Total Volatiles	63.0%	69.8%
Exempt solvents		
Water	0.1%	0.0%
Acetone	43.6%	51.7%
P-Chlorobenzotrifluoride	8.9%	6.2%
Organic Volatiles	10.4%	11.9%
Percent Non-Volatile	37.0%	30.2%
VOC Content	LB/Gal	g/L
Total	0.80	97
Less exempt solvents	1.92	230
Of solids	2.68	321
Of solids	0.28 lb/lb	0.28 kg/kg
	By wt	
By wt LVP-VOC	10.3%	

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) **0.46**

Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	C133724	
	LB/Gal	g/L
Coating Density	7.80	934
	By wt	By vol
Total Volatiles	63.0%	69.8%
Exempt solvents		
Water	0.1%	0.0%
Acetone	43.6%	51.7%
P-Chlorobenzotrifluoride	8.9%	6.2%
Organic Volatiles	10.4%	11.9%
Percent Non-Volatile	37.0%	30.2%
VOC Content	LB/Gal	g/L
Total	0.80	97
Less exempt solvents	1.92	230
Of solids	2.68	321
Of solids	0.28 lb/lb	0.28 kg/kg

Volatile Organic Compounds - EU Directive 2004/42/EC

	C133724	
	By wt	By vol
Total Volatiles	63.0%	69.8%
VOC Content	LB/Gal	g/L
Total	4.90	588

Volatile Organic Compounds - EU Directive 2010/75/EU

	C133724	
	By wt	By vol
Total Volatiles	63.0%	69.8%
VOC Content	LB/Gal	g/L
Total	4.90	588

Volatile Organic Compounds - Mexico

	C133724	
	LB/Gal	g/L
Coating Density	7.80	934
	By wt	By vol
Total Volatiles	63.0%	69.8%
Exempt solvents		
Water	0.1%	0.0%
Acetone	43.6%	51.7%
Organic Volatiles	19.3%	18.1%
Percent Non-Volatile	37.0%	30.2%
VOC Content	LB/Gal	g/L
Total	1.50	180
Less exempt solvents	3.11	373
Of solids	4.98	597
Of solids	0.52 lb/lb	0.52 kg/kg

Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	C133724	
	LB/Gal	kg/L
Volatile HAPS	0.01	0.001
Of solids	0.04	0.005
Of solids	0.00 lb/lb	0.00 kg/kg

Air Quality Data

Density of Organic Solvent Blend

7.03 lb/gal

Photochemically Reactive

No

Waste Disposal

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.
Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.