ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation

Feb 24, 2024

49 00 [0554]

PRODUCT NUMBER

MC14812SF

PRODUCT NAME

MAGNAMAX™ Precatalyzed Lacquer, Clear Tint Base Dull

MANUFACTURER'S NAME

M. L. CAMPBELL 101 W. Prospect Avenue Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

Hazard Category (for SARA 311.312)

MC14812SF = | Acute | Chronic | Fire |

Product WeightSpecific GravityFLASH POINT7.96 lb/gal0.9648 °F PMCC

Volatile Ingredients

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Ethanol 64-17-5	N	N	N	N	8	10
2-Propanol 67-63-0	N	N	N	N	7	8
1-Butanol 71-36-3	N	Υ	Υ	N	5	6
2-Methyl-1-propanol 78-83-1	N	Υ	N	N	2	2
Acetone 67-64-1	N	Υ	N	N	2	2
Ethyl Acetate 141-78-6	N	Υ	N	N	5	5
n-Butyl Acetate 123-86-4	N	Υ	N	N	34	37
1-Methoxy-2-Propanol Acetate 108-65-6	N	N	N	N	3	3

Volatile Organic Compounds - U.S. EPA / Canada

	MC14812SF		
	LB/Gal	g/L	
Coating Density	7.96	954	
	By wt	By vol	
Total Volatiles	67.0%	75.1%	
Federally exempt solvents			
Water	0.0%	0.0%	
Acetone	2.0%	2.4%	
Organic Volatiles	65.0%	72.7%	
Percent Non-Volatile	33.0%	24.9%	
VOC Content	LB/Gal	g/L	
Total	5.17	620	
Less exempt solvents	5.30	635	
Of solids	20.80	2493	
Of solids	1.97 lb/lb	1.97 kg/kg	
	By wt		
By wt LVP-VOC	64.6%		

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) 0.82

Volatile Organic Compounds - California

	MC14812SF		
	LB/Gal	g/L	
Coating Density	7.96	954	
	By wt	By vol	
Total Volatiles	67.0%	75.1%	
Exempt solvents			
Water	0.0%	0.0%	
Acetone	2.0%	2.4%	
Organic Volatiles	65.0%	72.7%	
Percent Non-Volatile	33.0%	24.9%	
VOC Content	LB/Gal	g/L	
Total	5.17	620	
Less exempt solvents	5.30	635	
Of solids	20.80	2493	
Of solids	1.97 lb/lb	1.97 kg/kg	
	By wt		
By wt LVP-VOC	64.6%		

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) 0.75

Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	MC14812SF		
	LB/Gal	g/L	
Coating Density	7.96	954	
	By wt	By vol	
Total Volatiles	67.0%	75.1%	
Exempt solvents			
Water	0.0%	0.0%	
Acetone	2.0%	2.4%	
Organic Volatiles	65.0%	72.7%	
Percent Non-Volatile	33.0%	24.9%	
VOC Content	LB/Gal	g/L	
Total	5.17	620	
Less exempt solvents	5.30	635	
Of solids	20.80	2493	
Of solids	1.97 lb/lb	1.97 kg/kg	

Volatile Organic Compounds - EU Directive 2004/42/EC

	MC14812SF		
	By wt	By vol	
Total Volatiles	67.0%	75.1%	
VOC Content	LB/Gal	g/L	
Total	5.33	639	

Volatile Organic Compounds - EU Directive 2010/75/EU

	MC14812SF		
	By wt	By vol	
Total Volatiles	67.0%	75.1%	
VOC Content	LB/Gal	g/L	
Total	5.33	639	

Volatile Organic Compounds - Mexico

	MC14812SF		
	LB/Gal	g/L	
Coating Density	7.96	954	
	By wt	By vol	
Total Volatiles	67.0%	75.1%	
Exempt solvents			
Water	0.0%	0.0%	
Acetone	2.0%	2.4%	
Organic Volatiles	65.0%	72.7%	
Percent Non-Volatile	33.0%	24.9%	
VOC Content	LB/Gal	g/L	
Total	5.17	620	
Less exempt solvents	5.30	635	
Of solids	20.80	2493	
Of solids	1.97 lb/lb	1.97 kg/kg	

Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	MC14812SF		
	LB/Gal	kg/L	
Volatile HAPS	0.00	0.000	
Of solids	0.00	0.000	
Of solids	0.00 lb/lb	0.00 kg/kg	

Air Quality Data

Density of Organic Solvent Blend

7.11 lb/gal

Photochemically Reactive

No

Waste Disposal

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Addition of reducers or other additives to this product may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.