#### **ENVIRONMENTAL DATA SHEET**

(Certified Product Data Sheet)

**Date of Preparation** 

Feb 24, 2024

# PRODUCT NUMBER

50 00 [0554]

C14512

#### **PRODUCT NAME**

KRYSTAL® High Solids Conversion Varnish, Dull

#### **MANUFACTURER'S NAME**

M. L. CAMPBELL 101 W. Prospect Avenue Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

#### Hazard Category (for SARA 311.312)

C14512 = | Acute | Chronic | Fire |

Product WeightSpecific GravityFLASH POINT8.20 lb/gal0.9960 °F PMCC

#### **Volatile Ingredients**

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Ethylbenzene 100-41-4	N	Υ	Υ	Υ	0.3	< 1
Xylene 1330-20-7	N	Υ	Υ	Υ	2	2
Ethanol 64-17-5	N	N	N	N	7	9
1-Butanol 71-36-3	N	Υ	Υ	N	5	6
1-Methoxy-2-propanol 107-98-2	N	N	N	N	3	3
2-Methyl-1-propanol 78-83-1	N	Υ	N	N	2	3
Methyl n-Amyl Ketone 110-43-0	N	N	N	N	3	4
Ethyl Acetate 141-78-6	N	Υ	N	N	2	2
dimethyl carbonate 616-38-6	N	N	N	N	1	1
n-Butyl Acetate 123-86-4	N	Υ	N	N	30	33

## Volatile Organic Compounds - U.S. EPA / Canada

	C14512	
	LB/Gal	g/L
Coating Density	8.20	982
	By wt	By vol
Total Volatiles	56.9%	65.4%
Federally exempt solvents		
Water	0.0%	0.0%
Dimethyl carbonate	1.4%	1.3%
Organic Volatiles	55.6%	64.1%
Percent Non-Volatile	43.1%	34.6%
VOC Content	LB/Gal	g/L
Total	4.55	545
Less exempt solvents	4.61	552
Of solids	13.14	1575
Of solids	1.29 lb/lb	1.29 kg/kg
	By wt	
By wt LVP-VOC	55.3%	

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) 0.93

# **Volatile Organic Compounds - California**

	C14512	
	LB/Gal	g/L
Coating Density	8.20	982
	By wt	By vol
Total Volatiles	56.9%	65.4%
Exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	56.9%	65.4%
Percent Non-Volatile	43.1%	34.6%
VOC Content	LB/Gal	g/L
Total	4.66	559
Less exempt solvents	4.66	559
Of solids	13.47	1614
Of solids	1.32 lb/lb	1.32 kg/kg
	By wt	
By wt LVP-VOC	56.7%	

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) 0.86

## Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	C14512	
	LB/Gal	g/L
Coating Density	8.20	982
	By wt	By vol
Total Volatiles	56.9%	65.4%
Exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	56.9%	65.4%
Percent Non-Volatile	43.1%	34.6%
VOC Content	LB/Gal	g/L
Total	4.66	559
Less exempt solvents	4.66	559
Of solids	13.47	1614
Of solids	1.32 lb/lb	1.32 kg/kg

### Volatile Organic Compounds - EU Directive 2004/42/EC

	C14512	
	By wt	By vol
Total Volatiles	56.9%	65.4%
VOC Content	LB/Gal	g/L
Total	4.66	559

## Volatile Organic Compounds - EU Directive 2010/75/EU

	C14512	
	By wt	By vol
Total Volatiles	56.9%	65.4%
VOC Content	LB/Gal	g/L
Total	4.66	559

## **Volatile Organic Compounds - Mexico**

C14512		
LB/Gal	g/L	
8.20	982	
By wt	By vol	
56.9%	65.4%	
0.0%	0.0%	
56.9%	65.4%	
43.1%	34.6%	
LB/Gal	g/L	
4.66	559	
4.66	559	
13.47	1614	
1.32 lb/lb	1.32 kg/kg	
	LB/Gal 8.20 By wt 56.9% 0.0% 56.9% 43.1% LB/Gal 4.66 4.66	

# Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	C14512	
	LB/Gal	kg/L
Volatile HAPS	0.16	0.019
Of solids	0.47	0.056
Of solids	0.04 lb/lb	0.04 kg/kg

#### **Air Quality Data**

**Density of Organic Solvent Blend** 

7.15 lb/gal

**Photochemically Reactive** 

No

#### **Waste Disposal**

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Addition of reducers or other additives to this product may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.